NovaLite Infrastructure — Synthetic Technical Bid

SYNTHETIC TEST DOCUMENT • intentionally messy and semantically varied

Vendor code: VEND-B02

Against tender: GEM-TEST-SSLM-2026-50

Submission date: 12/09/2026

Important: This is a synthetic vendor response created for BidVerify AI testing. It is not an actual vendor submission and must not be treated as procurement evidence.

Vendor cover note

We confirm that the offered solution is proposed against the purchaser's broad functional intent. Some details are described in narrative form rather than using the exact terminology of the tender. Supporting statements below deliberately mix tables, prose, abbreviations and reordered sections to stress-test semantic matching.

Vendor parameter	Offered value / statement	Source context
Impact protection	Impact class IK08.	Technical Schedule / Item T08
System capacity	Deployment controller supports 250 nodes.	Technical Schedule / Item T01
GPS	GNSS receiver provides latitude/longitude for every node.	Technical Schedule / Item T24
Warranty	Five-year comprehensive warranty.	Technical Schedule / Item T38
Battery capacity	Battery bank is 80 Ah.	Technical Schedule / Item T11
Remote monitoring	Cloud portal shows lamp state, battery health and active faults.	Technical Schedule / Item T19
Password policy	Local passwords require 14 characters.	Technical Schedule / Item T30
Price ceiling	Base price is INR 24,90,000 before an optional monitoring service.	Technical Schedule / Item T46

Vendor Technical Response — Section 1

General note: The following statements include both direct specifications and descriptive context. A sentence that does not correspond to a tender requirement should not be interpreted as one.

Ref	Vendor response / offered evidence	Status intent
T25	Controllers synchronize clock using NTP.	See attached technical evidence
T50	Optional 3-year extended warranty available.	See attached technical evidence
T22	Portal view includes present-state lamp health + alarm history + trend charts; in our terminology this is the NOC dashboard.	See attached technical evidence
T47	Initial site delivery in 24 days.	See attached technical evidence
T19	Cloud portal shows lamp state, battery health and active faults.	See attached technical evidence
T44	Battery recovery and disposal follows applicable environmental rules.	See attached technical evidence
T16	PIR detection zone up to 12 metres.	See attached technical evidence
T41	Critical spares maintained for 6 years.	See attached technical evidence
T13	Four-night battery autonomy.	See attached technical evidence
T38	Five-year comprehensive warranty.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.

Vendor Technical Response — Section 2

Ref	Vendor response / offered evidence	Status intent
T10	Module conversion efficiency 20.4%.	See attached technical evidence
T35	Per-node energy and operating-hour counters are available.	See attached technical evidence
T07	Housing protection IP66.	See attached technical evidence
T32	Local schedule continues lighting during communications loss.	See attached technical evidence
T04	CCT selectable between 4200 K and 4800 K.	See attached technical evidence
T29	Audit records retained for 24 months.	See attached technical evidence
T01	Deployment controller supports 250 nodes.	See attached technical evidence
T26	TLS 1.3 is used for management traffic.	See attached technical evidence
T48	Local content disclosure: 62%.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.

Vendor Technical Response — Section 3

General note: The following statements include both direct specifications and descriptive context. A sentence that does not correspond to a tender requirement should not be interpreted as one.

Ref	Vendor response / offered evidence	Status intent
T20	4G LTE modem with local store-and-forward buffer.	See attached technical evidence
T45	Luminaire water-ingress failure is covered under warranty.	See attached technical evidence
T17	Operating temperature is -10°C to +45°C.	See attached technical evidence
T42	English O&M, installation and commissioning manuals included.	See attached technical evidence
T14	Programmable dimming from 0 to 100 percent.	See attached technical evidence
T39	Critical support response is within 12 hours.	See attached technical evidence
T11	Battery bank is 80 Ah.	See attached technical evidence
T36	Installation and commissioning: 45 days from site handover.	See attached technical evidence
T08	Impact class IK08.	See attached technical evidence
T33	10 kV surge protection device fitted.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.

Vendor Technical Response — Section 4

Ref	Vendor response / offered evidence	Status intent
T05	Vendor states substantial compliance but one element of the requirement differs.	See attached technical evidence
T30	Local passwords require 14 characters.	See attached technical evidence
T02	Photometric output: 12.8 klm.	See attached technical evidence
T27	Secrets and sensitive configuration are encrypted at rest.	See attached technical evidence
T24	GNSS receiver provides latitude/longitude for every node.	See attached technical evidence
T21	Telemetry retention is 18 months; longer retention can be configured.	See attached technical evidence
T46	Base price is INR 24,90,000 before an optional monitoring service.	See attached technical evidence
T18	Structural design wind rating 160 km/h.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.

Vendor Technical Response — Section 5

General note: The following statements include both direct specifications and descriptive context. A sentence that does not correspond to a tender requirement should not be interpreted as one.

Ref	Vendor response / offered evidence	Status intent
T15	Astronomical/photocell control provides automatic dusk-to-dawn operation.	See attached technical evidence
T40	Replacement within 5 calendar days.	See attached technical evidence
T12	Vendor states substantial compliance but one element of the requirement differs.	See attached technical evidence
T37	Three administrator training sessions included.	See attached technical evidence
T09	PV module 180 Wp per pole.	See attached technical evidence
T34	Auxiliary supply PF = 0.98.	See attached technical evidence
T06	Rated life 60,000 h (L70).	See attached technical evidence
T31	Firmware updates require physical service; no OTA rollback.	See attached technical evidence
T03	LED efficacy is 132 lm/W.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.