SYNTHETIC PROCUREMENT TENDER — 50 REQUIREMENT TEST

GENERALIZATION TEST DATA — NOT A REAL GOVERNMENT TENDER

Tender code: BV-GEN50-2026. This synthetic document intentionally mixes technical specifications, ranges, units, qualitative clauses, abbreviations, notes and section text.

SECTION 1 — PROCUREMENT REQUIREMENTS

R01. The System processing capacity shall be at least **200 units/s**.

R02. The Display brightness shall be at least **500 nits**.

R03. The Storage capacity shall be at least **1 TB**.

R04. The acceptable operating temperature shall be **-10 to 50 °C**.

R05. The Power consumption shall be not more than **120 W**.

R06. The Battery capacity shall be at least **40 Ah**.

R07. The Battery backup shall be at least **6 hours**.

Evaluation note: marketing language is not evidence unless it explicitly addresses the criterion.

R08. The required ingress protection is **IP65** .

R09. The Warranty period shall be at least **3 years**.

R10. The Delivery period shall be not more than **30 days**.

SECTION 2 — PROCUREMENT REQUIREMENTS

R11. The network interface shall support/use one of: **Ethernet, Wi-Fi**.

R12. Mandatory requirement: **TLS 1.2 or higher in transit**.

R13. The processor architecture shall support/use one of: **64-bit**.

R14. The Memory capacity shall be at least **16 GB**.

Evaluation note: marketing language is not evidence unless it explicitly addresses the criterion.

R15. The usb interface shall support/use one of: **USB 3.0 or higher**.

R16. The Screen resolution shall be at least **1920 x 1080 pixels**.

R17. The Camera resolution shall be at least **8 MP**.

R18. The Audio output shall be at least **20 W**.

R19. The Noise level shall be not more than **45 dB**.

R20. The Weight shall be not more than **15 kg**.

SECTION 3 — PROCUREMENT REQUIREMENTS

R21. The LED efficacy shall be at least **120 lm/W**.

Evaluation note: marketing language is not evidence unless it explicitly addresses the criterion.

R22. The acceptable led color temperature shall be **4000 to 5000 K**.

R23. The Luminous output shall be at least **12000 lm**.

R24. The Color rendering index shall be at least **80 CRI**.

R25. The Solar panel efficiency shall be at least **20 %**.

R26. The Solar module rating shall be at least **450 W**.

R27. The charge controller type shall support/use one of: **MPPT**.

R28. Mandatory requirement: **powder-coated aluminum**.

Evaluation note: marketing language is not evidence unless it explicitly addresses the criterion.

R29. The required connector protection is **IP67** .

R30. The Power factor shall be at least **0.95** .

SECTION 4 — PROCUREMENT REQUIREMENTS

R31. The Flow rate shall be at least **50 L/min**.

R32. The acceptable pressure range shall be **2 to 6 bar**.

R33. The measurement accuracy shall have a maximum error of **±2%**.

R34. The acceptable operating voltage shall be **220 to 240 V**.

R35. The required frequency is **50 Hz**.

Evaluation note: marketing language is not evidence unless it explicitly addresses the criterion.

R36. The Response time shall be not more than **100 ms**.

R37. The Ingress protection for enclosure shall be at least **IP54** .

R38. Mandatory requirement: **BIS compliant**.

R39. Mandatory requirement: **ISO 9001 certified**.

R40. Mandatory requirement: **OEM authorization letter required**.

SECTION 5 — PROCUREMENT REQUIREMENTS

R41. The Installation time shall be not more than **2 days**.

R42. The Service response time shall be not more than **24 hours**.

Evaluation note: marketing language is not evidence unless it explicitly addresses the criterion.

R43. The Spare parts availability shall be at least **5 years**.

R44. The acceptable operating humidity shall be **20 to 80 % RH**.

R45. The acceptable mounting height shall be **1.5 to 2.5 m**.

R46. The Cable length shall be at least **10 m**.

R47. The required protection class is **Class II** .

R48. The material grade shall support/use one of: **SS 304 or better**.

R49. Mandatory requirement: **web-based remote monitoring**.

Evaluation note: marketing language is not evidence unless it explicitly addresses the criterion.

R50. Mandatory requirement: **user manual and maintenance manual supplied**.