EcoRay Smart Lighting — Synthetic Technical Bid

SYNTHETIC TEST DOCUMENT • intentionally messy and semantically varied

Vendor code: VEND-C03

Against tender: GEM-TEST-SSLM-2026-50

Submission date: 12/09/2026

Important: This is a synthetic vendor response created for BidVerify AI testing. It is not an actual vendor submission and must not be treated as procurement evidence.

Vendor cover note

We confirm that the offered solution is proposed against the purchaser's broad functional intent. Some details are described in narrative form rather than using the exact terminology of the tender. Supporting statements below deliberately mix tables, prose, abbreviations and reordered sections to stress-test semantic matching.

Vendor parameter	Offered value / statement	Source context
Impact protection	Impact class IK08.	Technical Schedule / Item T08
System capacity	Deployment controller supports 250 nodes.	Technical Schedule / Item T01
GPS	GNSS receiver provides latitude/longitude for every node.	Technical Schedule / Item T24
Warranty	Standard warranty is 4 years; fifth year is available as a paid extension.	Technical Schedule / Item T38
Battery capacity	LiFePO4 battery bank, 120 Ah.	Technical Schedule / Item T11
Remote monitoring	Cloud portal shows lamp state, battery health and active faults.	Technical Schedule / Item T19
Password policy	Local passwords require 14 characters.	Technical Schedule / Item T30
Price ceiling	Quoted base price INR 23,80,000.	Technical Schedule / Item T46

Vendor Technical Response — Section 1

General note: The following statements include both direct specifications and descriptive context. A sentence that does not correspond to a tender requirement should not be interpreted as one.

Ref	Vendor response / offered evidence	Status intent
T25	Controllers synchronize clock using NTP.	See attached technical evidence
T50	Optional extended warranty is available for 1 additional year.	See attached technical evidence
T22	Portal view includes present-state lamp health + alarm history + trend charts; in our terminology this is the NOC dashboard.	See attached technical evidence
T47	Initial site delivery in 24 days.	See attached technical evidence
T19	Cloud portal shows lamp state, battery health and active faults.	See attached technical evidence
T16	PIR detection zone up to 12 metres.	See attached technical evidence
T41	Critical spares maintained for 6 years.	See attached technical evidence
T13	Autonomy is 2 nights.	See attached technical evidence
T38	Standard warranty is 4 years; fifth year is available as a paid extension.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.

Vendor Technical Response — Section 2

Ref	Vendor response / offered evidence	Status intent
T10	Module conversion efficiency 20.4%.	See attached technical evidence
T35	Per-node energy and operating-hour counters are available.	See attached technical evidence
T07	Housing protection IP66.	See attached technical evidence
T32	Local schedule continues lighting during communications loss.	See attached technical evidence
T04	CCT is 3900 K to 5000 K; lower bound is slightly outside the tender range.	See attached technical evidence
T29	Audit records retained for 24 months.	See attached technical evidence
T01	Deployment controller supports 250 nodes.	See attached technical evidence
T26	TLS 1.3 is used for management traffic.	See attached technical evidence
T48	Local content is disclosed as approximately 45%.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.

Vendor Technical Response — Section 3

General note: The following statements include both direct specifications and descriptive context. A sentence that does not correspond to a tender requirement should not be interpreted as one.

Ref	Vendor response / offered evidence	Status intent
T45	Luminaire water-ingress failure is covered under warranty.	See attached technical evidence
T17	Outdoor electronics rated -20°C to +55°C.	See attached technical evidence
T42	English O&M, installation and commissioning manuals included.	See attached technical evidence
T14	Dimming is programmable from 20% to 100%; full 0-100% range is not available.	See attached technical evidence
T39	Critical ticket response SLA: 3 hours.	See attached technical evidence
T11	LiFePO4 battery bank, 120 Ah.	See attached technical evidence
T36	Installation and commissioning: 45 days from site handover.	See attached technical evidence
T08	Impact class IK08.	See attached technical evidence
T33	10 kV surge protection device fitted.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.

Vendor Technical Response — Section 4

Ref	Vendor response / offered evidence	Status intent
T05	CRI 80.	See attached technical evidence
T30	Local passwords require 14 characters.	See attached technical evidence
T02	Rated output is 10,500 lumens.	See attached technical evidence
T27	Secrets and sensitive configuration are encrypted at rest.	See attached technical evidence
T24	GNSS receiver provides latitude/longitude for every node.	See attached technical evidence
T21	Telemetry retained for 36 months.	See attached technical evidence
T46	Quoted base price INR 23,80,000.	See attached technical evidence
T18	Wind rating is 120 km/h.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.

Vendor Technical Response — Section 5

General note: The following statements include both direct specifications and descriptive context. A sentence that does not correspond to a tender requirement should not be interpreted as one.

Ref	Vendor response / offered evidence	Status intent
T15	Astronomical/photocell control provides automatic dusk-to-dawn operation.	See attached technical evidence
T40	Replacement SLA is 12 calendar days.	See attached technical evidence
T12	Battery chemistry: LiFePO4.	See attached technical evidence
T37	Three administrator training sessions included.	See attached technical evidence
T09	PV module is 120 Wp per pole.	See attached technical evidence
T34	Power factor is 0.90.	See attached technical evidence
T06	Rated life is 40,000 hours.	See attached technical evidence
T03	LED efficacy is 165 lumens per watt.	See attached technical evidence
NOTE	The supplier may use equivalent commercial terminology; this note is explanatory only.	Not a requirement

Commercial/clarification note: Price, scheduling, site conditions and final quantities are subject to purchaser confirmation where not explicitly stated above. This paragraph is not a separate technical requirement.