



ENGINE

| | |
|-----------------|--|
| Manufacturer | Kawasaki FS541V |
| HP | 15hp *Per SAE J 1995 |
| Displacement | 603-747cc |
| Cooling | Air cooled |
| Air Cleaner | Heavy duty air canister (not standard on 36" deck) |
| Engine Warranty | 3 year |

DRIVE SYSTEM

| | |
|----------------|------------------|
| Type | Dual hydrostatic |
| Pumps | Hydro-Gear 10cc |
| Wheel Motors | Parker TL0195 |
| Speed | Up to 8 mph |
| Parking Brakes | Hand operated |

DECKS

| | |
|-------------------|--|
| Cutting Width | 36" |
| Cutting Heights | 1.5"- 5.5" |
| Deck Lift | Hand operated |
| Depth | 5.5" |
| Blades | 2 48" |
| Blade Length | 17.86" x 2.50" x .20" |
| Spindles | Ductile cast iron with steel shafts and sealed ball bearings |
| Deck Belts | 1 |
| Drive | Electric PTO clutch |
| Construction | 7 ga. Fabricated |
| Spindle Mounts | 7 ga. with 11 ga. doubler |
| Impact/Trim Areas | 11 ga. formed channel with rolled bottom |

CONSTRUCTION

| | |
|---------------------|-------------------------------------|
| Frame | 1.5" x 2" x .179" steel |
| Engine Plate | 7 ga. with 11 ga. jackshaft doubler |
| Front Caster Wheels | Heavy duty ball bearing, greasable |
| Front Caster Forks | Fabricated 3/8" steel |
| Operator Platform | 7 ga. with embossed tread pattern |

GENERAL

| | |
|---------------|---|
| Fuel Capacity | 36": 6.5 gallons 48, 52, 60": 7.3 gallons |
| Front Tire | 36": 11 x 4 semi pneumatic 48", 52", 60": 13 x 5 semi pneumatic |
| Drive Tire | 36": 18 x 8.5 - 10 48", 52": 20 x 10 - 10 60": 20 x 12 - 10 |

DIMENSIONS

| | |
|-------------------|--|
| Weight | 36": 910 lbs 48": 1040 lbs 52": 1055 lbs 60": 1110 lbs |
| Height | 47.8" |
| Length | 36": 63.5" 48", 52": 64" 60": 66.5" |
| Width w/ chute up | 36": 39" 48": 50.4" 52": 54.4" 60": 62.4" |
| Tire Width | 36": 36.3" 48", 52": 44.7" 60": 49.1" |

PRODUCTIVITY

| | |
|----------------------|---|
| Acres Per Hour* | 36": 2.33 48": 3.49 52": 3.93 60": 4.36 |
| Optional Accessories | Mulch kit Grass catcher (4.4 cu.ft.) Light kit Cup holder Trash basket Stripe kit |



Visit hustlerturf.com
and try our compare mowers tool!

SUPER S | AT A GLANCE

- 36", 48", 52" or 60" welded steel side-discharge decks
- Kawasaki and Kohler engine options available
- 1.5" to 5.5" deck heights (1/4" increments)
- 8 or 9 mph speed options (depending on deck size)
- 6.5 or 7.3 gallon fuel capacity (depending on deck size)