```
# Experiment No. 4
# SQL DML queries: Use of SQL DML queries to retrieve, insert, delete and
update the database.
show databases;
use RMS 2;
select database();
desc Ticket;
# Inserting Records
insert into Ticket
values(308123905,596,'20:04:15','20:07:19',21673,420,70,'CNF');
insert into Ticket
values(1265577771,136,'12:47:10','12:50:10',22154,376,15,'CNF');
insert into Ticket
values(1975364587,245,'07:40:15','07:45:58',19134,298,63,'CNF');
insert into Ticket
values(2110755678,169,'16:20:38','16:24:34',27139,380,37,'CNF');
insert into Ticket
values(2120017791,101,'04:35:10','04:40:10',12139,289,12,'CNF');
select* from Ticket;
insert into Passenger values(201, 'John', 21, 'Male', 596, 308123905);
insert into Passenger values(217, 'Mark', 24, 'Male', 136, 1265577771);
insert into Passenger values(239, 'Alice', 29, 'Female', 245, 1975364587);
insert into Passenger values(340, 'Jenny', 32, 'Female', 169, 2110755678);
insert into Passenger values(367, 'Tony', 24, 'Male', 101, 2120017791);
select * from Passenger;
insert into Train values(11071, 'Kamyani Express', 'Superfast', 'Sleeper',
233, 'S2');
insert into Train values(12178, 'Gitanjali Express', 'Superfast', 'Sleeper',
193, 'S7');
insert into Train values(12124, 'Rajdhani Express', 'Express', 'AC', 233,
'A1');
insert into Train values(21353, 'Pungab Mail', 'Superfast', 'AC', 193,
'A2');
insert into Train values(12139, 'Sewagram Express', 'Express', 'Sleeper',
255, 'S5');
select * from train;
# Retreival
select P ID, P name from Passenger where
Gender='Male';
```

```
select P ID, P name from Passenger where
Gender='Female';
select P ID, P name from Passenger where Age between 25 and 35;
select P ID, P name, Age from Passenger where Age < 24 and Gender='Male';
select * from Passenger;
# use of distinct clause
select Age from Passenger;
select distinct Age from Passenger;
select P_name, Age from Passenger;
select distinct P name, Age from Passenger;
# use of order by clause
select * from Passenger;
select * from Passenger order by Age;
select * from Passenger order by Age asc;
select * from Passenger order by Age desc;
select * from Passenger order by Age asc, P ID desc;
# use of between operator
select * from Passenger
where Age between 25 and 35;
# use of like operator
select * from Passenger where Gender like 'M%';
select * from Passenger where Gender like 'F%';
# use of IN operator
select * from ticket;
select * from ticket
where Trainno in(21673,12139, 19134);
# use of is null
select * from ticket
where Ticket ID is null;
select * from ticket
where Ticket ID is not null;
# Update
update Passenger set P_name='Barry' where P_ID=201;
update Passenger set P name='Natasha' where P ID=340;
select * from Passenger;
```

```
# Deletion
insert into Ticket
values(2146865786,199,'11:20:38','11:24:34',29123,478,65,'CNF');
select * from Ticket;
insert into Passenger values(822, 'Pepper', 28, 'Female', 543, 2146865786);
select* from Passenger;
delete from Passenger where P ID=822; select * from Passenger;
#Output:
Enter password: ****
Welcome to the MySQL monitor. Commands end with ; or \g. Your MySQL
connection id is 30
Server version: 8.0.27 MySQL Community Server - GPL Copyright (c) 2000,
2021, Oracle and/or its affiliates.
Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective owners. Type
'help;' or '\h' for help. Type '\c' to clear the current input statement.
mysql> show databases;
+----+
Database
| b1 db1
| b2 db1
information schema
| mvsal
performance schema
rms 2
sys
+----+
7 rows in set (0.0056 sec)
mysql> use RMS 2; Database changed mysql> select database();
      + | database() |
      + | rms 2 |
      + 1 row in
set (0.00 sec) mysql> desc Ticket;
+----+
```

Field	Type	Null	Key	Default	Extra
PNR Ticket_ID Arrtime Deptime Trainno Tktamt Seat_no Reserve_status	int int time time int int int char(10)	NO YES YES YES YES YES YES YES YES YES	PRI 	NULL NULL NULL NULL NULL NULL NULL NULL	

mysql> insert into Ticket

-> values(308123905,596,'20:04:15','20:07:19',21673,420,70,'CNF'); Query OK, 1 row affected (0.01 sec) mysql> insert into Ticket -> values(1265577771,136,'12:47:10','12:50:10',22154,376,15,'CNF'); Query OK, 1 row affected (0.01 sec) mysql> insert into Ticket -> values(1975364587,245,'07:40:15','07:45:58',19134,298,63,'CNF');

Query OK, 1 row affected (0.01 sec) mysql> insert into Ticket
-> values(2110755678,169,'16:20:38','16:24:34',27139,380,37,'CNF');

Query OK, 1 row affected (0.03 sec) mysql> insert into Ticket
-> values(2120017791,101,'04:35:10','04:40:10',12139,289,12,'CNF');
Query OK, 1 row affected (0.01 sec)

mysql> select * from Ticket;

+------| Ticket ID | Arrtime | Deptime | Trainno | Tktamt | Seat no | Reserve_status | 596 | 20:04:15 | 20:07:19 | 21673 l 420 l 70 308123905 CNF 1265577771 136 | 12:47:10 | 12:50:10 | 22154 376 l 15 CNF 245 | 07:40:15 | 07:45:58 | 1975364587 19134 298 l 63 CNF 2110755678 169 | 16:20:38 | 16:24:34 | 27139 380 l 37 CNF 2120017791 101 | 04:35:10 | 04:40:10 | 12139 12 289

5 rows in set (0.0037 sec)

```
mysql> insert into Passenger values(201, 'John', 21, 'Male', 596, 308123905);
Query OK, 1 row affected (0.01 sec)
mysql> insert into Passenger values(217, 'Mark', 24, 'Male', 136, 1265577771);
Query OK, 1 row affected (0.01 sec)
mysql> insert into Passenger
values(239, 'Alice', 29, 'Female', 245, 1975364587);
Query OK, 1 row affected (0.01 sec) mysql> ^C
mysal> insert into Passenger
values(340, 'Jenny', 32, 'Female', 169, 2110755678); Query OK, 1 row affected
(0.03 \text{ sec})
mysql> insert into Passenger values(367, 'Tony', 24, 'Male', 101, 2120017791);
Query OK, 1 row affected (0.01 sec)
mysql> select * from Passenger;
+----+---+----+----+----+
| P ID | P name | Age | Gender | Ticket ID | PNR
                                 596 | 308123905 |
136 | 1265577771 |
245 | 1975364587 |
  201 | John
              | 21 | Male
  217 | Mark | 24 | Male
| 239 | Alice | 29 | Female |
  340 | Jenny | 32 | Female |
                                   169 | 2110755678 |
  367 | Tony | 24 | Male |
                                   101 | 2120017791 |
+----+----+---
5 rows in set (0.0032 sec)
mysql> insert into Train values(11071, 'Kamyani Express', 'Superfast',
'Sleeper', 233, 'S2'); Query OK, 1 row affected (0.01 sec)
mysql> insert into Train values(12178, 'Gitanjali Express', 'Superfast',
'Sleeper', 193, 'S7'); Query OK, 1 row affected (0.03 sec)
mysql> insert into Train values(12124, 'Rajdhani Express', 'Express', 'AC',
233, 'A1'); Query OK, 1 row affected (0.01 sec)
mysql> insert into Train values(21353, 'Pungab Mail', 'Superfast', 'AC',
193, 'A2'); Query OK, 1 row affected (0.01 sec)
mysql> insert into Train values(12139, 'Sewagram Express', 'Express',
'Sleeper', 255, 'S5'); Query OK, 1 row affected (0.01 sec)
mysql> select * from train;
```

```
11071 | Kamyani Express | Superfast | Sleeper | 233 | S2
  12124 | Rajdhani Express | Express | AC | 233 | A1
  12139 | Sewagram Express | Express | Sleeper | 255 | S5
  12178 | Gitanjali Express | Superfast | Sleeper | 193 | S7
  21353 | Pungab Mail | Superfast | AC |
                                           193 | A2
+-----
5 rows in set (0.0031 sec)
mysql> select P ID,P name from Passenger
where Gender='Male';
+----+
P_ID | P_name |
 201 | John
  217 | Mark
  367 | Tony
+----+
3 rows in set (0.0025 sec)
mysql> select P_ID,P_name from Passenger where Gender='Female';
+----+
| P ID | P name |
+----+
  239 | Alice
  340 | Jenny
+----+
2 rows in set (0.0021 sec)
mysql> select P ID,P name from Passenger where Age between 25 and 35;
+----+
239 | Alice
  340 | Jenny
```

+----+

2 rows in set (0.0019 sec)

mysql> select P_ID,P_name, Age from Passenger where Age < 24 and Gender='Male';

```
+----+
| P_ID | P_name | Age |
+----+
| 201 | John | 21 |
```

1 row in set (0.0036 sec)

mysql> select * from Passenger;

4		-	L	L	L
P_ID	P_name	Age	Gender	Ticket_ID	PNR
201 217 239 340 367	John Mark Alice Jenny Tony	21 24 29 32 24	Male Male Female Female Male	596 136 245 169 101	308123905 1265577771 1975364587 2110755678 2120017791

5 rows in set (0.0018 sec)

mysql> select Age from Passenger;

```
+----+
| Age |
+----+
| 21 |
| 24 |
| 29 |
| 32 |
| 24 |
+----+
```

5 rows in set (0.0017 sec)

mysql> select distinct Age from Passenger;

```
+----+
| age |
+----+
| 21 |
```

```
| 24 |
| 29 |
| 32 |
+----+
```

4 rows in set (0.0034 sec)

mysql> select P_name, Age from Passenger;

+ P_name	+ Age
+	 +
John	21
Mark	24
Alice	29
Jenny	32
Tony	24
+	+

5 rows in set (0.0032 sec)

mysql> select distinct P_name, Age from Passenger;

+	+
P_name	Age
+	+
John	21
Mark	24
Alice	29
Jenny	32
Tony	24
+	

5 rows in set (0.0026 sec)

mysql> select * from Passenger;

P_ID P_name	+ Age +	Gender	Ticket_ID	PNR 	+ +
201 John	21	Male	596	308123905	.
217 Mark	24	Male	136	1265577771	
239 Alice	29	Female	245	1975364587	
340 Jenny	32	Female	169	2110755678	
367 Tony	24	Male	101	2120017791	

5 rows in set (0.0021 sec)

mysql> select * from

Passenger order by Age;

P_ID	P_name	+ Age +	 Gender 	 Ticket_ID 	+ PNR
201	John	21	Male	596	308123905
217	Mark	24	Male	136	1265577771
367	Tony	24	Male	101	2120017791
239	Alice	29	Female	245	1975364587
340	Jenny	32	Female	169	2110755678

5 rows in set (0.0028 sec)

mysql> select * from
Passenger order by Age asc;

+ P_ID	+ P_name	+ Age 	Gender	+ Ticket_ID	+ PNR
201	John	21	Male	596	308123905
217	Mark	24	Male	136	1265577771
367	Tony	24	Male	101	2120017791
239	Alice	29	Female	245	1975364587
340	Jenny	32	Female	169	2110755678

5 rows in set (0.0023 sec)

mysql> select * from
Passenger order by Age desc;

P_ID P_name	+ Age +	+ Gender +	 Ticket_ID	++ PNR
340 Jenny 239 Alice 217 Mark 367 Tony 201 John	32 29 24 24 21	Female Female Male Male Male	169 245 136 101 596	2110755678 1975364587 1265577771 2120017791 308123905

5 rows in set (0.0023 sec)

mysql> select * from Passenger order by Age asc, P_ID desc;
+----+

P_ID	P_name	Age	Gender	Ticket_ID	PNR			
201	John	21	Male	596	308123905			
		•	Male		1265577771			
	Tony			101				
239	Alice	29	Female	245	1975364587			
340	Jenny	32	Female	169	2110755678			
ttttttt								
++ P_ID				+ Ticket_ID				
++		-		+				
					1975364587			
340				169				
	<pre>mysql> select * from Passenger where Gender like 'M%';</pre>							
++		-		+				
P ID	P name	Age	Gender	Ticket ID	PNR			
++		-		+				
201	John	21	Male	596	308123905			
217	Mark	24	Male	136	1265577771			
367	Tony	24	Male	101	2120017791			
	n set (0.		ŕ	+	1.1 1501			
				where Gender	like 'F%';			
P_ID	P_name	Age	Gender	Ticket_ID				
					1975364587			
					2110755678			
2 rows in set (0.0021 sec)								
<pre>mysql> select * from ticket;</pre>								
+			+	+	+			
-+		+						

| Ticket_ID | Arrtime | Deptime | Trainno | Tktamt | Seat_no

```
Reserve status
 596 | 20:04:15 | 20:07:19 |
                                 21673 | 420 |
                                                70
 308123905
l CNF
1265577771
             136 | 12:47:10 | 12:50:10 | 22154 | 376 |
                                                15
CNF
             245 | 07:40:15 | 07:45:58 | 19134 |
1975364587
                                         298
                                                63
CNF
             169 | 16:20:38 | 16:24:34 |
                                 27139 | 380 |
2110755678
                                                37
l CNF
                                         289 |
| 2120017791 |
             101 | 04:35:10 | 04:40:10 | 12139 |
                                                12
l CNF
+-----
-+----+
5 rows in set (0.0032 sec)
mysql> select * from ticket where Trainno in(21673,12139, 19134);
+-----
        | Ticket ID | Arrtime | Deptime | Trainno | Tktamt | Seat no
| Reserve status |
+------
             596 | 20:04:15 | 20:07:19 | 21673 | 420 |
 308123905
                                                70
l CNF
             245 | 07:40:15 | 07:45:58 | 19134 | 298 |
1975364587
                                                63
CNF
| 2120017791 |
             101 | 04:35:10 | 04:40:10 | 12139 | 289 |
                                                12
+-----
-+----+
3 rows in set (0.0021 sec)
mysql> select * from ticket where Ticket ID is null;
Empty set
(0.00 \text{ sec})
mysql> select * from ticket where Ticket_ID is not null;
+-----
        | Ticket ID | Arrtime | Deptime | Trainno | Tktamt | Seat no
| Reserve status |
```

```
596 | 20:04:15 | 20:07:19 |
  308123905
                                         21673
                                                  420
                                                           70
 CNF
                 136 | 12:47:10 | 12:50:10 |
                                         22154
 1265577771 l
                                                  376 l
                                                           15
 CNF
                 245 | 07:40:15 | 07:45:58 |
                                         19134
                                                  298
                                                           63
 1975364587
 CNF
                 169 | 16:20:38 | 16:24:34 |
 2110755678 |
                                         27139
                                                  380
                                                           37
 CNF
                 101 | 04:35:10 | 04:40:10 |
                                         12139
2120017791 |
                                                  289
                                                           12
+------
5 rows in set (0.0028 sec)
mysql> update Passenger set P name='Barry' where P ID=201;
Ouery OK, 1 row affected (0.01 sec) Rows matched: 1 Changed: 1 Warnings: 0
mysql> update Passenger set P_name='Natasha' where P_ID=340;
Query OK, 1 row affected
(0.03 \text{ sec})
Rows matched: 1 Changed: 1 Warnings: 0
mysql> select * from Passenger;
+----+----+----+
| P_ID | P_name | Age | Gender | Ticket ID | PNR
  201 | John
               21 | Male
                               596 l
                                     308123905
               24 | Male
  217 | Mark
                               136 | 1265577771
  239 | Alice | 29 | Female |
                               245 | 1975364587
                               169 | 2110755678
  340 Jenny
               32 | Female |
               24 | Male
                               101 | 2120017791 |
  367 | Tony
5 rows in set (0.0027 sec)
mysql> insert into Ticket
-> values(2146865786,199,'11:20:38','11:24:34',29123,478,65,'CNF');
Query OK, 1 row affected
(0.01 \text{ sec})
mysql> select * from Ticket;
+----+
-+----+
```

```
| Ticket ID | Arrtime | Deptime | Trainno | Tktamt | Seat no
PNR
| Reserve_status |
+-----
             596 | 20:04:15 | 20:07:19 | 21673 | 420 |
 308123905
                                                70
CNF
             136 | 12:47:10 | 12:50:10 | 22154 | 376 |
1265577771
                                                15
CNF
             245 | 07:40:15 | 07:45:58 | 19134 | 298 |
 1975364587
                                                63
CNF
             169 | 16:20:38 | 16:24:34 | 27139 | 380 |
2110755678
                                                37
CNF
| 2120017791 |
             101 | 04:35:10 | 04:40:10 | 12139 | 289 |
                                                12
l CNF
```

-+----+

5 rows in set (0.0020 sec)

mysql> insert into Passenger
values(822, 'Pepper', 28, 'Female', 543, 2146865786);
Query OK, 1 row affected
(0.03 sec)

mysql> select * from Passenger;

P_ID P_	_name Age	+ Gender	Ticket_ID	PNR
217 Ma 239 A] 340 Je	ohn 21 ark 24 lice 29 enny 32 ony 24	Male Male Female Female Male	596 136 245 169 101	308123905 1265577771 1975364587 2110755678 2120017791

5 rows in set (0.0019 sec)

mysql> delete from Passenger where P_ID=822; Query OK, 1 row affected
(0.03 sec)
mysql> select * from Passenger:

mysql> select * from Passenger;

+	+	+	+		+	+
P_ID	P_name	Age	Gender	Ticket_ID		
- 1	John		-	='	308123905	•
217	Mark	24	Male	136	1265577771	١
239	Alice	29	Female	245	1975364587	ĺ

3	40	Jenny	32	Female	169	2110755678
3	67	Tony	24	Male	101	2120017791
+	+	+-	+		+	+

5 rows in set (0.0019 sec)