## **EXPERIMENT NO: - 09**

```
# Write a program to demonstrate view.
# View creation:-
use RMS 2;
select * from Passenger;
select * from Ticket;
# creating a view V1
create view v1 as select * from Passenger
where Age>25;
select * from V1;
insert into V1 values(570, 'Walter', 31, 'Male', 370, 2120017791);
select * from V1;
select * from Passenger;
# updation
update v1
set Age=30
where P_name='Alice';
select * from V1;
select * from Passenger;
#deletion
delete from V1
where P name='Walter';
select * from V1;
select* from Passenger;
```

## **#Output: -**

Enter password: \*\*\*\*

Welcome to the MySQL monitor. Commands end with ; or \g. Your MySQL connection id is 33 Server version: 8.0.27 MySQL Community Server - GPL Copyright (c) 2000, 2021, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement. mysql> use RMS\_2; Database changed

mysql> select \* from Passenger;

```
| 201 | Barry | 21 | Male | 596 | 308123905 |
| 217 | Mark | 24 | Male | 136 | 1265577771 |
| 239 | Alice | 29 | Female | 245 | 1975364587 |
| 340 | Natasha | 32 | Female | 169 | 2110755678 |
| 367 | Tony | 24 | Male | 101 | 2120017791 |
5 rows in set (0.00 sec)
mysql> select * from Ticket;
+ + +
| PNR | Ticket_ID | Arrtime | Deptime | Trainno | Tktamt | Seat_no | Reserve_status |
| 308123905 | 596 | 20:04:15 | 20:07:19 | 21673 |
| 1265577771 | 136 | 12:47:10 | 12:50:10 | 22154 |
| 1975364587 | 245 | 07:40:15 | 07:45:58 | 19134 |
| 2110755678 | 169 | 16:20:38 | 16:24:34 | 27139 |
| 2120017791 | 101 | 04:35:10 | 04:40:10 | 12139 |
| 2146865786 | 199 | 11:20:38 | 11:24:34 | 29123 |
6 rows in set (0.00 sec) + 420 |
376 |
298 |
380 |
289 |
478 |
+
70 | CNF
15 | CNF
63 | CNF
37 | CNF
12 | CNF
65 | CNF
```

+

```
mysql> create view v1 as
-> select * from Passenger
-> where Age>25;
Query OK, 0 rows affected (0.02 sec)
mysql> select * from V1;
| P_ID | P_name | Age | Gender | Ticket_ID | PNR
              + +
                             +
| 239 | Alice | 29 | Female | 245 | 1975364587 |
| 340 | Natasha |
                      32 | Female | 169 | 2110755678 |
2
       rows in set (0.01 sec)
mysql> insert into V1 values(570,'Walter',31,'Male',370,2120017791);
Query OK, 1 row affected (0.00 sec)
mysql> select * from V1;
       +
| P_ID | P_name | Age | Gender | Ticket_ID | PNR
| 239 | Alice | 29 | Female | 245 | 1975364587 |
| 340 | Natasha | 32 | Female | 169 | 2110755678 |
| 570 | Walter |
                      31 | Male | 370 | 2120017791 |
3
       rows in set (0.00 sec)
mysql> select * from Passenger;
| P_ID | P_name | Age | Gender | Ticket_ID | PNR
| 201 | Barry | 21 | Male | 596 | 308123905 |
| 217 | Mark | 24 | Male | 136 | 1265577771 |
| 239 | Alice | 29 | Female | 245 | 1975364587 |
| 340 | Natasha | 32 | Female | 169 | 2110755678 |
| 367 | Tony | 24 | Male | 101 | 2120017791 |
                31 | Male | 370 | 2120017791 |
| 570 | Walter |
6 rows in set (0.00 sec)
```

```
mysql> update v1
# run at shell
-> set Age=30
-> where P_name='Alice';
Query OK,
1 row affected (0.03 sec)
Rows matched: 1
Changed: 1
Warnings: 0
mysql> select * from V1;
| P_ID | P_name | Age | Gender | Ticket_ID | PNR
       +
               +
                              +
| 239 | Alice | 30 | Female | 245 | 1975364587 |
| 340 | Natasha |
                      32 | Female | 169 | 2110755678 |
| 570 | Walter |
                      31 | Male | 370 | 2120017791 |
3 rows in set (0.00 sec)
mysql> select * from Passenger;
| P_ID | P_name | Age | Gender | Ticket_ID | PNR
| 201 | Barry | 21 | Male | 596 | 308123905 |
| 217 | Mark | 24 | Male | 136 | 1265577771 |
| 239 | Alice | 30 | Female | 245 | 1975364587 |
| 340 | Natasha |
                  32 | Female | 169 | 2110755678 |
| 367 | Tony | 24 | Male | 101 | 2120017791 |
                    31 | Male | 370 | 2120017791 |
| 570 | Walter |
6 rows in set (0.00 sec)
mysql> delete from V1
-> where P_name='Walter';
Query OK,
1 row affected (0.01 sec)
mysql> select * from V1;
```

```
| P_ID | P_name | Age | Gender | Ticket_ID | PNR |
         + + +
| 239 | Alice | 30 | Female | 245 | 1975364587 |
+ +
2 rows in set (0.00 sec)
mysql> select * from Passenger;
+ + + + +
| P_ID | P_name | Age | Gender | Ticket_ID | PNR
+ + + + + + +
| 201 | Barry | 21 | Male | 596 | 308123905 |
| 217 | Mark | 24 | Male | 136 | 1265577771 |
| 239 | Alice | 30 | Female | 245 | 1975364587 |
| 340 | Natasha | 32 | Female | 169 | 2110755678 |
| 367 | Tony | 24 | Male | 101 | 2120017791 |
+ + + + + +
```