zachatkinson / kineticslider
Type / to search
Code
Issues
Pull requests 2
Actions
Projects
Wiki
Security 3
Insights
Settings

← 🚀 CI/CD Pipeline

fix: replace Playwright GitHub Action with reliable fresh install app... #132

Cancel workflow
Summary
Jobs
Security Scan
Test & Quality
E2E Setup
Performance Analysis
Accessibility Tests
E2E Tests (Shard 1/8)
E2E Tests (Shard 2/8)
E2E Tests (Shard 3/8)
E2E Tests (Shard 4/8)
E2E Tests (Shard 5/8)
E2E Tests (Shard 6/8)
E2E Tests (Shard 7/8)
E2E Tests (Shard 8/8)
Run details
Usage
Workflow file

Triggered via push 13 minutes ago

zachatkinson pushed -o 6c10e78 refactor/complete-rewrite

Status: In progress

Total duration: –

Artifacts: 4

ci.yml
on: push

E2E Setup 1m 31s
Matrix: e2e
4/8 jobs completed
Show all jobs
Quality Gate
Deploy
Security Scan 38s
Test & Quality 10m 27s
Performance Analysis 51s
Accessibility Tests 43s

Annotations

40 errors and 4 notices

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:345:5 › Configuration System E2E › Accessibility Integration › should respect reduced motion preferences: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
1) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:345:5 › Configuration System E2E › Accessibility Integration › should respect reduced motion preferences
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6144
    [pid=6144][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6144
      - [pid=6144][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:288:5 › Configuration System E2E › Responsive Configuration › should apply responsive defaults based on viewport: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
3) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:288:5 › Configuration System E2E › Responsive Configuration › should apply responsive defaults based on viewport

    Retry #2 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6387
    [pid=6387][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6387
      - [pid=6387][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:288:5 › Configuration System E2E › Responsive Configuration › should apply responsive defaults based on viewport: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
3) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:288:5 › Configuration System E2E › Responsive Configuration › should apply responsive defaults based on viewport

    Retry #1 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6254
    [pid=6254][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6254
      - [pid=6254][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:288:5 › Configuration System E2E › Responsive Configuration › should apply responsive defaults based on viewport: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
3) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:288:5 › Configuration System E2E › Responsive Configuration › should apply responsive defaults based on viewport
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6128
    [pid=6128][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6128
      - [pid=6128][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:255:5 › Configuration System E2E › Defaults Management › should handle large slide sets intelligently: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
2) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:255:5 › Configuration System E2E › Defaults Management › should handle large slide sets intelligently

    Retry #2 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6425
    [pid=6425][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6425
      - [pid=6425][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:255:5 › Configuration System E2E › Defaults Management › should handle large slide sets intelligently: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
2) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:255:5 › Configuration System E2E › Defaults Management › should handle large slide sets intelligently

    Retry #1 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6285
    [pid=6285][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6285
      - [pid=6285][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:255:5 › Configuration System E2E › Defaults Management › should handle large slide sets intelligently: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
2) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:255:5 › Configuration System E2E › Defaults Management › should handle large slide sets intelligently
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6179
    [pid=6179][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6179
      - [pid=6179][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:209:5 › Configuration System E2E › Defaults Management › should apply intelligent defaults: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
1) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:209:5 › Configuration System E2E › Defaults Management › should apply intelligent defaults

    Retry #2 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6483
    [pid=6483][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6483
      - [pid=6483][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:209:5 › Configuration System E2E › Defaults Management › should apply intelligent defaults: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
1) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:209:5 › Configuration System E2E › Defaults Management › should apply intelligent defaults

    Retry #1 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6314
    [pid=6314][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6314
      - [pid=6314][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:209:5 › Configuration System E2E › Defaults Management › should apply intelligent defaults: src/__tests__/e2e/configuration-system.e2e.test.ts#L0

```
1) [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:209:5 › Configuration System E2E › Defaults Management › should apply intelligent defaults
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6165
    [pid=6165][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6165
      - [pid=6165][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:38:5 › Accessibility Implementation › Accessibility Manager Integration › should announce slide changes to screen readers: src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts#L0

```
3) [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:38:5 › Accessibility Implementation › Accessibility Manager Integration › should announce slide changes to screen readers

    Retry #2 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6442
    [pid=6442][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6442
      - [pid=6442][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:38:5 › Accessibility Implementation › Accessibility Manager Integration › should announce slide changes to screen readers: src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts#L0

```
3) [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:38:5 › Accessibility Implementation › Accessibility Manager Integration › should announce slide changes to screen readers

    Retry #1 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6311
    [pid=6311][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6311
      - [pid=6311][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:38:5 › Accessibility Implementation › Accessibility Manager Integration › should announce slide changes to screen readers: src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts#L0

```
3) [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:38:5 › Accessibility Implementation › Accessibility Manager Integration › should announce slide changes to screen readers
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6177
    [pid=6177][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6177
      - [pid=6177][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:24:5 › Accessibility Implementation › Accessibility Manager Integration › should initialize with proper ARIA attributes: src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts#L0

```
2) [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:24:5 › Accessibility Implementation › Accessibility Manager Integration › should initialize with proper ARIA attributes

    Retry #2 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6397
    [pid=6397][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6397
      - [pid=6397][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:24:5 › Accessibility Implementation › Accessibility Manager Integration › should initialize with proper ARIA attributes: src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts#L0

```
2) [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:24:5 › Accessibility Implementation › Accessibility Manager Integration › should initialize with proper ARIA attributes

    Retry #1 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6267
    [pid=6267][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6267
      - [pid=6267][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:24:5 › Accessibility Implementation › Accessibility Manager Integration › should initialize with proper ARIA attributes: src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts#L0

```
2) [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:24:5 › Accessibility Implementation › Accessibility Manager Integration › should initialize with proper ARIA attributes
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6151
    [pid=6151][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6151
      - [pid=6151][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation: src/__tests__/e2e/slider-core.e2e.test.ts#L821

```
1) [Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation

    Retry #2 ───────────────────────────────────────────────────────────
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   7648

      819 |
      820 |       // Should complete within reasonable time (less than 5 seconds)
    > 821 |       expect(duration).toBeLessThan(5000);
          |                        ^
      822 |
      823 |       // Slider should still be responsive
      824 |       await expect(_slider).toBeVisible();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/slider-core.e2e.test.ts:821:26
```

Show less

[Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation: src/__tests__/e2e/slider-core.e2e.test.ts#L821

```
1) [Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation

    Retry #1 ───────────────────────────────────────────────────────────
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   11634

      819 |
      820 |       // Should complete within reasonable time (less than 5 seconds)
    > 821 |       expect(duration).toBeLessThan(5000);
          |                        ^
      822 |
      823 |       // Slider should still be responsive
      824 |       await expect(_slider).toBeVisible();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/slider-core.e2e.test.ts:821:26
```

Show less

[Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation: src/__tests__/e2e/slider-core.e2e.test.ts#L0

```
1) [Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation

    Retry #1 ───────────────────────────────────────────────────────────
    Test timeout of 30000ms exceeded.
```

Show less

[Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation: src/__tests__/e2e/slider-core.e2e.test.ts#L821

```
1) [Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   8084

      819 |
      820 |       // Should complete within reasonable time (less than 5 seconds)
    > 821 |       expect(duration).toBeLessThan(5000);
          |                        ^
      822 |
      823 |       // Slider should still be responsive
      824 |       await expect(_slider).toBeVisible();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/slider-core.e2e.test.ts:821:26
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:711:5 › NavigationManager E2E Tests › Navigation Configuration › should configure swipe sensitivity: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
4) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:711:5 › NavigationManager E2E Tests › Navigation Configuration › should configure swipe sensitivity
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6228
    [pid=6228][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6228
      - [pid=6228][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:658:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle mouse navigation: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
3) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:658:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle mouse navigation

    Retry #2 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6438
    [pid=6438][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6438
      - [pid=6438][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:658:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle mouse navigation: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
3) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:658:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle mouse navigation

    Retry #1 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6312
    [pid=6312][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6312
      - [pid=6312][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:658:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle mouse navigation: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
3) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:658:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle mouse navigation
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6199
    [pid=6199][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6199
      - [pid=6199][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:609:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle keyboard navigation: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
2) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:609:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle keyboard navigation

    Retry #2 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6471
    [pid=6471][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6471
      - [pid=6471][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:609:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle keyboard navigation: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
2) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:609:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle keyboard navigation

    Retry #1 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6348
    [pid=6348][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6348
      - [pid=6348][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:609:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle keyboard navigation: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
2) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:609:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle keyboard navigation
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6155
    [pid=6155][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6155
      - [pid=6155][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:576:5 › NavigationManager E2E Tests › Touch and Gesture Navigation › should provide touch feedback: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
1) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:576:5 › NavigationManager E2E Tests › Touch and Gesture Navigation › should provide touch feedback

    Retry #2 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6444
    [pid=6444][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6444
      - [pid=6444][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:576:5 › NavigationManager E2E Tests › Touch and Gesture Navigation › should provide touch feedback: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
1) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:576:5 › NavigationManager E2E Tests › Touch and Gesture Navigation › should provide touch feedback

    Retry #1 ───────────────────────────────────────────────────────────
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6325
    [pid=6325][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6325
      - [pid=6325][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:576:5 › NavigationManager E2E Tests › Touch and Gesture Navigation › should provide touch feedback: src/__tests__/e2e/navigation-manager.e2e.test.ts#L0

```
1) [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:576:5 › NavigationManager E2E Tests › Touch and Gesture Navigation › should provide touch feedback
    Error: browserType.launch: Target page, context or browser has been closed
    Browser logs:

    <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
    <launched> pid=6283
    [pid=6283][err] Cannot parse arguments: Unknown option --no-sandbox
    Call log:
      - <launching> /home/runner/.cache/ms-playwright/webkit-2191/pw_run.sh --inspector-pipe --headless --no-startup-window --no-sandbox --disable-dev-shm-usage --disable-web-security --disable-features=TranslateUI --disable-ipc-flooding-protection --disable-backgrounding-occluded-windows --disable-renderer-backgrounding --disable-field-trial-config --disable-background-timer-throttling
      - <launched> pid=6283
      - [pid=6283][err] Cannot parse arguments: Unknown option --no-sandbox
```

Show less

[Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:370:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should trigger warnings and critical thresholds appropriately: src/__tests__/e2e/performance-monitor.e2e.test.ts#L0

```
3) [Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:370:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should trigger warnings and critical thresholds appropriately

    Retry #2 ───────────────────────────────────────────────────────────
    Test timeout of 30000ms exceeded.
```

Show less

[Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:370:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should trigger warnings and critical thresholds appropriately: src/__tests__/e2e/performance-monitor.e2e.test.ts#L0

```
3) [Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:370:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should trigger warnings and critical thresholds appropriately

    Retry #1 ───────────────────────────────────────────────────────────
    Test timeout of 30000ms exceeded.
```

Show less

[Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:370:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should trigger warnings and critical thresholds appropriately: src/__tests__/e2e/performance-monitor.e2e.test.ts#L0

```
3) [Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:370:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should trigger warnings and critical thresholds appropriately
    Test timeout of 30000ms exceeded.
```

Show less

[Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping: src/__tests__/e2e/loop-manager.e2e.test.ts#L680

```
1) [Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping

    Retry #2 ───────────────────────────────────────────────────────────
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   12274

      678 |
      679 |       // Should complete within reasonable time
    > 680 |       expect(duration).toBeLessThan(5000);
          |                        ^
      681 |
      682 |       // System should still be responsive
      683 |       await expect(_slider).toBeVisible();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/loop-manager.e2e.test.ts:680:24
```

Show less

[Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping: src/__tests__/e2e/loop-manager.e2e.test.ts#L680

```
1) [Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping

    Retry #1 ───────────────────────────────────────────────────────────
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   17169

      678 |
      679 |       // Should complete within reasonable time
    > 680 |       expect(duration).toBeLessThan(5000);
          |                        ^
      681 |
      682 |       // System should still be responsive
      683 |       await expect(_slider).toBeVisible();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/loop-manager.e2e.test.ts:680:24
```

Show less

[Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping: src/__tests__/e2e/loop-manager.e2e.test.ts#L0

```
1) [Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping

    Retry #1 ───────────────────────────────────────────────────────────
    Test timeout of 30000ms exceeded.
```

Show less

[Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping: src/__tests__/e2e/loop-manager.e2e.test.ts#L680

```
1) [Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   11669

      678 |
      679 |       // Should complete within reasonable time
    > 680 |       expect(duration).toBeLessThan(5000);
          |                        ^
      681 |
      682 |       // System should still be responsive
      683 |       await expect(_slider).toBeVisible();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/loop-manager.e2e.test.ts:680:24
```

Show less

[Mobile Chrome] › src/__tests__/e2e/complete-system.test.ts:692:5 › Complete System E2E › User Workflows › Complete User Journey Integration › should maintain usability during rapid user interactions: src/__tests__/e2e/complete-system.test.ts#L723

```
1) [Mobile Chrome] › src/__tests__/e2e/complete-system.test.ts:692:5 › Complete System E2E › User Workflows › Complete User Journey Integration › should maintain usability during rapid user interactions

    Retry #2 ───────────────────────────────────────────────────────────
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   5717

      721 |
      722 |       // Should remain responsive for user (performance requirement)
    > 723 |       expect(duration).toBeLessThan(5000);
          |                        ^
      724 |
      725 |       // Slider should still be interactive
      726 |       await _slider.focus();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/complete-system.test.ts:723:24
```

Show less

[Mobile Chrome] › src/__tests__/e2e/complete-system.test.ts:692:5 › Complete System E2E › User Workflows › Complete User Journey Integration › should maintain usability during rapid user interactions: src/__tests__/e2e/complete-system.test.ts#L723

```
1) [Mobile Chrome] › src/__tests__/e2e/complete-system.test.ts:692:5 › Complete System E2E › User Workflows › Complete User Journey Integration › should maintain usability during rapid user interactions

    Retry #1 ───────────────────────────────────────────────────────────
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   11018

      721 |
      722 |       // Should remain responsive for user (performance requirement)
    > 723 |       expect(duration).toBeLessThan(5000);
          |                        ^
      724 |
      725 |       // Slider should still be interactive
      726 |       await _slider.focus();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/complete-system.test.ts:723:24
```

Show less

[Mobile Chrome] › src/__tests__/e2e/complete-system.test.ts:692:5 › Complete System E2E › User Workflows › Complete User Journey Integration › should maintain usability during rapid user interactions: src/__tests__/e2e/complete-system.test.ts#L723

```
1) [Mobile Chrome] › src/__tests__/e2e/complete-system.test.ts:692:5 › Complete System E2E › User Workflows › Complete User Journey Integration › should maintain usability during rapid user interactions
    Error: expect(received).toBeLessThan(expected)

    Expected: < 5000
    Received:   7858

      721 |
      722 |       // Should remain responsive for user (performance requirement)
    > 723 |       expect(duration).toBeLessThan(5000);
          |                        ^
      724 |
      725 |       // Slider should still be interactive
      726 |       await _slider.focus();
        at /home/runner/work/kineticslider/kineticslider/src/__tests__/e2e/complete-system.test.ts:723:24
```

Show less

🎭 Playwright Run Summary

```
  171 failed
    [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:209:5 › Configuration System E2E › Defaults Management › should apply intelligent defaults
    [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:255:5 › Configuration System E2E › Defaults Management › should handle large slide sets intelligently
    [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:288:5 › Configuration System E2E › Responsive Configuration › should apply responsive defaults based on viewport
    [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:345:5 › Configuration System E2E › Accessibility Integration › should respect reduced motion preferences
    [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:397:5 › Configuration System E2E › Error Reporting › should provide detailed error information
    [webkit] › src/__tests__/e2e/configuration-system.e2e.test.ts:444:5 › Configuration System E2E › Performance Validation › should handle configuration processing efficiently
    [webkit] › src/__tests__/e2e/debug-console.test.ts:3:1 › debug console logs ──────────────────
    [webkit] › src/__tests__/e2e/error-handling.test.ts:19:5 › Error Handling E2E › Network and Resource Errors › should handle missing image resources gracefully
    [webkit] › src/__tests__/e2e/error-handling.test.ts:37:5 › Error Handling E2E › Network and Resource Errors › should show loading state for slow resources
    [webkit] › src/__tests__/e2e/error-handling.test.ts:78:5 › Error Handling E2E › Runtime Errors and Recovery › should recover from temporary errors
    [webkit] › src/__tests__/e2e/error-handling.test.ts:104:5 › Error Handling E2E › Runtime Errors and Recovery › should provide retry functionality
    [webkit] › src/__tests__/e2e/error-handling.test.ts:160:5 › Error Handling E2E › Configuration Errors › should handle invalid configuration gracefully
    [webkit] › src/__tests__/e2e/error-handling.test.ts:190:5 › Error Handling E2E › Accessibility in Error States › should announce errors to screen readers
    [webkit] › src/__tests__/e2e/error-handling.test.ts:220:5 › Error Handling E2E › Accessibility in Error States › should maintain keyboard navigation in error states
    [webkit] › src/__tests__/e2e/error-handling.test.ts:272:5 › Error Handling E2E › Performance Under Error Conditions › should not cause memory leaks during error recovery
    [webkit] › src/__tests__/e2e/error-handling.test.ts:322:5 › Error Handling E2E › Performance Under Error Conditions › should maintain responsiveness during error handling
    [webkit] › src/__tests__/e2e/filter-system-essential.e2e.test.ts:16:3 › Filter System E2E (Essential) › should load filter system UI components @smoke
    [webkit] › src/__tests__/e2e/filter-system-essential.e2e.test.ts:38:3 › Filter System E2E (Essential) › should open filter dropdown and show available filters @critical
    [webkit] › src/__tests__/e2e/filter-system-essential.e2e.test.ts:54:3 › Filter System E2E (Essential) › should handle basic filter workflow without crashing
    [webkit] › src/__tests__/e2e/keyboard-navigation.e2e.test.ts:19:5 › Keyboard Navigation E2E › should handle accessibility navigation flow
    [webkit] › src/__tests__/e2e/keyboard-navigation.e2e.test.ts:96:5 › Keyboard Navigation E2E › should handle escape key for accessibility
    [webkit] › src/__tests__/e2e/keyboard-navigation.e2e.test.ts:114:5 › Keyboard Navigation E2E › should announce slide changes to screen readers
    [webkit] › src/__tests__/e2e/keyboard-navigation.e2e.test.ts:152:5 › Keyboard Navigation E2E › should support keyboard shortcuts
    [webkit] › src/__tests__/e2e/keyboard-navigation.e2e.test.ts:208:5 › Keyboard Navigation E2E › should handle number key navigation
    [webkit] › src/__tests__/e2e/loop-manager.e2e.test.ts:15:5 › LoopManager E2E Tests › Infinite Loop Behavior › should loop from last slide to first slide seamlessly
    [webkit] › src/__tests__/e2e/loop-manager.e2e.test.ts:90:5 › LoopManager E2E Tests › Infinite Loop Behavior › should loop from first
```

Show more

🎭 Playwright Run Summary

```
  117 failed
    [Mobile Chrome] › src/__tests__/e2e/slider-core.e2e.test.ts:803:5 › Core Slider Functionality › Performance › should maintain smooth transitions during rapid navigation
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:24:5 › Accessibility Implementation › Accessibility Manager Integration › should initialize with proper ARIA attributes
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:38:5 › Accessibility Implementation › Accessibility Manager Integration › should announce slide changes to screen readers
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:63:5 › Accessibility Implementation › Keyboard Navigation Support › should support arrow key navigation
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:79:5 › Accessibility Implementation › Keyboard Navigation Support › should support space bar for play/pause
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:99:5 › Accessibility Implementation › Keyboard Navigation Support › should support escape key
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:115:5 › Accessibility Implementation › Motion Preference Handling › should respect prefers-reduced-motion setting
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:131:5 › Accessibility Implementation › Focus Management System › should manage focus correctly
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:147:5 › Accessibility Implementation › Screen Reader Compatibility › should provide proper ARIA announcements
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:161:5 › Accessibility Implementation › Screen Reader Compatibility › should update ARIA attributes on slide change
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:180:5 › Accessibility Implementation › Feature Integration › should maintain accessibility during transitions
    [Mobile Safari] › src/__tests__/e2e/accessibility-comprehensive.e2e.test.ts:199:5 › Accessibility Implementation › Basic Accessibility Compliance › should have basic WCAG 2.1 AA compliance elements
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:12:5 › Accessibility E2E › ARIA and Screen Reader Integration › should coordinate keyboard navigation with screen reader announcements
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:41:5 › Accessibility E2E › ARIA and Screen Reader Integration › should provide proper ARIA attributes and focus management
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:67:5 › Accessibility E2E › ARIA and Screen Reader Integration › should respect motion preferences in gesture handling
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:88:5 › Accessibility E2E › ARIA and Screen Reader Integration › should handle high contrast mode
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:108:5 › Accessibility E2E › Keyboard Navigation › should handle all keyboard interactions
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:173:5 › Accessibility E2E › Keyboard Navigation › should handle WASD navigation
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:235:5 › Accessibility E2E › Keyboard Navigation › should provide keyboard instructions
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:254:5 › Accessibility E2E › Screen Reader Compatibility › should provide meaningful announcements
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:273:5 › Accessibility E2E › Screen Reader Compatibility › should update aria-valuenow and aria-valuetext
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:341:5 › Accessibility E2E › Mobile Accessibility › should work with touch and voice controls
    [Mobile Safari] › src/__tests__/e2e/accessibility.test.ts:363:5 › Accessibility E2E › Mobile Accessibility › should maintain accessibility in po
```

Show less

🎭 Playwright Run Summary

```
  114 failed
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:576:5 › NavigationManager E2E Tests › Touch and Gesture Navigation › should provide touch feedback
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:609:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle keyboard navigation
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:656:5 › NavigationManager E2E Tests › Navigation Configuration › should toggle mouse navigation
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:711:5 › NavigationManager E2E Tests › Navigation Configuration › should configure swipe sensitivity
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:750:5 › NavigationManager E2E Tests › Navigation Accessibility › should provide screen reader announcements for navigation
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:781:5 › NavigationManager E2E Tests › Navigation Accessibility › should have proper ARIA attributes
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:802:5 › NavigationManager E2E Tests › Navigation Accessibility › should support high contrast mode
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:824:5 › NavigationManager E2E Tests › Navigation Accessibility › should handle focus management
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:851:5 › NavigationManager E2E Tests › Navigation Error Handling › should handle invalid navigation attempts
    [Mobile Safari] › src/__tests__/e2e/navigation-manager.e2e.test.ts:877:5 › NavigationManager E2E Tests › Navigation Error Handling › should recover from navigation failures
    [Mobile Safari] › src/__tests__/e2e/navigation-swipe-gestures.e2e.test.ts:17:3 › Navigation Swipe Gestures E2E › should detect left swipe gesture for next slide
    [Mobile Safari] › src/__tests__/e2e/navigation-swipe-gestures.e2e.test.ts:60:3 › Navigation Swipe Gestures E2E › should detect right swipe gesture for previous slide
    [Mobile Safari] › src/__tests__/e2e/navigation-swipe-gestures.e2e.test.ts:107:3 › Navigation Swipe Gestures E2E › should detect touch swipe on mobile
    [Mobile Safari] › src/__tests__/e2e/performance-monitor.e2e.test.ts:20:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should detect performance degradation during heavy operations
    [Mobile Safari] › src/__tests__/e2e/performance-monitor.e2e.test.ts:126:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should detect memory leaks over extended periods
    [Mobile Safari] › src/__tests__/e2e/performance-monitor.e2e.test.ts:247:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should provide accurate performance trend analysis
    [Mobile Safari] › src/__tests__/e2e/performance-monitor.e2e.test.ts:370:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should trigger warnings and critical thresholds appropriately
    [Mobile Safari] › src/__tests__/e2e/performance-monitor.e2e.test.ts:555:5 › PerformanceMonitor E2E › Performance Monitoring Integration › should integrate with rendering pipeline for real-time monitoring
    [Mobile Safari] › src/__tests__/e2e/physics-e2e.test.ts:44:5 › Physics E2E Tests › Physics-Driven User Interactions › should handle complete drag-to-momentum-to-snap user workflow
    [Mobile Safari] › src/__tests__/e2e/physics-e2e.test.ts:111:5 › Physics E2E Tests › Physics-Driven User Interactions › should handle physics-based gesture recognition
    [Mobile Safari] › src/__tests__/e2e/physics-e2e.test.ts:149:5 › Physics E2E Tests › Physics-Driven User Interactions › should handle spring-based displacement corrections in browser
    [Mobile Safari] › src/__tests__/e2e/physics-e2e.test.ts:189:5 › Physics E2E Tests › Physics-Driven User Interactions › should coordinate GSAP timeline sequencing in real browser
    [Mobile Safari] › src/__tests__/e2e/physics-e2e.test.ts:291:5 › Physics E2E Tests › Physics Performance in Browser
```

Show less

🎭 Playwright Run Summary

```
  7 failed
    [Mobile Chrome] › src/__tests__/e2e/complete-system.test.ts:692:5 › Complete System E2E - User Workflows › Complete User Journey Integration › should maintain usability during rapid user interactions
    [Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:662:5 › LoopManager E2E Tests › Loop Performance › should maintain smooth performance during rapid looping
    [Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:370:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should trigger warnings and critical thresholds appropriately
    [Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:555:5 › PerformanceMonitor E2E › Performance Monitoring Integration › should integrate with rendering pipeline for real-time monitoring
    [Mobile Chrome] › src/__tests__/e2e/physics-e2e.test.ts:291:5 › Physics E2E Tests › Physics Performance in Browser › should maintain good performance during physics-heavy interactions
    [Mobile Chrome] › src/__tests__/e2e/physics-e2e.test.ts:329:5 › Physics E2E Tests › Physics Performance in Browser › should handle rapid gesture sequences without performance degradation
    [Mobile Chrome] › src/__tests__/e2e/physics-e2e.test.ts:472:5 › Physics E2E Tests › Cross-Browser Physics Consistency › should maintain consistent velocity calculations across browsers
  5 flaky
    [Mobile Chrome] › src/__tests__/e2e/error-handling.test.ts:321:5 › Error Handling E2E › Performance Under Error Conditions › should maintain responsiveness during error handling
    [Mobile Chrome] › src/__tests__/e2e/keyboard-navigation.e2e.test.ts:19:3 › Keyboard Navigation E2E › should handle accessibility navigation flow
    [Mobile Chrome] › src/__tests__/e2e/loop-manager.e2e.test.ts:19:5 › LoopManager E2E Tests › Infinite Loop Behavior › should loop from last slide to first slide seamlessly
    [Mobile Chrome] › src/__tests__/e2e/performance-monitor.e2e.test.ts:20:5 › PerformanceMonitor E2E › Real-World Performance Monitoring › should detect performance degradation during heavy operations
    [Mobile Chrome] › src/__tests__/e2e/resource-loader.e2e.test.ts:416:5 › ResourceLoader E2E › Advanced Async Workflows › should handle concurrent loading with throttling
  160 passed (8.6m)
```

Show less

Artifacts

Produced during runtime

Name	Size	Digest
playwright-report-shard-4	1.68 MB	sha256:8802835b7c3f71ba9cb67aeda5d9be4ceb51c6df7dd2b419…
playwright-report-shard-5	73.5 MB	sha256:7ea3c2e4e02af56217304299b8c07a5ba705189fc82cf8ef…
playwright-report-shard-6	12.5 MB	sha256:863d69dd123b9a871118ee86ce71eac9433b6166f9f2eed0…
playwright-report-shard-7	16.3 MB	sha256:95de84953e9f434a3ec6a0ee995e7557fa97e939b7a0d8cd…