

MODEL NO. GBC048A3EMB0900000000000000000000000000
SERIAL NO. 22023812PA
DATE OF MFG. 1-22

GAS-FIRED



**LISTED COOLING PORTION OF
HEATING AND COOLING UNIT. GAS
HEATING PORTION CLASSIFIED BY
UL IN ACCORDANCE WITH
ANSI Z21.47-2016 / CSA 2.3-2016.**

ELECTRICAL DATA

ELECTRICAL RATING	208-230V/60HZ/3PH	OPERATING VOLT. RANGE	187-253V
CONTROL CIRCUIT VOLTS	24 VAC		
MIN. CIRCUIT AMPACITY	24 AMPS		
MAX. OVERCURRENT PROT.	35 AMPS		

	QTY	PH	HZ	RLA-VOLTS	LRA
COMPR#1	1	3	60	13.7-208	83
COMPR#2					

FAN(S)	QTY	PH	HZ	FLA-VOLTS	HP
COND.	1	1	60	1.4-208	.3 (.2 KW)
EVAP. STD	1	3	60	5.0-208	1.0 (.8 KW)
EVAP. O/S	1	3	60	6.1-208	2.0 (1.5 KW)

SCRATCH INK OFF SQUARE WHEN OVERSIZE MOTOR IS INSTALLED

COOLING DATA

R410A FACTORY CHARGED	MIN TEST PRESSURE
CIRCUIT#1- 3.70 LBS. (1.68 KG)	HIGH - 449 PSIG (3096 KPA)
CIRCUIT#2- .00 LBS. (.00 KG)	LOW - 238 PSIG (1641 KPA)

HEATING DATA – UNIT EQUIPPED FOR NATURAL GAS

RATED HEATING INPUT	115000 BTUH (34 KW)
HEATING OUTPUT	92000 BTUH (27 KW)
MIN HEATING INPUT	92000 BTUH (27 KW)
TEMP RISE	50-80 DEG F (28-44 DEG C)
MAX OUTLET AIR TEMP	180 DEG F (82 DEG C)
MAX EXT STATIC PRESS.	1.5 IN.W.C. (373.30 PA)
MAX GAS SUPPLY PRESS.	14 IN. W.C. (3487 PA)
MIN GAS SUPPLY PRESS. FOR INPUT ADJ	4.5 IN. W.C. (1120 PA)
MIN AMBIENT TEMP	-40 DEG F (-40 DEG C)
FACTORY EQUIPPED FOR USE AT ALTITUDES	OF UP TO 2000 FT. (610 M)
CANADA ONLY:	FROM 2000-4500 FT (610-1370 M),
	INPUT IS 90% OF SEA LEVEL

MANIFOLD PRESS.	3.5 IN. W.C. (871.8 PA)
ORIFICE DRILL SIZE	.120 IN. (2.95 MM)

**FOR INSTALLATION ON COMBUSTIBLE FLOORING OR A,B,C ROOF COVERING MATERIAL.
CLEARANCES TO COMBUSTIBLE MATERIAL: TOP-NO OBSTRUCTIONS;
L.SIDE-24IN. (610 MM); R. SIDE-24IN. (610 MM); FRONT-24IN. (610 MM); BACK-18IN. (457
MM)**

THIS UNIT SHOULD BE INSTALLED AND REGULARLY MAINTAINED IN ACCORDANCE WITH THE SERVICE LITERATURE MANUAL(S).

FOUNDATION™

43872461 Rev D

ASSEMBLED IN MEXICO

X39002718010



CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

[illegible]