

Carrier  
Corporation

111--

0002010139

Carrier

FACTORY CHARGED

| REF. | SYSTEM  | R-22 | TEST PRESSURE | GAGE |
|------|---------|------|---------------|------|
| 1    | 208/230 | 3 60 | 16.0          | 114  |
| 2    | 208/230 | 3 60 | 7.9           | 114  |
| 3    | 208/230 | 3 60 | 3.6           | 114  |
| 4    | 208/230 | 3 60 | 1.4           | 114  |
| 5    | 208/230 | 3 60 | 5.7           | 114  |
| 6    | 208/230 | 3 60 | 0.6           | 114  |

| REF. | SYSTEM  | R-22 | TEST PRESSURE | GAGE |
|------|---------|------|---------------|------|
| 1    | 208/230 | 3 60 | 16.0          | 114  |
| 2    | 208/230 | 3 60 | 7.9           | 114  |
| 3    | 208/230 | 3 60 | 3.6           | 114  |
| 4    | 208/230 | 3 60 | 1.4           | 114  |
| 5    | 208/230 | 3 60 | 5.7           | 114  |
| 6    | 208/230 | 3 60 | 0.6           | 114  |

OPERATION INSTRUCTIONS  
FOR SERVICE PERSONNEL ONLY

POWER SUPPLY 208/230 3 PH 60 HZ  
PERMISSIBLE VOLTAGE AT UNIT 254

MINIMUM CLEARANCES TO COMBUSTIBLE MATERIALS

| TOP    | BOTTOM       | DES    | FLUE SIDE  |
|--------|--------------|--------|------------|
| 31.0MM | 1.0IN 25.4MM | 61.0MM | 38IN 914MM |

DO NOT INSTALL ON UNSTABLE FLOORING OR CLAY, ASPH, OR C ROOFING MATERIAL

DO NOT INSTALL ON UNSTABLE FLOORING OR CLAY, ASPH, OR C ROOFING MATERIAL

35

MINIMUM TO CONNECT LRA

26

48

CONNECTION OF THE  
AND SERVICE UNIT

DO NOT FORGET THE SERVICE UNIT  
DO NOT FORGET THE SERVICE UNIT

DO NOT FORGET THE SERVICE UNIT 185F 85C

DO NOT FORGET THE SERVICE UNIT

DO NOT FORGET THE SERVICE UNIT

DO NOT FORGET THE SERVICE UNIT

120000

150000

86000

26000

35.2

44.0

28.1

35.2

80

NATUR

13WC 3.23KPA MAX 5WC 1.24KPA

2.2-3.5WC 0.55-0.87KPA

DO NOT FORGET THE SERVICE UNIT

DO NOT FORGET THE SERVICE UNIT

111--



LISTED

DO NOT FORGET THE SERVICE UNIT

