CS 4390: HW 3

Written by Zach Leach, NetID: zcl190002

Draft February 20, 2024

1 Data Rate Problem

It is desired to send a sequence of computer screen images over optical fiber. The screen is 3840×2160 pixels, each pixel being 24 bits. There are 60 screen images per second. What data rate is needed?

 $Data Rate = \frac{Number of bits}{Bits per second}$

There are 24 bits \cdot (3840 \times 2160) = 199,065,600 bits per image. Transmitting 60 images per second gives a data rate of data rate is 60 \cdot 199,065,600 = $\underline{1.194 \cdot 10^{10}}$ bits per second.

2 FDM Multiplexing Problem

Ten signals, each requiring 4000 Hz, are multiplexed onto a single channel using FDM. What is the minimum bandwidth required for the multiplexed channel? Assume that the guard bands are 400 Hz wide.

NEED TO FIX THIS

The minimum bandwidth required is $[10 \cdot 4000 \text{Hz}] + [(9) \cdot 400 \text{Hz}] = 43,600 \text{ Hz}.$

3 Analog Sampling Data Rate Problem

A 3-kHz (analog) signal is sampled every 1 msec. What is the (minimum) data rate of a digital channel required to carry this signal? Assume that the quantization uses 256 levels.

The minimum data rate is $2 \times (3 \cdot 10^3) \times \log_2(256)$ = 48,000 bits per second.

4 Network Topology Problem

Three packet-switching networks each contain n nodes. The first network has a star topology with a central switch, the second is a (bidirectional) ring, and the third is fully interconnected, with a wire from every node to every other node. What are the best-, average-, and worst-case transmission paths in hops?




Figure 2-29. (a) Fully interconnected network. (b) Centralized switch. (c) Two-level hierarchy.

The best-, average-, and worst-case for star topology with central switch is 2 hops (e.g., the hop from source to central switch, then from central switch to the destination).

The best-

Minimum Data Rate = $2 \times \text{Bandwidth} \times \log_2(\# \text{ of Q-Levels})$