

LABORATORY LAB 8F

ZACH N. SAGOSO

```
#include <iostream>

#include <string>

// note: j for row (month) and i for column (outlet)

using namespace std;

int main() {
    int outlet = 5;
    int months = 12;

    string monthNames[months] = { "Jan", "Feb", "Mar", "Apr", "May", "Jun",
        "Jul", "Aug", "Sep", "Oct", "Nov", "Dec" };

    double sales[outlet][months];
    double outletTotal[outlet] = {0};
    double monthTotal[months] = {0};

    cout << "enter sales performance from jan to dec : " << endl << endl;

    for (int i = 0; i < outlet; i++) {
        cout << "OUTLET NUMBER " << (i + 1) << endl;

        for (int j = 0; j < months; j++) {
            cout << "    " << monthNames[j] << " P";

            cin >> sales[i][j];
```

```

        outletTotal[i] = outletTotal[i] + sales[i][j];
        monthTotal[j] = monthTotal[j] + sales[i][j];
    }
    cout << endl << endl;
}

cout << "\t\t\t\t" << "ABC Corporation" << endl;
cout << "\t\t\t\t" << "General Santos City" << endl << endl;

cout << "OutletNo";

for (int j = 0; j < months; j++) {
    cout << "\t" << monthNames[j];
}
cout << "\tTotal Sales" << endl;

for (int i = 0; i < outlet; i++) {
    cout << (i + 1);
    for (int j = 0; j < months; j++) {
        cout << "\t" << sales[i][j];
    }
    cout << "\t" << outletTotal[i] << endl << endl;
}

cout << "Total Sales/Month";
for (int j = 0; j < months; j++) {
    cout << "\t" << monthTotal[j];
}
cout << endl << endl;

```

```

int highestOutlet = 0;
int lowestOutlet = 0;

for (int i = 1; i < outlet; i++) {
    if (outletTotal[i] > outletTotal[highestOutlet]) {
        highestOutlet = i;
    }
    if (outletTotal[i] < outletTotal[lowestOutlet]) {
        lowestOutlet = i;
    }
}

int highestMonthIdx = 0;
int lowestMonthIdx = 0;

for (int j = 1; j < months; j++) {
    if (monthTotal[j] > monthTotal[highestMonthIdx]) {
        highestMonthIdx = j;
    }
    if (monthTotal[j] < monthTotal[lowestMonthIdx]) {
        lowestMonthIdx = j;
    }
}

cout << "Highest sales (Outlet) : " << (highestOutlet + 1) <<
"\t\tHighest sales (Month) : " << monthNames[highestMonthIdx] << endl;

cout << "Lowest sales (Outlet) : " << (lowestOutlet + 1) << "\t\tLowest
sales (Month) : " << monthNames[lowestMonthIdx] << endl;

return 0;
}

```