

INTEGRATED RESOURCE TRACKING SYSTEM

BACKGROUND INFORMATION

[0001] This application claims priority to, and is a non-provisional application based on, provisional application 62/134,898, filed March 18, 2015.

1. Field:

[0002] The illustrative embodiments relate to improved computers and computer networks, particularly server computers having an integrated resource tracking system and, more particularly, to a method and system which integrates multiple systems and applications together to determine trends by analyzing tags and/or keywords of multiple users over the multiple integrated systems and applications.

2. Background:

[0003] Organizations have always had a need to manage, organize, track, and direct its ongoing activities. The well-known status report has been one technique for organization management. Status reports may provide information on the status of a person, activity, thing, project, group, an entire organization, or many other things. Thus, for example, a status report may relay information regarding the state of projects within an organization in relation to an overall goal of the organization. In still another example, a periodic status report may enable a manager to track performance and progress by an individual. Other examples may include tracking projects within teams, supporting communication of teams to executive management, monitoring project progress, monitoring accomplishments,

identifying bottlenecks, and/or identifying blocks. Many other examples are possible.

[0004] Manual means for generating and tracking such reports are inadequate for modern organizations. In many cases, the process of manually generating or collating reports is undesirably time consuming. In some cases, consolidation and alignment of different reports is unavailable. Thus, there may not be visibility on peer and cross team activities, multi-member project information may be repeated without alignment, links to organization objectives may be intangible, and other problems may arise. Another difficulty with manual techniques is that data for reports may be out of date by the time the report is to be evaluated.

[0005] Progress has been made with respect to addressing these difficulties using automated techniques. For example, templates with drop-down entries or blanks may speed the report generation process. Programs such as OUTLOOK® may be used to track projects, deadlines, or work activities. Programs such as RALLY® may be used to track software development projects. Programs such as YAMMER® may be used to provide a specialized social networking service to help organize groups, share files, and collaborate on projects. Many different kinds of these such programs exist.

[0006] In fact, there has been a proliferation of enterprise, project management, report generation, and human resource capital programs. Some modern work environments may use many such programs, but the individual user must track the use of such programs. Currently, there is no mechanism for integrating such tools on a dynamic basis, tools which may be published or produced by a wide variety of different companies or

individuals. Often, integration of different such tools is impossible or impractical.

SUMMARY

[0007] The illustrative embodiments provide for a computer network. The computer network includes a server computer having a server processor and a server non-transitory computer readable storage medium. The computer network also includes a first computer, operable by a first user, in communication with the server computer. The first computer has a first processor and a first non-transitory computer readable storage medium storing first program code which, when executed by the first processor, implements a first software tool having a first function and a second software tool having a second function. The computer network also includes a second computer, operable by a second user, in communication with the server computer, the second computer having a second processor and a second non-transitory computer readable storage medium storing second program code which, when executed by the second processor, implements the first software tool having the first function and the second software tool having the second function. The server non-transitory computer readable storage medium stores third program code which, when executed by the server processor, is configured to gather first data regarding use of the first software tool; gather second data regarding use of the second software tool; and based on the first data and the second data, link activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first user and the second user belong. In executing the program code, a communications link between the first computer and the second computer is improved.

[0008] The illustrative embodiments also provide for an apparatus. The apparatus includes a server computer having a server processor and a server non-transitory computer readable storage medium. The server computer is in communication with a first computer, operable by a first user. The first computer has a first processor and a first non-transitory computer readable storage medium storing first program code which, when executed by the first processor, implements a first software tool having a first function and a second software tool having a second function. The server computer is in communication with a second computer, operable by a second user, the second computer having a second processor and a second non-transitory computer readable storage medium storing second program code which, when executed by the second processor, implements the first software tool having the first function and the second software tool having the second function. The server non-transitory computer readable storage medium stores third program code which, when executed by the server processor, is configured to: gather first data regarding use of the first software tool; gather second data regarding use of the second software tool; and based on the first data and the second data, link activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first user and the second user belong. In executing the program code, the server computer improves a communication links between the first computer and the second computer.

[0009] The illustrative embodiments also provide for a method implemented in a server computer having a server processor and a server non-transitory computer readable

storage medium, the server computer being in communication with a first computer, operable by a first user, wherein the first computer has a first processor and a first non-transitory computer readable storage medium storing first program code which, when executed by the first processor, implements a first software tool having a first function and a second software tool having a second function, the server computer being in communication with a second computer, operable by a second user, the second computer having a second processor and a second non-transitory computer readable storage medium storing second program code which, when executed by the second processor, implements the first software tool having the first function and the second software tool having the second function. The server non-transitory computer readable storage medium stores third program code which, when executed by the server processor, implements the method. The method includes gathering first data regarding use of the first software tool. The method also includes gathering second data regarding use of the second software tool. The method also includes improving, using the server computer, a communications link between the first computer and the second computer by linking, based on the first data and the second data, activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first user and the second user belong.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

[0011] **Figure 1** is an illustration of different roles of different individuals in an organization, in accordance with an illustrative embodiment;

[0012] **Figure 2** illustrates a resource tracking system, in accordance with an illustrative embodiment;

[0013] **Figure 3** illustrates a view of a resource tracking system, in accordance with an illustrative embodiment;

[0014] **Figure 4** illustrates a view of a resource tracking system, in accordance with an illustrative embodiment;

[0015] **Figure 5** illustrates a view of a resource tracking system, in accordance with an illustrative embodiment;

[0016] **Figure 6** illustrates a view of a resource tracking system, in accordance with an illustrative embodiment;

[0017] **Figure 7** is a graph illustrating an output of a resource tracking system, in accordance with an illustrative embodiment;

[0018] **Figure 8** is a relationship diagram illustrating an output of a resource tracking system, in accordance with an illustrative embodiment;

[0019] **Figure 9** is a status report output by a resource tracking system, in accordance with an illustrative embodiment;

[0020] **Figure 10** is a bar graph report output by a resource tracking system, in accordance with an illustrative embodiment;

[0021] **Figure 11** is a block diagram of an architecture of a resource tracking system, in accordance with an illustrative embodiment;

[0022] **Figure 12** is a block diagram illustrating details of the resource tracking system architecture shown in **Figure 11**, in accordance with an illustrative embodiment;

[0023] **Figure 13** is an example of an application programming interface usable in a resource tracking system, in accordance with an illustrative embodiment;

[0024] **Figure 14** is a block diagram of a resource tracking system, in accordance with an illustrative embodiment;

[0025] **Figure 15** is a flowchart of a method for performing resource tracking, in accordance with an illustrative embodiment;

[0026] **Figure 16** is a block diagram of a data processing system, in accordance with an illustrative embodiment;

[0027] **Figure 17** is a block diagram of a cloud environment, in accordance with an illustrative embodiment; and

[0028] **Figure 18** is a block diagram of a data processing system, in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

[0029] The illustrative embodiments recognize and take into account that a multiplicity of reporting, tracking, scheduling, and project management software may result in an unwieldy system for producing reports, tracking a project, monitoring individual performance or progress, or otherwise monitoring and tracking the performance of an organization.

[0030] The illustrative embodiments may, broadly speaking, be referred to as a tracker. The tracker is embodied as a physical machine, or as program code stored on a non-transitory computer readable storage medium which subsequently makes one or more computers perform more efficiently.

[0031] Purposes of the tracker of the illustrative embodiments may include enriching organization operations, consolidating real information about an organization, and providing metrics for leaders, managers, and individuals to ensure organization is aligned and individuals are on track to complete their tasks and responsibilities. The tracker of the illustrative embodiments aims to reduce or eliminate the process of manual status reporting by providing simple tools for parsing information about individual activities. By building a visual pinboard of 'My Work', individuals can quickly visualize their work life and work activity.

[0032] Thus, the tracker of the illustrative embodiments provides quick insights into the top trends within an organization. The tracker provides links to the tools an organization already uses, including third party applications. The tracker can integrate with numerous third party tools and may have an exposed

application programming interface (API) that allows third party applications to integrate with its activity feed. Default APIs may be provided for commonly used programs such as, but not limited to, RALLY®, OUTLOOK®, CONFLUENCE®, and YAMMER®.

[0033] In computer programming, an API is a set of routines, protocols, or tools used for building software applications. An API may express a software component in terms of its operations, inputs, outputs, and underlying types. An API may define functionalities that are independent of their respective implementations, which allows definitions and implementations to vary without compromising an interface. An API may make developing a software program easier by providing the building blocks for the software program. A programmer, or another software program, can then put the blocks together.

[0034] The tracker of the illustrative embodiments may bridge a gap between goal management and ongoing organization activity by allowing a user to link, manually or automatically, activities to defined goals. For example, users can manually select an activity feed from an external source, and link it to a given goal. In another example, users can automatically associate a tag or reference to a particular goal. When an activity comes in the feed with a link to that tag or reference, the activity may be automatically associated with the related goal.

[0035] The illustrative embodiments may provide quick insights into the trends within an organization by identifying tags and most common terms and word references through text and data mining. Trends can be measured on an overall company metric, by department, team, and individual.

[0036] The illustrative embodiments may show cross-departmental collaboration and alignment by assessing information about individuals collaborating together on a given activity. The illustrative embodiments may provide an up to date status-tracking tool that shows the overarching organizational activity in alignment to the overall organizational, team, and individual goals.

[0037] The functionality behind the tracker of the illustrative embodiments includes both product functionality and a new product. The functionality of the illustrative embodiments includes the ability to integrate external third party sources such as, but not limited to, CONFLUENCE®, OUTLOOK®, RALLY®, YAMMER®, and others, with an aggregator in order to perform one or more functions. These functions include the ability to track activities users perform on daily, weekly, monthly, and yearly bases; or, to find top trends within an organization.

[0038] The tracker of the illustrative embodiments may link relevant organization activity, such as the work workers perform on a daily and ongoing base, with human resources, performance, strategic planning, and talent management. The tracker may aggregate information from third party APIs and pool them to provide insights into the knowledge and work within the company. This knowledge then may be leveraged in order to identify the trending activities within a company and used to identify internal dialect, acronyms, and knowledge.

[0039] The tracker of the illustrative embodiments can also leverage the information gathered from third party integration tools in order to build out a competency catalog that is aligned with the work being done within the company. From a strategic management perspective, the tracker may provide insights into the types of

activities being performed in order to achieve various types of goals.

[0040] For example, the tracker can identify requirements for the goal to 'build a new product'. The product manager typically may spend the first few weeks of the goal's start dates doing research and meeting with the user experience and user interface teams. The product manager may also typically spend a few months after the start of a goal in a program such as RALLY®, building features and user stories, and in meetings with a scrum team. The product manager may also spend several months into the goal working with product marketing in order to build "go to market" trends.

[0041] From an individual review perspective, the tracker of the illustrative embodiments can provide a timeline of all the work an individual has done throughout the course of the performance cycle. In this context, the individual can view an interactive map that shows their work patterns, key collaborators, and overall accomplishments throughout the year.

[0042] The illustrative embodiments may also have the ability to integrate with reward and feedback modules, and may provide a tool for building or cascading strategic goals and defining performance review cycles. Beyond human resource data, the tracker of the illustrative embodiments can provide tools to link with project management and customer relationship management solutions in order to incorporate project plans, customer data, and related tasks into the tracker and its human resource processes.

[0043] **Figure 1** is an illustration of different roles of different individuals in an organization, in accordance with an illustrative embodiment. Team environment **100** may be two or more individuals working

towards a common goal, possibly within a single organization but possibly operating in different organizations. Person **102** may be a lower-level worker whose purpose is to implement specific tasks with respect to an aspect of the goal. For example, if person **102** were an engineer, person **102** might keep track of issues such as what progress has the person made on a design project within a time period, whether he or she is working on the correct action items, whether milestones have been met, or possibly many other engineering level issues.

[0044] In turn, person **104** may be a team leader with several engineers operating under person **104**, including person **102**. As a team leader, person **104** may keep track of team goals, track individual and group performance, track whether worker goals are aligned, or possibly many other matters.

[0045] At a higher level of organization, person **106** may be an executive responsible for managing the project, or possibly an entire enterprise or organization. Thus, person **106** may be concerned with different matters, such as whether organizational initiatives are on track, whether teams or individuals are working on the correctly assigned projects, whether teams are operating within budget, and possibly many other matters.

[0046] In addition, for larger organizations, other departments may be involved, such as person **108** who is responsible for some aspect of human resource management. Such a person may be responsible for tracking what skills are being used most, whether persons in the organization are being evaluated correctly, determining what skills are needed, and possibly many other matters.

[0047] The tracker of the illustrative embodiments allows each one of these persons to answer these

questions and more. The tracker of the illustrative embodiments improves the efficiency and speed of computer networks by quickly analyzing and reporting desirable information. The tracker of the illustrative embodiments may also allow individual users access to tailored information important to their particular role.

[0048] For example, the illustrative embodiments may allow person **102** to quickly align work activities with business objectives, gather continuous feedback on project performance, and quickly obtain peer support, and many other aspects of performing his or her role, all by integrating the various software tools used by person **102**. Examples of this use of the tracker of the illustrative embodiments are described further below. Likewise, the tracker of the illustrative embodiments can similarly assist each person of person **104**, person **106**, and person **108** to accomplish their roles within the organization, and thereby more efficiently or more quickly achieve the goals of the organization.

[0049] **Figure 2** is a block diagram illustrating a resource tracking system, in accordance with an illustrative embodiment. Resource tracking system **200** is implemented on a server computer, such as computing system **1600** of **Figure 16** or data processing system **1800** of **Figure 18**. Alternatively, resource tracking system **200** may be implemented as a network of multiple computers. Optionally, resource tracking system **200** may be implemented on a single client computer.

[0050] In any case, resource tracking system **200** preferably receives input from multiple applications or tools, though possibly resource tracking system **200** could receive information only from a single application or tool. Resource tracking system **200** may directly link organizational activity to organizational goals to show

organizational alignment and progress. Resource tracking system 200 may show organizational trends and changes in organizational velocity, as described further below. This functionality may be achieved by leveraging tagging and text mining to identify common terms and acronyms within the organization, and tracking their overall usage over time. Resource tracking system 200 may also be used for integration with worker feedback and performance management.

[0051] In the illustrative embodiment shown in **Figure 2**, resource tracking system 200 receives input from four applications or tools, including application A 202, application B 204, application C 206, and application D 208. Resource tracking system 200 receives the output from each application, or actively retrieves desired information from each application, and then collates the aggregate information into a form which is useful for tracking aspects of an organizational, team, or personal goal. Resource tracking system 200 then may present this information to the user, or possibly generate a report for the user. This information could be presented in many different ways, as described here and further below.

[0052] For example, an output of resource tracking system 200 may be to display on a tangible display device recent activities performed by the user of each of the applications. Thus, for example, recent activities display 210 may show that application A 202 may show that a particular percentage of completion towards a project has been met, and how that percentage corresponds to the prior week's performance. In another example, recent activities display 210 may show scheduling information from application B 204. In still another example, recent activities display 210 may show social networking information from application C 206. In yet another

example, recent activities display **210** may show different social networking or scheduling information from a different program, namely application D **208**.

[0053] Resource tracking system **200** may display this type of information in different manners. For example, the graphical user interface may show circular chart **212** indicating a proportional use of each of application A **202**, application B **204**, application C **206**, and application D **208**. A total number of activities may be displayed in the center of circular chart **212**.

[0054] The information obtained and collated and modified by resource tracking system **200** may be presented in a variety of different ways. Thus, the illustrative embodiments are not necessarily limited to the techniques shown in **Figure 2**. For example, alternative methods for collating and displaying information are shown in **Figure 3** through **Figure 10**.

[0055] **Figure 3** is a block diagram illustrating a view of a resource tracking system, in accordance with an illustrative embodiment. Graphical user interface **300** may display a result of the operation of a resource tracking system, such as resource tracking system **200** of **Figure 2**. Thus, **Figure 3** and **Figure 2** share common reference numerals and have similar descriptions. Graphical user interface **300** may be implemented on a tangible display based on output from hardware or software stored on a non-transitory computer readable storage medium and executed by a processor.

[0056] **Figure 3** shows a variation of a graphical user interface for an output of resource tracking system **200** of **Figure 2**. Thus, for example, recent activities display **210** is shown, along with circular graph **302**. Circular graph **302** may be colored, hashed, or otherwise highlighted in each section to identify an application

visually. Thus, for example, section **304** could be colored red or hashed or otherwise highlighted, with the highlighting visually informing the user that application A is used in the most number of activities among a total of 60 activities.

[0057] Different areas of graphical user interface **300** may be selectable by a user in order to display different information. For example, what is displayed may be organized by an individual, such as "me" button **306**. Information for all of the applications used by a team may be selected by selecting "team" button **308**. Information for the entire organization may be selected by selecting "organization" button **310**. In each case, proportionate use of each application may be displayed in circular graph **302** and/or recent activities display **210**.

[0058] Other information may also be displayed. For example, graphical user interface **300** may display the number of goals being tracked in area **312**. Graphical user interface **300** may display the number of activities performed over time in the form of a graph, as shown in area **314**. Another area, area **316**, may show a name or other identifier of a particular project taken from of a list of projects involved in an overall project, with the information relating to the particular project shown elsewhere on graphical user interface **300**.

[0059] Other user input areas or information display areas may be present on graphical user interface **300**. For example, a search term input area **318** may be present to allow a user to drill down into specific information. Other areas may be selectable on graphical user interface **300** to access other functionalities.

[0060] **Figure 4** is a block diagram illustrating a view of a resource tracking system, in accordance with an illustrative embodiment. Graphical user interface **400**

may display a result of the operation of a resource tracking system, such as resource tracking system 200 of **Figure 2**. Thus, **Figure 4** and **Figure 2** share common reference numerals and have similar descriptions. Graphical user interface 400 may be a variation of graphical user interface 300 of **Figure 3**. Graphical user interface 400 may be implemented on a tangible display based on output from hardware or software stored on a non-transitory computer readable storage medium and executed by a processor.

[0061] Graphical user interface 400 shows additional details and functionality relative to graphical user interface 300 of **Figure 3**. Like graphical user interface 300 of **Figure 3**, graphical user interface 400 shows circular graph 402 which shows proportional use of five programs or tools, which now include application E 404. The center of circular graph 402 may show the number of activities related to the group and the goal selected. This selection may be made by selecting any one of "me" button 306, "team" button 308, or "organization" button 310.

[0062] Circular graph 402 may be designed such that goals are displayed from largest to smallest by number of activities in a clockwise manner, with a starting point of twelve o'clock. Colors, hashing, or other highlighting may remain consistent such that the same color or highlighting indicates the largest activity. Alternatively, colors may indicate which program or activity type is displayed.

[0063] Additional functionality is provided in navigation bar 408, such as a "home" button to return a user to a home page, a dashboard button to change information shown in graphical user interface 400, and other buttons as shown to access other functionalities.

In addition, goals may be shown in area **406** of graphical user interface **400**. Arrows **410** may be provided to cycle through or find additional goals. Clicking on one of the goals will show the statistical information and recent activities, thereby changing circular graph **402** and recent activities display **210**. Additionally, the current user may be displayed in area **412**, a designation which may be changed by selection of area **414**.

[0064] Other areas may show other functionalities or information, such as mail button **416**, which allows a user to view mail collected by one or more of the applications (application A **202**, application B **204**, application C **206**, application D **208**, or application E **404**). In another example, arrows **418** may be used to scroll through recent activities. The displayed areas may be selectable in order to bring up information about them or to call other functionalities. Alternatively, the activities may be static or not selectable in order to prevent modifying what is shown in recent activities display **210**.

[0065] In addition, graphical user interface **400** also includes one or more pop-up displays when a user moves a cursor over a section of circular graph **402**, such as pop-up display **420**. Such a pop-up display may display additional information, such as the number activities accounted for by the application represented by section **304**.

[0066] As noted above, circular graph **402**, which may be characterized as a pie chart, may show either activities or applications in use, or both. In the illustrative embodiment shown in **Figure 4**, circular graph **402** may show the top five activities relating to the currently selected goal. Clicking a section or running a cursor over a section may show activity name and count. The color of other sections may become dull if a current

activity type is selected. The sum of each activity may equal the total number of activities displayed in the center. In other illustrative embodiments, the number of applications used in the activities may be displayed and relative application use shown in circular graph 402. Thus, the illustrative embodiments are not necessarily limited by the specific example shown in **Figure 4**.

[0067] **Figure 5** is a block diagram illustrating a view of a resource tracking system, in accordance with an illustrative embodiment. Graphical user interface 500 may display a result of the operation of a resource tracking system, such as resource tracking system 200 of **Figure 2**. Thus, **Figure 5** and **Figure 2** share common reference numerals and have similar descriptions. **Figure 5** also shares common reference numerals with similar descriptions within **Figure 4**. Graphical user interface 500 may be a variation of graphical user interface 300 of **Figure 3** or graphical user interface 400 of **Figure 4**. Graphical user interface 500 may be implemented on a tangible display based on output from hardware or software stored on a non-transitory computer readable storage medium and executed by a processor.

[0068] Graphical user interface 500 shows an effect of selecting "team" button 308, relative to graphical user interface 400 shown in **Figure 4**. In this case, area 502 now shows members of the team. The icon representing each person may be selected for information regarding that individual's activities and performance. In an illustrative embodiment, "all" icon 504 may be selected such that a manager can view a combined view of the activities for the team they manage. The number of activities in graphical user interface 500 shows this combined number. Circular graph 402 may be updated as a result of selecting one of the individuals (showing

activities for that person) or the group (showing activities for the team as a whole). The updated circular graph may display activities or applications used accordingly.

[0069] In a specific illustrative embodiment, recent activities display **210** need not be updated when a user clicks on different groups or goals. Alternatively, updates or changes may be indicated in recent activities display **210** when a user clicks on different individuals in area **502**, or "all" icon **504**.

[0070] **Figure 6** is a block diagram illustrating a view of a resource tracking system, in accordance with an illustrative embodiment. Graphical user interface **600** may display a result of the operation of a resource tracking system, such as resource tracking system **200** of **Figure 2**. Thus, **Figure 6** and **Figure 2** share common reference numerals and have similar descriptions. **Figure 6** also shares common reference numerals with similar descriptions within **Figure 4**. Graphical user interface **600** may be a variation of graphical user interface **300** of **Figure 3**, graphical user interface **400** of **Figure 4**, or graphical user interface **500** of **Figure 5**. Graphical user interface **600** may be implemented on a tangible display based on output from hardware or software stored on a non-transitory computer readable storage medium and executed by a processor.

[0071] Graphical user interface **600** shows an effect of selecting "organization" button **310**, relative to graphical user interface **400** shown in **Figure 4** or graphical user interface **500** shown in **Figure 5**. In this case, area **602** now shows a button which may be selected to indicate the user's particular contributions to the team. Circular graph **402** may be updated as a result of selecting "organization" button **310**. The updated

circular graph may display activities performed by the entire organization as a whole or applications used by the entire organization as a whole. In graphical user interface **600**, section **604** is selected and pop-up window **606** indicates the number of activities performed in that section. In this particular example, a number of promotions are shown, which are part of the total number of activities shown.

[0072] The illustrative embodiments shown in **Figure 4** through **Figure 6** may be varied. For example, the location of various icons and areas may be varied. Thus, these specific examples do not necessarily limit the claimed illustrative embodiments.

[0073] **Figure 7** is a graph illustrating an output of a resource tracking system, in accordance with an illustrative embodiment. Graph **700** may be an alternative to the graphical user interfaces shown in **Figure 2** through **Figure 6**. Graph **700** may be displayed on a tangible display as a result of the output of a tracking system, as described above.

[0074] Graph **700** shows a graph of activity count **702** versus goal lifecycle **704**. Each line shown in the graph shows a count of a type of activity over time. The various types of dashes show the various types of activities being tracked. In this manner, a user can easily see increasing or decreasing trends in activities over time for an individual person, for a team, for an entire organization, or perhaps for a set of selected individuals or for the activities of other software programs. Stated differently, graph **700** shows activity trends towards a selected goal and allows a user to identify where most time is spent throughout a life cycle of a goal for an individual, a team, an organization, or

a selected number of individuals or the activities of other software programs.

[0075] In area **706** of the graphical user interface the number of activities and the graph of total activities over time may be displayed. A total percentage increase or decrease in activities over a selected time period may also be displayed in area **706**.

[0076] **Figure 8** is a relationship diagram illustrating an output of a resource tracking system, in accordance with an illustrative embodiment. Relationship graph **800** may be an alternative to the graphical user interfaces shown in **Figure 2** through **Figure 7**. Relationship graph **800** may be displayed on a tangible display as a result of the output of a tracking system, as described above.

[0077] Relationship graph **800** shows that the tracker of the illustrative embodiments may bring together true visibility on cross-departmental work activities and common engagements. Relationship graph **800** also shows that the tracker of the illustrative embodiments may identify main collaborators across teams to identify strong connections between individuals and to identify work patterns.

[0078] The tracker of the illustrative embodiments allows a user to identify specific relationships among different applications and corresponding individuals, teams, or organizations that use those different applications. Use of an application may be considered an activity.

[0079] **Figure 8** shows the four applications described above, including application A **202**, application B **204**, application C **206**, and application D **208**. In addition, five users are shown. Three users are more commonly associated with application A **202**, including user A **802**, user B **804**, and user C **806**. Two users are more commonly

associated with application D **208**, including user D **808** and user E **810**. Lines between an application and a user show which users are using which applications, such as line **812** or line **814**. Lines between users show relationships among users, for example where one user is consulting with another via one or more of the applications shown, or, for example, where a user uses the result of an activity of another user. Examples of lines between users include line **816**, line **818**, and line **820**, though other lines are shown. The lines between users may be colored, thickened, dashed, or otherwise marked to convey additional information. For example, line **816** is thickened and marked with the number five hundred to show a large number of connected activities between user C **806** and user E **810**. In contrast, line **820** is thin and is marked with the number five to show a relatively small number of connected activities between User A **802** and User C **806**.

[0080] Thus, in the specific example shown in **Figure 8**, a user desires to see relationships among application A **202** and application D **208** and the users of those applications. Thus, to prevent relationship graph **800** from becoming cluttered, application C **206** and application B **204** are faded out and their connections and users are not displayed. Then several users of application A **202** are shown and several users of application D **208** are shown, along with the activity connections among those users. As described above, indicators such as line thickness, line color, or other information may be displayed to convey additional information. The additional information may be activity type, number of activities, a strength of the relationship among users, and possibly other information.

[0081] **Figure 9** is a status report output by a resource tracking system, in accordance with an illustrative embodiment. Graphical user interface **900** shows that the tracker of the illustrative embodiments may cause a display of a summary of activities for an individual. Thus, graphical user interface **900** shows an alternative to the various graphical user interfaces and graphs shown in **Figure 2** through **Figure 8**.

[0082] In the example of **Figure 9**, the tracker of the illustrative embodiments has put together and caused display of a summary of the activities and relationships of an individual user, user X **902**. The name, picture, and various information about user X **902** may be displayed in area **904**, such as the job title and team or organization assignment. Key accomplishments, goals, or goals under consideration for assignment to user X **902** may be displayed in area **906**. The number and types of activities performed by user X **902** may be shown in area **908**. The information in area **908** may be color coded for easier recognition. The types of activities may be presented as a horizontal bar graph to quickly show the proportion of time used relative to other activities or perhaps the proportion of a given activity to the total number of activities.

[0083] Other information may be displayed. For example, in area **910** a timeline may be shown that also displays the time interval for which the reporting data is collated. In this particular example, the reporting period is the month of August, with other the other twelve months of the year shown faded to indicate that the information for these months is not currently displayed. The time interval could be changed to years, weeks, days, or even hours. In some cases, another menu

may be provided so that the user may select the desired time interval for reporting.

[0084] In addition, graphical user interface **900** may include information regarding with which other persons User X **902** works. For example, area **912** may show the top three individuals with whom User X **902** works. More or fewer users may be displayed. Teams or organizations or customers could be displayed.

[0085] Thus, the illustrative embodiment of **Figure 9** is a specific example only and may be varied. For example, instead of showing the activities of a single person, information about a team or the whole organization may be displayed. Thus, for example, if a team is displayed, then total activities of the team and the three most worked with outside teams may be displayed. The number of "most worked with" people may be varied. The time period may be varied from "by month" to "by year" or "by week" or even "by day" or "by hour". More or less information may be displayed. The layout of the information shown in **Figure 9** may be varied. Thus, the illustrative embodiments are not necessarily limited to the example shown in **Figure 9**.

[0086] **Figure 10** is a bar graph report output by a resource tracking system, in accordance with an illustrative embodiment. Thus, graphical user interface **1000** shows an alternative to the various graphical user interfaces and graphs shown in **Figure 2** through **Figure 9**. Graphical user interface **1000** shows that the tracker of the illustrative embodiments may cause a display of a summary of activities for an individual, team, or organization by activity count and by time interval. This summary may take the form of bar graph **1002**.

[0087] Bar graph **1002** may display the average activity account on a month-by-month basis. Different time

periods may be used. Bar graph **1002** also shows different sections within individual bars. Each bar has a total equal to every other bar, because the top of bar graph **1002** represents one hundred percent of activities for the given month. Different highlighted sections within an individual month shows a relative percentage of a given type of activity is performed for the given month. The coloring, hashing, or other highlighting indicates which activity is being indicated.

[0088] Thus, bar graph **1002** aggregates and presents patterns in work towards similar goals. Bar graph **1002** also shows product initiative goal trends.

[0089] The illustrative embodiment of **Figure 10** may be further varied. More or different information may be presented. The time periods may be varied, and more or fewer activity types may be present. Different types of highlighting are possible. The layout or look and feel of bar graph **1002** may change. Thus, the illustrative embodiments are not necessarily limited to the specific examples shown in **Figure 10**.

[0090] Attention is now turned to examples of how to implement the tracker of the illustrative embodiments. These illustrative embodiments are exemplary and may be varied. **Figure 11** shows the overall architecture, **Figure 12** shows the details of the tracking system, and **Figure 13** is an exemplary application programming interface (API).

[0091] **Figure 11** is a block diagram of an architecture of a resource tracking system, in accordance with an illustrative embodiment. Tracking system architecture **1100** may be implemented using hardware, such as computing system **1600** of **Figure 16** or data processing system **1800** of **Figure 18**, possibly in the context of a network or cloud operating environment such as cloud computing

environment 1700 of **Figure 17**. Tracking system architecture 1100 may also be implemented in the form of software or program code stored on a non-transitory computer readable storage medium which, when executed, improves the efficiency of the overall network or the server by more efficiently gathering and presenting desired data.

[0092] Tracking system architecture 1100 includes client layer 1102, services layer 1104, and data layer 1106. Each of client layer 1102, services layer 1104, and data layer 1106 may be implemented as described above for tracking system architecture 1100. Each layer communicates only with the immediately preceding and immediately succeeding layer, although in some illustrative embodiments a client in client layer 1102 may communicate directly with servers or non-transitory computer readable storage media in data layer 1106.

[0093] Client layer 1102 includes one or more client systems. A client system may be a computer, an application, or a third party request through some other computer. Thus, a client system may be a requesting computer or program communicating through a cloud environment. The various graphical user interfaces described with respect to **Figure 2** through **Figure 10** may be shown on tangible display devices of the client's systems in client layer 1102. Client layer 1102 communicates through one or more communication channels with services layer 1104.

[0094] Services layer 1104 provides for common encapsulation, common security, and common error handling with respect to requests and data reception from client layer 1102. Services layer 1104 may include application layer 1108 and data services layer 1110. Details regarding services layer 1104, application layer 1108,

and data services layer **1110** are described with respect to **Figure 12**. However, in general, application layer **1108** handles requests for applications and data services layer **1110** handles application programming interfaces for building requests to data layer **1106**.

[0095] Data layer **1106**, in turn, includes one or more databases, such as database **1112**. One or more of these databases may be stored on an individual non-transitory computer readable storage medium. These databases may contain the underlying information which is consumed and then returned to the clients in client layer **1102** in order to present the graphical user interfaces shown in **Figure 2** through **Figure 10**. Thus, tracking system architecture **1100** is a service oriented architecture which is highly scalable and which provides multi-device support.

[0096] **Figure 12** is a block diagram illustrating details of the resource tracking system architecture shown in **Figure 11**, in accordance with an illustrative embodiment. Specifically, services layer **1200** is an example of services layer **1104** of **Figure 11**. Reference numerals common to **Figure 2** have common descriptions.

[0097] In an illustrative embodiment, data requests (either from a push or a pull) are transmitted back and forth from applications, such as application A **202**, application B **204**, application C **206**, and application D **208**. These requests are then received by one or more application programming interfaces (APIs), such as application programming interface **1202** within data services **1204**, to build a request of database **1206** (which may be in data layer **1106** of **Figure 11**). These application programming interfaces may be built using one or more languages, such as language X **1208**, language Y

1210, or language Z 1212, depending on the author of the corresponding application.

[0098] Thus, the illustrative embodiments may use information taken from third party applications of a variety of proprietary formats and still present a coherent set of information to the user, as shown in **Figure 2** through **Figure 10**. Additionally, the architecture is scalable as more or different programs may be provided to the tracking system, which then, accordingly, updates subsequent reports shown to the user.

[0099] In a specific illustrative embodiment, the tracking system of the illustrative embodiments may be backed by a REST-JSON API, written in Ruby on Rails version 4. Other languages or other APIs may be used in other illustrative embodiments. The API is then is used to import data from the organization which is responsible for the tracker of the illustrative embodiments (and any third party APIs) and to serve the front end of the tracking system. In a specific illustrative embodiment, the development environment may be the RubyMine integrated development environment using the railsAPI gem. However, other development environments are possible.

[00100] Any given API used with the tracking system of the illustrative embodiments may include three models: work item, tag, and person. Each model has an endpoint. In an illustrative embodiment there is a many-to-many relationship between these models. The models inherit from ActiveRecord the object relational mapping built into Rails, which comes preconfigured with sqlite3 for development. The controllers may support five actions: index, show, create, update, and destroy. The resources are automatically routed, including nested resources.

[00101] **Figure 13** is an example of an application programming interface usable in a resource tracking system, in accordance with an illustrative embodiment. Application programming interface **1300** may be an example of one or more of the application programming interfaces used to implement the tracker of the illustrative embodiments, as described with respect to **Figure 12**. The pseudo-code shown in **Figure 13**, which implements application programming interface **1300**, is exemplary only and may be varied.

[00102] As described above, each application programming interface includes three models: work item, tag, and person. The work item model is shown in lines three through ten in **Figure 13**, which is code to describe which application is being accessed or used and what information is to be taken from the underlying database.

[00103] The tag model is shown in lines eleven through fifteen in **Figure 13**. Although only one tag is shown, more or fewer tags may be present. Tags are basic words or phrases that are commonly used as reference points when describing an element of value or clarification on an associated object. Tags can be linked to meta-data elements within a platform. While tags can theoretically be linked to any data model objects, the following objects may be supported in a particular example: global person, position, organization unit, job family, capability and asset. Tags may be used to analyze trends across different applications and platforms, or to otherwise assist in collating desired information.

[00104] The person model is shown in lines 16 through 22 of **Figure 13**. The person model provides one or more forms of identification of the person involved in the requested data. More or fewer people could be present. More or fewer forms of identification may be present. In

the illustrative embodiment shown in **Figure 13**, a single person is described by three identifiers: first name, last name, and email address. The application programming interface then uses this person's information as part of determining what information to retrieve and then present to the user in a graphical user interface, such as shown in **Figure 2** through **Figure 10**.

[00105] **Figure 14** is a block diagram of a resource tracking system, in accordance with an illustrative embodiment. System **1400** is implemented as a data processing system, such as computing system **1600** of **Figure 16** or data processing system **1800** of **Figure 18**. System **1400** may implement a variation of the techniques described with respect to **Figure 1** through **Figure 13**. System **1400** may be described as a computer; however, in the context of **Figure 14** the term "system", including system **1400**, may refer to any processor, application specific integrated circuit, application specific processor, or any other tangible physical hardware operating in conjunction with a tangible physical display, tangible physical input devices, and a non-transitory computer readable storage medium.

[00106] Thus, system **1400** may include computer network **1402**. Computer network **1402** may include server computer **1404** having server processor **1406** and server non-transitory computer readable storage medium **1408**. Computer network **1402** may be part of, or constitute, a cloud environment, such as cloud computing environment **1700** of **Figure 17**.

[00107] Computer network **1402** may also include first computer **1410**. First computer **1410** may be in communication with the server computer and may be operable by a first user. First computer **1410** has first processor **1412** and first non-transitory computer readable

storage medium **1414** storing first program code **1416**. First program code **1416**, when executed by the first processor, implements a first software tool having a first function and a second software tool having a second function.

[00108] Computer network **1402** may also include second computer **1418** in communication with the server computer operable by a second user. Second computer **1418** has second processor **1420** and second non-transitory computer readable storage medium **1422** storing second program code **1424**. Second program code **1424**, when executed by the second processor, implements the first software tool having the first function and the second software tool having the second function.

[00109] Server non-transitory computer readable storage medium **1408** stores third program code **1426**. Third program code **1426**, when executed by server processor **1406**, is configured to perform a number of functions. The functions include gathering first data regarding use of the first software tool and gathering second data regarding use of the second software tool. The functions also include, based on the first data and the second data, linking activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first user and the second user belong. In executing third program code **1426**, communications link **1428** or **1430** between the server computer and the first computer **1410** or second computer **1418** is improved.

[00110] The illustrative embodiments described with respect to **Figure 14** may be varied. For example, in an illustrative embodiment, third program code **1426** may be further configured to cause a physical display device to

present proportional use information comprising a proportional comparison of: use of the first software tool on both the first computer and the second computer relative to use of the second software tool on both the first computer and the second computer.

[00111] In another illustrative embodiment, third program code **1426** may be further configured to: based on the first data and the second data, calculate a first amount of work the first user contributed to the performance goal and calculate a second amount of work the second user contributed to the performance goal. In another illustrative embodiment, third program code **1426** may be further configured to, based on the first data and the second data, calculate a performance of the first user relative to the second user.

[00112] In another illustrative embodiment, the first user has a first assigned goal. In this case, third program code **1426** may be further configured to track a total number of activities by the first user for the first assigned goal.

[00113] In still another illustrative embodiment, third program code **1426** may be further configured to calculate, for the first user, a proportional use of the first software tool and the second software tool. In this case, third program code **1426** may be further configured to display which of the first user and the second user performs a most number of particular activities towards the performance goal. In this manner, it may be determined which user should be consulted regarding a question regarding the particular activities.

[00114] In yet another illustrative embodiment, the performance goal is for the organization. The organization has a plurality of departments and the first user is in a first department and the second user is in a

second department. In this case, third program code **1426** may be further configured to, based on the first data and the second data, display cross-departmental collaboration between the first user and the second user.

[00115] In still another illustrative embodiment, any of the examples described above with respect to **Figure 14** may be described with respect to server computer **1404** itself. Thus, the claimed illustrative embodiments are not necessarily limited to computer network **1402**, but also may be characterized as server computer **1404** configured to receive information from first computer **1410** and second computer **1418** as described above.

[00116] Other variations are possible. Thus, the claimed illustrative embodiments are not necessarily limited by the examples described with respect to **Figure 14**.

[00117] **Figure 15** is a flowchart of a method for performing resource tracking, in accordance with an illustrative embodiment. Method **1500** is implemented using a data processing system, such computing system **1600** of **Figure 16** or data processing system **1800** of **Figure 18**. Method **1500** may be implemented in a cloud environment, such as cloud computing environment **1700** of **Figure 17**. Method **1500** may be a variation of the techniques described with respect to **Figure 1** through **Figure 14**. The various operations described with respect to method **1500** are described as being performed by a computer; however, in the context of **Figure 15** the term "computer" may refer to any processor, application specific integrated circuit, application specific processor, or any other tangible physical hardware operating in conjunction with a tangible physical display, tangible physical input devices, and a non-transitory computer readable storage medium.

[00118] Method **1500** may be implemented in a server computer having a server processor and a server non-transitory computer readable storage medium. The server computer may be in communication with a first computer, operable by a first user. The first computer may have a first processor and a first non-transitory computer readable storage medium storing first program code. The first program code, when executed by the first processor, implements a first software tool having a first function and a second software tool having a second function. The server computer may be in communication with a second computer, operable by a second user. The second computer may have a second processor and a second non-transitory computer readable storage medium storing second program code. The second program code, when executed by the second processor, implements the first software tool having the first function and the second software tool having the second function. The server non-transitory computer readable storage medium stores third program code. The third program code, when executed by the server processor, implements method **1500**.

[00119] Method **1500** may include gathering first data regarding use of the first software tool (operation **1502**). Method **1500** may also include gathering second data regarding use of the second software tool (operation **1504**).

[00120] Method **1500** may also include improving, using the server computer, a communications link between the server computer and the first computer or the second computer by linking, based on the first data and the second data, activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first

user and the second user belong (operation **1506**). The process may terminate thereafter.

[00121] Method **1500** may be further varied. For example, method **1500** may also include altering a physical display device by displaying proportional use information comprising a proportional comparison of: use of the first software tool on both the first computer and the second computer relative to use of the second software tool on both the first computer and the second computer.

[00122] In another example, method **1500** may also include calculating, based on the first data and the second data, a first amount of work the first user contributed to the performance goal and calculating a second amount of work the second user contributed to the performance goal, and altering a physical display device by displaying the first amount of work and the second amount of work.

[00123] In another example, method **1500** may also include calculating, for the first user, a proportional use of the first software tool and the second software tool, and altering a physical display device by displaying which of the first user and the second user performs a most number of particular activities towards the performance goal.

[00124] Thus, the illustrative embodiments described with respect to **Figure 15** are exemplary only and do not necessarily limit the claimed illustrative embodiments. Further variations of method **1500** are possible, such as other techniques described with respect to **Figure 1** through **Figure 14**.

[00125] **Figure 16** is a block diagram of a data processing system, in accordance with an illustrative embodiment. **Figure 16** is an illustrative architecture of a computing system **1600** implemented as embodiments of the

present illustrative embodiment. The computing system 1600 is only one example of a suitable computing system and is not intended to suggest any limitation as to the scope of use or functionality of the illustrative embodiment. Also, computing system 1600 should not be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in computing system 1600.

[00126] As shown in **Figure 16**, computing system 1600 includes a computing device 1605. The computing device 1605 can be resident on a network infrastructure such as within a cloud environment, or may be a separate independent computing device (e.g., a computing device of a third party service provider). The computing device 1605 may include a bus 1610, a processor 1615, a storage device in storage devices 1620, a system memory (hardware device) 1625, one or more input devices 1630, one or more output devices 1635, and a communication interface 1640.

[00127] The bus 1610 permits communication among the components of computing device 1605. For example, bus 1610 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, or a local bus using any of a variety of bus architectures to provide one or more wired or wireless communications links or paths for transferring data and/or power to, from, or between various other components of computing device 1605.

[00128] The processor 1615 may be one or more conventional processors or microprocessors that include any processing circuitry operative to interpret and execute computer readable program instructions, such as program instructions for controlling the operation and performance of one or more of the various other components of computing device 1605. In embodiments,

processor **1615** interprets and executes the processes, steps, functions, and/or operations of the present illustrative embodiment, which may be operatively implemented by the computer readable program instructions. For example, the processor **1615** implements the processes as described throughout including the examples herein. In embodiments, the processor **1615** integrates multiple systems and applications together, and determines trends by analyzing tags and/or keywords of one or more users over the multiple integrated systems and applications.

[00129] In other embodiments, processor **1615** may receive input signals from one or more input devices **1630** and/or drive output signals through one or more output devices **1635**. The input devices **1630** may be, for example, a keyboard or touch sensitive user interface (UI) as further described below. The output devices **1635** can be, for example, any display device, printer, etc., as further described below.

[00130] The storage device in storage devices **1620** may include removable/non-removable, volatile/non-volatile computer readable media, such as, but not limited to, non-transitory media such as magnetic and/or optical recording media and their corresponding drives. The drives and their associated computer readable media provide for storage of computer readable program instructions, data structures, program modules and other data for operation of computing device **1605** in accordance with the different aspects of the present illustrative embodiment. In other embodiments, storage device in storage devices **1620** may store operating system **1645**, application programs **1650**, and program data **1655** in accordance with aspects of the present illustrative embodiment.

[00131] The system memory **1625** may include one or more storage mediums, including for example, non-transitory media such as flash memory, permanent memory such as read-only memory ("ROM"), semi-permanent memory such as random access memory ("RAM"), any other suitable type of storage component, or any combination thereof. In some embodiments, an input/output system **1660** (BIOS) including the basic routines that help to transfer information between the various other components of computing device **1605**, such as during start-up, may be stored in the ROM. Additionally, data and/or program modules **1665**, such as at least a portion of operating system **1645**, application programs **1650**, and/or program data **1655**, that are accessible to and/or presently being operated on by processor **1615** may be contained in the RAM.

[00132] The one or more input devices **1630** may include one or more mechanisms that permit an operator to input information to computing device **1605**, such as, but not limited to, a touch pad, dial, click wheel, scroll wheel, touch screen, one or more buttons (e.g., a keyboard), mouse, game controller, track ball, microphone, camera, proximity sensor, light detector, motion sensors, biometric sensor, and combinations thereof. The one or more output devices **1635** may include one or more mechanisms that output information to an operator, such as, but not limited to, audio speakers, headphones, audio line-outs, visual displays, antennas, infrared ports, tactile feedback, printers, or combinations thereof.

[00133] The communication interface **1640** may include any transceiver-like mechanism (e.g., a network interface, a network adapter, a modem, or combinations thereof) that enables computing device **1605** to communicate with remote devices or systems, such as a mobile device or other computing devices such as, for

example, a server in a networked environment, e.g., cloud environment. For example, computing device 1605 may be connected to remote devices or systems via one or more local area networks (LAN) and/or one or more wide area networks (WAN) using communication interface 1640.

[00134] As discussed herein, computing system 1600 may be configured to implement the processes as described throughout including the functionality and examples herein, as shown in the figures attached herein including the underlying functionality of the screen displays as described herein, in addition to the process flows and the illustrative examples. That is, amongst many different aspects described herein, the computing system 1600 is an integrated resource tracking system and, more particularly, provides processes and systems to integrate multiple systems and applications together to determine trends by analyzing tags and/or keywords of multiple users over the multiple integrated systems and applications.

[00135] In particular, computing device 1605 may perform tasks (e.g., process, steps, methods and/or functionality) in response to processor 1615 executing program instructions contained in a computer readable medium, such as system memory 1625. The program instructions may be read into system memory 1625 from another computer readable medium, such as a data storage device in data storage devices 1620, or from another device via the communication interface 1640 or server within or outside of a cloud environment. In embodiments, an operator may interact with computing device 1605 via the one or more input devices 1630 and/or the one or more output devices 1635 to facilitate performance of the tasks and/or realize the end results of such tasks in accordance with aspects of the present

illustrative embodiment. In additional or alternative embodiments, hardwired circuitry may be used in place of or in combination with the program instructions to implement the tasks, e.g., steps, methods and/or functionality, consistent with the different aspects of the present illustrative embodiment. Thus, the steps, methods, and/or functionality disclosed herein can be implemented in any combination of hardware circuitry and software.

[00136] **Figure 17** is a block diagram of a cloud environment, in accordance with an illustrative embodiment. **Figure 17** shows an exemplary cloud computing environment **1700**. Cloud computing is a computing model that enables convenient, on-demand network access to a shared pool of configurable computing resources, e.g., networks, servers, processing, storage, applications, and services, that can be provisioned and released rapidly, dynamically, and with minimal management efforts and/or interaction with the service provider. In embodiments, one or more aspects, functions, and/or processes described herein may be performed and/or provided via cloud computing environment **1700**.

[00137] As depicted in **Figure 17**, cloud computing environment **1700** includes cloud resources **1705** that are made available to client devices **1710** via a network **1715**, such as the Internet. Cloud resources **1705** can include a variety of hardware and/or software computing resources, such as servers, databases, storage, networks, applications, and platforms. In embodiments, the systems and processes herein can be integrated into the cloud resources in order to provide tracking and trending capabilities as described and shown herein.

[00138] Cloud resources **1705** may be on a single network or a distributed network. Cloud resources **1705** may be

distributed across multiple cloud computing systems and/or individual network enabled computing devices. Client devices **1710** may comprise any suitable type of network-enabled computing device, such as servers, desktop computers, laptop computers, handheld computers (e.g., smartphones, tablet computers), set top boxes, and network enabled hard drives. Cloud resources **1705** are typically provided and maintained by a service provider so that a client does not need to maintain resources on a local implementation of client device **1710**. In embodiments, cloud resources **1705** may include one or more computing system **1600** of **Figure 16** that is specifically adapted to perform one or more of the functions and/or processes described herein.

[00139] Cloud computing environment **1700** may be configured such that cloud resources **1705** provide computing resources to client devices **1710** through a variety of service models, such as Software as a Service (SaaS), Platforms as a service (PaaS), Infrastructure as a Service (IaaS), and/or any other cloud service models. Cloud resources **1705** may be configured, in some cases, to provide multiple service models to a client device **1710**. For example, cloud resources **1705** can provide both SaaS and IaaS to a client device **1710**. Cloud resources **1705** may be configured, in some cases, to provide different service models to different types of client devices **1710**. For example, cloud resources **1705** can provide SaaS to a first type of client device **1710** and PaaS to a second type of client device **1710**.

[00140] Cloud computing environment **1700** may be configured such that cloud resources **1705** provide computing resources to client devices **1710** through a variety of deployment models, such as public, private, community, hybrid, and/or any other cloud deployment

model. Cloud resources **1705** may be configured, in some cases, to support multiple deployment models. For example, cloud resources **1705** can provide one set of computing resources through a public deployment model and another set of computing resources through a private deployment model.

[00141] One or more of cloud resources **1705** may be conceptually structured in multiple layers. In one example, the layers include a firmware and hardware layer, a kernel layer, an infrastructure service layer, a platform service layer, and an application service layer. The firmware and hardware layer may be the lowest layer upon which the other layers are built, and may include generic contributing nodes (e.g., data centers, computers, and storage devices) geographically distributed across the Internet and may provide the physical resources for implementing the upper layers of the cloud service provider. The kernel layer is above the firmware and hardware layer and may include an operating system and/or virtual machine manager that host the cloud infrastructure services. The kernel layer controls and communicates with the underlying firmware and hardware layer through one or more hardware/firmware-level application programming interfaces (APIs). The infrastructure service layer is above the kernel layer and may include virtualized resources, such as virtual machines, virtual storage (e.g., virtual disks), virtual network appliances (e.g., firewalls), and so on. The infrastructure service layer may also include virtualized services, such as database services, networking services, file system services, web hosting services, load balancing services, message queue services, map services, e-mail services, and so on. The platform service layer is above the infrastructure service layer and may include

platforms and application frameworks that provide platform services, such as an environment for running virtual machines or a framework for developing and launching a particular type of software application. The application service layer is above the platform service layer and may include a software application installed on one or more virtual machines or deployed in an application framework in the platform service layer. The software application can also communicate with one or more infrastructure service components (e.g., firewalls, databases, web servers, etc.) in the infrastructure service layer.

[00142] In another example, one or more cloud resources in cloud resources **1705** may be conceptually structured in functional abstraction layers including a hardware and software layer, a virtualization layer, a management layer, and a workloads layer. The hardware and software layer may include hardware and software components such as mainframes, RISC (reduced instruction set computer) architecture based servers, storage devices, networks and networking components, application server software, and database software. The virtualization layer may include virtual entities such as virtual servers, virtual storage, virtual networks, virtual applications, and virtual clients. The management layer may provide functions such as resource provisioning, metering and pricing, security, user portals, service level management, and service level agreement planning and fulfillment. The workloads layer may provide functions for which the cloud computing environment is utilized, such as mapping and navigation, software development and lifecycle management, data analytics and processing, and transaction processing.

[00143] In embodiments, software and/or hardware that performs one or more of the aspects, functions, and/or processes described herein may be accessed and/or utilized by a client (e.g., an enterprise or an end user) as one or more of an SaaS, PaaS, and IaaS model in one or more of a private, community, public, and hybrid cloud. Moreover, although this disclosure includes a description of cloud computing, the systems and methods described herein are not limited to cloud computing and instead can be implemented on any suitable computing environment.

[00144] Cloud resources **1705** may be configured to provide a variety of functionality that involves user interaction. Accordingly, a user interface (UI) can be provided for communicating with cloud resources **1705** and/or performing tasks associated with cloud resources **1705**. The UI can be accessed via a client device **1710** in communication with cloud resources **1705**. The UI can be configured to operate in a variety of client modes, including a fat client mode, a thin client mode, or a hybrid client mode, depending on the storage and processing capabilities of cloud resources **1705** and/or client device **1710**. Therefore, a UI can be implemented as a standalone application operating at the client device in some embodiments. In other embodiments, a web browser-based portal can be used to provide the UI. Any other configuration to access cloud resources **1705** can also be used in various implementations.

[00145] The technical solutions provided herein include the integration of many different systems/applicants and the providing of an analysis of tags/keywords, etc. to determine trending information, amongst other things. The technical solutions are implemented in the computer infrastructure of **Figure 16** and/or the environment of **Figure 17**, and can be integrated in many different

systems described herein. The following examples, amongst all of the functionality and examples herein, can include a computer program product which includes computer readable program instructions stored on computer readable storage medium (or media) for implementing any of the combinations of processes and systems herein. The computer readable storage medium include the one or more storage medium as described with regard to **Figure 16**, e.g., non-transitory media, a tangible device, etc. The method, and/or computer program product implementing the flows or examples provided herein can be downloaded to respective computing/processing devices, e.g., computing system of **Figure 16** as already described herein, or implemented on a cloud infrastructure as described with regard to **Figure 17**. Accordingly, the processes associated with each flow of the present illustrative embodiment can be implemented by special purpose hardware-based systems that perform the specified functions or acts or carry out combinations of special purpose hardware and computer instructions.

[00146] Turning now to **Figure 18**, an illustration of a data processing system is depicted in accordance with an illustrative embodiment. Data processing system **1800** in **Figure 18** is an example of a data processing system that may be used to implement the illustrative embodiments, such as those described with respect to **Figure 1** through **Figure 15**. In this illustrative example, data processing system **1800** includes communications fabric **1802**, which provides communications between processor unit **1804**, memory **1806**, persistent storage **1808**, communications unit **1810**, input/output (I/O) unit **1812**, and display **1814**.

[00147] Processor unit **1804** serves to execute instructions for software that may be loaded into memory **1806**. This software may be an associative memory,

content addressable memory, or software for implementing the processes described elsewhere herein. Processor unit **1804** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation. A number, as used herein with reference to an item, means one or more items. Further, processor unit **1804** may be implemented using a number of heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **1804** may be a symmetric multi-processor system containing multiple processors of the same type.

[00148] Memory **1806** and persistent storage **1808** are examples of storage devices **1816**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and/or other suitable information either on a temporary basis and/or a permanent basis. Storage devices **1816** may also be referred to as computer readable storage devices in these examples. Memory **1806**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **1808** may take various forms, depending on the particular implementation.

[00149] For example, persistent storage **1808** may contain one or more components or devices. For example, persistent storage **1808** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **1808** also may be removable. For example, a removable hard drive may be used for persistent storage **1808**.

[00150] Communications unit **1810**, in these examples, provides for communicating with other data processing systems or devices. In these examples, communications unit **1810** is a network interface card. Communications unit **1810** may provide communications through the use of physical and/or wireless communications links.

[00151] Input/output (I/O) unit **1812** allows for input and output of data to and from other devices that may be connected to data processing system **1800**. For example, input/output (I/O) unit **1812** may provide a connection for user input through a keyboard, a mouse, and/or some other suitable input device. Further, input/output (I/O) unit **1812** may send output to a printer. Display **1814** provides a mechanism to display information to a user.

[00152] Instructions for the operating system, applications, and/or programs may be located in storage devices **1816**, which are in communication with processor unit **1804** through communications fabric **1802**. In these illustrative examples, the instructions are in a functional form on persistent storage **1808**. These instructions may be loaded into memory **1806** for execution by processor unit **1804**. The processes of the different embodiments may be performed by processor unit **1804** using computer implemented instructions, which may be located in a memory, such as memory **1806**.

[00153] These instructions are referred to as program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **1804**. The program code in the different embodiments may be embodied on different physical or computer readable storage media, such as memory **1806** or persistent storage **1808**.

[00154] Program code **1818** is located in a functional form on computer readable media **1820** that is selectively

removable and may be loaded onto or transferred to data processing system **1800** for execution by processor unit **1804**. Program code **1818** and computer readable media **1820** form computer program product **1822** in these examples. In one example, computer readable media **1820** may be computer readable storage media **1824** or computer readable signal media **1826**. Computer readable storage media **1824** may include, for example, an optical or magnetic disk that is inserted or placed into a drive or other device that is part of persistent storage **1808** for transfer onto a storage device, such as a hard drive, that is part of persistent storage **1808**. Computer readable storage media **1824** also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory, that is connected to data processing system **1800**. In some instances, computer readable storage media **1824** may not be removable from data processing system **1800**.

[00155] Alternatively, program code **1818** may be transferred to data processing system **1800** using computer readable signal media **1826**. Computer readable signal media **1826** may be, for example, a propagated data signal containing program code **1818**. For example, computer readable signal media **1826** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, wire, and/or any other suitable type of communications link. In other words, the communications link and/or the connection may be physical or wireless in the illustrative examples.

[00156] In some illustrative embodiments, program code **1818** may be downloaded over a network to persistent storage **1808** from another device or data processing system through computer readable signal media **1826** for

use within data processing system **1800**. For instance, program code stored in a computer readable storage medium in a server data processing system may be downloaded over a network from the server to data processing system **1800**. The data processing system providing program code **1818** may be a server computer, a client computer, or some other device capable of storing and transmitting program code **1818**.

[00157] The different components illustrated for data processing system **1800** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to or in place of those illustrated for data processing system **1800**. Other components shown in **Figure 18** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code. As one example, the data processing system may include organic components integrated with inorganic components and/or may be comprised entirely of organic components excluding a human being. For example, a storage device may be comprised of an organic semiconductor.

[00158] In another illustrative example, processor unit **1804** may take the form of a hardware unit that has circuits that are manufactured or configured for a particular use. This type of hardware may perform operations without needing program code to be loaded into a memory from a storage device.

[00159] For example, when processor unit **1804** takes the form of a hardware unit, processor unit **1804** may be a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some

other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device is configured to perform the number of operations. The device may be reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. With this type of implementation, program code **1818** may be omitted because the processes for the different embodiments are implemented in a hardware unit.

[00160] In still another illustrative example, processor unit **1804** may be implemented using a combination of processors found in computers and hardware units. Processor unit **1804** may have a number of hardware units and a number of processors that are configured to run program code **1818**. In this depicted example, some of the processes may be implemented in the number of hardware units, while other processes may be implemented in the number of processors.

[00161] As another example, a storage device in data processing system **1800** is any hardware apparatus that may store data. Memory **1806**, persistent storage **1808**, and computer readable media **1820** are examples of storage devices in a tangible form.

[00162] In another example, a bus system may be used to implement communications fabric **1802** and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course, the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system.

Additionally, a communications unit may include one or more devices used to transmit and receive data, such as a modem or a network adapter. Further, a memory may be, for example, memory **1806**, or a cache, such as found in an interface and memory controller hub that may be present in communications fabric **1802**.

[00163] The different illustrative embodiments can take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment containing both hardware and software elements. Some embodiments are implemented in software, which includes, but is not limited to, forms such as, for example, firmware, resident software, and microcode.

[00164] Furthermore, the different embodiments can take the form of a computer program product accessible from a computer usable or computer readable medium providing program code for use by or in connection with a computer or any device or system that executes instructions. For the purposes of this disclosure, a computer usable or computer readable medium can generally be any tangible apparatus that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

[00165] The computer usable or computer readable medium can be, for example, without limitation an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, or a propagation medium. Non-limiting examples of a computer readable medium include a semiconductor or solid state memory, a magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk, and an optical disk. Optical disks may include compact

disk - read only memory (CD-ROM), compact disk - read/write (CD-R/W), and DVD.

[00166] Further, a computer usable or computer readable medium may contain or store a computer readable or computer usable program code such that when the computer readable or computer usable program code is executed on a computer, the execution of this computer readable or computer usable program code causes the computer to transmit another computer readable or computer usable program code over a communications link. This communications link may use a medium that is, for example without limitation, physical or wireless.

[00167] A data processing system suitable for storing and/or executing computer readable or computer usable program code will include one or more processors coupled directly or indirectly to memory elements through a communications fabric, such as a system bus. The memory elements may include local memory employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some computer readable or computer usable program code to reduce the number of times code may be retrieved from bulk storage during execution of the code.

[00168] Input/output (I/O) devices can be coupled to the system either directly or through intervening I/O controllers. These devices may include, for example, without limitation, keyboards, touch screen displays, and pointing devices. Different communications adapters may also be coupled to the system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Non-limiting examples of modems and network adapters are just

a few of the currently available types of communications adapters.

[00169] The illustrative embodiments relate to an integrated resource tracking system and, more particularly, to a method and system which integrates multiple systems and applications together to determine trends by analyzing tags and/or keywords of multiple users over the multiple integrated systems and applications. The terms used below refer to similar objects described above with respect to **Figure 1** through **Figure 18**. Thus, the following may be read in view of **Figure 1** through **18**. Additional details are provided below.

[00170] The illustrative embodiments relate to an integrated resource tracking system and, more particularly, to a method and system which integrates multiple systems and applications together to determine trends by analyzing tags and/or keywords of multiple users over the multiple integrated systems and applications. Hereinafter the integrated resource tracking system can be referred to as processes, systems, ADPTrackr, the tracker of the illustrative embodiments, and variants thereof.

[00171] Tags are basic words or phrases that are commonly used as reference points when describing an element of value or clarification of an associated object. Tags can be linked to meta-data elements within a global human capital management platform. While tags can theoretically be linked to any data model objects, the following objects will support tags in its first out-of-box release: global person, position, organization unit, job family, capability, and asset, as examples.

[00172] The tracker of the illustrative embodiments may be backed by a REST-JSON API, written in Ruby on Rails

version 4; although this example, and the examples below, do not necessarily limit the claimed inventions as other implementations are contemplated by the illustrative embodiments. The application programming interface is used to import data from the owner of the tracking program and third party application programming interfaces, and to serve the tracker of the illustrative embodiments front-end. The development environment includes the Ruby Mine integrated development environment, and can use the railsAPI gem. The API may include three models: work item, tag, and person, though more or fewer models may be present. There is a many-to-many relationship between them. The models inherit from Active Record: the object relational mapping built into Rails, which comes preconfigured with sqlite3 for development, and the controllers of the illustrative embodiments can support at least the following actions: index, show, create, update, and destroy. Resources are automatically routed, including nested resources. Application programming interfaces can be tested using the Postman extension to GOOGLE® CHROME®.

[00173] The functionality behind the tracker of the illustrative embodiments may include both product functionality and a new product. For example, the functionality may include:

[00174] (i) the ability to integrate external third party sources (such as CONFLUENCE®, OUTLOOK®, RALLY®, YAMMER®, etc.) with an aggregator in order to track activities users perform on a daily, weekly, monthly, and yearly base, and to find top trends within an organization; and

[00175] (ii) the overlaying solution may leverage the parsing of external data in order to align with a goal and performance management product.

[00176] In addition, the tracker of the illustrative embodiments may provide quick insights into the top trends within an organization. For example, the tracker may:

[00177] (i) link to the tools an organization uses already (in reference to third party application);

[00178] (ii) integrate with numerous third party tools and have an exposed application programming interface that allows third party applications to integrate with its activity feed. The default applications may be as described above;

[00179] (iii) bridge the gap between goal management and ongoing organization activity by allowing a user to manually and automatically link activities to defined goals. For example, users can manually select an activity feed from an external source, and link it to a given goal. Automatically, users can associate a tag or reference to a particular goal. When an activity comes in their feed with a link to that tag or reference, the activity is automatically associated with the related goal;

[00180] (iv) provide quick insights into the trends within an organization by identifying tags and most common terms and word references through text and data mining. These trends can be measured on an overall organization metric, by department, team, and individual, amongst other things;

[00181] (v) show cross-departmental collaboration and alignment by assessing information about individuals collaborating together on a given activity; and

[00182] (vi) provide an up-to-date status-tracking tool that shows the overarching organizational activity in alignment with the overall organizational, team, and individual goals.

[00183] The tracker of the illustrative embodiments may link relevant organization activity (the work individuals do on a daily and ongoing bases) with human resources, performance, strategic planning, and talent management, and their related databases containing relevant information using application programming interfaces. The tracker of the illustrative embodiments may aggregate information from third party application programming interfaces and pool them to provide insights into the knowledge and work within the organization. This knowledge is then leveraged in order to identify the trending activities within an organization and used to identify internal dialect, acronyms, and knowledge, possibly tasks or goals that have not been previously done.

[00184] The tracker of the illustrative embodiments can also leverage the information gathered from third party integration tools in order to build out a competency catalog that is aligned with the work being done within the organization. From a strategic management perspective, the application may provide insights into the types of activities being performed in order to achieve various types of goals. For example, the tracker of the illustrative embodiments can identify that, for the goal to 'Build a new product', a product manager typically:

[00185] (i) Spends a predetermined time, typically a few weeks, of the goal's start dates doing research and meeting with the user experience research and user interface teams;

[00186] (ii) spends the one to three months after the start of a goal in RALLY® or related programs building features and user stories, and in meetings with the serum team; and

[00187] (iii) and three to six months into the goal the manager may work with product marketing in order to build go-to-market trends.

[00188] In this way, the technical features of the illustrative embodiment solve a technical problem or provide a technical contribution to current systems by integrating systems and tracking trends using terms, tags, and keywords from one or multiple users on a team or over an enterprise or any subset thereof. The illustrative embodiment can monitor data from many different real-time data sources to achieve these and other technical solutions.

[00189] From an individual review perspective, the tracker of the illustrative embodiments can provide a timeline of all the work an individual has done throughout the course of the performance cycle. In this context, the individual can view an interactive map that shows their work patterns, key collaborators, and overall accomplishments throughout the year. The tracker of the illustrative embodiments has the ability to integrate with feedback modules, and may provide a tool for building/cascading strategic goals and defining performance review cycles. The tracker of the illustrative embodiments may provide tools to link with project management and customer relationship management solutions in order to incorporate project plans, customer data, and related tasks into the application and its human resources processes.

[00190] Attention is now turned to the integration of MICROSOFT® OUTLOOK® with the tracker of the illustrative embodiments. Current integration steps may include:

[00191] i. The user may be prompted with a credential entry screen, similar to userAuthFrontEnd.png. This front end may be generated by index.html. On this page,

the user may supply their OUTLOOK® username and password, as well as the particular OUTLOOK® folders they wish to integrate with, such as "outbox", "in box", and "calendar";

[00192] ii. once the user submits the request, app-dev.js may execute one to three processes to handle the user request; one for each OUTLOOK® folder;

[00193] iii. from this point forward, the user's inbox is provided as example, although other OUTLOOK® folders are handled in a similar fashion;

[00194] iv. the app-dev.js passes parameters to soap_request_inbox.js including the initial soap envelope id_request_inbox.xml as well as the user's credentials;

[00195] v. the soap_request_inbox.js passes id_request_inbox.xml to the OUTLOOK® Exchange Web Server (EWS) along with the user's credentials via a CURL command;

[00196] vi. the EWS responds to the CURL command and returns an xml file of unique IDs. These IDs correspond to all of the email items currently in the user's inbox;

[00197] vii. the soap_request_inbox.js traverses the xml returned by EWS, extracts the unique IDs, and dynamically generates a second soap request (XML file);

[00198] viii. this second soap request now queries the EWS for further detail on the emails identified by the unique IDs via a similar CURL command;

[00199] ix. the EWS returns yet another XML file, which is traversed for each unique ID. The soap_request_inbox.js extracts fields including, but not limited to: subject, sensitivity, dateRecieved, importance, dateSent, senderN arne, senderEmail, recipients, ccrecipients, and textBody from an email; and

[00200] x. those extracted fields are then persisted in MongoDB in the inbox collection. Steps iii-ix are

repeated for sent items, as well as calendar information, if the user elects to pull/persist those data.

[00201] By way of another example, current RALLY® integration includes:

[00202] i. the rallyPullTasks.js currently fetches all current user Tasks via the RALLY® application programming interface. When fetching the tasks, information such as task: description, Owner, Project, Parent, Children, TaskName, State, etc. is considered; and

[00203] ii. for each current task, rallyPullTasks.js then persists each task using the defined schema into MongoDB's rallyTasks collection. Currently, the product fetches and persists the current sprint's user tasks at the time of execution of rallyPullTasks.js. This gives a snapshot of what is being developed or worked on, but does not consider the history of those work items.

[00204] Figures described above can be representative of block diagrams and underlying functionality of the screen displays in accordance with aspects of the illustrative embodiments, which are implemented within the environments shown in **Figure 11** through **Figure 13**. The figures described and shown herein can thus be illustrative of a system, a method, and/or a computer program product and related functionality implemented on the computing system of **Figure 16** through **Figure 18**, in accordance with aspects of the illustrative embodiments.

[00205] Attention is now turned to profile definitions. The tracker of the illustrative embodiments may provide four distinct benefits for strategic management. Each benefit may be divided into independent modules within the overarching solution. These modules include strategic planning and ongoing goal management, status reporting and activity tracking, performance management, and reporting and analytics.

[00206] Attention is first turned to the strategic planning and ongoing goal management module. This module may provide tools for short and long term workforce strategic plans through the use of guiding tools that support and advise organization transformation activities within the organization. The tracker of the illustrative embodiments supports the definition of strategic goals and enables the monitoring of workforce activity towards these goals. It enables organizations to understand which goals are on track, and which goals may be delayed.

[00207] With the integration of activity tracking, subsequently described, the strategic planning solution can predictively and proactively recognize changes in organization practices and explicitly identify the following items:

[00208] i. planned and unplanned initiatives the workforce is actively focusing on;

[00209] ii. emerging trends that are surfacing with the organization;

[00210] iii. impact of changing current strategic initiatives, and who is impacted most;

[00211] which departments are most aligned with the strategic vision;

[00212] iv. how the strategic vision has evolved over time; and

[00213] v. recommended adjustment to the strategic vision based on actual recorded activities and their success rates.

[00214] The strategic planning and goal management module is unique due to many factors, including the ability for a software tool to analyze the activity of an organization's organizational practices, and provide intelligent recommendations on desired changes to the corporate strategy. This functionality is not available

using traditional project management software. In the most rudimentary explanation, this module serves as an artificial intelligence engine to support the executive leadership in understanding the internal dynamics of the organization by providing technical capabilities to integrate different systems together, analyze information passed within the system and users, and determined trending points. Beyond the clear strategic benefits, the tracker of the illustrative embodiments changes the way goals and performance management can be used within the organization.

[00215] The tracker of the illustrative embodiments need not be a top-down goal management process, but rather an organically emerging goal builder which thrives on the activities individuals are doing today, and provides insights on how to optimize that activity towards a more strategic organizational purpose. This ability is a completely different paradigm as to what organizations do today. This ability allows individuals to continuously monitor their ongoing goals and view their trending patterns, as described more in the next section particularly over an entire enterprise using multiple integrated systems.

[00216] Attention is now turned to the next module, status reporting and activity tracking. Purposes of the tracker of the illustrative embodiments may include enriching organization operations, consolidating real information about an organization, and providing metrics for leaders, managers, and individuals to ensure the organization is aligned and individuals are on track with their tasks and responsibilities. The tracker of the illustrative embodiments aims to reduce or eliminate the process of manual status reporting by providing simple tools for parsing information about individual

activities. By building a visual pinboard of 'My Work', individuals can quickly visualize their work life and work activity.

[00217] With full control on the individual level, the product aids individuals in managing their information dashboard, and filtering any conflicting or non-relevant information. By integrating with the software and applications used by the workforce today, the tracker of the illustrative embodiments can track active work within the organization, and processes information to understand what work the individuals are actively doing.

[00218] Examples of tools that may be integrated with the solution provided herein include, but are not limited to:

[00219] OUTLOOK® - processing of work calendars and email exchanges;

[00220] RALLY® - processing of backlog definition, status, and ownership assignment;

[00221] CONFLUENCE® - active posts, updates, and discussions raised by users;

[00222] SALESFORCE® - processing of sales data to identify closing times and general sales metrics by user;

[00223] GOOGLE® DOCS® - for processing of shared information and collaboration across teams; and

[00224] OFFICE® & SHAREPOINT® - ability to implement rich site summary (RSS) changes to a document for processing in the tracker of the illustrative embodiments.

[00225] Beyond the software identified above, the tracker of the illustrative embodiments may have exposed application programming interfaces on a marketplace of applications and may encourage third parties to provide integration tools with their software such that the above examples should not be considered an exhaustive list.

[00226] Attention is now turned to tagging and activity tracking. Tagging and text/data processing may enable the connection of free text with tangible keywords about an individual or a body of work. Tagging assists in the processing of work feeds from third party solutions as tagging enables the software to make relevant connections across different bodies of work.

[00227] Individual, team, and departmental trending tags may be identified by counting the number of times a tag is used by the person/team/department. Such trending tags may also be identified by monitoring the frequency in which the tag was used. The more frequently the tag is used, and the most recently it has been used, the more that tag is trending. For teams and departments, the span of which the tag is used is also relevant. The span refers to the amount of people using it.

[00228] Watching trends: All users can put a 'watch' on a particular trend/tag. When 'watching a tag', the user gets prompted when a tag is being used. There are various prompt options that can define how the user is notified, such as but not limited to email notification, application alert, weekly report, and others.

[00229] Promoting trends: Users such as managers and executive leaders can promote trends for their span of control. When promoting a trend, all individuals within that organization will see the trend as prompted by the promoted individuals in their dashboard, and with a recommendation to work towards that trend. A message by the promoter can be provided alongside the trend.

[00230] Work dashboard: The work dashboard may provide insights on numerous traditionally intangible factors that allow an individual to understand their purpose within an organization and to process their strengths within the organization.

[00231] Gauging alignment of goals: By processing departmental and individual goals and analyzing the trends from the individual's work activity, the tracker of the illustrative embodiments can identify how aligned an individual is to their existing goals, at an individual, departmental, and strategic level.

[00232] Managing individual goals: Individuals can generate new individual goals. While they can do this manually, new goals are typically generated based on recommendations from the system. Recommendations may be based on the set of trends, that is, tags, surfacing from an individual feed. Individuals may also be advised by the system to collaborate with another individuals based on the similarity of their goals. They may then create a collaborating page to align between their individual initiatives.

[00233] When reviewing their dashboard, individuals can create auto-filters to process activities towards goals. By recognizing the type of activities associated with a given goal, the system may recognize that a given activity should be auto-associated with a goal. Auto-associations are based on a tag or set of tags used in the activity itself.

[00234] Additionally, when an individual views a given goal, he/she can define specific tags or combinations of tags that are relevant for that goal. In doing such, he or she can also review the system recommended tags for the goal, and adjust as needed.

[00235] Viewing work trends: In reviewing their dashboard and profile, individuals may see a tag cloud based on the top internal organization acumen used by themselves. A tag cloud is like a word cloud, though the identifiers are tags. The tag cloud is an exceptional way for peers and managers to better understand the

professional knowledge and active engagement the individual is currently focused on.

[00236] In some illustrative embodiments, additional tags cannot be added into the word cloud. Individuals can choose to hide any of the tags within the cloud. In other illustrative embodiments, tags may be added or removed from the tag cloud. Individuals might be able to see hidden tags. Individuals also may have access to individual work patterns including an understanding of their general work habits such as, work hour patterns; types of activities performed throughout the week based on tools; emerging trends for them and their team based on tags identified in their work activity; and top collaborators and contributors towards their goal or trend.

[00237] Understand organizational influence: Finally, individuals can measure themselves on their level of expertise within the organization based on tag usage, collaboration span, and tag frequency. Collaboration span may be a number of people with whom an individual collaborates, but also could be extended to team or organizational comparisons. Individuals can be measured via the following influence factors:

[00238] i. Specialist: uniqueness of their tag cloud and strength of the tags within the cloud;

[00239] ii. Leader: breath of engagement in various goals and with various collaborators based on volume of different activities and volume of people the individual is working with; and

[00240] iii. Team Player: high supporter of departmental goals and team initiatives.

[00241] **Figure 3**, described above, is an example of a sample activity tracker dashboard. With an application that consolidates real-time information about work

activities by an individual and groups of individuals, the process of traditional status reporting becomes obsolete. Just as managers and executives can promote trends down the organization, individuals and their managers can upstream recommendations and communications to their managers. These upstream notifications provide insights and comments on a given tag, trend, or goal to ensure clarification is provided when needed.

[00242] Attention is now turned to the performance management modules. The tracker of the illustrative embodiment's individual-centric performance management is a continuously aligned process tracking ongoing activities. With a spot-check report, individuals and managers can compile a profile of individuals, including their activities, their alignment to goals, collaborations with others, and tag clouds associated with them.

[00243] Feedback Gathering: At any point in time, an individual or manager can request and give feedback from/to other individuals. Based on interaction patterns with other individuals, the tracker can intelligently request feedback from colleagues about a particular individual.

[00244] Typical Feedback may be short, with an option to give an individual a thumbs-up or accolades, possibly alongside a comment. A more formal feedback review can also be requested in which the individual is evaluated based on the performance of their goals. Peers can be requested to give feedback on an individual's goal accomplishment, but only if they had substantial involvement with the goal, as assessed by the system. The system therefore is intelligent enough to understand which aspects of the goal the peer should participate in reviewing.

[00245] Annual Performance Review: The system expects that individuals and their managers meet regularly to discuss the individual's performance. The system therefore may be designed to support continuous communications and to make blockers and successes transparent to the manger. The annual review provides a compilation of all achievement accomplished by the individuals throughout the year. Differentiating the tracker of the illustrative embodiments from other solutions, the system provides clear insights into the changes made to the individual's goals over the course of the year. The system therefore not only provides an assessment of the individual's capabilities, but also the potential volatility within the team or organization. While the summary of the individual's performance over the year can be accessed at any time, it is during the formal annual review that comments are documented between both the individual and manager. This session should be treated as a retrospective over the year.

[00246] Both the individual and manager may provide their feedback in the form of a rating for each of the goals set by the individual, and a final rating may be calculated. A flag may be raised if there is a high discrepancy between the individual and manager ratings, or if either rating is significantly different from the system's projected average rating based on the activities gathered.

[00247] Talent Calibration: Managers or other users can maintain a continuous talent calibration grid depicting their individuals under their authority on a performance versus potential axis. The system then may be extended to overlay a velocity versus impact metric, showing the volume of activities an individual performs on an ongoing

basis, their overall influence factors, and goal completion metrics.

[00248] Attention is now turned to the reporting and analytics module. Reports and analytics are embedded throughout the tracker of the illustrative embodiments to help users compare and analyze the information stored in the system. The reporting engine provides a graph database analysis of the top and emerging trends within the organization, department, team, or individual. The reporting engine may provide insights into the top trends that are associated with high, medium, and low performers, and look for correlations that can help the organization improve its organizational structure and strategic initiatives. The reporting engine also may identify the arteries of the organization based on individual influence factors and may provide search capabilities to fully drill down into the data provided.

[00249] Detailed Functionality: The tracker of the illustrative embodiments may be designed for knowledge workers, with specifically designed functionality for individual, line-manager, multi-level manager, and executive level users.

[00250] Interaction with the tracker and accessing the application: Integrated via a single sign on function, with initial integration point to and REDBOX ENTERPRISE® and VANTAGE®. There may be an optional independent login.

[00251] On initial deployment of the system, the client may specify the following elements, which are then used as part of the tracking process: What are the organization core values, what is the corporate mission statement, and all strategically set goals for the organization. Information may be entered in a front end

user interface designed for the executive user. Tasks can be delegated to human resources or assistant users.

[00252] In addition, the client's administrator may specify which tools they would like to integrate with the tracker of the illustrative embodiments in order to process activity feeds. While it is not mandatory to integrate with a tool, it is highly recommended for significantly higher insights and functionality.

[00253] When each end user logs into the system, they will have the option to configure their individual connections to the enabled application. If the client already has a single sign on between the third party look and their account via their internal portal, this will not be required.

[00254] The foregoing examples have been provided merely for the purpose of explanation and are in no way to be construed as limiting of the present illustrative embodiment. While aspects of the present illustrative embodiment have been described with reference to an exemplary embodiment, it is understood that the words which have been used herein are words of description and illustration, rather than words of limitation. Changes may be made, within the purview of the appended claims, as presently stated and as amended, without departing from the scope and spirit of the present illustrative embodiment in its aspects. Although aspects of the present illustrative embodiment have been described herein with reference to particular means, materials, and embodiments, the present illustrative embodiment is not intended to be limited to the particulars disclosed herein; rather, the present illustrative embodiment extends to all functionally equivalent structures, methods and uses, such as are within the scope of the appended claims.

[00255] Thus, the illustrative embodiments may provide for a method implemented in a computer system which comprises: integrating multiple systems and applications; and determining trends by analyzing tags and/or keywords of multiple users over the integrated systems and applications. This method may be varied.

[00256] For example, the multiple systems and applications may be computer systems and software applications including communication applications. The method may include using APIs to import data from the multiple systems and applications. In this case, the APIs may include at least three models: work item, tag, and person with many-to-many relationship between them.

[00257] In another illustrative embodiment, the method may also include integrating external third party sources with an aggregator in order to track activities users perform on a daily, weekly, monthly, and yearly base, and find top trends within an organization. In this case, the method may also include parsing of external data, in order to align with a goal and performance management product.

[00258] In still another illustrative embodiment, the integrator integrates with numerous third party tools and has an exposed API that allows third party applications to integrate with its activity feed. In yet another illustrative embodiment, the method further includes associating a tag or reference to a particular goal and, when an activity comes in a feed with a link to the tag or reference, the activity is automatically associated with a related goal. In still another illustrative embodiment, identifying trends may include identifying tags and most common terms and word references through text and data mining. In yet another illustrative embodiment, the method may further include analyzing an

activity and providing intelligent recommendations on required changes by identifying the trends.

[00259] Still other variations are possible. For example, the illustrative embodiments may provide for a computer system for generating trending information for recommendations, comprising: a hardware memory device that stores program instructions; and a processor that executes the program instructions and causes the computer system to perform the steps of the above examples and any combination thereof. In another example, the illustrative embodiments may provide for a computer program product comprising computer readable program instructions stored on non-transitory computer readable storage medium, the computer readable program instructions causing a computing device to perform the steps of the above examples and any combination thereof.

[00260] The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different features as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

What is claimed is:

1. A computer network comprising:

a server computer having a server processor and a server non-transitory computer readable storage medium;

a first computer, operable by a first user, in communication with the server computer, wherein the first computer has a first processor and a first non-transitory computer readable storage medium storing first program code which, when executed by the first processor, implements a first software tool having a first function and a second software tool having a second function;

a second computer, operable by a second user, in communication with the server computer, the second computer having a second processor and a second non-transitory computer readable storage medium storing second program code which, when executed by the second processor, implements the first software tool having the first function and the second software tool having the second function;

wherein the server non-transitory computer readable storage medium stores third program code which, when executed by the server processor, is configured to:

gather first data regarding use of the first software tool;

gather second data regarding use of the second software tool; and

based on the first data and the second data, link activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first user and the second user belong, and wherein, in

executing the third program code, a communications link between the server computer and the first computer or the second computer is improved.

2. The computer network of claim 1 wherein the third program code is further configured to:

cause a physical display device to present proportional use information comprising a proportional comparison of: use of the first software tool on both the first computer and the second computer relative to use of the second software tool on both the first computer and the second computer.

3. The computer network of claim 1 wherein the third program code is further configured to:

based on the first data and the second data, calculate a first amount of work the first user contributed to the performance goal and calculate a second amount of work the second user contributed to the performance goal.

4. The computer network of claim 1 wherein the third program code is further configured to:

based on the first data and the second data, calculate a performance of the first user relative to the second user.

5. The computer network of claim 1 wherein the first user has a first assigned goal and wherein the third program code is further configured to:

track a total number of activities by the first user for the first assigned goal.

6. The computer network of claim 1 wherein the third program code is further configured to:

calculate, for the first user, a proportional use of the first software tool and the second software tool.

7. The computer network of claim 6 wherein the third program code is further configured to:

display which of the first user and the second user performs a most number of particular activities towards the performance goal, whereby it may be determined which user should be consulted regarding a question regarding the particular activities.

8. The computer network of claim 1, wherein the performance goal is for the organization, wherein the organization has a plurality of departments, wherein the first user is in a first department and the second user is in a second department, and wherein the third program code is further configured to:

based on the first data and the second data, display cross-departmental collaboration between the first user and the second user.

9. An apparatus comprising:

a server computer having a server processor and a server non-transitory computer readable storage medium;

the server computer being in communication with a first computer, operable by a first user, wherein the first computer has a first processor and a first non-transitory computer readable storage medium storing first program code which, when executed by the first processor, implements a first software tool having a first function and a second software tool having a second function;

the server computer being in communication with a second computer, operable by a second user, the second computer having a second processor and a second non-transitory computer readable storage medium storing second program code which, when executed by the second processor, implements the first software tool having the first function and the second software tool having the second function;

wherein the server non-transitory computer readable storage medium stores third program code which, when executed by the server processor, is configured to:

gather first data regarding use of the first software tool;

gather second data regarding use of the second software tool; and

based on the first data and the second data, link activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first user and the second user belong, and wherein, in executing the third program code, the server computer improves a communications link between the server computer and the first computer or the second computer.

10. The apparatus of claim 9, wherein the third program code is further configured to:

cause a physical display device to present proportional use information comprising a proportional comparison of: use of the first software tool on both the first computer and the second computer relative to use of the second software tool on both the first computer and the second computer.

11. The apparatus of claim 9, wherein the third program code is further configured to:

based on the first data and the second data, calculate a first amount of work the first user contributed to the performance goal and calculate a second amount of work the second user contributed to the performance goal.

12. The apparatus of claim 9, wherein the third program code is further configured to:

based on the first data and the second data, calculate a performance of the first user relative to the second user.

13. The apparatus of claim 9, wherein the first user has a first assigned goal and wherein the third program code is further configured to:

track a total number of activities by the first user for the first assigned goal.

14. The apparatus of claim 9, wherein the third program code is further configured to:

calculate, for the first user, a proportional use of the first software tool and the second software tool.

15. The apparatus of claim 14, wherein the third program code is further configured to:

display which of the first user and the second user performs a most number of particular activities towards the performance goal, whereby it may be determined which user should be consulted regarding a question regarding the particular activities.

16. The apparatus of claim 9, wherein the performance goal is for the organization, wherein the organization has a plurality of departments, wherein the first user is in a first department and the second user is in a second department, and wherein the third program code is further configured to:

based on the first data and the second data, display cross-departmental collaboration between the first user and the second user.

17. A method implemented in a server computer having a server processor and a server non-transitory computer readable storage medium, the server computer being in communication with a first computer, operable by a first user, wherein the first computer has a first processor and a first non-transitory computer readable storage medium storing first program code which, when executed by the first processor, implements a first software tool having a first function and a second software tool having a second function, the server computer being in communication with a second computer, operable by a second user, the second computer having a second processor and a second non-transitory computer readable storage medium storing second program code which, when executed by the second processor, implements the first software tool having the first function and the second software tool having the second function, wherein the server non-transitory computer readable storage medium stores third program code which, when executed by the server processor, implements the method, the method comprising:

gathering first data regarding use of the first software tool;

gathering second data regarding use of the second software tool; and

improving, using the server computer, a communications link between the server computer and the first computer or the second computer by linking, based on the first data and the second data, activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first user and the second user belong.

18. The method of claim 17 further comprising:

altering a physical display device by displaying proportional use information comprising a proportional comparison of: use of the first software tool on both the first computer and the second computer relative to use of the second software tool on both the first computer and the second computer.

19. The method of claim 17 further comprising:

calculating, based on the first data and the second data, a first amount of work the first user contributed to the performance goal and a second amount of work the second user contributed to the performance goal; and

altering a physical display device by displaying the first amount of work and the second amount of work.

20. The method of claim 17 further comprising:

calculating, for the first user, a proportional use of the first software tool and the second software tool; and

altering a physical display device by displaying which of the first user and the second user performs a

most number of particular activities towards the
performance goal.

ABSTRACT

A computer network including a server computer, a first computer implementing a first software tool having a first function and a second software tool having a second function, and a second computer implementing the first software tool and the second software tool. The server computer is configured to gather first data regarding use of the first software tool; gather second data regarding use of the second software tool; and based on the first data and the second data, link activities of the first user and the second user to a performance goal for any one of the first user, the second user, a team including at least the first user or the second user, or an organization to which the first user and the second user belong. In executing the third program code, a communications link between the server computer and the first computer or the second computer is improved.