
WearWise

SECURITY DOCUMENTATION

WearWise security

How WearWise protects participants' data across the sensor patch, the phone app, the backend and the web dashboard: controls, secrets, testing, open risks and the owner's responsibilities.



Author: Zakiul Atheef

Version 1.0 · 14 October 2026 · handover release v1.0.0

WearWise Project Team: Zakiul Atheef · Hari Bethelli · Siri Bethelli · Thevindu Kodagoda Munasinghage

Research prototype. Not a medical device. Not certified or independently tested.

Contents

PART 1 · OVERVIEW

1 About this document 3
2 Security summary 4
3 System overview and trust boundaries 5
4 Data inventory and classification 6

PART 2 · THREAT MODEL

5 Assets and threat actors 7
6 Threats and mitigations 7

PART 3 · SECURITY CONTROLS

7 Patch firmware and Bluetooth 9
8 Wi-Fi streaming 9
9 Phone app 10
10 Accounts and authentication 11
11 Database access control 11
12 Sharing and live view 12
13 Storage and Realtime 12
14 Web dashboard 12
15 Repository, build and supply chain 13

PART 4 · SECRETS AND OPERATIONS

16 Secrets inventory 14
17 Account lifecycle and administration 15
18 Incident response 15
19 Backups, logging and monitoring 16
20 Local development security 16

PART 5 · ASSURANCE

21 Security testing and verification 17
22 Review history and finding status 18
23 Changes since the 13 October audit 18

PART 6 · RISKS AND RESPONSIBILITIES

24 Risk register 20
25 Owner responsibilities before real participants 21
26 Dependency advisories 21
A Where the security controls live 23
B Glossary and references 23

PART 1

Overview

What this document covers, the security position in one page, and the system and data it protects.

1 About this document

Title	WearWise Security Documentation
Author	**Zakiul Atheef**
Project team	WearWise Project Team: Zakiul Atheef, Hari Bethelli, Siri Bethelli and Thevindu Kodagoda Munasinghage (roles at the end of this document)
Licence	PolyForm Noncommercial License 1.0.0 (`LICENSE`): free for noncommercial use, not for sale
Version and date	1.0, 14 October 2026
Applies to	Handover release v1.0.0: phone app 0.1.0 (Expo SDK 57, React Native 0.86), web dashboard 0.1.0, patch firmware 0.9.6 (ESP-IDF 5.4), Supabase backend with 11 database migrations
Audience	The project owner, the organisation's IT and privacy staff, ethics reviewers, and developers who maintain WearWise
Classification	Internal: for the project owner and authorised maintainers. It contains no secrets.
Status	Engineering documentation of a **research prototype**. Not a certification, a penetration-test report or a medical-device assessment.
Next review	Before any use with real participants, after any major upgrade, and at least once a year

Sources. This document consolidates and brings up to date the security material in the repository: `docs/security.md`, the security audit of 13 October 2026 (`docs/security/audit-2026-10-13.md`), the release security report of 20 September 2026, the database, firmware, Bluetooth-protocol and deployment documentation, and the handover dry run and hardware tests of 14 October 2026. Where the code has changed since an earlier review, this document follows the current code.

Severity labels used throughout: High Medium Low Info. Status: Fixed for resolved items.

2 Security summary

Position statement

WearWise is a capstone **research prototype** that handles health-related data. Its security practices are informed by relevant guidance: the OWASP Mobile Application Security Verification Standard (MASVS), the OWASP Top 10, and Supabase's security recommendations. **No part of the system has been certified, penetration-tested by a third party or formally audited**, and it is not a medical device. Treat it as a prototype until the owner's own independent review says otherwise.


What is in place

- ✓ **Authorisation lives in the database.** Row Level Security on every table, no privileges for anonymous users, least-privilege grants, and server-side checks for roles, account status, consent, 18+ and terms. 277 SQL checks and 8 pgTAP tests verify it.
- ✓ **Participant-controlled sharing.** One-time hashed share codes create scoped, revocable grants. A participant's email is never shown to researchers.
- ✓ **Encrypted at every hop.** Bluetooth LE Secure Connections with a 6-digit passkey. Optional Wi-Fi streaming over TLS with a certificate pinned over the authenticated Bluetooth link. HTTPS only in release builds.
- ✓ **Encrypted on the phone.** SQLCipher database with its key in the OS secure store, Android backup off, screenshots blocked in release builds, and an iOS privacy cover.
- ✓ **No secrets in the code or the repository.** The apps carry only the project URL and its publishable key. A handover scan found no credentials.
- ✓ **Hardened dashboard.** Strict Content-Security-Policy allowing one backend host, no framing, HSTS, PKCE sign-in, and no caching of recordings.

Most important open items (Part 6)

Risk	Rating	Issue
R-01	High	Patch flash is unencrypted and USB download is open: brief physical access can copy bonds, the TLS key and the PIN. Fix: Secure Boot V2 and flash encryption (one-way, per chip).
R-02	Medium	No two-factor sign-in for researchers and clinicians.
R-03	Medium	Open sign-up: scripted accounts could fill storage (no CAPTCHA or enrolment code).
R-04	Medium	The app can't cryptographically prove a patch is genuine.
R-05	Medium	Hosted project settings outside the migrations (Site URL, SMTP, email confirmation) must be set by the owner.

3 System overview and trust boundaries



WearWise architecture. The patch talks only to the phone. The phone talks to Supabase. The dashboard reads only what participants share.

Component	Role	Technology
Sensor patch	Reads sensors and streams packets to one phone	ESP32, ESP-IDF 5.4, C (firmware 0.9.6)
Phone app	Pairing, live view, recording, encrypted local store, upload, sharing	React Native 0.86, Expo SDK 57, SQLCipher
Backend	Accounts, cloud copy of recordings, sharing, alerts, live-view relay	Supabase: Postgres 17, Auth, Storage, Realtime, PostgREST
Web dashboard	Researchers and clinicians (and participants' own view); Patch setup over USB	React 19, Vite, static site

Trust boundaries

1. **Radio (patch ↔ phone):** Bluetooth LE, and optionally Wi-Fi on the local network. Anyone nearby can transmit, so links must be encrypted and authenticated.
2. **Phone ↔ Internet ↔ Supabase:** HTTPS. The app and its publishable key are public, so **every privilege decision is made by the database**, never by the app.
3. **Browser ↔ Supabase:** the same public API, with the same rules. The dashboard is a static site holding no secrets.
4. **Device storage:** phones and patches can be lost or stolen. Data at rest on the phone is encrypted. On the patch it is not yet (R-01).
5. **Administration:** Supabase project members, service keys and access tokens bypass Row Level Security, so they must be held by few people.

Design choices that reduce the attack surface: there are no Edge Functions and no server code of WearWise's own (Postgres functions and policies do the server work); the patch never talks to the backend; and the backend is chosen by configuration only.

4 Data inventory and classification

The apps contain no analytics or remote crash-reporting service, so no health data leaves through telemetry. Recordings are encrypted on the phone and protected by access control in the cloud. They are not end-to-end encrypted with the phone's key, so a Supabase project administrator can read them.

Data	Class	Where it is kept	Protection and visibility
Recordings: ECG, pulse wave, heart rate, SpO_2, skin temperature, movement	Health (sensitive)	Phone: SQLCipher database. Cloud: `recorded_sessions`, `recorded_channels` rows and private Storage files (`.wwch`)	Encrypted on the phone. Cloud: RLS and private bucket. Viewers see only granted signals while the grant is live
Possible falls, vital alerts	Health (sensitive)	Phone database; `fall_events`, `vital_alerts`	RLS. Falls are visible to a viewer only if the grant includes falls
Health profile: sex, date of birth, height, weight, blood group	Health (sensitive)	**Phone only** (encrypted database)	Never uploaded
Email, display name, role, status	Personal	Supabase Auth, `profiles`	Own row only. Viewers see the display name, **never the email**
Password	Credential	Supabase Auth (salted hash)	Never stored by the apps. Minimum 10 characters, enforced by the server
Consent, 18+ and terms records	Compliance record	`profiles`	Timestamps set by the server. Only known terms versions are accepted
Share codes	Access token	`share_codes`	SHA-256 hash only. Single use, 24 h. RPC only
Access grants	Authorisation record	`access_grants`	Changed only by RPCs. Revoked rows kept as an audit trail
Session tokens	Credential	Phone: OS secure store (this device only). Browser: storage managed by supabase-js	Wiped on sign-out (on the phone, even when offline)
Wi-Fi name and password	Credential	Phone secure store, per patch and per account. Patch: RAM only	Sent only over the authenticated, encrypted Bluetooth link
Patch identity, Bluetooth address, connection events	Device identifier	Phone database	Encrypted, scoped to the account
Patch label PIN, bonds, TLS private key	Credential	Patch flash (`wwcfg`, NVS)	**Plain-text flash** (R-01)
Live-view readings	Health (transient)	Nowhere: Realtime broadcast only	Private channel per grant. Nothing stored
Preferences (theme, sync toggle)	Non-sensitive	Phone: unencrypted key-value store. Browser: local storage	No personal or health data

PART 2

Threat model

Who might attack WearWise, what they're after, and how each threat is handled.

5 Assets and threat actors

Assets

Participants' health recordings and alerts · account credentials and sessions · the authorisation model (who may see whom) · patch pairing secrets · service keys and signing keys · availability of recording (it must not be lost).

Actors

A curious or malicious **app user** holding the public key · a **researcher** trying to see more than was shared · an **attacker within radio range** · an attacker on the **same Wi-Fi** · a **thief** of a phone or patch · **automated abuse** of sign-up · a compromised **dependency** · a careless or compromised **administrator**.

6 Threats and mitigations

Threat	Mitigation	Residual
A user calls the API directly with the public key to read others' data (OWASP: broken access control)	RLS on every table, `anon` has no privileges, own-row policies, viewer access only through live grants, Storage object-name rules. Verified by 277 SQL checks, 8 pgTAP tests and two-user API tests	Low
A user promotes themselves to researcher, or edits consent or status columns	Only `display_name` is client-writable. Roles change only through admin SQL. The sign-up trigger refuses sign-ups without consent, 18+ and known terms	Low
A researcher sees more than the participant shared	Grants scoped to signal types and falls. Sessions visible only if they contain a granted signal. Email hidden. Access ends at once when revoked or suspended	Low: session metadata (device name, firmware) is visible (R-07)
Share codes are guessed or brute-forced	Single-use codes, about 49.5 bits, 24 h, SHA-256 stored, 10 failures per hour per viewer (locked per researcher against races)	Low
Eavesdropping or tampering on Bluetooth	LE Secure Connections only, passkey (label PIN), bonding. Every characteristic needs an encrypted, authenticated link. Weak or short-key links are dropped and their bonds deleted	Low
A nearby attacker pairs with a patch	Pairing only with no bonds or within 60 s of pressing BOOT. Lock-out after 3 failures. At most two bonded devices. Unauthenticated links dropped after 30 s	Medium: label PIN is fixed per patch (R-06)

Threat	Mitigation	Residual
A look-alike patch receives the Wi-Fi password or sends fake readings	A saved patch whose identity changes is refused. Strict protocol and packet checks (CRC, IDs, rates)	**Medium**: no cryptographic patch identity (R-04)
Interception or hijack of the Wi-Fi stream	TLS with the patch certificate pinned (SHA-256 read over authenticated Bluetooth). Per-socket proof-of-possession within 3 s, compared in constant time. Release builds refuse Wi-Fi without a pin	**Low**: 4-byte PoP (R-10)
A stolen phone exposes recordings	SQLCipher with the key in Keychain/Keystore (this device only). Android backup off. Screenshots blocked	**Low**: depends on the device lock
A stolen patch is cloned	None in the current build	**High** (R-01)
Scripted sign-ups fill storage	Uploads only into one's own folder with the app's exact file names. 50 MiB per file. Consent required	**Medium** (R-03)
Phishing or reuse of a researcher's password	10+ characters, common passwords refused by the apps, suspension ends all sessions	**Medium**: no 2FA (R-02)
Script injection in the dashboard (OWASP: injection, XSS)	React escaping, strict CSP (`script-src 'self'`, one backend host), no framing. Live-view values validated and clamped	**Low**
Password-reset or sign-in link abuse	PKCE flow, recovery links only, refusal of a link for a different account, redirect allow-list	**Low**
Malicious dependency install scripts (supply chain)	`ignore-scripts=true`, lockfile, pinned flasher library	**Low**: see the advisories (section 26)
Secrets committed or bundled into an app	Gitignored `.env` and keystores, release-config check, APK audit script, handover scan	**Low**
A malicious `wearwise://` link crashes or misdirects the app	Every incoming link is checked before the router reads it. Protected routes check session ownership	**Low**
Administrator error or a compromised admin	Admin scripts check their inputs and end sessions on change. Tokens read without echoing them. Few project members	**Medium**: organisational (section 17)

PART 3

Security controls

The controls in each layer, and where they live in the code.

7 Patch firmware and Bluetooth

Pairing mode	I/O capability DisplayOnly, bonding, MITM protection, **LE Secure Connections only**, 16-byte keys. A link that isn't Secure Connections, isn't authenticated or uses a short key is dropped and its bond deleted.
Passkey	The 6-digit **label PIN**, written by the dashboard's Patch setup (random, guessable values like 123456 skipped, verified on the chip). A patch never set up there makes its own and prints it once on the serial console.
When pairing is allowed	Only with no bonds, or within **60 s of pressing BOOT**. **Three failed pairings** lock pairing until BOOT is pressed (survives reboots).
Bonds	At most **two** bonded phones or tablets. A third replaces the oldest. One connection at a time.
Link protection	Every characteristic requires an encrypted, authenticated link. A link that doesn't authenticate is dropped after **30 s** (60 s while the PIN prompt is up), so nobody can hold the only connection slot.
Randomness	Secrets are generated with the hardware true-random source enabled.
Serial console	The PIN is printed only for an unlabelled patch. Readings only in a debug build.
Packets	Versioned binary format with CRC-32. The app checks length, framing, version, sensor, encoding, CRC, session ID and patch ID on every packet.
At rest	**Open** Flash, NVS (bonds, TLS key) and the PIN record are plain text, and ROM download mode is open (R-01). The documented fix is in the firmware README, "Production hardening": Secure Boot V2, flash encryption in release mode, NVS encryption and disabled ROM download. These burn eFuses (permanent) and need chip revision 3.0 or later plus a signed-update path in Patch setup.

Code: `firmware/wearwise-esp32/main/communication/` (`gatt.c`, `ble_pairing.c`), `main/core/factory_config.h`. Protocol: `docs/ble-protocol.md`. The hardware tests of 14 October confirmed an encrypted, authenticated, bonded link with a 128-bit key on reconnect, and a fresh PIN pairing (H6, H13).

8 Wi-Fi streaming

Bluetooth carries all data on its own. Wi-Fi is an optional, faster path on the same local network:

1. The phone sends the network name and password over the **authenticated Bluetooth link**. The patch keeps them in RAM only. The phone keeps them in its secure store, per patch and per account.
2. The phone reads the SHA-256 of the patch's self-signed P-256 certificate over Bluetooth, and opens `wss://<patch-ip>/stream` accepting **only** that certificate (native pinned-WebSocket modules).
3. Within 3 s it sends a proof-of-possession value that only a phone which read it over authenticated Bluetooth knows. A wrong or late value closes the socket. Each socket is authenticated separately, with at most two sockets.
4. Frames are byte-identical to Bluetooth packets and get the same checks. Release builds refuse Wi-Fi streaming without a pin.

Residual: the proof-of-possession value is 4 bytes, lasts one boot and is shared by bonded phones (R-10). The patch supports 2.4 GHz networks only. WPA2 passwords under 8 characters are refused before they're sent.

9 Phone app

Local database	op-sqlite with **SQLCipher**. The key is 32 random bytes in the OS secure store. If the store can't open, the app runs memory-only and says so: there is no plain-text fallback.
Session	Stored by supabase-js in Keychain/Keystore with `AFTER_FIRST_UNLOCK_THIS_DEVICE_ONLY`. Sign-out wipes stored keys even offline. A fresh iOS install discards a session left by an earlier install.
Account isolation on one phone	The device registry, saved Wi-Fi and sync state belong to the account. Notifications are cleared on sign-out. Sync checks account identity.
Network	**HTTPS only in release builds**, checked at run time (`public-config.ts`) and at build time (`scripts/check-release-config.cjs`, which refuses http, loopback and private-LAN hosts, and any non-public key). The release Android manifest forbids cleartext traffic.
Screens	Release Android builds set `FLAG_SECURE` (no screenshots or recent-apps previews). iOS shows a privacy cover in the app switcher.
Backups	Android `allowBackup=false`. Data is excluded from cloud backup and device transfer.
Deep links	Every incoming `wearwise://` link is validated before Expo Router reads it. Email links use PKCE.
Input from the patch and the cloud	Strict protocol checks on Bluetooth and Wi-Fi. Restored recordings are checked (sample counts, sensors, rates) before display.
Other	Share code cleared from the clipboard after 2 minutes. Uploads sent as not cacheable. Generic error messages (no server details). Release Android permissions limited to Internet and Bluetooth (location only on Android ≤ 11, for scanning), plus vibration and notifications for alerts.
Signing	The owner's own release keystore (RSA-3072, created by `create-release-signing.cjs`). The build refuses to run without it.

10 Accounts and authentication

- **Supabase Auth, email and password.** Minimum 10 characters, enforced by the server. The apps also refuse common passwords and show strength (`packages/password`).
- **Sign-up gate.** The `create_profile_after_signup` trigger refuses an account without consent, an 18+ confirmation and a terms version the server knows. The server stamps the times itself.
- **Roles are server-controlled:** participant, researcher, clinician. Researcher and clinician accounts can't be self-registered. Administrators create them with `supabase/admin/create-viewer.sql` (one-time password, terms accepted by the person at first sign-in).
- **Account status:** active or suspended. RESTRICTIVE policies stop suspended accounts uploading, and viewers see nothing. Suspension, role change and admin password reset **end every session** of the account.
- **Email links:** PKCE in the app and the dashboard. Redirect allow-list: `wearwise://auth/confirmed`, `wearwise://auth/reset` and the dashboard's `/reset-password`.
- **Changing a password** in the dashboard asks for the current one.

Not yet: multi-factor authentication (R-02), CAPTCHA or an enrolment code at sign-up (R-03), and leaked-password protection (a Supabase plan setting).

11 Database access control

RLS is **enabled on every table in `public`**, and privileges start from nothing: `anon` has no table privilege and can execute no function. `authenticated` gets only what the apps use (pinned by a test), and RLS then decides which rows.

Table	Read	Write
`profiles`	Own row	Trigger creates it. Own row, `display_name` column only, while active
`recorded_sessions`	Own. A viewer: non-discarded sessions with a granted signal	Own, active and 18+ accounts. Server-stamped columns excluded
`recorded_channels`	Own. A viewer: granted signals	Own rows, into own sessions only
`fall_events`	Own. A viewer: if the grant includes falls	Own, into own sessions
`vital_alerts`	Own. A viewer: granted signals	Own. A session reference must be own and uploaded
`access_grants`	Participant: own, including revoked. Grantee: live ones only	RPC only
`share_codes`, `share_code_attempts`	None	RPC only (no table privileges at all)

A "viewer" holds a **live** grant: not revoked, both accounts active, and the grantee still a researcher or clinician. Access ends the moment any of these stops being true. All RPCs are `security definer` with an empty `search_path`. A read-only **schema fingerprint** (`supabase/admin/schema-fingerprint.sql`) proves that a hosted database matches the migrations.

12 Sharing and live view

- **Share codes:** created by the participant with `create_share_code()`. Format `XXXXX-XXXXX`, about 49.5 bits from an unbiased generator, valid 24 h, single use. A new code replaces an unused one, and only the SHA-256 hash is stored.
- **Redemption** (`redeem_share_code()`): researchers and clinicians only. 10 failures per hour per viewer, with a per-viewer lock against racing. Failures are returned as results, not errors.
- **Grants:** scoped to signal types and whether falls are included. Either side can revoke (`revoke_access_grant()`), and the participant can narrow the scope (`update_access_grant()`). One live grant per pair. Revoked rows are kept as the participant's audit trail.
- **Privacy:** `list_shared_participants()` returns display names only, **never emails**. Browser notifications on the dashboard say only what kind of alert.
- **Live view:** started by the participant for 30 min to 8 h, on a **private Realtime channel** `live:<grant id>` that only the two parties may join. **Nothing is stored.** It pauses in the background, and removing or narrowing a viewer refreshes it at once. The phone acts only on `stop`, `record` and `record-stop` from a viewer, and a recording starts only when the participant taps Start.

13 Storage and Realtime

- **Bucket `recordings`:** private, 50 MiB per file, `application/octet-stream` only. Writes are allowed only into the uploader's own folder, by an active account, with exactly the name `<uid>/<session uuid>/<channel uuid>.wwch`. Reads: own folder, or a viewer with a live grant covering that channel.
- **Postgres changes:** only `fall_events` and `vital_alerts`, INSERT and UPDATE only. DELETE events are not filtered by RLS, so they aren't published.
- **Broadcast:** private channels only, no presence. `alerts:<user id>` may be joined only by its owner, and nobody may send on it.
- **Hosted setting:** Realtime "Allow public access" **off**, so a client that forgets `private: true` fails closed.

14 Web dashboard

Content-Security-Policy	`default-src 'self'`; `script-src 'self'`; `connect-src 'self' https://<backend> wss://<backend>` (one host only); `frame-ancestors 'none'`; `object-src 'none'`; `base-uri 'self'`; `form-action 'self'`; `upgrade-insecure-requests`. `style-src` allows inline styles for the theme tokens.
Other headers	`Strict-Transport-Security: max-age=63072000; includeSubDomains`, `X-Frame-Options: DENY`, `X-Content-Type-Options: nosniff`, `Referrer-Policy: no-referrer`, `Cross-Origin-Opener-Policy: same-origin`, and `Permissions-Policy` allowing only `serial` (for Patch setup).
Generated per deployment	`npm run deploy-config -w dashboard` writes the headers for the chosen backend. The build stops if the headers name another backend.

Sign-in	supabase-js with PKCE. A reset link for a different account than the one signed in is refused. Safe return paths after sign-in. The 18+ and terms gate reads server columns, not client metadata.
Caching	Every request is `cache: 'no-store'`, so decoded recordings don't outlive sign-out in the disk cache.
Patch setup (Web Serial)	Runs only between the tab and the USB port. Nothing about a patch is sent to Supabase. Firmware chosen from a file always needs confirmation and shows its SHA-256 (real authenticity needs Secure Boot, R-01).

15 Repository, build and supply chain

- **No secrets in the repository.** Real `.env` files, keystores, Apple signing files, device databases, build outputs and Supabase Studio's saved queries (`supabase/snippets/`) are gitignored. Templates are `.env.example`.
- **Install scripts disabled:** the root `.npmrc` sets `ignore-scripts=true`, so dependencies can't run code at install time. The flasher library (esptool-js) is pinned.
- **Release checks:** `check-release-config.cjs` (HTTPS public backend, publishable key, signing present) and `tools/audit-apk.ps1`, which checks a built APK for leaked secrets and developer paths.
- **Published history:** the handover repository was published as a **fresh history** (14 October 2026). The personal data found in the original development history (a commit email, an old screenshot, absolute paths) is not in it.
- **Dependencies:** see section 26 for current advisories. Never run `npm audit fix --force`: it downgrades Expo.

PART 4

Secrets and operations

Which secrets exist and who holds them, account administration, incidents, logging and local development.

16 Secrets inventory

Nothing in this table is in the repository, and none of it should ever be.

Secret	Created by	Kept in	Never
Supabase database password	The owner, at project creation	The organisation's password manager	In a file, in the repo, in an app
Service-role / `sb_secret_` key	Supabase	Supabase dashboard. Used only by admin tooling at run time (`admin.mjs` fetches it in memory)	In an app, `.env` or a log
Personal access token (`sbp_…`)	Each administrator	The CLI's keychain (`supabase login`), or one shell session (`read -rs`)	Committed or shared
SMTP credentials	The owner	Supabase → Authentication → SMTP	In the repo
Android release keystore and passwords	The owner (`create-release-signing.cjs`)	`apps/mobile/` (gitignored) **plus a secure backup**. Losing it means the app can't be updated	Committed
Apple signing certificate and profiles	The owner's Apple team (Xcode)	The macOS keychain and Apple account	Committed
Patch label PINs	Patch setup, per patch	The patch's flash and its printed label	In the repo or Supabase
Patch TLS key, Wi-Fi PoP	The patch (first boot / each boot)	The patch	—
Secure Boot signing key (once R-01 is done)	The owner	Offline, in a secure store	On a build machine without protection

Public by design: the project URL and the publishable (anon) key ship inside the apps, so treat them as public. RLS protects the data. The local stack's keys and the demo password `wearwise-demo-only` work only against a local stack on the developer's own machine. If a **private** secret is ever committed or exposed, **rotate it**: deleting the file is not enough.

17 Account lifecycle and administration

Task	Tool	Security notes
Add a researcher or clinician	`supabase/admin/create-viewer.sql`	One-time password, sent privately and separately. The person accepts the terms and changes the password at first sign-in. See the guide *Adding a Researcher or Clinician*
Make an existing account a viewer	`set-role.sql`	Confirmed email only. Ends all sessions
Locked-out viewer	`reset-password.sql`	New one-time password. Ends all sessions
Suspend or reactivate	`set-status.sql`	Takes effect on the next request. Nothing deleted
Review who has access	`overview.sql` (read-only)	Run regularly, and at every handover
Delete an account and its data	`admin.mjs delete-account`	Removes Storage files first, then the account (cascade). Can't be undone
Find orphaned files	`orphaned-recordings.sql` (read-only)	Files left by accounts deleted in Authentication → Users

Good practice: one account per person; Supabase project membership only for people who administer it; suspend promptly when someone leaves; delete saved SQL Editor queries that contain email addresses. Terms changes need a migration that adds the new version to `private.terms_versions` **before** an app that sends it ships.

18 Incident response

Follow the organisation's incident and privacy procedures. These playbooks cover the WearWise-specific steps.

Incident	Immediate steps
Service key, database password or access token exposed	Rotate it in the Supabase dashboard (Project Settings → API keys / Database), revoke exposed personal tokens, review Supabase logs for its use, run `schema-fingerprint.sql` to confirm the schema is unchanged, and remove the secret from wherever it leaked (history included).
Researcher or clinician account compromised	`set-status.sql` → suspended (ends sessions and hides every share at once). Then `reset-password.sql`, and review `overview.sql` for the affected participants. Reactivate once safe.
Participant's phone lost or stolen	Local data is encrypted and tied to the device's secure store. Run `reset-password.sql` for the account to end its sessions, and have the participant set a new password. If the phone was paired with a patch, use **New PIN** on that patch.
Patch lost or stolen	Treat its bonds and TLS key as exposed (R-01). Participants **Forget** it in the app and remove it in the phone's Bluetooth settings. A recovered patch is reset with **Set up** (new PIN, settings erased).

Incident	Immediate steps
Suspected unauthorised data access	Suspend the accounts involved, preserve Supabase logs, and involve the privacy officer. Notification duties (for example, Australia's Notifiable Data Breaches scheme) are the organisation's decision.
Vulnerable or malicious dependency	Identify where it is used (`npm ls <package>`), update through `npx expo install --fix` or the Expo SDK, retest on devices, and rebuild and redistribute releases.

19 Backups, logging and monitoring

- **Backups:** enable the Supabase plan's backups or point-in-time recovery for the hosted database. Recordings also stay on participants' phones, and the cloud is an upload-only mirror plus a one-time restore onto a new phone.
- **Logs:** Supabase keeps Auth, API and database logs for a period that depends on the plan. WearWise has **no audit log of its own** for researcher reads (R-08). Revoked grants are kept as the participant's audit trail.
- **No telemetry:** the apps send no analytics or crash reports. The firmware prints no readings outside debug builds.
- **Monitoring** to set up: storage growth (abuse, R-03), sign-up rate, failed sign-ins, and Realtime usage, using the Supabase dashboard's reports.

20 Local development security

- `supabase start` publishes the API, database, Studio and Mailpit ports on **all network interfaces**, so phones on the Wi-Fi can reach the API. Use it only on a trusted network, or firewall ports 54322–54324.
- Development builds accept `http://` to local and LAN hosts, and the Android debug manifest allows cleartext traffic. **Release builds do neither.**
- Every development build on the network loads its code from the developer's Metro server (port 8081). Switching backends switches all of them.
- Never use real participants' data on a local stack or a developer's machine. The demo seed refuses to run on a database that has accounts outside `@example.invalid`.
- Test against hosted projects only with dedicated test accounts. `rls-live.mjs` creates random-password users and deletes exactly its own, but a separate development project is better.

PART 5

Assurance

How the controls were verified, the history of reviews, and what changed since the last audit.

21 Security testing and verification

Check	Date	Result
Database RLS and security suites on a real local Supabase stack	14 Oct 2026	**Pass** 277 plain-SQL checks + 8 pgTAP
Sync and Storage isolation through the public API, two accounts (`sync-live.mjs`)	14 Oct 2026	**Pass** 7/7 (local)
Two-account isolation on the hosted project	13 Oct 2026	**Pass** 19/19. Anonymous requests to any table or RPC: permission denied
Hosted database matches the migrations (schema fingerprint)	14 Oct 2026	**Match** in everything that affects behaviour (one function differs only by a comment)
Unit tests and type checks	14 Oct 2026	**Pass** app 283 tests (40 suites), dashboard 110, legal 49
Hardware: pairing, encryption, reconnect, pinned-TLS Wi-Fi, sharing, live view (H1–H13, firmware 0.9.6, Samsung phone)	14 Oct 2026	**Pass** 13/13, including an authenticated, bonded 128-bit link and a fresh PIN pairing
Malformed `wearwise://` links	13 Oct 2026	**Pass** app stays up (Android emulator, iOS simulator)
Handover scan of tracked files and history for credentials and personal data	13 Oct 2026	**Pass** no credentials. Personal data redacted or excluded (fresh history)
Git history of the published repository (7 commits, 661 file versions): keys, tokens, private keys, personal data, local paths, sensitive files, Claude traces	14 Oct 2026	**Pass** none found. Patch MAC addresses (now redacted) remain in older commits
Dependency alerts (Dependabot, 13)	14 Oct 2026	**8 fixed** 5 assessed, none reachable in the app unmitigated (section 26)
Bundled firmware rebuilt from the committed tree	14 Oct 2026	**Pass** manifest records commit `52e94d8`; code byte-identical to the previous bundle (only build timestamps and hashes differ)
Release APK inspection (signing, permissions, FLAG_SECURE, bundle scan)	20 Sep 2026	**Pass** for build 0.1.0. Repeat for every release with `tools/audit-apk.ps1`

Not tested

- An independent penetration test or code review.
- Over-the-air attacks with a hostile Bluetooth device, and whether each phone OS forces encryption when reconnecting to a bonded patch.
- An iOS release build on a real device, and sign-in over local http on iOS.
- Hosted project settings outside the migrations (email auto-confirm, refresh-token lifetime, rate limits): the owner checks these (section 25).

22 Review history and finding status

Review	Scope and outcome
Release security report, 20 Sep 2026	Android release candidate 0.1.0, reviewed against relevant MASVS principles. Release signing, session isolation between accounts, backups off, permissions trimmed, deep-link filtering, PKCE callbacks. Raised the firmware pairing and backend policy items that the later audit closed.
Security audit, 13 Oct 2026	Five read-only reviews (app, dashboard, database, firmware, repository), then fixes. **No Critical findings**, and no leaked secrets in code, history or the app bundle. Two High findings, both in the firmware: pairing (**fixed**) and plain-text flash (**open**, R-01). Database fixes in migration 9 were applied to production on 13 Oct.
Handover verification, 14 Oct 2026	Two clean dry runs of the documented setup, hardware tests H1–H13, and a schema fingerprint of the hosted project. Fixes went into the documentation and the test infrastructure.

Area (13 Oct audit)	Findings	Status now
Phone app (M1–M12)	12	10 fixed. M2 patch authenticity partly fixed (R-04). M12 minor Android surface left as is.
Web dashboard (D1–D11)	11	9 fixed. D10 mitigated by CSP. D11 capped by the bucket's file limit.
Database, storage and sign-in (B1–B14)	14	9 fixed. Partly: B1 (no 2FA, R-02), B4 (sign-up abuse, R-03), B10 (session metadata, R-07), B12 (hosted settings, R-05). B3 fixed for the study team.
Firmware (F1–F10)	10	8 fixed. F2 open (R-01). F9 partly (R-10).
Repository (R1–R10)	10	R1, R2, R4, R5, R7, R9 resolved. R6 mostly fixed. R3 tracked (section 26). R8 is local only. R10 (no CI or secret scanning) open (R-09).

23 Changes since the 13 October audit

- **Firmware 0.9.6:** a patch remembers **two** phones (a third replaces the oldest), instead of one owner. The unauthenticated-link deadline is **30 s** (60 s with the PIN prompt), up from 15 s and 40 s, because some Android phones ask "Pair?" before the PIN box. Hardware tests H6 and H13 confirmed the pairing behaviour.
- **Repository:** published to a private remote as a fresh history. The development tool configuration that gave write access to production (`.mcp.json`, audit R1) is not part of the repository. The original project reference was replaced with configuration. Studio's saved queries are now gitignored.

- **Test infrastructure:** plain-SQL suites moved to `supabase/sql_tests/`. A bare `supabase test db` could otherwise have run a stub granting full default privileges on a real stack (fixed during the dry run). Database checks went from 261 to 277, plus 8 pgTAP.
- **Documentation:** the admin runbook now covers the SQL Editor's warnings and saved queries, and the guide *Adding a Researcher or Clinician* was added.
- **Public-release review (14 October):** patch MAC addresses and the device IDs derived from them were redacted from test evidence, screenshots and test fixtures; the stale September change list was removed; 8 of 13 dependency alerts were fixed; the bundled firmware was rebuilt from the committed tree so its manifest records the commit; and the published git history was audited (section 21).

PART 6

Risks and responsibilities

The open risks, what the owner must do before real participants, and dependency advisories.

24 Risk register

ID	Risk	Rating	Recommendation
R-01	Patch flash unencrypted, ROM download open: physical access can clone a patch or flash other firmware	High	For patches that leave the lab: Secure Boot V2, flash encryption (release), NVS encryption, disabled ROM download (firmware README, "Production hardening"). Needs chip revision ≥ 3.0, an offline signing key, signed images in Patch setup, and an OTA path. Try on spare boards first: eFuses are permanent.
R-02	Single-factor staff accounts: one leaked password exposes every participant sharing with that person	Medium	Add TOTP enrolment and verification to the dashboard, require it for viewer access in the database, and enable leaked-password protection if the plan allows.
R-03	Open sign-up: scripted accounts can consume storage	Medium	CAPTCHA (e.g. Cloudflare Turnstile, hCaptcha) or a study enrolment code. Monitor storage growth.
R-04	No cryptographic patch identity: a look-alike board could receive Wi-Fi details or inject readings	Medium	A per-patch secret printed on the label next to the PIN, checked with a challenge on every connect before Wi-Fi details are sent.
R-05	Hosted settings outside the migrations: Site URL, redirects, SMTP, email confirmation, Realtime public access	Medium	Apply `docs/deployment.md` §3: email confirmation on, own SMTP, Site URL and redirects for the hosted dashboard only (no localhost), Realtime public access off.
R-06	The label PIN is fixed per patch: anyone who reads it and presses BOOT can pair	Low	Keep patches under supervision. Use **New PIN** whenever a patch changes hands.
R-07	Viewers see all columns of shareable sessions (device name, firmware, settings)	Low	A column-limited view for viewers.
R-08	No audit log of researcher reads beyond Supabase's own logs	Low	Retain Supabase logs per the protocol, or add read auditing for viewer RPCs.
R-09	No CI, automated tests on change, or secret scanning	Low	A gitleaks pre-commit hook and a CI job running the unit tests and database suites.

ID	Risk	Rating	Recommendation
R-10	Wi-Fi proof-of-possession is 4 bytes, per boot, shared by bonded phones	Low	A longer, per-phone value in a future protocol version.
R-11	Five dependency advisories with no non-breaking fix (section 26)	Low	Upgrade the Expo SDK and retest on devices; then dismiss or close the remaining alerts.
R-12	No retention or purge policy in the app or backend	Medium (privacy)	Define retention with the ethics approval, and implement purge and consent-withdrawal handling.
R-13	The original capstone Supabase project still exists with its own data and keys	Medium	Retire it, or hand it over deliberately to the owner's organisation (`docs/deployment.md`).
R-14	The iOS release build and pinned-WebSocket module have had less device testing	Low	Test an iOS release build on devices before use.

25 Owner responsibilities before real participants

- ✓ **Ethics and governance:** an approved protocol, a data-storage region and retention period that match it, and a privacy notice. Fill in the organisation details in `packages/legal/src/org.ts`; the legal documents show a "draft" notice until you do.
- ✓ **Own deployment:** a Supabase project under the organisation's account. Apply the migrations (never the demo seed), then confirm with the schema fingerprint.
- ✓ **Project settings:** email confirmation on, own SMTP, Site URL and redirect URLs for the hosted dashboard only, Realtime public access off, minimum password length 10 (R-05).
- ✓ **Hosting:** dashboard on HTTPS with the generated security headers (`npm run deploy-config -w dashboard`).
- ✓ **Keys:** your own Android keystore and Apple signing, backed up. Database password and tokens in the organisation's secret store. Rotate anything ever exposed.
- ✓ **Accounts:** one per person, created with the admin scripts, suspended when people leave. Few Supabase project members.
- ✓ **Patches:** decide on production hardening (R-01) before patches go to participants. Label each patch and keep a register.
- ✓ **Backups:** enable the plan's backups or point-in-time recovery.
- ✓ **Updates:** keep the Expo SDK, React Native, Supabase CLI and images, and ESP-IDF current, and rerun every test suite after each upgrade.
- ✓ **Independent review** before any use beyond a supervised research prototype.

26 Dependency advisories

GitHub Dependabot raised **13 alerts** on the repository (from `package-lock.json`). On 14 October 2026 **8 were fixed** by lockfile updates within the version ranges the dependents already allow (no forced upgrades), including the only critical one. After the fix `npm audit` reports 65 entries across the

workspace (0 critical, 49 high, 16 moderate), or 44 without development-only packages. These are counted once per dependent path; they come from **five underlying packages**:

Package	Severity	Status	Path and assessment
`shell-quote`	Critical	Fixed 1.12.0	React Native developer tools
`compression`	High	Fixed 1.8.2	Expo CLI development server
`brace-expansion` (6 alerts)	High	Fixed 1.1.21 / 5.0.12	File matching in build and lint tooling
`braces`	High	No fix exists	File matching in Metro and Jest. Patterns come from the project, not users; not in the app or dashboard bundle
`node-forge`	High	No fix exists	Expo CLI tooling (certificates, update signing). Expo Updates signing isn't used; not in the app bundle
`sprintf-js`	Moderate	No fix exists	Test-coverage tooling, development only
`uuid`	Moderate	Not affected	iOS prebuild tooling (`xcode`), which only calls `v4()` ; the bug is in v3/v5/v6 with a buffer
`decode-uri-component`	Moderate	Mitigated	Expo Router URL parsing, **in the app at run time**. Incoming links over 2,048 characters or with malformed percent-encoding are refused before Expo Router reads them; Android refuses any `%` . Fixed in Expo Router 58

The full per-alert assessment is in `docs/security/dependency-advisories.md` . The remaining five clear with an Expo SDK upgrade and a device retest. `npm audit fix --force` would install much older Expo versions and break the app.

A Where the security controls live

Path	What
`supabase/migrations/` (11 files)	Schema, RLS policies, grants, RPCs, triggers, Storage and Realtime policies. Migration 9 is the security review.
`supabase/sql-tests/`, `supabase/tests/`	277 plain-SQL checks, 8 pgTAP tests, API isolation scripts
`supabase/admin/`, `supabase/scripts/admin.mjs`	Administration scripts and the schema fingerprint
`supabase/config.toml`	Local Auth settings (password length, redirects)
`firmware/wearwise-esp32/main/communication/`	Bluetooth pairing, GATT security, Wi-Fi TLS server, proof-of-possession
`firmware/wearwise-esp32/README.md`	Production hardening (Secure Boot, flash encryption)
`apps/mobile/src/platform/secure-storage/`, `src/data/local/`	Secure store, SQLCipher key and database
`apps/mobile/src/data/remote/public-config.ts`, `scripts/check-release-config.cjs`	HTTPS-only release configuration checks
`apps/mobile/modules/pinned-websocket/`	Certificate-pinned Wi-Fi stream (Android, iOS)
`apps/mobile/src/app/+native-intent.tsx`	Incoming deep-link filter
`apps/dashboard/scripts/deploy-headers.mjs`	CSP and security headers
`apps/dashboard/src/data/client.ts`	PKCE sign-in, no-store requests
`packages/password`, `packages/legal`	Password rules; terms and their version
`.npmrc`, `.gitignore`, `tools/audit-apk.ps1`	Supply chain, ignored secrets, APK audit
`docs/security.md`, `docs/security/`	Security notes, the 13 October audit, the 20 September release report
`docs/operations/researcher-access.md`	Admin runbook for researcher and clinician access

B Glossary and references

RLS (Row Level Security)	Postgres rules that decide which rows each user may read or change
RPC	A database function the apps call by name. In WearWise, `security definer` with fixed checks
Publishable / anon key	The public Supabase key that ships in the apps. Not a secret
Service-role / secret key	A Supabase key that bypasses RLS. Admin use only, never in an app
PKCE	Proof Key for Code Exchange: protects email sign-in and reset links from interception
LE Secure Connections	Bluetooth Low Energy pairing based on elliptic-curve key exchange, here with a passkey

Bond	Keys a patch and a phone keep after pairing, so they reconnect encrypted
Certificate pinning	Accepting only one known certificate (by its SHA-256) instead of any trusted one
PoP	Proof-of-possession: a value showing the phone read it over the authenticated link
SQLCipher	Encrypted SQLite, used for the phone's database
CSP	Content-Security-Policy: browser rules limiting where a page may load code and connect
eFuse	One-time programmable bits in the ESP32 that permanently enable security features

References

- OWASP Mobile Application Security Verification Standard (MASVS): mas.owasp.org/MASVS
- OWASP Top 10: owasp.org/Top10
- Supabase security guidance: supabase.com/docs/guides/security
- Supabase Row Level Security: supabase.com/docs/guides/database/postgres/row-level-security
- Espressif ESP-IDF security guides (Secure Boot V2, flash encryption): docs.espressif.com
- Bluetooth Core Specification, LE Security: bluetooth.com/specifications

Made by the WearWise Project Team

Zakiul Atheef	Project Lead, Scrum Master, Technical Lead, Security Engineering Lead and Integration Lead
Hari Bethelli	Cloud & Data Engineer
Siri Bethelli	UI/UX & Data Visualisation Engineer
Thevindu Kodagoda Munasinghage	Security Engineer, Documentation Lead and QA & Testing Lead

Project Owner: Shanmuga Sundar Dhanabalan, Deputy Director, CTI, La Trobe University (project brief and stakeholder direction). **Development:** the WearWise Project Team, the student development team.

© 2026 WearWise Project Team · La Trobe University CSE3CAP Capstone Project. Licensed under the PolyForm Noncommercial License 1.0.0: free to use, copy and change for noncommercial purposes, not for sale. See `LICENSE`, `NOTICE` and `TEAM.md` in the repository.

WearWise Security Documentation · Author: Zakiul Atheef · Version 1.0, 14 October 2026 · handover release v1.0.0. WearWise is a research prototype and not a medical device. Its security practices are informed by relevant guidance; nothing about WearWise is certified or independently tested.