

WearWise


ADMINISTRATOR GUIDE

Adding a researcher or clinician

Create a dashboard account for a researcher or clinician, hand it over safely, and manage their access later. No coding needed: everything is done in the Supabase SQL Editor and the WearWise dashboard.







Handover release v1.0.0 · app 0.1.0 · firmware 0.9.6
October 2026 · WearWise Project Team

Research prototype.
Not a medical device.

Contents

PART 1 · BEFORE YOU START

1 How access works 3

2 What you need 3

PART 2 · CREATE THE ACCOUNT

3 Open the SQL Editor 5

4 Paste the script and fill in three values 5

5 Run it 6

6 Copy the one-time password 6

7 Send the welcome details 7

PART 3 · THE RESEARCHER'S FIRST SIGN-IN

8 Sign in with the one-time password 8

9 Accept the terms 8

10 Change the password 9

11 Ready: add participants 9

PART 4 · CHECK AND MANAGE ACCESS

12 See every researcher and clinician 11

13 Make an existing account a researcher 11

14 Locked out: a new one-time password 12

15 Suspend or reactivate someone 12

16 Removing access for good 13

PART 5 · HELP

17 Troubleshooting 14

18 Good practice 15

A The create-viewer.sql script 16

B For developers: the command line 17

The short version

1. Supabase Dashboard → **SQL Editor** → paste `supabase/admin/create-viewer.sql` → change the email, role and name → **Run** (choose **Run without RLS** if asked).
2. Send the person the **dashboard address** and their **email**. Send the **one-time password** separately and privately.
3. They sign in, accept the terms, and change the password (top-right menu → **Change password**).
4. Participants share with them using a **share code** from the WearWise app.

PART 1

Before you start

How dashboard access works, and what you need to have ready.

1 How access works

WearWise participants own their data. A researcher or clinician (a "viewer") uses the **web dashboard**, and sees a participant's data only after that participant shares it with them. Viewer accounts **can't be created by signing up**: an administrator creates them, as described in this guide.

1

You create the account

In the Supabase SQL Editor. You get a one-time password to hand over privately.

2

They sign in

They accept the terms themselves and choose their own password.

3

Participants share

A participant creates a one-time share code in the app. The researcher enters it on the dashboard and sees only the signals that participant chose.

Role	What it means
Researcher	Dashboard access: participants who share with them, sessions, charts, CSV downloads, alerts, live view, and Patch setup (installing firmware on patches).
Clinician	The same dashboard and permissions. The role label is shown to participants, so choose the one that describes the person.
Participant	A normal app user. Participants create their own accounts in the app. Use this guide only for researchers and clinicians.

Nothing is shared automatically

A new researcher account sees **no data at all** until a participant gives them a share code. The participant decides which signals are shared and can remove access at any time. The researcher can also remove a participant from their own list.

2 What you need

- ✓ **Access to the WearWise Supabase project.** You must be a member of the Supabase organisation that holds the project, at supabase.com. Local test setups use Supabase Studio at `http://127.0.0.1:54323` instead: same screens.

- ✓ **The file** `supabase/admin/create-viewer.sql` from the WearWise repository. If you don't have the repository, its full text is in Appendix A.
- ✓ **The person's email address.** It must **not already be a participant account**: one account can't share data with itself. Ask them for a work address that they don't use in the WearWise app.
- ✓ **Their role** (researcher or clinician) and the **name participants will see**, for example "Dr Alex Chen".
- ✓ **The dashboard address** for your project, for example `https://wearwise-dashboard.example.org`.
- ✓ **A private way to send a password**, separate from email: a phone call, a text message, or your organisation's password-sharing tool.

The screenshots in this guide come from a local test copy of WearWise (Supabase Studio and a local dashboard) using made-up details. The hosted Supabase Dashboard uses the same SQL Editor.

PART 2

Create the account


About five minutes in the Supabase SQL Editor.

3 Open the SQL Editor

1. Go to **supabase.com**, sign in, and open the **WearWise project**. (Local test setup: open `http://127.0.0.1:54323`.)
2. In the left sidebar, click **SQL Editor** (the `>_` icon).
3. Click **+** (New query) to get an empty editor.

4 Paste the script and fill in three values

Open `supabase/admin/create-viewer.sql` in any text editor, copy **all** of it, and paste it into the SQL Editor. Then change only the three values on the lines marked `<-- CHANGE`, keeping the single quotes around each one:



Lines 15–17 hold the three values: the email, the role, and the name participants will see.

Line	Change this	To (example)
15	`'dr.name@example.org'`	their email: `'dr.chen@example.invalid'`
16	`'researcher'`	`'researcher'` or `'clinician'`, exactly as written
17	`'Dr Name'`	the name participants see: `'Dr Alex Chen'` (up to 80 characters)

Change nothing else

Leave the rest of the script exactly as it is. If a name contains an apostrophe, type it twice: `'Dr O''Brien'`.


5 Run it

Click the green **Run** button (top right). The SQL Editor may stop and warn you first:

"Potential issues detected" says the query has "destructive operations" and "creates a table without enabling Row Level Security". Both refer to `new_viewer`, a **temporary scratch table** the script uses to hold the details while it works. It exists only for this one run and is never reachable from the apps.

Click **Run without RLS**.

"Run and enable RLS" would also work, but it adds a step that isn't needed. **Cancel** changes nothing.



The SQL Editor's warning. Choose **Run without RLS**.

6 Copy the one-time password

After a moment, **Results** shows one row: the email, role, name and a **one-time password**.

```
15  select lower(trim('dr.chen@example.invalid')) as email,      -- <-- CHANGE: their email
16         'researcher'::text                      as role,       -- <-- CHANGE: 'researcher' or 'clinician'
17         'Dr Alex Chen'::text                    as display_name, -- <-- CHANGE: name shown to participants
18         translate(encode(extensions.gen_random_bytes(12), 'base64'), '+/', '-_') as one_time_password;
```

Results | Chart — 1 row — Export

email	role	display_name	one_time_password
dr.chen@example.invalid	researcher	Dr Alex Chen	••••••••• (hidden)

The result. The password is hidden in this guide. Yours shows 16 random letters and numbers.

- Copy the password now and keep it somewhere private until you've sent it. It isn't stored anywhere you can read later. If it's lost, make a new one (section 14).
- The account is ready at once. The email address is already confirmed, so no confirmation email is sent.
- The SQL Editor **saves your query**, with the email in it, under **Private** in its side list. Once you're done, right-click it there and choose **Delete query**.

Handle the password carefully

Anyone with the email address and this password can sign in as the researcher. Never put it in the same message as the email address or the dashboard link, in a shared document, or in a group chat.

7 Send the welcome details

Send two separate messages. The first can be an ordinary email:

Example welcome email (no password in it)

```
Subject: Your WearWise dashboard account

Hello Dr Chen,

Your WearWise researcher account is ready.

  Dashboard:  https://<your dashboard address>
  Email:      dr.chen@example.invalid

I'll send your one-time password separately. When you first sign in,
please read and accept the terms, then change the password: click your
name at the top right, then "Change password".

Participants share their data with you by giving you a one-time share
code from the WearWise app. Enter it under Participants → Add participant.
For Patch setup (installing firmware on patches), use Chrome or Edge.
```

Send the **one-time password** separately and privately: a phone call, a text message, or your organisation's password-sharing tool.

PART 3


The researcher's first sign-in

What the new researcher or clinician sees. You can send them this part.

8 Sign in with the one-time password

1. Open the dashboard address in a web browser on a computer.
2. Type your email and the one-time password exactly as received. It's case-sensitive.
3. Click **Sign in**.

"Invalid login credentials"? Check for spaces before or after the password, and that you're on the right dashboard address. Still stuck? Ask the administrator for a new password (section 14).




The sign-in page.

9 Accept the terms

The first time, the dashboard asks the person to read and agree to the **Terms of Use**, the **Privacy Policy**, the **Collection Notice**, the research information and the **Researcher & clinician terms**. Each one is a link.

Tick the box and click **Continue**.


> **Why the administrator can't do this**
>
> Agreeing to the terms is a personal decision. The script deliberately leaves it for the person to do at their first sign-in. When the terms are updated later, everyone is asked again.




"Before you continue": tick, then Continue.

10 Change the password


Right away, replace the one-time password with one only the person knows:



1. Click your name (top right) → **Change password**.




2. Current (one-time) password, then the new one twice.



3. "Password changed". Click **Done**.

The new password needs **at least 10 characters** and can't be a common password. Capital and lowercase letters, a number and a symbol are recommended, and the strength bar shows how strong it is. The same menu has the light/dark **Theme** and **Sign out**.


11 Ready: add participants




A new researcher's dashboard. "No one is sharing with you yet" until a participant gives them a share code.

1. The **participant** opens the WearWise app: **Profile → Privacy & access → Share my data**, ticks the signals to share, and taps **Create code**.
2. They give the researcher the code, for example `AWWXK-59EF5`. It works **once** and expires after **24 hours**.
3. The **researcher** clicks **+ Add participant**, types the code and clicks **Add participant**. The participant appears straight away.

The **WearWise User Guide** explains every dashboard screen (sections 16–22).



The participant's code.



The researcher enters it.

PART 4


Check and manage access

Seeing who has access, promoting an existing account, resetting a password, and suspending someone.

Each task below uses another script from `supabase/admin/`, run the same way: **SQL Editor → New query → paste the whole file → change the lines marked `<-- CHANGE` → Run**.

12 See every researcher and clinician

`overview.sql` is read-only: it changes nothing. It holds two queries, and the SQL Editor shows the result of the **last one only** (who shares what with whom). To see the list of researchers and clinicians, **select the lines of query 1** with the mouse and click **Run selected**:



Query 1 selected, then "Run selected". Every researcher and clinician, their status, when they were created, and how many participants share with them now.

Run the whole file (nothing selected) to see query 2: each participant, the viewer they share with, which signals (`1` ECG, `2` SpO_2, `3` temperature, `4` heart rate, `5` movement, `6` pulse wave), whether falls are included, and since when. This is a good list to review regularly, and to hand over when the project changes hands.

13 Make an existing account a researcher

If the person **already has a WearWise account** (for example, they tried the app), `create-viewer.sql` stops with an error and changes nothing (section 17). Use `set-role.sql` instead: change their email and

the role, then Run.

- It works only if the account's **email address is confirmed**. "No rows returned" means no account with that email, or an unconfirmed one: nothing was changed.
- The person is **signed out everywhere** and signs in again under the new role. Their own recordings are kept.
- A researcher or clinician **can't create share codes**, so a separate email for dashboard work is usually better.
- The same script with `'participant'` turns a viewer back into a normal app user. They lose dashboard access at once.

14 Locked out: a new one-time password

First, the person can try **Forgot password?** on the dashboard sign-in page, which emails a reset link. If the email can't reach them, run `reset-password.sql` with their email:

- Like `create-viewer.sql`, it may show the "**Potential issues detected**" warning. Choose **Run without RLS**.
- The result shows a new **one-time password** and `account_found = true`. (`false` means no account has that email, and nothing changed.)
- The account is signed out everywhere, so the old password stops working. Send the new one privately, as in section 7. The person changes it after signing in.

15 Suspend or reactivate someone

When a researcher leaves the study, or their access should pause, run `set-status.sql` with `'suspended'` and their email:

```
10  with changed as (
11    update public.profiles p
12       set account_status = 'suspended'                    -- <-- CHANGE: 'suspended' or 'active'
13      from auth.users u
14     where u.id = p.id
15       and lower(u.email) = lower(trim('dr.chen@example.invalid'))   -- <-- CHANGE: their email
16    returning p.id, u.email, p.display_name, p.account_role, p.account_status
17  ), signed_out as (
18    delete from auth.sessions s
```

Results | Chart — 1 row — Export

email	display_name	account_role	account_status	sessions_ended
dr.chen@example.invalid	Dr Alex Chen	researcher	suspended	1

Suspended. The result confirms the new status and how many signed-in sessions were ended.

- A suspended researcher or clinician **sees nothing**. The dashboard signs them out and says *"You can't use this dashboard"*.
- Every participant's share with them is hidden at once. **Nothing is deleted**: run the script again with `'active'` and their access comes back as it was.
- Suspending a **participant** hides their shared data from every viewer, and their unused share code stops working.

The change takes effect on the person's very next request. The database checks the account's status itself, whatever a browser still has open.



What a suspended researcher sees.

16 Removing access for good


You want to…	Do this
End one participant's sharing with one researcher	The participant: app → Profile → Privacy & access → **Remove access**. Or the researcher: dashboard → the participant → **Remove participant**.
End everything a researcher can see, keeping the record	**Suspend** them (section 15). It can be undone.
Delete an account and all its data	A developer runs `node supabase/scripts/admin.mjs delete-account <email>` (Appendix B). It deletes the account's recording files first, then the account. **This can't be undone.** Don't delete users from Authentication → Users: that leaves their recording files behind in Storage.

PART 5

Help

Error messages, good practice, and the script itself.

17 Troubleshooting



"… already has an account. Nothing was changed." The most common error. Use `set-role.sql` (section 13), or ask the person for a different email.

Message or problem	What to do
`Not an email address: …`	Check line 15: one address, inside single quotes, no spaces.
`Role must be researcher or clinician, not "…"`	Line 16 must say exactly `'researcher'` or `'clinician'`.
`syntax error at or near …`	A quote was deleted, or a name contains an apostrophe. Paste the whole file again and type `''` for an apostrophe.
"Potential issues detected"	Expected for `create-viewer.sql` and `reset-password.sql`. Choose **Run without RLS** (section 5).
`set-role.sql` / `set-status.sql`: no rows returned	No account with that email (check spelling). For `set-role.sql`, the account's email may not be confirmed yet.
The one-time password was lost	Run `reset-password.sql` (section 14).
"Invalid login credentials" on first sign-in	Spaces copied with the password, or the wrong dashboard address (a test site instead of the real one). Otherwise reset the password.
"You can't use this dashboard"	The account is suspended (section 15).
Signed in, but sees *My data* and *Sharing* instead of Participants	That's a participant account. Make it a researcher with `set-role.sql`.

Message or problem	What to do
"Forgot password?" emails never arrive	The project needs its own email (SMTP) settings: Supabase → Authentication → Emails. See `docs/operations/researcher-access.md`.
Share code "invalid or expired"	Codes work once and last 24 hours, and a newer code replaces an unused one. Ask the participant for a new code.
Patch setup is missing or can't find the patch	Use Chrome or Edge on a computer, with a researcher or clinician account (see the Setup Guide).

18 Good practice

- ✓ One account per person. Never share a login between colleagues.
- ✓ Use an email address the person doesn't use as a WearWise participant.
- ✓ Send the one-time password separately from the email address and the dashboard link, and ask the person to change it at first sign-in.
- ✓ Delete your saved queries in the SQL Editor once you're done: they contain email addresses.
- ✓ Suspend accounts promptly when someone leaves the study.
- ✓ Review `overview.sql` regularly, and whenever the project changes hands.
- ✓ Only people who need to manage accounts should be members of the Supabase project.

WearWise is a research prototype, not a medical device. Its security practices are informed by relevant guidance; nothing about WearWise is certified.

A The create-viewer.sql script

For administrators without the WearWise repository: this is the complete script, as of handover release v1.0.0. Copy all of it. The repository copy at `supabase/admin/create-viewer.sql` is authoritative if the two ever differ.

supabase/admin/create-viewer.sql

```
-- WearWise admin: create a researcher or clinician account for the viewer dashboard.
--
-- Supabase Dashboard → SQL Editor → New query → paste this whole file →
-- change the three values marked  <-- CHANGE  → Run.
-- The result shows a one-time password. Give it to the person privately (not in
-- the same email as the address); they replace it in the dashboard with
-- top bar → Change password.
--
-- Use an email that is NOT already a participant account: one account can't share
-- data with itself. If the address already has an account, this stops with an
-- error and changes nothing — use set-role.sql to promote that account instead.

drop table if exists pg_temp.new_viewer;
create temp table new_viewer as
select lower(trim('dr.name@example.org')) as email,      -- <-- CHANGE: their email
       'researcher'::text                 as role,       -- <-- CHANGE: 'researcher' or 'clinician'
       'Dr Name'::text                    as display_name, -- <-- CHANGE: name shown to participants
       translate(encode(extensions.gen_random_bytes(12), 'base64'), '+/', '-_') as one_time_password;

do $$
declare
  v record;
  new_id uuid := gen_random_uuid();
begin
  select * into v from pg_temp.new_viewer;
  if v.email !~ '^[^@[:space:]]+@[^@[:space:]]+\.[^@[:space:]]+$' then
    raise exception 'Not an email address: %', v.email;
  end if;
  if v.role not in ('researcher', 'clinician') then
    raise exception 'Role must be researcher or clinician, not "%"', v.role;
  end if;
  if exists (select 1 from auth.users u where lower(u.email) = v.email) then
    raise exception '% already has an account. Nothing was changed. Use set-role.sql to promote it.', v.email;
  end if;

  -- A confirmed email+password user. The profiles trigger creates their profile: it
  -- needs consent_recorded_at, adult_confirmed_at and a terms_version the server
  -- knows in the metadata, so they're set here. The terms acceptance is then
  -- cleared again: the person accepts the current terms, researcher terms included,
  -- themselves when they first sign in, not the administrator for them.
  insert into auth.users (instance_id, id, aud, role, email, encrypted_password, email_confirmed_at,
    raw_app_meta_data, raw_user_meta_data, created_at, updated_at,
    confirmation_token, recovery_token, email_change, email_change_token_new, email_change_token_current,
    phone_change, phone_change_token, reauthentication_token)
  values ('00000000-0000-0000-0000-000000000000', new_id, 'authenticated', 'authenticated',
    v.email, extensions.crypt(v.one_time_password, extensions.gen_salt('bf')), now(),
    '{"provider":"email","providers":["email"]}'::jsonb,
    jsonb_build_object('display_name', left(v.display_name, 80), 'consent_recorded_at', now(), 'adult_confirmed_at', now(),
                       'terms_version', (select max(t.version) from private.terms_versions t)),
    now(), now(), '', '', '', '', '', '', '', '');

  insert into auth.identities (id, user_id, provider_id, provider, identity_data, last_sign_in_at, created_at, updated_at)
  values (gen_random_uuid(), new_id, new_id::text, 'email', jsonb_build_object('sub', new_id::text, 'email', v.email),
now(), now(), now());

  update public.profiles
     set account_role = v.role, terms_version = null, terms_accepted_at = null
   where id = new_id;
  update auth.users
     set raw_user_meta_data = raw_user_meta_data - 'terms_version'
   where id = new_id;
end $$;

select email, role, display_name, one_time_password from pg_temp.new_viewer;
```

B For developers: the command line

`supabase/scripts/admin.mjs` does the same tasks from a terminal, using a Supabase **personal access token** (Supabase → Account → Access Tokens). Read the token without showing it or saving it in your shell history:

Terminal (in the wearwise folder)

```
$ read -rs SB_PAT && export SB_PAT      # paste the token, press Enter (nothing is shown)
$ node supabase/scripts/admin.mjs create-viewer dr.chen@clinic.org clinician "Dr Chen"
$ node supabase/scripts/admin.mjs set-role someone@example.org researcher
$ node supabase/scripts/admin.mjs delete-account someone@example.org        # dry run: shows what would go
$ node supabase/scripts/admin.mjs delete-account someone@example.org --yes  # deletes; can't be undone
$ unset SB_PAT
```

A token is personal: each administrator creates their own, and never commits or shares it. Full details: `docs/operations/researcher-access.md`.

WearWise: Adding a Researcher or Clinician · handover release v1.0.0, October 2026. Screenshots use a local test copy with made-up details.