



Uncertainty in AI: Probabilistic Reasoning

CSE 415: Introduction to Artificial Intelligence
University of Washington
Winter 2019

© S. Tanimoto and University of Washington, 2019



Outline

- Motivation
- Definitions and Laws of Probability
- Generalizing Modus Ponens
- Bayes' Rule
- Odds
- The Monty Hall Problem

Univ. of Wash.

Probabilistic Reasoning

2



Motivation

In the real world:

- data is often noisy,
- many processes cannot be modeled deterministically in a reliable and practical way;
 - parts may be insufficiently understood, other
 - parts too complex for efficient computation.
- logical reasoning does not match the available information,
- adversarial agents may not always obey rationality assumptions.
OR the two agents may have different ways of analyzing the system

Univ. of Wash.

Probabilistic Reasoning

3



Motivation (continued)

Therefore, we need a means to

- represent the certainty/uncertainty of information,
- compute certainty/uncertainty of related information.

The mathematics of probability is our tool of choice.

Univ. of Wash.

Probabilistic Reasoning

4



Definitions

A **random variable** X is a symbol that represents a class of events that may occur any number of times, and which take on values in a given set D called a **domain**.

Example: Let C be a coin-toss random variable with domain $D=\{H, T\}$.

A **probability distribution** P for a random variable is a function that assigns to each domain element d_i a value p_i in the range 0 to 1. If D is finite then P is often given as a table.

d_i	p_i
H	0.5
T	0.5

Univ. of Wash.

Probabilistic Reasoning

5



Definitions

A **joint distribution** over a set of random variables X_1, X_2, \dots, X_n is a function that assigns to each n -tuple of domain elements $(d_{1,j_1}, d_{2,j_2}, \dots, d_{n,j_n})$ a value $p_{j_1 j_2 \dots j_n}$ in the range 0 to 1. If all the domains D_j are finite then P is often given as a table.

Example with $n=2$:

$d_{1,j_1} \in D_1$	$d_{2,j_2} \in D_2$	$P(d_{1,j_1}, d_{2,j_2})$	$P(X_1=d_{1,j_1}, X_2=d_{2,j_2})$
rain	no crash	1/4	
rain	crash	1/8	
clear	no crash	5/16	
clear	crash	1/16	
snow	no crash	1/8	
snow	crash	1/8	

Univ. of Wash.

Probabilistic Reasoning

6

$P(X_1 = d_1, X_2 = d_2) = P(X_1 = d_1)P(X_2 = d_2)$ iff X_1 and X_2 are independent



Definitions

The *conditional probability* of $P(X=d_i | Y=d_j)$ is the probability of $X=d_i$, given $Y=d_j$.

Example:

Let $D=\{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$.

Let Odd be the set of outcomes $X=1, X=3, \dots, X=9$.

Let Even " " $X=0, X=2, \dots, X=8$.

Let Prime " " $X=2, X=3, X=5, X=7$.

$P(\text{Odd}) = 5/10 = 0.5$

$P(\text{Prime}) = 4/10 = 0.4$

$P(\text{Odd} | \text{Prime}) = |\text{odd and prime}| / |\text{prime}| = 3/4 = 0.75$.

$P(\text{Prime} | \text{Odd}) = |\text{odd and prime}| / |\text{odd}| = 3/5 = 0.6$.

Univ. of Wash.

Probabilistic Reasoning

7



Two Laws of Probability

The sum rule: $\sum_{i=1 \leq i \leq m} P(X = d_i) = 1$

Adding the probabilities of all the possible outcomes for a random variable must give a total of 1.0.

The product rule: $P(X=x, Y=y) = P(X=x) P(Y=y | X=x)$.

The joint probability of two random variables is equal to the product of the marginal of one times the conditional of the other given the one.

Univ. of Wash.

Probabilistic Reasoning

8



Logic vs Probability: Generalizing Modus Ponens

Modus Ponens:

$P \rightarrow Q$

P

—————

Q

If it's raining then I do my homework.
It's raining.

I do my homework.

Bayes' Rule: (general idea)

If P then sometimes Q

P

—————

Maybe Q

If it's raining then I might do my homework.
It's raining.

I might do my homework.

(Bayes' rule lets us calculate the probability of Q , taking P into account.)

Univ. of Wash.

Probabilistic Reasoning

9

If P implies Q
AND
 P is true
THEREFORE
 Q is true



Bayes' Rule

E : Some evidence exists, i.e., a particular condition is true
 H : some hypothesis is true.

$P(E|H)$ = probability of E given H .

$P(E|\sim H)$ = probability of E given not H .

$P(H)$ = probability of H , independent of E .

$$P(H|E) = \frac{P(E|H) P(H)}{P(E)}$$

$$P(E) = P(E|H) P(H) + P(E|\sim H)(1 - P(H))$$

Univ. of Wash.

Probabilistic Reasoning

10



Applying Bayes' Rule

E : The patient's white blood cell count exceeds 110% of average.

H : The patient is infected with tetanus.

$P(E|H) = 0.8$ class-conditional probability

$P(E|\sim H) = 0.3$ "

$P(H) = 0.01$ prior probability

posterior probability:

$$P(H|E) = \frac{P(E|H) P(H)}{P(E)} = \frac{(0.8) (0.01)}{(0.8) (0.01) + (0.3) (0.99)} = \frac{0.008}{0.305} = 0.0262$$

$$P(E) = P(E|H) P(H) + P(E|\sim H)(1 - P(H))$$

Univ. of Wash.

Probabilistic Reasoning

11



Odds

Odds are 10 to 1 it will rain tomorrow.

$$P(\text{rain}) = \frac{10}{10 + 1} = \frac{10}{11}$$

Suppose $P(A) = 1/4$

Then $O(A) = (1/4) / (3/4) = 1/3$

$$\text{in general: } O(A) = \frac{P(A)}{P(\sim A)} = \frac{P(A)}{1 - P(A)}$$

Univ. of Wash.

Probabilistic Reasoning

12

Un
Uncertainty

Bayes' Rule reformulated...

$$P(H|E) = \frac{P(E|H) P(H)}{P(E)}$$

$$P(\sim H|E) = \frac{P(E|\sim H) P(\sim H)}{P(E)}$$

$$O(H|E) = \frac{P(E|H)}{P(E|\sim H)} O(H)$$

Univ. of Wash. Probabilistic Reasoning 13

Un
Uncertainty

Odds-Likelihood Form of Bayes' Rule

E: The patient's white blood cell count exceeds 110% of average.

H: The patient is infected with tetanus.

$O(H) = 0.01/0.99$

$O(H|E) = \lambda O(H)$ λ is called the *sufficiency* factor.

$O(H|\sim E) = \lambda' O(H)$ λ' is called the *necessity* factor.

$\lambda = P(E|H)/P(E|\sim H) = 0.8/0.3 \approx 2.67$

$\lambda' = P(\sim E|H)/P(\sim E|\sim H) = 0.2/0.7 \approx 0.286$

Univ. of Wash. Probabilistic Reasoning 14

Un
Uncertainty


Now For A Brain Teaser

The following puzzle is an effective stimulant for thinking about probabilities, and how judgments about probabilities should take into consideration the results of observations.

Univ. of Wash. Probabilistic Reasoning 15

Un
Uncertainty

The Monty Hall Problem



Univ. of Wash. Probabilistic Reasoning 16

Un
Uncertainty

The Monty Hall Problem

There are three doors: a red door, green door, and blue door. Behind one is a car, and behind the other two are goats. You get to keep whatever is behind the door you choose.

You choose a door (say, red).

The host opens one of the other doors (say, green), which reveals a goat.

The host says, "Would you like to select the OTHER door?"

Should you switch?

Univ. of Wash. Probabilistic Reasoning 17