Honeypot Threat Report

What the internet throws at an exposed server

REPORTING PERIOD · OCTOBER 2026

Findings from an internet-facing multi-honeypot sensor in Australia: who connected, what they targeted, what they did once inside and what organisations should do about it.



AUTHOR Zachary Lehmann

COVERS October 2026
PUBLISHED November 2026
VERSION 1.0 · Public release

REPORT

Contents

1. Executive summary . . . 3

2. How the data was collected . . . 4

3. Sources: everywhere and nowhere . . . 5

4. Services attackers look for . . . 6

5. RDP and SSH: the password grind . . . 7

6. What attackers do once they are 'in' . . . 8

7. Exploits, phone fraud, databases and industrial systems . . . 9

8. Everything the sensor recorded . . . 10

9. Lessons for anyone running something online . . . 11

Appendix: Indicators of compromise . . . 12

About this report

TITLE	Honeypot Threat Report: November 2026
REPORTING PERIOD	October 2026
AUTHOR	Zachary Lehmann
PUBLISHED	November 2026
VERSION	1.0
CLASSIFICATION	TLP:CLEAR. May be shared freely.
DATA SOURCE	One multi-honeypot sensor on an Australian internet connection
SCOPE	353,797 events from 1,088 public IP addresses; the operator's own traffic removed

Attacker IP addresses and malware hashes are published as indicators of compromise for defenders. Nothing in this report identifies the sensor, its location beyond country level or its owner's network.

SECTION 01 · SUMMARY

Executive summary

353,797
events recorded from outside sources

1,088
unique source IP addresses

64
countries (by IP geolocation)

255
different networks (ASNs)

4,153
SSH / Telnet password guesses

63.8%
of source IPs already on public reputation blocklists

Key findings

A server on the open internet is found quickly and probed constantly by over a thousand machines. Most of it is automated, cheap and noisy. A small part is scripted intrusion that ends with a file being dropped on the server.

- **Remote Desktop (RDP) is the single most hammered service.** RDP drew 37,462 honeypot interactions. **98.7% of them came from one host**, a rented cloud server that made 18,480 separate RDP connections.
- **Weak passwords are still the whole game for SSH and Telnet.** 4,153 login attempts came from 40 addresses. The top passwords were `123456`, `123` and `1234`. The username `root` was tried 1,480 times.
- **Once 'in', attackers moved fast.** 55 logins were let into the fake shell and 28 addresses typed 408 commands. Attackers fingerprinted the system, tested whether the shell was real and uploaded a file named `.16`. The upload happened 5 times from 4 different addresses.
- **98.9% of SSH clients identified as** `SSH-2.0-Go`, the signature of automated Go-based brute-force tooling, not people.
- **Recent, critical web flaws are being sprayed blindly.** Detections included React Server Components / Next.js remote code execution (CVE-2025-55182, CVSS 10.0), Cisco IOS XE (CVE-2023-20198) and the Dovecot mail server (CVE-2019-11500). The web decoys also saw FreePBX admin-page probes.
- **Phone systems and industrial controls are on the menu too.** 593 SIP `INVITE` requests tried to place calls through a 'PBX' (toll fraud). Separately, 17 addresses probed an industrial-control decoy, mostly over IEC 60870-5-104, a power-grid control protocol.
- **Blocking by country does not work.** The busiest source geolocated to Australia: 261,487 events from just 7 addresses. Bulgaria sent 19,132 events from 22 addresses. Most traffic came from commercial cloud and hosting networks, not from any one country.
- **AI tooling is still a target.** Attackers tried the username `claude` 25 times and probed `/mcp`, `/sse` and `/api/mcp`, the web endpoints used by AI-agent (Model Context Protocol) servers.
- **Reputation lists help a lot.** 694 of the 1,088 source addresses (63.8%) were already flagged by public reputation feeds.

SECTION 02 · METHOD

How the data was collected

What a honeypot is

A honeypot is a decoy. It looks like a real, vulnerable server, but it has no real data and is isolated from everything else, so anything that connects to it is, by definition, unsolicited. That makes it a clean way to see what attackers actually do on today's internet, without the noise of legitimate users.

This report covers activity during October 2026. The sensor is a **multi-honeypot platform** built from open-source components. It bundles around twenty decoy services with network-level monitoring:

COMPONENT	WHAT IT PRETENDS TO BE / DOES
Cowrie	SSH and Telnet server with a fake Linux shell that records logins, commands and uploaded files
RDP honeypot	Windows Remote Desktop login screen
Dionaea	SMB, MySQL, MSSQL, MongoDB, FTP, MQTT, PPTP VPN and other common services
SentryPeer	SIP / VoIP phone system
ConPot	Industrial control system (IEC 60870-5-104, SNMP and others)
Tanner, H0neytr4p	Web applications and known-vulnerable web endpoints
Cisco ASA, Redis, Heralding, Mailoney, others	VPN gateway, database, VNC, mail and more
Suricata, P0f, Fatt	Network intrusion detection, passive OS and client fingerprinting (they observe, they do not emulate)

Isolation. The sensor sat on its own network segment with no route to any real system and tightly restricted outbound access, so anything that 'compromised' it could not go further. Its management interface was never exposed to the internet.

Cleaning. All traffic from the operator's own administration and testing, from the sensor itself and from private address ranges was removed before analysis. What remains is 353,797 events from 1,088 public IP addresses.

Two kinds of number. *Events* include everything the network sensors logged (Suricata alerts, fingerprints and flows), so one connection can produce several events. *Honeypot interactions* (61,754) are only the records from the decoy services themselves. Where 'how many attackers' matters more than 'how loud', this report counts *unique source IP addresses*.

Limits worth knowing

IP geolocation shows where a server is, not where the person behind it is. Most attackers rent cloud servers or use compromised machines and proxies. Some sources are legitimate internet-scanning and research companies. Counts reflect a single sensor in a single location, so treat them as a snapshot rather than a national statistic.

SECTION 03 · WHO CONNECTS

Sources: everywhere and nowhere

1,088 distinct public IP addresses touched the sensor, spread across 64 countries and 255 networks (autonomous systems). Counted by addresses, the United States and China lead, mostly because that is where the big cloud providers are.




Figure 1. Countries ranked by unique source IP addresses.

Counted by volume instead, Australia comes first, with 261,487 events from only 7 addresses. That is almost entirely one machine: a rented server on Contabo's Asia hosting network, geolocated to Australia, that hammered RDP. Bulgaria is second-largest after the United States by volume with 19,132 events from 22 addresses, driven by a few SSH and VPN scanners. One noisy host can rewrite a country chart, which is exactly why country blocking is a poor defence.

Networks with the most distinct sources

NETWORK (ASN)	UNIQUE IPS	WHAT IT IS
AS25369 Hydra Communications	78	Hosting network
AS211298 Driftnet	73	Internet-wide scanning company
AS15169 Google	63	Google Cloud
AS8075 Microsoft	49	Azure cloud
AS396982 Google	47	Google Cloud
AS6939 Hurricane Electric	42	Transit and hosting
AS213412 ONYPHE	34	Attack-surface scanning company
AS4837 China Unicom	31	Chinese national carrier

Cloud and hosting providers dominate. Their servers are cheap, disposable and come with clean-looking IP space, which is why they are the attacker's default launch pad.

SECTION 04 · WHAT THEY TARGET

Services attackers look for

Web ports, Telnet and SSH attract the widest range of sources. Most of those are scanners cataloguing what is online. The next tier is more telling: Remote Desktop, VoIP and databases that should never face the internet at all.




Figure 2. Ports ranked by the number of distinct source IPs that targeted them.

Breadth is one thing, depth is another. Looking only at the decoy services, two attract almost all of the effort:




Figure 3. Honeypot interactions by decoy service (log scale: each gridline is 10x the last).

SECTION 05 · BRUTE FORCE

RDP and SSH: the password grind

98.7%
of RDP traffic came from a single host

18,480
RDP connections made by that host

36
addresses tried RDP in total

The RDP decoy was found and then hammered by one rented server: 260,822 events, every one aimed at port 3389. Across all RDP traffic, Suricata raised 37,215 'RDP connection request' alerts and 100 RDP 'SYN then reset' denial-of-service alerts. Only 14 actual RDP login attempts were recorded, mostly as `Admin`. This is the classic pattern behind ransomware: find exposed RDP, guess passwords until something works, then log in as a human.

SSH and Telnet

4,584
SSH / Telnet sessions from 158 addresses

4,153
login attempts from 40 addresses

98.9%
of SSH clients were automated Go tooling




Figure 4. Most-tried usernames (left) and passwords (right) on the SSH and Telnet decoy.

The lists read like a default-settings checklist: `root`, `ubuntu`, `admin` and `postgres`, with passwords like `123456`, `password` and `P@ssw0rd`. The most common pairs were `admin / admin` (26 times), `root / 123456` and `ubuntu / ubuntu`. Product-specific names show up too: `Tronlong` (an embedded-board vendor), `lighthouse` (a cloud server image), `minecraft` and `claude`. That last one suggests machines set up for AI coding agents are on attackers' wordlists.

One hosting network stood out: four addresses on AS198364 (Banatsync) each generated thousands of events, aimed almost entirely at SSH. The busiest of them produced 16,218 events alone.

SECTION 06 · AFTER THE LOGIN

What attackers do once they are 'in'

Cowrie deliberately accepts some logins so it can watch what happens next. 55 logins were let into its fake shell and 28 addresses typed commands, 408 in total. The behaviour falls into a few clear playbooks:

PLAYBOOK	WHAT WAS SEEN	WHY
IoT botnet escalation	`enable`, `system`, `shell`, `sh` and `linuxshell`, each seen 15 times, alongside `config terminal`, `start` and `su`	Tries to break out of router and camera menus into a Linux shell. The pattern is typical of Mirai-family botnets.
System fingerprinting	`uname -s -v -n -r -m` (11 times), `/bin/./uname -s -v -n -r -m` (6 times) and `uname -a` (3 times)	Picks the right malware build for the CPU and OS
Honeypot detection	Arithmetic shell tests such as `423*908+75` (grouped at 21 commands) and `echo xsec` (3 times)	Checks whether the shell really does arithmetic and echoes text, because a weak fake shell would fail the test
Drop and run	Upload a file named `.16`, then `chmod +x '/root/.16'` (4 times) and a `sudo -S` fallback with a guessed password	Installs the payload and tries to gain root with the same weak passwords

Captured malware

Attackers uploaded files 5 times from 4 different IP addresses. Two unique files were captured, both named `.16`. They were **not** run and were kept off any working system. Only their fingerprints are shared here.

SHA-256	SEEN	NOTES
`a151d3f4f2422531f30a843ffb35479596c86722bb103bdf8591105687f9b125`	4 uploads, 4 IPs	Dropped as `.16` on the SSH decoy
`72b4db8a74da275ed7c51ce919e9e8b6d0897c45e50ad8a4bb748a9b681c7ea5`	1 upload, 1 IP	Also named `.16`, from an address that had uploaded the first file

Uploading source addresses: 80.94.92.55, 80.94.92.179, 2.57.122.150, 195.178.110.232.

The takeaway

None of this needed a clever exploit. A guessable password was the only way in. From there, getting a file onto the server took a handful of scripted commands. Key-only SSH, no root login and no default passwords would have stopped every one of these sessions.

SECTION 07 · BEYOND PASSWORDS

Exploits, phone fraud, databases and industrial systems

Known vulnerabilities seen in traffic

CVE	PRODUCT AND FLAW	SEVERITY	ALERTS
CVE-2025-55182	React Server Components / Next.js: pre-authentication remote code execution ('React2Shell')	CVSS 10.0	7
CVE-1999-0517	SNMP default, null or missing community string	Legacy	14
CVE-2019-11500	Dovecot IMAP: out-of-bounds write, possible remote code execution	CVSS 9.8	3
CVE-2023-20198	Cisco IOS XE web UI: create a privilege-15 admin account (on CISA's Known Exploited list)	CVSS 10.0	1

Exploit attempts are sprayed at every address regardless of what is running there. A sensor that runs neither React nor Cisco still received both. The web decoys also saw probes for FreePBX admin pages (`/admin/modules/framework/amp_conf/htdocs/admin/config.php`*) and for leaked secrets files such as* `/.env` *and* `/config.json`*. Tanner also logged 7 requests for* `/SDK/webLanguage`*, a path used against some IP camera web servers.*

VoIP toll fraud

The SIP decoy logged 896 events from 34 addresses: **593 INVITE** requests trying to place calls and 266 REGISTER attempts guessing extension accounts. Callers posed as `FPBX-15.0.17` and `Linksys-SPA942` devices or used the SIPVicious `friendly-scanner`. An exposed phone system with a weak extension password can rack up thousands of dollars in international calls overnight.

Databases and file sharing

Dionaea recorded MySQL (289 connections), PPTP VPN (258), SMB (130), MongoDB (73), MQTT (38) and MSSQL (24), with login names `sa` (99), `root` (95) and `admin` (88) tried most. Suricata also flagged inbound scans for PostgreSQL (181 alerts), MySQL (80), MSSQL (40) and Oracle (17). The Redis decoy received `PING` and `INFO` reconnaissance commands.

Industrial control systems

17 addresses interacted with the industrial decoy: 96 events used **IEC 60870-5-104**, the telecontrol protocol used by electricity grids and utilities. Another 14 were SNMP queries. Most of this is reconnaissance, but it shows that anything industrial that is reachable from the internet will be found and catalogued.

SECTION 08 · FULL PICTURE

Everything the sensor recorded

For completeness, here is every main data source on the sensor that saw outside traffic, with what stood out in each. The decoys and the network sensors together make up the 353,797 events in this report.

SOURCE	RECORDS	UNIQUE IPS	WHAT STOOD OUT
RDP honeypot	37,462	36	Windows Remote Desktop connections; 98.7% from one host
Cowrie (SSH / Telnet)	22,099	158	4,153 password guesses, 408 commands, 5 malware uploads
SentryPeer (SIP)	896	34	593 call attempts (INVITE), 266 extension guesses (REGISTER)
Dionaea	848	108	MySQL 289, PPTP VPN 258, SMB 130, MongoDB 73, MQTT 38, MSSQL 24, Windows RPC 18, FTP 18
ConPot (industrial)	110	17	IEC 60870-5-104 grid telecontrol 96, SNMP 14
Tanner (web app)	90	27	General crawling plus FreePBX admin-page probes
Cisco ASA decoy	65	19	Router and device probes (`appGet.cgi`, `login.cgi`, `SETTINGS.CFG`) and AI `/mcp` and `/sse` endpoint probes
H0neytr4p (web exploits)	71	33	`/.env` secrets, FreePBX and Asterisk paths, `/api/mcp` and an Exchange autodiscover probe
Redis	48	12	`PING` and `INFO` reconnaissance
Honeytrap	28	15	UPnP (1900) 10, Oracle DB (1521) 9, Memcached (11211) 9
Mailoney (SMTP)	16	6	`EHLO`, `STARTTLS` and `AUTH NTLM` probing of a mail server
Heralding	15	4	VNC remote desktop 12, PostgreSQL logins as `postgres` 3
Medpot (medical)	2	2	Connections to the medical-device decoy
Suricata IDS	130,099	1,083	77,885 alerts from 675 addresses; flows, RDP, SSH, SIP and TLS metadata
P0f	119,195	1,012	Passive operating-system fingerprints
Fatt	42,749	195	Client handshake fingerprints: TLS 20,128, RDP 18,606, SSH 3,901

What the network sensors add

Suricata's threat-intelligence rules matched well-known bad actors: 809 'ET SCAN' alerts for scanning activity (such as Nmap SYN scans and database port sweeps), 406 for sources on the CINS poor-reputation list, 169 each for DShield and Spamhaus DROP blocklisted sources, 115 for 'known compromised or hostile' hosts and 100 for RDP denial-of-service patterns. Only 10 matched web attack signatures and 7 matched exploit signatures. Most activity is opportunistic, high-volume probing.

Reputation of the 1,088 sources

694 addresses (63.8%) carried at least one label from the sensor's reputation feeds. Some carried more than one.

LABEL	IPS	LABEL	IPS	LABEL	IPS	LABEL	IPS
Bad reputation	284	Service abuse	52	Compromised	3	Bot activity	2
Scan source	232	SSH abuse	25	Mail abuse	4	SIP abuse	2
Mass scanner	81	Attack source	6	Web attacker	2	Web abuse	1

SECTION 09 · SO WHAT

Lessons for anyone running something online

Nearly everything in this report is automated and opportunistic. That is good news: the defences that stop it are basic, cheap and well understood.

1 **Never expose RDP to the internet**
Put Remote Desktop behind a VPN or zero-trust gateway with MFA. It was the single most attacked service.

2 **SSH by key only**
Turn off password logins and root login. Every intrusion seen here started with a guessed password.

3 **Kill default credentials**
admin/admin, root/123456 and vendor defaults are the first things tried on every device type. Names like `claude` and `minecraft` show that new kinds of servers are quickly added to the lists.

4 **Patch internet-facing software fast**
React/Next.js, Cisco IOS XE, Dovecot and FreePBX flaws were all being tried. Follow CISA's Known Exploited list and ACSC advisories.

5 **Keep databases and management ports private**
MySQL, MSSQL, MongoDB, Redis, PostgreSQL, SNMP and industrial protocols should never be reachable from the internet.

6 **Lock down VoIP**
No open SIP, use strong extension passwords and restrict international calling to limit toll-fraud losses.

7 **Use reputation blocklists, not country blocks**
63.8% of sources were already on public lists, while the busiest attacker geolocated to Australia.

8 **Watch, don't just block**
An IDS and centralised logs turn background noise into early warning and show when something gets further than it should.

For Australian businesses

These controls line up with the ACSC Essential Eight, especially multi-factor authentication, patching applications and restricting administrative privileges. If a server faces the internet, assume it is being tested right now, because it is.

APPENDIX

Indicators of compromise

The highest-volume source addresses seen by the sensor. They are shared for blocklisting and abuse reporting. Many will be compromised machines or rented servers rather than the attacker's own, so they may be reassigned over time.

SOURCE IP	NETWORK (ASN)	GEOLOCATION	MAIN TARGET	EVENTS
109.123.227.33	AS141995 Contabo Asia	Australia	RDP 3389	260,822
77.239.124.158	AS198364 Banatsync	United States	SSH 22	16,218
109.160.32.178	AS198364 Banatsync	Bulgaria	SSH 22	16,112
77.239.124.67	AS198364 Banatsync	United States	SSH 22	6,883
77.239.124.39	AS198364 Banatsync	United States	SSH 22	6,806
27.102.116.43	AS45996 DAOU Technology	South Korea	SSH 22	1,864
154.18.197.29	AS142271 EWS DS Networks	Philippines	SSH 22	1,797
77.90.185.30	AS213790 Limited Network	Germany	MySQL 3306	1,704
93.123.109.6	AS48090 Techoff Srv	Bulgaria	PPTP 1723	1,428
195.178.110.232	AS48090 Techoff Srv	Bulgaria	SSH 22	968
112.184.193.210	AS4766 Korea Telecom	South Korea	Telnet 23	936

Malware uploaders (SSH / SCP)

80.94.92.55 · 80.94.92.179 · 2.57.122.150 · 195.178.110.232

Malware SHA-256

a151d3f4f2422531f30a843ffb35479596c86722bb103bdf8591105687f9b125
72b4db8a74da275ed7c51ce919e9e8b6d0897c45e50ad8a4bb748a9b681c7ea5

Notes and sources

- Data: a multi-honeypot sensor with Cowrie, Dionaea, SentryPeer, ConPot, RDP and web honeypots; Suricata IDS with Emerging Threats rules; IP geolocation and ASN from the sensor's built-in GeoIP enrichment; reputation from bundled IP reputation feeds.
- CVE details: NVD (nvd.nist.gov) for CVE-2019-11500 and CVE-2023-20198; OSV (osv.dev) for CVE-2025-55182; CISA Known Exploited Vulnerabilities catalogue.
- Counts exclude the operator's own management and test traffic, the sensor's own traffic and private address ranges.
- Captured malware was never executed and is not distributed. Hashes are provided so defenders can check their own systems.