SC4001 · Part A

YourName | Neural Networks and Deep Learning | October 3, 2026

Generative AI declaration

I used OpenAI Codex / ChatGPT for planning, code generation/debugging, experiment execution, analysis, figures, report drafting and submission packaging. Outputs were checked against the brief/slides and library source, 96 behavioral tests, CUDA checkpoint restoration and artifact/hash audits. FeatureAblation scores were independently aggregated and checked by manual replacements. All results below come from completed saved experiments. I remain responsible for reviewing and understanding the submitted work.

Data and common training protocol

Chronological partitions: 2017–2020 train (87,370), 2021 validation (29,057), 2022 test (26,702); 2023 is excluded. Inputs are month, town, flat model type, storey range and six continuous variables; year, address and station name are excluded. Category encoders and standardization statistics are fitted on training only (sample SD for continuous inputs; population SD for price), then refitted on 2017–2021 for combined-data runs. Adam uses LR 0.01, batch 512, standardized-target MSE. Selection uses seed 42, at most 20 epochs, patience 4 and RMSE improvement 0.0001 SGD.

A1. Baseline diagram, parameters and Ray grid search




Figure A1a. Supplied baseline (H=64, d=8); the output before inverse scaling is linear.

P = d(13+27+44+18) + (4d+10)H + 1. Default: 816 embedding + 2,496 first-linear + 128 LayerNorm + 65 output-linear = 3,505 trainable parameters. Unknown category ID 0 is an ordinary learned embedding.




Figure A1b. Minimum actual validation RMSE per fresh Ray Tune trial [1]; outlined cell is selected.

All H in {16,32,64,128,256} × d in {2,4,8,12,16} combinations completed. Select H=256, d=4: 7,065 parameters, validation RMSE SGD 58,627.10, R^2 0.870061, epoch 6. This is 5.61% lower RMSE than the default (SGD 62,109.01). Exact ties favor fewer parameters, smaller H, then smaller d.

A1 · learning curves, final refit and interpretation




Figure A1c–d. Selected trial: train/validation RMSE on the same axes. Fresh refit: combined training only. Dashed lines mark epochs 6 and 4; test metrics are not plotted against epochs.

Evidence for the selected configuration

The selected trial's epoch-6 training RMSE is SGD 34,372.58, versus validation 58,627.10. At epoch 10, training falls to 31,678.96 while validation rises to 70,715.09. This widening gap is consistent with overfitting after the saved checkpoint. The smaller H=16,d=2 trial has higher train/validation errors (37,147.82/65,190.26 SGD), suggesting more limited fit under this budget; one trajectory does not isolate capacity from optimization or temporal shift.

The full grid favors the wider hidden layer with a modest embedding dimension. Increasing d is not consistently beneficial: the next-best H=128,d=12 configuration scores 59,688.99 SGD with 8,649 parameters, while H=256,d=16 uses 20,577 parameters. The chosen 7,065-parameter model has the lowest validation RMSE. Selection is on one seed and one validation year, so the ranking is not an estimate of seed stability.

Fresh combined-data refit and final test result

H / d	Parameters	E_val / E*	2022 test RMSE (SGD)	Test R^2
256 / 4	7,065	6 / 4	96,901.64	0.676082

A fresh seed-42 model was trained on all 116,427 combined 2017–2021 rows using the saved refit preprocessing. As explicitly authorized by the professor, test RMSE monitored this refit's stopping under the same 20/4/0.0001 rule. Eight epochs completed; the restored best checkpoint is E*=4. E_val=6 belongs to the separate original-split selection run. Final scores above cover every test row.

Test-assisted stopping limitation

The 2022 test set selected A1's stopping checkpoint, so its final score is not an untouched-holdout estimate. A2/A3 inherit the selected four-epoch budget. The higher test RMSE can reflect temporal distribution changes and model error; it is not proof of overfitting alone. Validation and test scores use different fitting periods and transforms, so their difference does not isolate the benefit of refitting. Following the updated plotting instruction, test results appear only in final tables/comparisons.

Sources: assignment brief pp. 2–4, slides pp. 2–3; supplied professor clarifications on plots and refit stopping.

[1] Ray Tune 2.58.0 documentation: grid_search (Cartesian-product search).

A2 · controlled ablations across five seeds

All three variants were initialized fresh for seeds 42–46 and trained for exactly four epochs on 2017–2021. They reuse A1's refit preprocessing, H=256, LR 0.01, batch 512 and the same seeded row order. All-input variants use d=4 and matched initial weights. Each run receives one final test evaluation; there is no A2 validation/test stopping. Reported SD is sample SD (ddof=1), not a confidence interval.

Model	Parameters	Test RMSE (SGD): mean ± SD	Test R^2: mean ± SD
Baseline (ReLU)	7,065	102,427.90 ± 5,289.17	0.637311 ± 0.037428
Continuous only	2,561	108,252.68 ± 9,605.81	0.593204 ± 0.068794
All inputs (Sigmoid)	7,065	101,821.96 ± 4,082.21	0.641892 ± 0.028889

A2a. Remove all four categorical embeddings




Figure A2a. Separate categorical ablation: all five seed pairs; squares/error bars show mean ± sample SD.

Only six continuous inputs enter Linear(6,256) → LayerNorm → ReLU → Linear(256,1), giving 2,561 parameters. Mean test RMSE rises by 5,824.79 SGD (5.69%), worsening in four of five seeds; mean R^2 falls by 0.044107. This supports retaining categorical information under this recipe. Removal also reduces capacity by 63.75%, so information loss and fewer parameters are confounded.

A2b. Replace hidden ReLU with Sigmoid




Figure A2b. Separate activation ablation: same inputs, parameter count and matched initialization. Test results are final values, not epoch curves.

Sigmoid lowers mean RMSE by only 605.94 SGD (0.59%) and improves three of five seeds; paired RMSE difference SD is 2,024.47 SGD. It can saturate and alter optimization, but gradients/saturation were not measured. The small, sign-changing gain does not establish a reliable advantage. Both comparisons use a short budget chosen for ReLU and inherited from test-assisted A1 stopping; no settings were retuned.

A3 · wide-and-deep comparison

Both branches receive the same 22-vector of shared embeddings and continuous inputs: $\hat{z} = \text{MLP}(x) + \lambda \cdot \text{Linear}(22,1)(x)$; apply the target inverse transform once after the sum. The MLP is A1's Linear(22,256) → LayerNorm → ReLU → Linear(256,1). The linear branch adds 23 parameters, for 7,088 total. Keep all A1 settings fixed and select λ using original train/validation partitions, seed 42 and validation-RMSE stopping. Exact ties favor smaller λ.

λ	Saved / completed epoch	Train RMSE (SGD)	Validation RMSE (SGD)	Validation R^2
0	6 / 10	34,372.58	58,627.10	0.870061
0.25	6 / 10	34,371.57	59,279.07	0.867155
0.5	6 / 10	34,465.69	59,294.97	0.867084
1	6 / 10	34,460.04	58,315.02	0.871441
2	**3 / 7**	**36,881.17**	**57,905.65**	**0.873239**

Select λ=2: validation RMSE improves by 721.46 SGD (1.23%) over λ=0, with saved epoch 3. λ=0 reproduced A1's trained baseline tensors and scores exactly. For the controlled final comparison, fresh seeds 42–46 use the saved combined-data transforms and A1's four-epoch budget, matching baseline MLP initialization and row order; the five A2 baseline results are reused.

Model	Parameters	Test RMSE (SGD): mean ± SD	Test R^2: mean ± SD
Baseline (ReLU)	7,065	102,427.90 ± 5,289.17	0.637311 ± 0.037428
Wide + deep, λ=2	7,088	101,413.74 ± 6,407.58	0.644081 ± 0.044905




Figure A3. Five matched final-seed comparisons and mean ± sample SD (ddof=1). A1's individual seed-42 score remains separately reported on page 2.

Mean RMSE improves 1,014.15 SGD (0.99%), in four of five seeds; paired difference SD is 2,811.40 SGD. Mean R^2 improves 0.006770. Seed 45 worsens by 3,246.47 SGD, so the gain is modest relative to seed variability and is not a statistical-significance claim.

A direct linear route can fit additive associations and shorten the gradient path to embeddings. The earlier/lower-error validation checkpoint is consistent with altered optimization or generalization, but branch-specific effects were not measured. Any positive λ can be absorbed into unrestricted linear weights/bias, so positive candidates share a function class but differ in effective initialization and finite-time optimization. Confounds include 23 extra parameters, jointly learned embeddings, one-seed λ selection and the short test-assisted epoch budget. The evidence does not isolate one mechanism.

A4 · FeatureAblation in Singapore dollars

Captum FeatureAblation [2] explains the matching seed-42, epoch-4 A1/A3 checkpoints on all 26,702 test rows and all ten original inputs. For feature j, a_{ij} = f_SGD(x_i) − f_SGD(x_i with j replaced); importance is mean$_i|a_{ij}|$. Categorical IDs are replaced before embedding lookup, with ten distinct mask IDs. Shared training-only references are month 7, SENGKANG, flat type '4 ROOM, Model A', storey '04 TO 06', and each continuous variable's training mean (standardized zero).




Figure A4a. All ten baseline scores, ranked descending. Values are mean absolute prediction changes in SGD.




Figure A4b. All ten wide-and-deep scores under the same replacement references and saved preprocessing.

Baseline top three: floor area (71,537.72 SGD), remaining lease (46,187.61), distance to Dhoby Ghaut (41,163.95). Wide-and-deep: floor area (73,119.34), remaining lease (48,364.21), flat model type (42,280.28). Flat type and Dhoby distance swap third/fourth; eight other ranks match. The similar rankings suggest broadly similar reliance under these references, with jointly trained branch/embedding differences.

These are reference-dependent model sensitivities, not causal price effects. Replacing one correlated input can create unrealistic feature combinations; mean absolute scores hide signs and sample variability. Nonlinear effects need not add to the total prediction change, and larger scores do not imply better accuracy. Only one matched seed was explained. Independent global aggregation and manual replacements matched, with maximum manual difference 0 SGD and unchanged checkpoints.

[2] Captum 0.9.0 documentation: FeatureAblation (replacement references and feature masks).