Efficient and Adaptable Detection of Malicious Prompts via Bootstrap Aggregation

Shayan Ali Hassan[†*] Zaeem Mohtashim Khan[‡*] Tao Ni[†] Zafar Qazi[‡,†] Marco Canini[†]
[†]*KAUST* [‡]*LUMS*
[†]{shayan.hassan, tao.ni, zafar.qazi, marco}@kaust.edu.sa [‡]26100107@lums.edu.pk

Large language models are increasingly deployed in user-facing systems, but they remain vulnerable to malicious prompts, including direct harmful requests, jailbreaks, and prompt-injection attacks. Existing defenses often impose an undesirable trade-off: black-box moderation APIs are easy to deploy but difficult to inspect or adapt, while white-box LLM-based guardrails can be accurate but expensive to run and update. We address this gap with **BAGEL** (**B**ootstrap **AG**gregated **E**nsemble **L**ayer), a lightweight and incrementally updatable framework for malicious prompt detection.

BAGEL is built as an ensemble of k small specialized classifiers, which we call *promptcops*. Each promptcop is an 86M-parameter Prompt Guard 2 model fine-tuned on a distinct malicious-prompt dataset, allowing different members of the ensemble to specialize in different attack families. At inference time, BAGEL first extracts lightweight structural features from the incoming prompt and uses an interpretable random forest router to predict the most suitable promptcop. It then samples $n-1$ additional promptcops uniformly at random, averages the selected models' maliciousness probabilities, and compares the result against a calibrated threshold. This combines mixture-of-experts-style routing with bagging-style variance reduction: the router provides targeted expertise, while stochastic aggregation helps recover from router mistakes and improves robustness across attack types. When a new attack family appears, BAGEL can be updated by fine-tuning just one additional promptcop, adding it to the ensemble, and recalibrating the router and decision threshold, rather than retraining a monolithic guardrail.

We evaluate BAGEL on nine large-scale single-turn datasets covering diverse malicious prompt types. Figure 1 highlights the central efficiency result. With $k = 9$ available promptcops, selecting only $n = 5$ promptcops nearly saturates performance, while $n = 5$ reduces the number of model calls by roughly 45%. This suggests that BAGEL can obtain most of the benefit of an ensemble without paying the full inference cost. The same experiment also shows that random-forest routing closely tracks an oracle strategy that always selects the best promptcop, indicating that stochastic aggregation compensates well when the router is imperfect.

Across comparative single-turn benchmarks, BAGEL achieves an F1 score of 0.922, with ASR = 0.095 and FPR = 0.066, using only 430M effective inference parameters at




Figure 1: Efficiency vs. performance tradeoff at $k = 9$.

		Strategy	F1↑	ASR↓	FPR↓
BAGEL ($k = 9$)	$n = 1$	Full-Conv.	0.636	0.232	0.593
		Chunk-Level	0.625	0.117	0.862
	$n = 5$	Full-Conv.	0.660	0.106	0.748
		Chunk-Level	0.648	0.054	0.894
	$n = 9$	Full-Conv.	0.704	0.155	0.508
		Chunk-Level	0.664	0.180	0.597
OpenAI Mod-API		Full-Conv.	0.192	0.886	0.062
		Chunk-Level	0.375	0.709	0.239
Shield-Gemma		Full-Conv.	0.258	0.835	0.100
		Chunk-Level	0.312	0.775	0.196
Toxic-Detector		Full-Conv.	0.647	0.486	0.067
		Chunk-Level	–	–	–

Table 1: Multi-turn attack detection performance.

$n = 5$. This outperforms or matches stronger black-box and white-box baselines while remaining substantially easier to update. Adaptability experiments further show that BAGEL remains robust as new promptcops are added over time, with F1 staying above 0.92 across sequential dataset additions.

Finally, we test whether single-turn promptcops generalize to multi-turn adversarial conversations without multi-turn fine-tuning. As shown in Table 1, BAGEL obtains the best balanced multi-turn performance among evaluated methods, reaching F1 = 0.704 with the full-conversation strategy at $n = 9$. Although multi-turn attacks remain harder than single-turn prompts, these results suggest that ensembles of small, specialized classifiers can provide a practical path toward safety systems that are efficient, interpretable, and adaptable as prompt attacks evolve.

*Student author


Efficient & Adaptable Detection of Malicious LLM Prompts via Bootstrap Aggregation

Shayan Ali Hassan, Zaeem Mohtashim Khan, Tao Ni, Zafar Ayyub Qazi, Marco Canini

QR Code to preprint

OSDI 26

Background



- Existing defenses against malicious LLM prompts offer limited transparency, adaptability (black-box methods), and high computational costs (white-box methods).
- BAGEL maintains an ensemble of k 'promptcops'.
- Each promptcop is a 86M parameter classifier finetuned on a specific dataset.
- At inference, n promptcops are chosen for probability aggregation and prediction.
- When a new attack pattern emerges, BAGEL is updated simply by finetuning and adding a new promptcop, avoiding full system re-training.

Comparative Benchmarking


Method	ASR↓	FPR↓	F1 Score↑	Parameters	Fine-tunable
BAGEL	0.095	0.066	0.922	86M per finetune, 430M for n=5	✓
ToxicDetector	0.045	0.326	0.847	300M + 7B	✓
ShieldGemma	0.624	0.038	0.534	2B	✓
OpenAIModerationAPI	0.881	0.024	0.208	Not Known	✗
Perspective API	0.569	0.068	0.642	Not Known	✗
LastLayer	0.598	0.171	0.519	Not Applicable	✗

Dataset Details


- We test BAGEL in both single-turn and multi-turn malicious prompt scenarios:
  - For single-turn prompts (accuracy, efficiency, adaptability and comparative experiments), we use 9 datasets (thus $k_{max} = 9$)
  - Total samples = 839,140 in a 7:1:2 split (finetuning : calibration : test).
  - For multi-turn conversational prompts (multi-turn performance experiment), we construct a combined set from 3 datasets.
  - Total samples = 2,400.

Key Takeaway: Ensembles of small, finetuned classifiers can match or exceed the performance of billion-parameter guardrails in terms of *accuracy*, *efficiency* and *adaptability*.

BAGEL Overview



Accuracy & Efficiency



Multi-Turn Performance

	Strategy	F1↑	ASR↓	FPR↓
BAGEL ($k = 9$), $n = 1$	Full-Conv.	0.636	0.232	0.593
	Chunk-Level	0.625	0.117	0.862
BAGEL ($k = 9$), $n = 5$	Full-Conv.	0.660	0.106	0.748
	Chunk-Level	0.648	0.054	0.894
BAGEL ($k = 9$), $n = 9$	Full-Conv.	0.704	0.155	0.508
	Chunk-Level	0.664	0.180	0.597
OpenAI Mod-API	Full-Conv.	0.192	0.886	0.062
	Chunk-Level	0.375	0.709	0.239
Shield-Gemma	Full-Conv.	0.258	0.835	0.100
	Chunk-Level	0.312	0.775	0.196
Toxic-Detector	Full-Conv.	0.647	0.486	0.067
	Chunk-Level	–	–	–

Adaptability

