

Kubernetes Exercise: Deploy Loki Stack with Log Collector and Sample App

Objectives

By the end of this exercise, you will:

1. Deploy the **Loki Stack** (Loki, Promtail, and Grafana) using Helm.
 2. Deploy a **sample application** that emits logs.
 3. View the application logs in **Grafana** using **LogQL**.
-

Prerequisites

- A Kubernetes cluster (minikube, kind, cloud, etc.)
 - `kubectl` installed and configured
 - `helm` installed (<https://helm.sh/docs/intro/install/>)
 - Optional: port 3000 open on localhost for Grafana
-

Step 1: Add and Install Loki Stack with Helm

```
helm repo add grafana https://grafana.github.io/helm-charts
helm repo update

# Create a monitoring namespace
kubectl create namespace monitoring

# Install the Loki stack (Loki + Promtail + Grafana)
helm install loki-stack grafana/loki-stack --namespace monitoring \
  --set grafana.enabled=true \
  --set promtail.enabled=true \
  --set loki.persistence.enabled=false \
  --set grafana.service.type=NodePort
```

Wait until everything is ready:

```
kubectl get pods -n monitoring
```

Step 2: Access Grafana UI

Port forward Grafana:

```
kubectl port-forward -n monitoring service/loki-stack-grafana 3000:80
```

Then open: <http://localhost:3000>

Login credentials:

- **User:** admin
 - **Password:** prom-operator (default for Loki Helm chart)
-

Step 3: Deploy a Sample App with Logs

Here's a simple "log generator" app that prints messages to stdout.


```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: log-emitter
  namespace: default
spec:
  replicas: 1
  selector:
    matchLabels:
      app: log-emitter
  template:
    metadata:
      labels:
        app: log-emitter
    spec:
      containers:
        - name: logger
          image: busybox
          command: ["/bin/sh"]
          args: ["-c", "while true; do echo Hello from $(hostname); sleep 5; done"]
```

Apply it:

```
kubectl apply -f log-emitter.yaml
```

Step 4: View Logs in Grafana

Add the Loki data source (if not already added)

1. Go to Grafana UI →  **Configuration** → **Data Sources**
2. Click **Add data source** → choose **Loki**
3. URL: `http://loki-stack:3100`
4. Click **Save & Test**

Explore logs

1. Go to **Explore**
2. Select **Loki** as the datasource
3. Use a query like:

```
{app="log-emitter"}
```

You should see logs like:


```
Hello from log-emitter-xxxx
```

Bonus Tasks

- Scale the deployment to `replicas: 3` and observe the logs.
 - Modify the log message (e.g., include timestamps or random IDs).
 - Add a `label` to logs and filter by it in LogQL.
-

Cleanup

```
kubectl delete deployment log-emitter  
helm uninstall loki-stack -n monitoring  
kubectl delete namespace monitoring
```

 August 23, 2025