

PRODUCT DATA SHEET



BI-DIRECTIONAL PIG SIGNALLER MODEL: LS2-TQZ



BI-DIRECTIONAL INTRUSIVE PIG SIGNALLER

A robust pipeline device that detects the passage of a pig in either direction and provides reliable indication to operators.

-  Detects pig passage in both directions
-  Intrusive mechanical trigger mechanism
-  Reliable operation even if installed in reverse orientation
-  Positive indication of pig presence at a specific point in the line
-  Suitable for cleaning, batching and inspection pigging applications
-  Rugged, dependable signal for pipeline operators
-  Ideal for oil, gas, water and process pipelines

Document Information

Brand

LINESIG

Product

Bi-Directional Intrusive Pig Signaller

Model

LS2-TQZ

Document Code

LNS-DS-PS-001

Revision

Rev. 2

Standard Output

Mechanical flag

Optional Outputs

Electrical switch or wireless alert, subject to approved configuration

Details

www.linesig.com

1. General Description

The **LS2-TQZ** Bi-Directional Intrusive Pig Signaller is a robust pipeline accessory designed to detect, signal and confirm pig passage in both directions. The intrusive trigger provides positive mechanical activation under varying pipeline conditions. The source datasheet also states weatherproof and hazardous area construction; final certification shall be confirmed against the approved project documentation.

2. Key Features

- Bi-directional detection for forward and reverse pig runs.
- Intrusive trigger for positive mechanical activation.
- Mechanical flag indicator as the standard local output.
- Electrical switch or wireless alert options, subject to approved configuration.
- Stainless-steel wetted parts for durability.
- Manual reset arrangement.
- Suitable for oil, gas, water and chemical pipeline service.

3. Technical Specifications

Parameter	Specification
Pipeline Size	4 in to 48 in; custom sizes available
Pressure Rating	Up to 25 bar; source also references ANSI Class 300
Temperature Range	-20°C to +120°C
Body Material	Stainless steel; SS316 on request, as stated in source
Wetted Parts	SS316
Seal Material	Viton / PTFE
Indicator Type	Mechanical flag
Process Connection	2 in NPT / flanged as per ASME B16.5
Certification	ATEX / IECEx Zone 1 & 2, as stated in source
Reset Option	Manual
Stand-off Length	172-177 mm
Trigger Insertion	21-22 mm inside pipe
Nozzle Height	As per stand-off length
Designed to Detect	Sphere, steel-body pigs and polyurethane pigs

4. Typical Applications

- Oil and gas transmission pipelines
- Product batching lines
- Chemical and petrochemical lines
- Water and industrial utility pipelines

Important:

Pressure rating, flange class, hazardous-area certification and installation dimensions shall be confirmed against the approved order datasheet and certified drawings.

5. Output Options

Option	Description
Mechanical Flag	Standard local visual indication stated in the source datasheet
Electrical Switch	Remote status output, subject to approved configuration
Wireless Alert	Wireless notification option, subject to approved configuration

6. Ordering Information

Model	Type	Output	Reset	Material
LS2-TQZ	Intrusive bi-directional	Mechanical flag	Manual	Stainless steel

7. Standard Compliance

- ASME B31.4 / B31.8
- API 6D and API RP 1130
- ATEX / IECEx for hazardous installations, as stated in the source datasheet

8. Document Control and Clarifications

- The source file name refers to LS-3-SS, while the datasheet identifies the model as LS2-TQZ.
- This document retains LS2-TQZ because it is the explicit model shown in the original datasheet.
- Final materials, pressure rating, process connection, insertion dimensions and certification shall be confirmed in the approved order documents.

