

PIG SIGNALER

DATA SHEET

BI-DIRECTIONAL PIG SIGNALER

MODEL:

LS2S-TQZ

(DIGITAL SIGNAL)



RELIABLE CONFIRMATION
OF PIG PASSAGE FOR
SAFE & EFFICIENT
PIPELINE OPERATIONS



BI-DIRECTIONAL
OPERATION



MANUAL FLAG
OR DIGITAL
INDICATION



ALL SS 316
WET PARTS &
FULL BODY



DURABLE
CORROSION
RESISTANT



EASY INSTALLATION
& MAINTENANCE

DOCUMENT CONTROL

REV.	DATE	DESCRIPTION	PREPARED BY	CHECKED BY	APPROVED BY
00		FOR ISSUE			



Document Information	Details
Brand	LINESIG
Product	Bi-Directional Intrusive Pig Signaller
Model	LS2S-TQZ
Document Code	LNS-DS-LS2S-001
Revision	Rev. 0
Standard Output	Digital signal
Optional Outputs	Mechanical flag + digital/Digital wireless alert, subject to approved configuration

1. General Description

The LS2S-TQZ Bi-Directional Intrusive Pig Signaller is a robust pipeline accessory designed to detect, signal and confirm pig passage in both directions. The intrusive trigger provides positive mechanical activation under varying pipeline conditions.

For the LS2S-TQZ digital type, pig passage is converted into a remote digital status indication for connection to a control, monitoring or alarm system. Final electrical arrangement and hazardous-area certification shall be confirmed against the approved project documentation.

2. Key Features

- Bi-directional detection for forward and reverse pig runs.
- Intrusive trigger for positive mechanical activation.
- Digital signal output for remote pig-passage indication.
- Optional mechanical flag or wireless alert, subject to approved configuration.
- Stainless-steel wetted parts for durability.
- Suitable for oil, gas, water and chemical pipeline service.

3. Technical Specifications

Parameter	Specification
Pipeline Size	4 in to 48 in; custom sizes available
Pressure Rating	Up to 25 bar; source also references ANSI Class 300
Temperature Range	-20°C to +120°C
Body Material	Stainless steel; SS316 on request, as stated in source
Wetted Parts	SS316
Seal Material	Viton / PTFE
Indicator Type	Digital signal output
Process Connection	2 in NPT / flanged as per ASME B16.5
Certification	ATEX / IECEx Zone 1 & 2, where specified in approved project documentation
Reset Option	As per approved digital configuration
Stand-off Length	172-177 mm
Trigger Insertion	21-22 mm inside pipe
Nozzle Height	As per stand-off length
Designed to Detect	Sphere, steel-body pigs and polyurethane pigs

4. Typical Applications

- Oil and gas transmission pipelines
- Product batching lines
- Chemical and petrochemical lines
- Water and industrial utility pipelines

Important: Pressure rating, flange class, hazardous area certification, electrical interface and installation dimensions shall be confirmed against the approved order datasheet and certified drawings.

Option	Description
Digital Signal	Standard remote status output for control or monitoring systems
Mechanical Flag	Optional local visual indication, subject to approved configuration
Wireless Alert	Optional wireless notification, subject to approved configuration

6. Ordering Information

Model	Type	Output	Reset	Material
LS2S-TQZ	Intrusive bi-directional	Digital signal	As configured	Stainless steel

7. Standard Compliance

- ASME B31.4 / B31.8
- API 6D and API RP 1130
- ATEX / IECEx for hazardous installations, where specified

8. Digital Interface Notes

The LS2-TQZ source datasheet identifies electrical switch output only as an option and does not define the switch type, contact logic, supply voltage, current rating, terminal arrangement, cable entry, enclosure rating or detailed digital interface.

Accordingly, these electrical parameters remain order-specific for model LS2S-TQZ and shall be taken from the approved wiring, terminal and project documentation.

9. Document Control and Clarifications

- This LS2S-TQZ datasheet follows the same technical basis and product-family structure as the LS2-TQZ manual-flag datasheet.
- The standard indication is changed from mechanical flag to digital signal for model LS2S-TQZ.
- Final materials, pressure rating, process connection, insertion dimensions, electrical output and certification shall be confirmed in approved order documents.

