

PIG SIGNALER

DATA SHEET

BI-DIRECTIONAL PIG SIGNALER

MODEL:

LS2-TQZ

MECHANICAL FLAG



RELIABLE CONFIRMATION
OF PIG PASSAGE FOR
SAFE & EFFICIENT
PIPELINE OPERATIONS



BI-DIRECTIONAL
OPERATION



MANUAL FLAG
OR DIGITAL
INDICATION



ALL SS 316
WET PARTS &
FULL BODY



DURABLE
CORROSION
RESISTANT



EASY INSTALLATION
& MAINTENANCE

DOCUMENT CONTROL

REV.	DATE	DESCRIPTION	PREPARED BY	CHECKED BY	APPROVED BY
01		FOR ISSUE			



Document Information	Details
Brand	LINESIG
Product	Bi-Directional Intrusive Pig Signaller
Model	LS2-TQZ
Document Code	LNS-DS-PS-001
Revision	Rev. 2
Standard Output	Mechanical flag
Optional Outputs	Electrical switch or wireless alert, subject to approved configuration

1. General Description

The **LS2-TQZ** Bi-Directional Intrusive Pig Signaller is a robust pipeline accessory designed to detect, signal and confirm pig passage in both directions. The intrusive trigger provides positive mechanical activation under varying pipeline conditions. The source datasheet also states weatherproof and hazardous area construction; final certification shall be confirmed against the approved project documentation.

2. Key Features

- Bi-directional detection for forward and reverse pig runs.
- Intrusive trigger for positive mechanical activation.
- Mechanical flag indicator as the standard local output.
- Electrical switch or wireless alert options, subject to approved configuration.
- Stainless-steel wetted parts for durability.
- Manual reset arrangement.
- Suitable for oil, gas, water and chemical pipeline service.

3. Technical Specifications

Parameter	Specification
Pipeline Size	4 in to 48 in; custom sizes available
Pressure Rating	Up to 25 bar; source also references ANSI Class 300
Temperature Range	-20°C to +120°C
Body Material	Stainless steel; SS316 on request, as stated in source
Wetted Parts	SS316
Seal Material	Viton / PTFE
Indicator Type	Mechanical flag
Process Connection	2 in NPT / flanged as per ASME B16.5
Certification	ATEX / IECEx Zone 1 & 2, as stated in source
Reset Option	Manual
Stand-off Length	172-177 mm
Trigger Insertion	21-22 mm inside pipe
Nozzle Height	As per stand-off length
Designed to Detect	Sphere, steel-body pigs and polyurethane pigs

4. Typical Applications

- Oil and gas transmission pipelines

- Product batching lines
- Chemical and petrochemical lines
- Water and industrial utility pipelines

Important:

Pressure rating, flange class, hazardous-area certification and installation dimensions shall be confirmed against the approved order datasheet and certified drawings.

5. Output Options

Option	Description
Mechanical Flag	Standard local visual indication stated in the source datasheet
Electrical Switch	Remote status output, subject to approved configuration
Wireless Alert	Wireless notification option, subject to approved configuration

6. Ordering Information

Model	Type	Output	Reset	Material
LS2-TQZ	Intrusive bi-directional	Mechanical flag	Manual	Stainless steel

7. Standard Compliance

- ASME B31.4 / B31.8
- API 6D and API RP 1130
- ATEX / IECEx for hazardous installations, as stated in the source datasheet

8. Document Control and Clarifications

- The source file name refers to LS-3-SS, while the datasheet identifies the model as LS2-TQZ.
- This document retains LS2-TQZ because it is the explicit model shown in the original datasheet.
- Final materials, pressure rating, process connection, insertion dimensions and certification shall be confirmed in the approved order documents.

