Practical 12 - Code and Output

Yacc file: practical12.y

Open practical12.y Save

```
%{
#include <stdio.h>
#include <stdlib.h>
int yyerror(char *s);
int num1,num2;
%}
%token NUM1 NUM2 PLUS
%%
E: E PLUS E
    { printf("Addition: %d\n",num1+num2); }
    | NUM1
    ;
%%
int main(void)
{
    printf("Enter two numbers: ");
    scanf("%d %d", &num1,&num2);
    return 0;
}

int yyerror(char *s)
{
    printf("Error: %s\n",s);
    return 1;
}

//Name :- Mohammed Zaid Shaikh
//PRN :- 24070521043
//Batch :- A2
```

Lex file: practical12.l

Open practical12.l ~ Save

```
%{
#include "y.tab.h"
%}

%%
"int"|"float"|"char"  { return KEY; }
[a-zA-Z_][a-zA-Z0-9]* { return ID; }
[0-9]+                { return NUM; }
";"                   { return SEMI; }
[ \t\n]
.                     { return yytext[0]; }
%%

int yywrap()
{
    return 1;
}

//Name :- Mohammed Zaid Shaikh
//PRN :- 24070521043
//Batch :- A2
```

Output

```
zaid787@LAPTOP-ID0Q783M:~$ gedit practical12.y
zaid787@LAPTOP-ID0Q783M:~$ gedit practical12.l
zaid787@LAPTOP-ID0Q783M:~$ yacc -d practical12.y
zaid787@LAPTOP-ID0Q783M:~$ flex practical12.l
zaid787@LAPTOP-ID0Q783M:~$ gcc lex.yy.c y.tab.c -o practical12
zaid787@LAPTOP-ID0Q783M:~$ ./practical12
Enter a declaration: int awe1;
Valid declaration
^Z
[1]+  Stopped                 ./practical12
zaid787@LAPTOP-ID0Q783M:~$ ./practical12
Enter a declaration: float 123ab;
Invalid declaration
zaid787@LAPTOP-ID0Q783M:~$ ./practical12
Enter a declaration: float ab123;
Valid declaration
^Z
[2]+  Stopped                 ./practical12
zaid787@LAPTOP-ID0Q783M:~$
```