DreamOS: A Locally Run Semantic File Manager with a Knowledge Graph, Conversational Memory and a Checkable Privacy Audit

Zaid Ali Syed, Om Vyas and Krushna Kadam
Department of Information Technology, Institute of Information and Communication Technology (IICT)
MGM University, Chhatrapati Sambhajinagar, India | sidzaid72@gmail.com

Abstract: Personal file collections are organised by names chosen at save time, and those names rarely describe the content later. We present DreamOS, a locally run desktop file manager that finds, opens, relates and organises files from natural-language requests using only a local embedding model and a local 3B-parameter language model. Six modules cooperate: intent routing, semantic search, a reversible organiser, a knowledge graph, a context-memory engine and a workspace manager, and a privacy audit reports from live configuration which endpoints the system can reach. On 36 labelled queries over a 37-file vault, DreamOS ranks the intended file first for 94% of queries (MRR 0.97), against 56% (MRR 0.61) for a BM25 content index and 33% for filename matching; on the 10 queries that share no word with their target, both lexical baselines score 0.00 and DreamOS scores 0.80. On synthetic collections of 500 to 5,000 files, removing three all-pairs computations from graph construction cut a 2,000-file rebuild from 246.1 s to 1.3 s and a 5,000-file rebuild from 143.3 s to 3.2 s, after which embedding the files, not graph construction, dominates indexing time. We also document a failure in which a language model's own reference flag overrode a confident direct answer, and the rule precedence that fixed it. Limitations, including the small hand-labelled query set, are stated in full.

Index Terms: semantic search, sentence embeddings, knowledge graph, local language models, personal information management, conversational memory, privacy by design.

I. INTRODUCTION

A personal computer accumulates thousands of files whose names were chosen once, in a hurry, and rarely describe what the file is about. A user who saved final_final_v3.txt must later remember that exact name, or the folder it went into, to find it again. Mainstream desktop search is lexical: a query must share vocabulary with the file name, its metadata or its text [5]-[7]. Semantic file systems [1], [8] and dense retrieval [3], [9] show that matching by meaning is feasible, but the closest recent system, LSFS [1], is designed for software agents calling an API, and neither it nor the consumer tools report in a checkable way what could leave the user's machine.

DreamOS lets a person describe a file in plain language and have it found, opened, related to other files, or organised, with every inference step running on the user's own computer. The six modules map loosely onto the memory vocabulary of cognitive science [10]: the embedding index and knowledge graph play the role of semantic memory, the stored conversation turns and open events that of episodic memory, and the session context that of working memory. We use this only as a design analogy and make no claim of cognitive modelling. The contributions are:

1) An architecture that exposes semantic retrieval and action through one conversational interface for a human user, with six cooperating modules and a reversible organiser.
2) A controlled retrieval comparison against two lexical baselines on a labelled query set, partitioned by whether a query shares any word with its target, with confidence intervals and the failures listed.
3) A deterministic-precedence rule for conversational follow-ups, introduced after a live failure in which the language model's own flag for "refers to previous" overrode a confident direct search result.
4) A vectorised, equivalence-tested knowledge-graph construction with mean-centred similarity and average-linkage clustering, evaluated at up to 5,000 files with the real local models, in which profiling-driven fixes removed all-pairs computations and brought the 5,000-file rebuild to seconds.
5) A privacy audit that reports endpoints from live configuration, with an independent network-level check that can falsify it.

II. RELATED WORK

A. Semantic file systems and personal retrieval

Gifford et al. introduced semantic file systems, in which attributes extracted from content are exposed as virtual directories [8]. Stuff I've Seen made previously encountered personal information retrievable by content rather than location [11]. LSFS, presented at ICLR 2025, indexes files as embedding vectors and exposes create, retrieve, update and roll-up operations to an LLM agent, showing that embedding indexes can replace command-based file operations at the operating-system-agent level [1]. DreamOS follows the same architectural direction but targets a person rather than an agent, adds a relationship graph and conversational memory, and reports an auditable privacy statement.

B. Dense retrieval, anisotropy and ranking

Word and sentence embeddings place related text near each other [2], [3]; dense passage retrieval showed that learned embeddings can rival lexical ranking such as BM25 [9], [12]. Sentence-embedding spaces are anisotropic, so unrelated texts have high cosine similarity [13], [14]; DreamOS observes this directly (median document-pair cosine 0.52 on its vault) and counters it by mean-centring before graph construction, in the spirit of [14]. Approximate nearest-neighbour indexes such as HNSW [15] are what the vector store uses internally.

C. Consumer desktop search

Windows Search indexes names, metadata and text but matches lexically [5]; Spotlight layers metadata and ranking heuristics on a keyword index [6]; Everything indexes NTFS file names for instant lookup without reading content [7]. Table I summarises the capability gap. None of the three retrieves by meaning in the documented configuration, and none reports a checkable statement of what leaves the machine.

TABLE I. Capability Comparison with Existing File-Search Systems

Capability	Windows Search [5]	Spotlight [6]	Everything [7]	LSFS [1]	DreamOS
Retrieval by embedding similarity (meaning)	No	No	No	Yes	Yes
Indexes file content	Yes	Yes	No (names)	Yes	Yes
Conversational requests with follow-ups	No	No	No	No (agent API)	Yes
Opens a file only above a confidence bar	No	No	No	Not assessed	Yes
Reversible AI-assisted organisation	No	No	No	Not assessed	Yes
Typed file-relationship graph with reasons	No	No	No	Not assessed	Yes
Needs no cloud model or service	Yes	Yes	Yes	Not shown	Yes
Live, checkable privacy report	No	No	No	No	Yes

"No" means the capability is not provided in the standard configuration documented in [5]-[7]; vendor features added after those documents (for example AI-assisted search on newer hardware) were not evaluated. LSFS was assessed from its published paper only; "Not assessed" marks properties that paper does not state.

III. SYSTEM DESIGN

A. Architecture

DreamOS is a client-server application confined to one machine (Fig. 1). A Tauri 2 shell hosts a React interface with four views (chat, knowledge graph, workspaces, privacy). The interface calls a FastAPI service bound to 127.0.0.1:8420, which calls a local Ollama runtime for two models, nomic-embed-text [16] for embeddings and llama3.2 (3B) for intent classification, summaries and tags, and reads and writes three local stores: SQLite for relational data, ChromaDB [4] for chunk vectors and a sandboxed vault of files. No component is reachable from outside the machine by default.

B. Pipelines

Two pipelines share these components (Fig. 2). Indexing extracts text, chunks it, embeds each chunk, stores the vectors, asks the language model for a summary, tags and a category, and rebuilds the graph; unchanged files are skipped by content hash. The query pipeline classifies each message into one of five intents (search, open, related, workspace, organise), resolves any reference to earlier results, and routes the request to the matching module.




Fig. 1. DreamOS architecture. A desktop client talks over loopback HTTP to a local service with eight components (blue: request modules; green: supporting modules). The service calls a local model runtime and three local stores. Nothing in the path leaves the machine.




Fig. 2. (a) The indexing pipeline turns files into vectors, summaries, tags and graph edges. (b) The query pipeline classifies a message, resolves references (amber: the step that carries the paper's precedence rule), and routes to one of five actions.

C. Data model

Table II lists the design tables. Every derived table (edges, turns, usage, workspace membership) is keyed on the file's integer identifier, not its path. The organiser renames files when it moves them, but the identifier survives, so relationships and memory never need re-synchronising after a move, and a move can be reversed from the stored original path.

TABLE II. Database Design: Tables, Key Fields and Role

Store / table	Key fields	Role
SQLite / files	id (PK), path (unique), original_path, content_hash, summary, tags, category	One row per file; stable identity
SQLite / file_edges	src_id, dst_id, kind, weight	similar, references, shared_tag
SQLite / conversation_turns	session_id, role, message, intent, file_ids	Episodic memory of the chat
SQLite / usage_events	file_id, kind, created_at	Open history; tie-break and rules
SQLite / workspaces, workspace_files	name (unique); workspace_id, file_id	Named groups of files
ChromaDB / vectors	id, document chunk, embedding, metadata (path)	Nearest-neighbour retrieval

IV. METHODS

A. Semantic search

A query q is embedded and compared with every chunk c. A file f takes the score of its best chunk, plus a small boost for literal vocabulary overlap, where Q is the query's content words (stop-words removed, plurals folded) and T_f the words of the file's name and text:

$$s(f) = max_c\ cos(e_q, e_c) + \lambda \cdot |Q \cap T_f| / |Q| \qquad (1)$$

$$keep\ f\ \ iff\ \ s(f) \geq max(\tau, s^* - \delta) \qquad (2)$$

with floor $\tau = 0.47$, margin $\delta = 0.06$ below the best score s^*, and $\lambda = 0.08$. A fixed cut-off was abandoned because it dropped correct answers to short queries (20 of 27 on the tuning set, against 27 of 27 with the relative rule). Results below a confidence bar of 0.55 are labelled low-confidence, and the open action never launches a file from such a result.

B. Knowledge graph

Three typed, weighted edge kinds connect files: similar (cosine of mean chunk embeddings), references (one file's text names another by file name) and shared_tag (at least two AI-generated tags in common). Raw cosine is compressed by anisotropy, so vectors are first mean-centred, $\hat{h}_f = (h_f - \mu) / \|h_f - \mu\|$, which spreads unrelated pairs to about 0 and related pairs to 0.25-0.4; the similar-edge threshold is 0.25 on that scale and each file keeps its three strongest neighbours. Clusters use average-linkage merging, joining two groups only while the mean edge weight between their members, counting missing edges as 0, exceeds 0.12. Plain connected components chained unrelated groups through single weak bridges (a 7-file cluster mixing resumes with proposals); average linkage cannot chain.

The pairwise Python loop was replaced by one matrix product, $S = \hat{H}\hat{H}^T$, with neighbours chosen by partial sort. An equivalence test on random vectors confirms identical edges, so the rewrite changes speed and not behaviour. An inverted index for shared tags removed another quadratic term. Profiling the 5,000-file rebuild then showed the reference check, an all-pairs regular-expression search, taking 98% of the time; each file name is now filed under its rarest alphanumeric token and a text is searched only for the names whose token it contains, which cannot miss a bounded occurrence and is checked against the exhaustive search in a test. Clustering uses a heap over per-group adjacency instead of rescanning every link after each merge; on random graphs without ties it matches the original loop exactly, and with ties it breaks them by lowest group id.

C. Context memory and deterministic precedence

Each turn is stored with the identifiers of the files it showed, so follow-ups such as "open the second one" or "open it" resolve after a restart or a file move. Fig. 3 gives the resolution order: ordinal and bare-pronoun rules first, then a direct search on the topic the classifier extracted, and only if that search is below the confidence bar does the model's own "refers to previous" flag act as a last resort.




Fig. 3. Follow-up resolution flowchart. Amber: decisions, evaluated top to bottom; green: outcomes. Deterministic evidence precedes the language model's own judgement.

The order was fixed after a live rehearsal. Asked "what is related to my resume" after a search for invoices, the system answered about an invoice file. The 3B model set its continuation flag to true for this sentence while correctly extracting "resume" as the topic, apparently because the sentence matched an example in its own instructions; the system had trusted the flag unconditionally. A regression test that fails on the old precedence and passes on the new guards it.

D. Privacy audit

An endpoint reads live configuration and lists every address the service is set to call, whether each is loopback, and what is stored locally. It states that it checks configuration, not traffic, and names the independent check (listing listening sockets with netstat to confirm loopback-only binding), so the claim can be falsified.

E. Organiser and workspaces

For each file the model proposes a summary, tags, a category and a reason; a move is applied only on confirmation and is reversible. Workspace recommendations (related groups, frequently opened files, duplicates, uncategorised and stale files) are rule-based on purpose, so they are reproducible and explainable and cost no extra model calls.

V. EXPERIMENTAL SETUP

All runs used one laptop (AMD Ryzen 7 6800H, 16 GB RAM, Windows 11, CPU only) with nomic-embed-text and llama3.2 3B served by Ollama. The suite of 123 automated tests runs offline against fixtures and on every push in continuous integration.

A. Retrieval comparison

The corpus is the 37-file demonstration vault: deliberately messy text, Markdown and source files (CVs, invoices, meeting notes, a recipe, scripts). We wrote 36 queries with their relevant files before running any system. Each query is partitioned automatically by whether any of its content words, after the system's own stop-word and plural folding, occurs in a relevant file's name or text: 26 do, 10 do not. Four systems return at most 8 files: (i) filename match, a lexical match on names only, standing in for name-index tools [7]; (ii) BM25 [12] over name and text, standing in for lexical content indexes [5], [6]; (iii) embedding only, DreamOS without the keyword boost and cut-off; (iv) DreamOS as shipped. Metrics are Hit@1, Hit@3 and mean reciprocal rank (MRR), with 95% Wilson intervals [17] on Hit@1.

B. Scale evaluation

Synthetic vaults of 500, 2,000 and 5,000 text files across twelve topics were generated, about half with one distractor sentence from another topic. Each size ran in a fresh process with a fresh database and the real models. We measured indexing throughput (including the graph rebuild that follows an index pass), graph rebuild time, the latency of 36 queries, and precision at 5 against the generated topic label. The scripts (bench_scale.py, eval_retrieval.py) are part of the project repository.

TABLE III. Retrieval Comparison on 36 Labelled Queries (37 Files)

System	Hit@1 (all)	Hit@3 (all)	MRR (all)	Hit@1, shares words (n=26)	Hit@1, no shared words (n=10)	MRR, no shared words
Filename match	0.33	0.36	0.35	0.46	0.00	0.00
BM25 over name and text	0.56	0.67	0.61	0.77	0.00	0.00
Embedding only	0.92	1.00	0.95	0.92	0.90	0.95
DreamOS (shipped)	0.94	1.00	0.97	1.00	0.80	0.90

VI. RESULTS

A. Retrieval quality

Table III and Fig. 4 show the comparison. DreamOS places a relevant file first for 94% of all queries and within the first three for 100%, against 56% and 67% for BM25. The partition explains the gap: when a query shares a word with its target, BM25 reaches Hit@1 0.77 and DreamOS 1.00; when it shares none, both lexical baselines score exactly 0.00 by construction, while DreamOS scores 0.80 with all 10 targets inside the top three. Examples are "present for my mother" finding the gift list that says "Mom's birthday", and "how to brew a hot drink with spices" finding the chai recipe.




Fig. 4. Hit@1 by system and query group, with 95% Wilson intervals. Lexical systems cannot answer queries that share no word with the target; the embedding-based systems can.

Two findings are less favourable and are reported as measured. First, the keyword boost helps queries that share words (Hit@1 0.92 to 1.00) but costs one of the 10 paraphrase queries (0.90 to 0.80); the intervals overlap, so the data cannot separate the two configurations. Second, DreamOS missed rank 1 on two queries ("remarks from our mentor about what to improve" and "spending breakdown for the semester"), both of which placed an unrelated quotes file first with the correct file second. With 36 queries the Hit@1 interval for DreamOS is wide (about 0.82 to 0.99), so differences of a few points between the embedding systems should not be over-read.

B. Scale

Table IV and Fig. 5 report the scale runs. Indexing stays above 18.1 files per second up to 5,000 files and median search latency grows from 34.5 ms to 204.7 ms. Graph construction was sped up in two stages. Vectorising the similarity step cut the 500-file rebuild from 17.0 s to 1.7 s and the 2,000-file rebuild from 246.1 s to 24.8 s, but profiling the 5,000-file rebuild (143.3 s) showed that 98% of it was the reference check, an all-pairs regular-expression search. Replacing that with a token index, and the clustering with a heap over per-group adjacency, brought the rebuilds to 0.4 s, 1.3 s and 3.2 s at 500, 2,000 and 5,000 files, with the same edge set. Indexing is now dominated by embedding: at 5,000 files the graph is 1% of the 276.3 s index pass. Precision at 5 is 1.00 at every size, which shows only that the twelve synthetic topics separate; it is not a quality claim for real documents.

TABLE IV. Scale Benchmark Across the Three Graph-Construction Stages (n/m: not measured)

Files	Index files/s (first / final)	Graph rebuild s (loop / vectorised / final)	Graph edges	Search p50 (ms)	Search p95 (ms)	Precision@5
500	12.4 / 19.9	17.0 / 1.7 / 0.4	1062	34.5	60.7	1.00
2,000	5.4 / 23.2	246.1 / 24.8 / 1.3	4747	106.5	126.7	1.00
5,000	n/m / 18.1	n/m / 143.3 / 3.2	11938	204.7	232.7	1.00




Fig. 5. Scale results from the same runs as Table IV. (a) Graph rebuild time on a log scale at three stages: the original pairwise loop, vectorised similarity only, and the final version (token-indexed reference check, heap clustering). (b) Indexing throughput, which includes the graph rebuild. (c) Median and 95th-percentile search latency, which grows with the number of stored vectors.

C. Defects found by testing

Table V lists the three defects that testing exposed. Each was diagnosed by measurement rather than assumption: the first by profiling, which located the time inside the socket connect call rather than in inference; the second by scaling the input and observing super-linear growth; the third by a live rehearsal that the unit tests had not anticipated. Each fix has a test that fails against the prior code.

D. Intent routing

The intent prompt was evaluated rather than guessed: a 32-message tuning set and a separate 26-message held-out set were run on the real llama3.2. The first prompt scored 80% on the held-out set and the revised prompt 88% (23 of 26). The remaining misses are borderline phrasings, for example "which files should I archive" routed to organise rather than workspace. Every module sits behind this classifier, so this error rate bounds how often a request is routed to the wrong module.

E. Interface

Fig. 6 shows three of the four views. The chat view returns result cards, each with an action and, for related-file answers, the reason the files are linked (similar content, a direct reference or shared tags). The graph view lays out files and edges by force-directed layout; the workspace view lists recommendations with the rule that produced each, and creates workspaces that open together.

TABLE V. Defects Exposed by Testing, Their Causes and Fixes

Defect	Symptom	Cause	Fix and evidence
Name-resolution delay	About 1 s added to every embedding call	"localhost" tried IPv6 first; the model server listens on IPv4	Use 127.0.0.1; call about 15 ms; 100-file index 0.41 to 19.6 files/s
All-pairs graph computations	Rebuild 246.1 s at 2,000 and 143.3 s at 5,000 files	Pairwise similarity loop; then all-pairs regex reference check and full-table clustering rescan	Matrix product, token index, heap; equivalence tests; 3.2 s at 5,000
Stale-context override	Answer about the previous topic	Model flag trusted over a confident direct search	Rules first, flag last; regression test fails on old order




Fig. 6. Screenshots of the desktop client: (a) chat results with the reason each related file is linked, (b) the knowledge-graph view, (c) workspaces with rule-based suggestions.

VII. DISCUSSION AND THREATS TO VALIDITY

Meaning-based matching is what separates the systems, and it comes from the embedding model, not from the surrounding engineering; what DreamOS adds is a single interface over retrieval, action and memory, evidence-ordered resolution of follow-ups, and a privacy statement that can be falsified. The negative results matter as much: the keyword boost trades a paraphrase query for several shared-word ones, and the dense pairwise-similarity matrix still grows with the square of the number of files (about 200 MB at 5,000 files), which is the next limit rather than the graph rebuild time.

Threats to validity. Internal: the authors wrote and labelled the queries, which risks unconscious favouring of the system; labels were fixed before the run, the partition is computed rather than judged, and failures are listed. Baselines are

reference implementations of the lexical class (name match, BM25 with the system's own tokeniser), not the Windows Search, Spotlight or Everything products, so Table III supports a claim about lexical versus embedding retrieval, not about any named product. Construct: precision on synthetic topic labels measures topic separation, not usefulness. External: 37 files and 36 queries, one author's vault, one machine, one pair of small models; intent classification is 88% correct (23 of 26) on held-out phrasings and borderline phrasing is misrouted. Reproducibility: all numbers in this paper are read from committed result files produced by the two scripts above.

VIII. CONCLUSION

DreamOS shows that a single laptop with two small local models can support meaning-based file retrieval, conversational follow-ups and a relationship graph, with a privacy claim that can be checked. In a controlled comparison it retrieved paraphrased targets that lexical indexes cannot, at the cost of a small, reported regression on one query; measurement exposed performance defects (a name-resolution delay and three all-pairs computations in graph construction) and one behavioural defect, each fixed and tested. Future work is a labelled evaluation on consented real documents, an approximate nearest-neighbour graph for collections beyond 10,000 files, and a head-to-head run against the shipped desktop-search products.

ACKNOWLEDGMENT

The authors thank their project guide, Dr. Minakshi R. Rajput, and the Institute of Information and Communication Technology, MGM University, for the Project Monitoring structure under which this work was reviewed.

REFERENCES

[1] Z. Shi et al., “From Commands to Prompts: LLM-Based Semantic File System for AIOS,” in Proc. ICLR, 2025, arXiv:2410.11843.

[2] T. Mikolov, K. Chen, G. Corrado and J. Dean, “Efficient Estimation of Word Representations in Vector Space,” arXiv:1301.3781, 2013.

[3] N. Reimers and I. Gurevych, “Sentence-BERT: Sentence Embeddings Using Siamese BERT-Networks,” in Proc. EMNLP-IJCNLP, 2019.

[4] Chroma, “Chroma: the open-source embedding database,” github.com/chroma-core/chroma.

[5] Microsoft, “Windows Search overview,” Microsoft Learn documentation.

[6] Apple Inc., “Spotlight User Guide,” support.apple.com.

[7] voidtools, “Everything: locate files and folders by name instantly,” voidtools.com.

[8] D. K. Gifford, P. Jouvelot, M. A. Sheldon and J. W. O'Toole, “Semantic file systems,” in Proc. 13th ACM Symp. on Operating Systems Principles (SOSP), 1991.

[9] V. Karpukhin et al., “Dense Passage Retrieval for Open-Domain Question Answering,” in Proc. EMNLP, 2020.

[10] E. Tulving, “Episodic and semantic memory,” in Organization of Memory, E. Tulving and W. Donaldson, Eds. Academic Press, 1972.

[11] S. Dumais, E. Cutrell, J. J. Cadiz, G. Jancke, R. Sarin and D. C. Robbins, “Stuff I've Seen: A System for Personal Information Retrieval and Re-Use,” in Proc. ACM SIGIR, 2003.

[12] S. Robertson and H. Zaragoza, “The Probabilistic Relevance Framework: BM25 and Beyond,” Found. Trends Inf. Retr., vol. 3, no. 4, 2009.

[13] K. Ethayarajh, “How Contextual are Contextualized Word Representations? Comparing the Geometry of BERT, ELMo, and GPT-2 Embeddings,” in Proc. EMNLP-IJCNLP, 2019.

[14] J. Mu and P. Viswanath, “All-but-the-Top: Simple and Effective Postprocessing for Word Representations,” in Proc. ICLR, 2018.

[15] Y. A. Malkov and D. A. Yashunin, “Efficient and Robust Approximate Nearest Neighbor Search Using Hierarchical Navigable Small World Graphs,” IEEE Trans. Pattern Anal. Mach. Intell., vol. 42, no. 4, 2020.

[16] Z. Nussbaum, J. X. Morris, B. Duderstadt and A. Mulyar, “Nomic Embed: Training a Reproducible Long Context Text Embedder,” arXiv:2402.01613, 2024.

[17] E. B. Wilson, “Probable inference, the law of succession, and statistical inference,” J. Amer. Statist. Assoc., vol. 22, no. 158, 1927.