

A Subspace Decomposition Framework for Nonlinear Optimization: Global Convergence and Global Rate

S. Gratton

CERFACS and ENSEEIHT, France

May 19, 2014 — SIOPT, San Diego

`http://www.cerfacs.fr/~gratton`

- 1 Derivative-free optimization
- 2 A subspace decomposition framework
- 3 Global convergence and global rate
- 4 Applications to derivative-free optimization
- 5 Very preliminary numerical results
- 6 Concluding remarks

In this talk, to make things simple:

- we consider an unconstrained optimization problem

$$\min_{x \in \mathbb{R}^n} f(x);$$

In this talk, to make things simple:

- we consider an unconstrained optimization problem

$$\min_{x \in \mathbb{R}^n} f(x);$$

- we suppose that minimising f directly is out of reach.

In this talk, to make things simple:

- we consider an unconstrained optimization problem

$$\min_{x \in \mathbb{R}^n} f(x);$$

- we suppose that minimising f directly is out of reach.
- we aim for methods that are based on decomposition of the variable space **derivative-free methods, or large scale optimisation with derivatives.**

In this talk, to make things simple:

- we consider an unconstrained optimization problem

$$\min_{x \in \mathbb{R}^n} f(x);$$

- we suppose that minimising f directly is out of reach.
- we aim for methods that are based on decomposition of the variable space derivative-free methods, or large scale optimisation with derivatives.
- These methods are naturally adapted to massively parallel computers.
But: convergence, fault tolerance

Subspace techniques (I)

- [Domain decomposition for PDE's](#) based on Schwarz techniques. The full space is decomposed.
 - Conditions of convergence exist (fixed point theory using a generalized Cauchy-Schwarz inequality)
 - Crucial role of the problem-based decomposition (overlapping, coarse space,..)
- ASPIN from Cai and Keyes (for nonlinear equations)
- N. Gould, A. Sartenaer, and Ph. L. Toint, [On iterated-subspace minimization methods for nonlinear optimization](#). Rutherford Appleton Laboratory, 1994
- Y. Yuan, [Subspace techniques for nonlinear optimization](#). Some topics in industrial and applied mathematics 8 (2007): 206–218

Subspace techniques (II)

- Block Jacobi (linear/nonlinear equations), block coordinate descent
- M. C. Ferris, O. L. Mangasarian, [Parallel variable distribution](#). SIAM Journal on Optimization 4, no. 4 (1994): 815–832
- M. Fukushima, [Parallel variable transformation in unconstrained optimization](#). SIAM Journal on Optimization 8, no. 3 (1998): 658–672
- S. Boyd, L. Xiao, A. Mutapcic, and J. Mattingley, [Notes on decomposition methods](#). Notes for EE364B, Stanford University, 2007
- C. Audet, J. E. Dennis Jr, and S. Le Digabel, [Parallel space decomposition of the mesh adaptive direct search algorithm](#). SIAM Journal on Optimization 19, no. 3 (2008): 1150–1170

A subspace decomposition framework

- Suppose that the current iterate is x_k .

A subspace decomposition framework

- Suppose that the current iterate is x_k .
- Decomposition:

A subspace decomposition framework

- Suppose that the current iterate is x_k .
- Decomposition:
 - select spaces $\mathcal{S}_k^{(1)}, \mathcal{S}_k^{(2)}, \dots, \mathcal{S}_k^{(m_k)}$ such that

$$\mathbb{R}^n = \sum_{i=0}^{m_k} \mathcal{S}_k^{(i)};$$

A subspace decomposition framework

- Suppose that the current iterate is x_k .
- Decomposition:
 - select spaces $\mathcal{S}_k^{(1)}, \mathcal{S}_k^{(2)}, \dots, \mathcal{S}_k^{(m_k)}$ such that

$$\mathbb{R}^n = \sum_{i=0}^{m_k} \mathcal{S}_k^{(i)};$$

or use (at least one) gradient related subspace(s) in a truncated sum

- minimize $f(x_k + d)$ with respect to d on $\mathcal{S}_k^{(i)}$, and obtain $d_k^{(i)}$ ($i = 1, 2, \dots, m_k$).

A subspace decomposition framework

- Suppose that the current iterate is x_k .
- **Decomposition:**
 - select spaces $\mathcal{S}_k^{(1)}, \mathcal{S}_k^{(2)}, \dots, \mathcal{S}_k^{(m_k)}$ such that

$$\mathbb{R}^n = \sum_{i=0}^{m_k} \mathcal{S}_k^{(i)};$$

or use (at least one) gradient related subspace(s) in a truncated sum

- minimize $f(x_k + d)$ with respect to d on $\mathcal{S}_k^{(i)}$, and obtain $d_k^{(i)}$ ($i = 1, 2, \dots, m_k$).
- How to compose the step d_k ?

A subspace decomposition framework

- Suppose that the current iterate is x_k .
- **Decomposition:**
 - select spaces $\mathcal{S}_k^{(1)}, \mathcal{S}_k^{(2)}, \dots, \mathcal{S}_k^{(m_k)}$ such that

$$\mathbb{R}^n = \sum_{i=0}^{m_k} \mathcal{S}_k^{(i)};$$

or use (at least one) gradient related subspace(s) in a truncated sum

- minimize $f(x_k + d)$ with respect to d on $\mathcal{S}_k^{(i)}$, and obtain $d_k^{(i)}$ ($i = 1, 2, \dots, m_k$).
- How to compose the step d_k ?
 - Set

$$d_k = \sum_{i=0}^{m_k} d_k^{(i)} ?$$

A subspace decomposition framework

- Suppose that the current iterate is x_k .
- **Decomposition:**
 - select spaces $\mathcal{S}_k^{(1)}, \mathcal{S}_k^{(2)}, \dots, \mathcal{S}_k^{(m_k)}$ such that

$$\mathbb{R}^n = \sum_{i=0}^{m_k} \mathcal{S}_k^{(i)};$$

- minimize $f(x_k + d)$ with respect to d on $\mathcal{S}_k^{(i)}$, and obtain $d_k^{(i)}$ ($i = 1, 2, \dots, m_k$).
- **Composition** (M. Fukushima, 1998)

A subspace decomposition framework

- Suppose that the current iterate is x_k .
- **Decomposition:**
 - select spaces $\mathcal{S}_k^{(1)}, \mathcal{S}_k^{(2)}, \dots, \mathcal{S}_k^{(m_k)}$ such that

$$\mathbb{R}^n = \sum_{i=0}^{m_k} \mathcal{S}_k^{(i)};$$

- minimize $f(x_k + d)$ with respect to d on $\mathcal{S}_k^{(i)}$, and obtain $d_k^{(i)}$ ($i = 1, 2, \dots, m_k$).
- **Composition** (M. Fukushima, 1998)
 - set

$$\mathcal{S}_k = \text{span} \left\{ d_k^{(1)}, d_k^{(2)}, \dots, d_k^{(m_k)} \right\};$$

A subspace decomposition framework

- Suppose that the current iterate is x_k .

- **Decomposition:**

- select spaces $\mathcal{S}_k^{(1)}, \mathcal{S}_k^{(2)}, \dots, \mathcal{S}_k^{(m_k)}$ such that

$$\mathbb{R}^n = \sum_{i=0}^{m_k} \mathcal{S}_k^{(i)};$$

- minimize $f(x_k + d)$ with respect to d on $\mathcal{S}_k^{(i)}$, and obtain $d_k^{(i)}$ ($i = 1, 2, \dots, m_k$).

- **Composition** (M. Fukushima, 1998)

- set

$$\mathcal{S}_k = \text{span} \left\{ d_k^{(1)}, d_k^{(2)}, \dots, d_k^{(m_k)} \right\};$$

- minimize $f(x_k + d)$ with respect to d on \mathcal{S}_k , and obtain d_k .

Globalization technique

Let $h_k^{(i)}$ be a model of f that “satisfies” $P_k^{(i)} \nabla h_k^{(i)}(x_k) = P_k^{(i)} \nabla f(x_k)$.

Globalization technique

Let $h_k^{(i)}$ be a model of f that “satisfies” $P_k^{(i)} \nabla h_k^{(i)}(x_k) = P_k^{(i)} \nabla f(x_k)$.

- Levenberg-Marquardt (natural for least-squares, nonlinear filtering):

$$\min_{d \in \mathcal{S}_k^{(i)}} h_k^{(i)}(x_k + d) + \frac{1}{2} \sigma_k \|d\|^2$$

Let $h_k^{(i)}$ be a model of f that “satisfies” $P_k^{(i)} \nabla h_k^{(i)}(x_k) = P_k^{(i)} \nabla f(x_k)$.

- Levenberg-Marquardt (natural for least-squares, nonlinear filtering):

$$\min_{d \in \mathcal{S}_k^{(i)}} h_k^{(i)}(x_k + d) + \frac{1}{2} \sigma_k \|d\|^2$$

- Trust-region:

$$\begin{aligned} \min \quad & h_k^{(i)}(x_k + d) \\ \text{s.t.} \quad & d \in \mathcal{S}_k^{(i)} \\ & \|d\| \leq \Delta_k \end{aligned}$$

Let $h_k^{(i)}$ be a model of f that “satisfies” $P_k^{(i)} \nabla h_k^{(i)}(x_k) = P_k^{(i)} \nabla f(x_k)$.

- Levenberg-Marquardt (natural for least-squares, nonlinear filtering):

$$\min_{d \in \mathcal{S}_k^{(i)}} h_k^{(i)}(x_k + d) + \frac{1}{2} \sigma_k \|d\|^2$$

- Trust-region:

$$\begin{aligned} \min \quad & h_k^{(i)}(x_k + d) \\ \text{s.t.} \quad & d \in \mathcal{S}_k^{(i)} \\ & \|d\| \leq \Delta_k \end{aligned}$$

- How to update Δ_k or σ_k ?

Globalization technique

Let $h_k^{(i)}$ be a model of f that “satisfies” $P_k^{(i)} \nabla h_k^{(i)}(x_k) = P_k^{(i)} \nabla f(x_k)$.

- Levenberg-Marquardt (natural for least-squares, nonlinear filtering):

$$\min_{d \in \mathcal{S}_k^{(i)}} h_k^{(i)}(x_k + d) + \frac{1}{2} \sigma_k \|d\|^2$$

- Trust-region:

$$\begin{aligned} \min \quad & h_k^{(i)}(x_k + d) \\ \text{s.t.} \quad & d \in \mathcal{S}_k^{(i)} \\ & \|d\| \leq \Delta_k \end{aligned}$$

- How to update Δ_k or σ_k ?

$$\rho_k = \frac{f(x_k) - f(x_k + d_k)}{\sum_{i=1}^{m_k} \left[f(x_k) - h_k^{(i)}(x_k + d_k^{(i)}) \right]}$$

Globalization technique

Let $h_k^{(i)}$ be a model of f that “satisfies” $P_k^{(i)} \nabla h_k^{(i)}(x_k) = P_k^{(i)} \nabla f(x_k)$.

- Levenberg-Marquardt:

$$\min_{d \in \mathcal{S}_k^{(i)}} h_k^{(i)}(x_k + d) + \frac{1}{2} \sigma_k \|d\|^2$$

- Trust-region:

$$\begin{aligned} \min \quad & h_k^{(i)}(x_k + d) \\ \text{s.t.} \quad & d \in \mathcal{S}_k^{(i)} \\ & \|d\| \leq \Delta_k \end{aligned}$$

- How to update Δ_k or σ_k ?

$$\rho_k = \frac{f(x_k) - f(x_k + d_k)}{\sum_{i=1}^{m_k} \left[f(x_k) - h_k^{(i)}(x_k + d_k^{(i)}) \right]}$$

Levenberg-Marquardt framework

Algorithm (Levenberg-Marquardt framework)

Levenberg-Marquardt framework

Algorithm (Levenberg-Marquardt framework)

Step 1. Select a constant $\eta \in [0, 1)$, pick a starting point $x_0 \in \mathbb{R}^n$, choose a positive number σ_0 , and select constants $\eta_1, \eta_2, \eta_3, \theta$, and γ so that

$$0 \leq \eta_1 \leq \eta_2 \leq \eta_3, \text{ and } 0 < \theta < 1 < \gamma. \quad (1)$$

Set $k = 0$.

Algorithm (Levenberg-Marquardt framework)

Step 1. Select a constant $\eta \in [0, 1)$, pick a starting point $x_0 \in \mathbb{R}^n$, choose a positive number σ_0 , and select constants $\eta_1, \eta_2, \eta_3, \theta$, and γ so that

$$0 \leq \eta_1 \leq \eta_2 \leq \eta_3, \text{ and } 0 < \theta < 1 < \gamma. \quad (1)$$

Set $k = 0$.

Step 2. Choose nonzero subspaces $\mathcal{S}_k^{(i)}$ ($i = 1, 2, \dots, m_k$) of \mathbb{R}^n so that

$$\sum_{i=1}^{m_k} \mathcal{S}_k^{(i)} = \mathbb{R}^n.$$

Levenberg-Marquardt framework

Algorithm (Levenberg-Marquardt framework)

Step 1. Select a constant $\eta \in [0, 1)$, pick a starting point $x_0 \in \mathbb{R}^n$, choose a positive number σ_0 , and select constants $\eta_1, \eta_2, \eta_3, \theta$, and γ so that

$$0 \leq \eta_1 \leq \eta_2 \leq \eta_3, \text{ and } 0 < \theta < 1 < \gamma. \quad (1)$$

Set $k = 0$.

Step 2. Choose nonzero subspaces $\mathcal{S}_k^{(i)}$ ($i = 1, 2, \dots, m_k$) of \mathbb{R}^n so that

$$\sum_{i=1}^{m_k} \mathcal{S}_k^{(i)} = \mathbb{R}^n.$$

Step 3. For $i = 1, 2, \dots, m_k$, **approximately** solve the following problem to get $d_k^{(i)}$:

$$\min_{d \in \mathcal{S}_k^{(i)}} h_k^{(i)}(x_k + d) + \frac{1}{2} \sigma_k \|d\|^2.$$

Algorithm (Levenberg-Marquardt framework cont.)

Step 4. Determine $d_k \in \text{span}\{d_k^{(1)}, d_k^{(2)}, \dots, d_k^{(m_k)}\}$ so that

$$f(x_k + d_k) \leq f(x_k + \sum_{i=1}^{m_k} d_k^{(i)}).$$

Algorithm (Levenberg-Marquardt framework cont.)

Step 4. Determine $d_k \in \text{span}\{d_k^{(1)}, d_k^{(2)}, \dots, d_k^{(m_k)}\}$ so that

$$f(x_k + d_k) \leq f(x_k + \sum_{i=1}^{m_k} d_k^{(i)}).$$

Step 5. Let

$$\rho_k = \frac{f(x_k) - f(x_k + d_k)}{\sum_{i=1}^{m_k} \left[f(x_k) - h_k^{(i)}(x_k + d_k^{(i)}) \right]},$$

and set

$$x_{k+1} = \begin{cases} x_k + d_k & \text{if } \rho_k \geq \eta_1 \\ x_k & \text{if } \rho_k < \eta_1. \end{cases}$$

Algorithm (Levenberg-Marquardt framework cont.)

Step 6. Set

$$\sigma_{k+1} = \begin{cases} \theta \sigma_k & \text{if } \rho_k \geq \eta_3 \\ \sigma_k & \text{if } \eta_2 \leq \rho_k < \eta_3 \\ \gamma \sigma_k & \text{if } \rho_k < \eta_2. \end{cases}$$

Increment k by 1, and go to **Step 2**.

Trust-region framework

Algorithm (Trust-region framework)

Algorithm (Trust-region framework)

Step 1. Select a constant $\eta \in [0, 1)$, pick a starting point $x_0 \in \mathbb{R}^n$, choose $\Delta_0 > 0$, and select constants $\eta_1, \eta_2, \eta_3, \theta$, and γ so that

$$0 \leq \eta_1 \leq \eta_2 \leq \eta_3, \text{ and } 0 < \theta < 1 < \gamma. \quad (2)$$

Set $k = 0$.

Algorithm (Trust-region framework)

Step 1. Select a constant $\eta \in [0, 1)$, pick a starting point $x_0 \in \mathbb{R}^n$, choose $\Delta_0 > 0$, and select constants $\eta_1, \eta_2, \eta_3, \theta$, and γ so that

$$0 \leq \eta_1 \leq \eta_2 \leq \eta_3, \text{ and } 0 < \theta < 1 < \gamma. \quad (2)$$

Set $k = 0$.

Step 2. Choose subspaces $\mathcal{S}_k^{(i)}$ ($i = 1, 2, \dots, m_k$) of \mathbb{R}^n so that

$$\sum_{i=1}^{m_k} \mathcal{S}_k^{(i)} = \mathbb{R}^n.$$

Trust-region framework

Algorithm (Trust-region framework)

Step 1. Select a constant $\eta \in [0, 1)$, pick a starting point $x_0 \in \mathbb{R}^n$, choose $\Delta_0 > 0$, and select constants $\eta_1, \eta_2, \eta_3, \theta$, and γ so that

$$0 \leq \eta_1 \leq \eta_2 \leq \eta_3, \text{ and } 0 < \theta < 1 < \gamma. \quad (2)$$

Set $k = 0$.

Step 2. Choose subspaces $\mathcal{S}_k^{(i)}$ ($i = 1, 2, \dots, m_k$) of \mathbb{R}^n so that

$$\sum_{i=1}^{m_k} \mathcal{S}_k^{(i)} = \mathbb{R}^n.$$

Step 3. For $i = 1, 2, \dots, m_k$, **approximately** solve the following problem to obtain $d_k^{(i)}$:

$$\begin{aligned} \min_{d \in \mathcal{S}_k^{(i)}} \quad & h_k^{(i)}(x_k + d) \\ \text{s.t.} \quad & \|d\| \leq \Delta_k. \end{aligned}$$

Algorithm (Trust-region framework cont.)

Step 4. Determine $d_k \in \text{span}\{d_k^{(1)}, d_k^{(2)}, \dots, d_k^{(m_k)}\}$ so that

$$f(x_k + d_k) \leq f(x_k + \sum_{i=1}^{m_k} d_k^{(i)}).$$

Algorithm (Trust-region framework cont.)

Step 4. Determine $d_k \in \text{span}\{d_k^{(1)}, d_k^{(2)}, \dots, d_k^{(m_k)}\}$ so that

$$f(x_k + d_k) \leq f(x_k + \sum_{i=1}^{m_k} d_k^{(i)}).$$

Step 5. Let

$$\rho_k = \frac{f(x_k) - f(x_k + d_k)}{\sum_{i=1}^{m_k} [f(x_k) - h_k^{(i)}(x_k + d_k^{(i)})]},$$

and set

$$x_{k+1} = \begin{cases} x_k + d_k & \text{if } \rho_k \geq \eta_1 \\ x_k & \text{if } \rho_k < \eta_1. \end{cases}$$

Algorithm (Trust-region framework cont.)

Step 6. Set

$$\Delta_{k+1} = \begin{cases} \gamma\Delta_k & \text{if } \rho_k \geq \eta_3 \\ \Delta_k & \text{if } \eta_2 \leq \rho_k < \eta_3 \\ \theta\Delta_k & \text{if } \rho_k < \eta_2. \end{cases}$$

Increment k by 1, and go to **Step 2**.

Assumptions

Assumption

Assumption

- ① *The function f is bounded from below and twice continuously differentiable, and $\nabla^2 f$ is bounded on \mathbb{R}^n .*

Assumption

- 1 *The function f is bounded from below and twice continuously differentiable, and $\nabla^2 f$ is bounded on \mathbb{R}^n .*
- 2 *The sequence $\{m_k\}$ is bounded.*

Assumption

- 1 *The function f is bounded from below and twice continuously differentiable, and $\nabla^2 f$ is bounded on \mathbb{R}^n .*
- 2 *The sequence $\{m_k\}$ is bounded.*
- 3 *The smallest eigenvalues of $\sum_{i=1}^{m_k} P_k^{(i)}$ are bounded away from zero, where $P_k^{(i)}$ is the orthogonal projection matrix from \mathbb{R}^n onto $S_k^{(i)}$.*

Assumption

- ① *The function f is bounded from below and twice continuously differentiable, and $\nabla^2 f$ is bounded on \mathbb{R}^n .*
- ② *The sequence $\{m_k\}$ is bounded.*
- ③ *The smallest eigenvalues of $\sum_{i=1}^{m_k} P_k^{(i)}$ are bounded away from zero, where $P_k^{(i)}$ is the orthogonal projection matrix from \mathbb{R}^n onto $S_k^{(i)}$.*
- ④ *$\{\nabla^2 h_k^{(i)}\}$ is uniformly bounded on \mathbb{R}^n .*

Assumption

- 1 The function f is bounded from below and twice continuously differentiable, and $\nabla^2 f$ is bounded on \mathbb{R}^n .
- 2 The sequence $\{m_k\}$ is bounded.
- 3 The smallest eigenvalues of $\sum_{i=1}^{m_k} P_k^{(i)}$ are bounded away from zero, where $P_k^{(i)}$ is the orthogonal projection matrix from \mathbb{R}^n onto $\mathcal{S}_k^{(i)}$.
- 4 $\{\nabla^2 h_k^{(i)}\}$ is uniformly bounded on \mathbb{R}^n .
- 5 On subspace $\mathcal{S}_k^{(i)}$, $d_k^{(i)}$ achieves a decrease proportional to the Cauchy decrease.

Theorem

Suppose that the assumptions stated before hold, then the iterates $\{x_k\}$ generated by the Levenberg-Marquardt framework satisfy

$$\liminf_{k \rightarrow \infty} \|\nabla f(x_k)\| = 0.$$

Sketch of the proof:

- The k -th iteration is successful if σ_k is large enough.
- $\{\sigma_k\}$ is bounded from above.
- Contradiction if $\liminf_{k \rightarrow \infty} \|\nabla f(x_k)\| > 0$.

Theorem

Suppose that the assumptions stated before hold, and $\eta_1 > 0$, then the iterates $\{x_k\}$ generated by either of the Levenberg-Marquardt framework satisfy

$$\lim_{k \rightarrow \infty} \|\nabla f(x_k)\| = 0.$$

Sketch of the proof:

- $\{\sigma_k\}$ is bounded from above.
- $\{f(x_k)\}$ is decreasing and bounded from below.
- The convergence follows from the decreases obtained when the iterates move.

Theorem

Suppose that the assumptions stated before hold, then the iterates $\{x_k\}$ generated by the Levenberg-Marquardt framework satisfy

$$\min_{0 \leq \ell \leq k} \|\nabla f(x_\ell)\| \leq C \sqrt{\frac{1}{k}}.$$

Sketch of the proof:

- Because of the boundedness of $\{\sigma_k\}$, the number of unsuccessful iterations is linearly bounded by that of the successful ones.
- Because of the boundedness of $\{f(x_k)\}$ and the decreases achieved on the successful iterations, the number of successful iterations is bounded by $\mathcal{O}(\epsilon^{-2})$.

Similar results can be derived for the trust-region framework.

Properties of the framework

Properties of the framework

- *It can be applied to optimization with or without derivatives.*

Properties of the framework

- *It can be applied to optimization with or without derivatives.*
- *It is naturally parallel.*

Properties of the framework

- *It can be applied to optimization with or without derivatives.*
- *It is naturally parallel.*
- *It is naturally multilevel.*

Applications to derivative-free optimization

Properties of the framework

- *It can be applied to optimization with or without derivatives.*
- *It is naturally parallel.*
- *It is naturally multilevel.*



Our goal

Parallel and *multilevel* algorithms *without using derivatives* and capable of solving relatively *large* problems.

Very preliminary numerical results

- Use the Levenberg-Marquardt framework
- Subproblem solver: NEWUOA
- Number of subspaces: $\sqrt{n/2}$
- Benchmark: NEWUOA (NPT=2N+1; RHOEND=1.0E-6)
- Very preliminary: not parallel, not multilevel, not large-scale . . .
- Dimension of test problems: 25, 30, 35, 40
- Denote our code as SSD

Table: Numerical results of VARDIM

n	25	30	35	40	
$\#f$	8343	8926	12689	17741	NEWUOA
	3592	6222	7507	16653	SSD
f_{final}	1.61E-11	4.08E-11	4.93E-11	1.76E-10	NEWUOA
	9.74E-11	6.85E-10	5.74E-11	7.89E-13	SSD

$$f(x) = \sum_{i=1}^n (x_i - 1)^2 + \left[\sum_{i=1}^n i(x_i - 1) \right]^2 + \left[\sum_{i=1}^n i(x_i - 1) \right]^4$$

Table: Numerical results of PENALTY1

n	25	30	35	40	
$\#f$	9532	10947	14427	13577	NEWUOA
	2089	2784	2348	2812	SSD
f_{final}	2.03E-04	2.48E-04	2.93E-04	3.39E-04	NEWUOA
	2.04E-04	2.50E-04	2.95E-04	3.41E-04	SSD

$$f(x) = 10^{-15} \sum_{i=1}^n (x_i - 1)^2 + \left(\frac{1}{4} - \sum_{i=1}^n x_i^2 \right)^2$$

Table: Numerical results of SBRYBND

n	25	30	35	40	
$\#f$	968	576	2052	2363	NEWUOA
	27889	53103	90304	206608	SSD
f_{final}	235	326	342	395	NEWUOA
	3.08	3.08	3.08	3.08	SSD
	134	284	233	229	

$$f(x) = \sum_{i=1}^n \left[(2 + 5p_i^2 x_i^2) p_i x_i + 1 - \sum_{j \in J_i} p_j x_j (1 + p_j x_j) \right]^2,$$

where $J_i = \{j \mid j \neq i, \max\{1, i-5\} \leq j \leq \min\{n, j+1\}\}$, and $p_i = \exp\left(6 \frac{i-1}{n-1}\right)$.

Table: Numerical results of CHROSEN

n	25	30	35	40	
$\#f$	1123	1445	1717	1859	NEWUOA
	96040	103296	127726	142272	SSD
f_{final}	8.94E-12	1.07E-11	1.13E-11	3.14E-11	NEWUOA
	2.95E-10	5.49E-10	7.26E-10	8.09E-10	SSD

$$f(x) = \sum_{i=1}^{n-1} \left[4(x_i - x_{i+1}^2)^2 + (1 - x_{i+1})^2 \right]$$

Concluding remarks

- A subspace decomposition framework (two versions) with global convergence and known convergence rate
- Possible to develop parallel and multilevel methods with or without derivative


- A subspace decomposition framework (two versions) with global convergence and known convergence rate
- Possible to develop parallel and multilevel methods with or without derivative
- “Clever” way of choosing subspaces . . .

- A subspace decomposition framework (two versions) with global convergence and known convergence rate
- Possible to develop parallel and multilevel methods with or without derivative
- “Clever” way of choosing subspaces ...
 - not try to cover the whole space, but ...


- A subspace decomposition framework (two versions) with global convergence and known convergence rate
- Possible to develop parallel and multilevel methods with or without derivative
- “Clever” way of choosing subspaces ...
 - not try to cover the whole space, but ...
 - choose subspaces randomly

- A subspace decomposition framework (two versions) with global convergence and known convergence rate
- Possible to develop parallel and multilevel methods with or without derivative
- “Clever” way of choosing subspaces ...
 - not try to cover the whole space, but ...
 - choose subspaces randomly
 - take into account failures in the step computation

Fault tolerance



(a) Average of function values.



(b) Average of absolute error of iterates.

Levenberg-Marquart with wrong gradient at a given iteration frequency on Rosebrock

Thanks!

Thanks!