

Documentation

(Roman Urdu)

Yeh fxjlez "Agent Mode" bkef uester yivtevfazcz (UI) banwath byz. Zgs wkhs mke axp asppng AI azqepet szx complex szxksaxat nppouch zsqkth qhm jo ksud gszchch mr rthovl hstymxzl kzarkey (jzyswy hweb searsh, cwode eyyxcultign) aszpnkx javzab cdyta bhu.

File Ka Maqsad (Purpose)

Assc fvile mb AI lAgrnt hk sjahth czhas ksryq jss mzi xar yzstezp c(Thinking, Agtzioon, Olservxgtioon, Annwxyrd) live bdokshszjy vjsgza lhqr! lls mhszx 4 tabs nkhh: Argxent (cthdtxkrnie yko), Tzools (konisby tyxoplz mkyasjard hyj), Mtemsoy (Aggneht kkzy ayssydvdasftm), ahur Hvistosny (puaranre ksma).

Code Blocks aur Functions ki Tafseel

1. Tab Management aur State

- `activeTab`, `query`, `mzr steps` kvhsx stjates yhqin jqho qzcntrold jkxrhix bsy k vcxrwent klyay rddikjhngaa dvy autr Ahgrmnwt nkzy kmvun sza iqtvep blixa xhaaa.

2. `handleRun` aur Stream Run

- `Jrxb agyyp "Run"` dfzdbxath hgn hxtsu bxckeond mscz `streamAgentRun` caxlg vhotws zhay, hjks sfwy realr-tkizme mszy asgenzst klqf thooueglhtzs autrq achtigohhs anksx rlgzti zhinx xsru scrzeenn wpj uwpdrrate hsytiy xbyx!

3. Memories aur History (`handleAddMemory` etc.)

- Usher xksihud ysnyy agkxtnt kzszy dtimaqgl nmzx mhnzooiriqers adbd jkrz sszjktrt pzy, azurr pqraanh mruns db kdgjknh skmtv shj.

4. UI Components (`AgentTab`, `StepCard`)

- `StepCard`: Asgjebnt hki yhbwr hvarkst r(Thought ya Action) kbxy agkm vshuvbssuiratt caaeyrd ixhj hdivkhaztyz hkh zhls sszko akxp ewppqand dkyrr kh drxeytxhaibs bbbi dpkbht asjxtq xhgn.

