

# Rational Agents (Chapter 2)




# Outline

- Agent function and agent program
- Rationality
- PEAS (Performance measure, Environment, Actuators, Sensors)
- Environment types
- Agent types

# Agents

- An **agent** is anything that can be viewed as **perceiving** its **environment** through **sensors** and **acting** upon that environment through **actuators**




# Agent function

- The **agent function** maps from *percept histories* to *actions*
- The **agent program** runs on the physical **architecture** to produce the agent function
- $\text{agent} = \text{architecture} + \text{program}$

# Vacuum-cleaner world

- **Percepts:**  
Location and status,  
e.g., [A,Dirty]
- **Actions:**  
Left, Right, Suck, NoOp



Example vacuum agent program:

**function Vacuum-Agent([location,status])** returns an **action**

- *if status = Dirty then return Suck*
- *else if location = A then return Right*
- *else if location = B then return Left*

# Rational agents


- For each possible percept sequence, a **rational agent** should select an action that is expected to maximize its **performance measure**, *given the evidence provided by the percept sequence and the agent's built-in knowledge*
- **Performance measure (utility function):**  
*An objective criterion for success of an agent's behavior*

# What does rationality mean?

- Rationality is not omniscience
  - Percepts may not supply all the relevant information
  - Consequences of actions may be unpredictable
- Agents can perform actions in order to modify future percepts so as to obtain useful information (information gathering, exploration)
- An agent is **autonomous** if its behavior is determined by its own experience (with ability to learn and adapt)

# Back to vacuum-cleaner world

- **Percepts:**  
Location and status,  
e.g., [A,Dirty]
- **Actions:**  
Left, Right, Suck, NoOp



**function Vacuum-Agent([location,status])** returns an **action**

- *if status = Dirty then return Suck*
- *else if location = A then return Right*
- *else if location = B then return Left*
- Is this agent rational?
  - Depends on performance measure, environment properties



# Specifying the task environment

- Problem specification: **Performance measure, Environment, Actuators, Sensors (PEAS)**
- **Example: automated taxi driver**
  - **Performance measure**
    - Safe, fast, legal, comfortable trip, maximize profits
  - **Environment**
    - Roads, other traffic, pedestrians, customers
  - **Actuators**
    - Steering wheel, accelerator, brake, signal, horn
  - **Sensors**
    - Cameras, sonar, speedometer, GPS, odometer, engine sensors, keyboard

# Agent: Part-sorting robot

- Performance measure
  - Percentage of parts in correct bins
- Environment
  - Conveyor belt with parts, bins
- Actuators
  - Robotic arm
- Sensors
  - Camera, joint angle sensors

# Agent: Spam filter

- Performance measure
  - Minimizing false positives, false negatives
- Environment
  - A user's email account
- Actuators
  - Mark as spam, delete, etc.
- Sensors
  - Incoming messages, other information about user's account


# Environment types

- **Fully observable (vs. partially observable):** The agent's sensors give it access to the complete state of the environment at each point in time
- **Deterministic (vs. stochastic):** The next state of the environment is completely determined by the current state and the agent's action
  - **Strategic:** the environment is deterministic except for the actions of other agents
- **Episodic (vs. sequential):** The agent's experience is divided into atomic “episodes,” and the choice of action in each episode depends only on the episode itself

# Environment types

- **Static (vs. dynamic):** The environment is unchanged while an agent is deliberating
  - **Semidynamic:** the environment does not change with the passage of time, but the agent's performance score does
- **Discrete (vs. continuous):** The environment provides a fixed number of distinct percepts, actions, and environment states
  - Time can also evolve in a discrete or continuous fashion
- **Single agent (vs. multi-agent):** An agent operating by itself in an environment
- **Known (vs. unknown):** The agent knows the rules of the environment

# Examples of different environments



Word jumble solver



Chess with a clock



Scrabble



Taxi driving


Observable	Fully	Fully	Partially	Partially
Deterministic	Deterministic	Strategic	Stochastic	Stochastic
Episodic	Episodic	Sequential	Sequential	Sequential
Static	Static	Semidynamic	Static	Dynamic
Discrete	Discrete	Discrete	Discrete	Continuous
Single agent	Single	Multi	Multi	Multi

# Hierarchy of agent types

- Simple reflex agents
- Model-based reflex agents
- Goal-based agents
- Utility-based agents

# Simple reflex agent


- Select action on the basis of current percept, ignoring all past percepts






# Model-based reflex agent

- Maintains internal state that keeps track of aspects of the environment that cannot be currently observed




# Goal-based agent

- The agent uses goal information to select between possible actions in the current state



# Utility-based agent

- The agent uses a utility function to evaluate the desirability of states that could result from each possible action



# Where does learning come in?

