

## Problem Solving Agents & Problem Formulation

AIMA 2.3, 3.1-2

CIS 521 - 2015



## Outline for today's lecture

- **Defining Task Environments**
- Environment types
- Formulating Search Problems

CIS 521 - 2015



## Task environments

- To design a rational agent we need to specify a **task environment**
  - a problem specification for which the agent is a solution
- **PEAS**: to specify a task environment
  - Performance measure
  - Environment
  - Actuators
  - Sensors



CIS 521 - 2015



## PEAS: Specifying an automated taxi driver

**Performance measure:**

- ?

**Environment:**

- ?

**Actuators:**

- ?

**Sensors:**

- ?



CIS 521 - 2015



## PEAS: Specifying an automated taxi driver

**Performance measure:**

- safe, fast, legal, comfortable, maximize profits

**Environment:**

- roads, other traffic, pedestrians, customers

**Actuators:**

- steering, accelerator, brake, signal, horn

**Sensors:**

- cameras, sonar, speedometer, GPS



CIS 521 - 2015



## PEAS: Medical diagnosis system

- **Performance measure:** Healthy patient, minimize costs, lawsuits

- **Environment:** Patient, hospital, staff

- **Actuators:** Screen display (form including: questions, tests, diagnoses, treatments, referrals)

- **Sensors:** Keyboard (entry of symptoms, findings, patient's answers)

CIS 521 - 2015



## Outline for today's lecture

- Defining Task Environments
- **Environment types**
- Formulating Search Problems

CIS 521 - 2015



8

## Environment types: Definitions I

- **Fully observable** (vs. partially observable): An agent's sensors give it access to the complete state of the environment at each point in time.
- **Deterministic** (vs. stochastic): The next state of the environment is completely determined by the current state and the action executed by the agent.
  - If the environment is deterministic except for the actions of other agents, then the environment is **strategic**.
- **Episodic** (vs. sequential): The agent's experience is divided into atomic "episodes" during which the agent perceives and then performs a single action, and the choice of action in each episode depends only on the episode itself.

CIS 521 - 2015



9

## Environment types: Definitions II

- **Static** (vs. dynamic): The environment is unchanged while an agent is deliberating.
  - The environment is **semidynamic** if the environment itself does not change with the passage of time but the agent's performance score does.
- **Discrete** (vs. continuous): A limited number of distinct, clearly defined percepts and actions.
- **Single agent** (vs. multiagent): An agent operating by itself in an environment.

(See examples in AIMA,  
however I don't agree with some of the judgments)

CIS 521 - 2015



10

## Environment Restrictions for Now

- We will assume environment is
  - **Static**
  - **Fully Observable**
  - **Deterministic**
  - **Discrete**

CIS 521 - 2015



11

## The rational agent designer's goal

- Goal of AI practitioner who designs rational agents: given a **PEAS** task environment,
  1. Construct agent function  $f$  that maximizes (the expected value of) the performance measure,
  2. Design an agent program that implements  $f$  on a particular architecture

CIS 521 - 2015



12

## Outline for today's lecture

- Defining Task Environments
- Environment types
- **Formulating Search Problems (AIMA, 3.1-3.2)**

CIS 521 - 2015




13

## Example search problem: 8-puzzle

### • Formulate **goal**

- Pieces to end up in order as shown...



### • Formulate **search problem**

- States:** configurations of the puzzle (9! configurations)
- Actions:** Move one of the movable pieces ( $\leq 4$  possible)
- Performance measure:** minimize total moves


### • Find **solution**

- Sequence of pieces moved: 3,1,6,3,1,...

CIS 521 - 2015



## Example search problem: holiday in Romania

CIS 331 - Intro to AI  
CIS 521 - 2015

## Holiday in Romania II

### • On holiday in Romania; currently in Arad

- Flight leaves tomorrow from Bucharest

### • Formulate **goal**

- Be in Bucharest

### • Formulate **search problem**

- States:** various cities
- Actions:** drive between cities
- Performance measure:** minimize distance

### • Find **solution**

- Sequence of cities; e.g. Arad, Sibiu, Fagaras, Bucharest, ...

CIS 521 - 2015



## More formally, a problem is defined by:

1. A set of **states**  $S$
2. An **initial state**  $s_i \in S$
3. A **set of actions**  $A$ 
  - $\forall s, \text{Actions}(s)$  = the set of actions that can be executed in  $s$ , that are **applicable** in  $s$ .
4. **Transition Model:**  $\forall s \forall a \in \text{Actions}(s), \text{Result}(s, a) \rightarrow s_r$ 
  - $s_r$  is called a **successor** of  $s$
  - $\{s_i\} \cup \text{Successors}(s_i)^* = \text{state space}$
5. **Goal test**  $\text{Goal}(s)$ 
  - Can be implicit, e.g. **checkmate**( $x$ )
  - $s$  is a goal state if  $\text{Goal}(s)$  is true
6. **Path cost** (additive)
  - e.g. sum of distances, number of actions executed, ...
  - $c(x, a, y)$  is the step cost, assumed  $\geq 0$ 
    - (where action  $a$  goes from state  $x$  to state  $y$ )

CIS 521 - 2015



## Solution

A **solution** is a sequence of actions from the **initial state** to a **goal state**.

**Optimal Solution:**

A solution is **optimal** if no solution has a lower path cost.

CIS 521 - 2015



## Hard subtask: Selecting a state space

- **Real world is absurdly complex**
  - State space must be **abstracted** for problem solving
- (abstract) **State** = set (equivalence class) of real world states
- (abstract) **Action** = complex combination of real world actions
  - e.g.  $\text{Arad} \rightarrow \text{Zerind}$  represents a complex set of possible routes, detours, rest stops, etc
  - The abstraction is valid if the path between two states is reflected in the real world
- (abstract) **Solution** = set of abstract paths that are solutions in the abstract space
- Each abstract action should be "easier" than the real problem

CIS 521 - Intro to AI



## Formulating a Search Problem


Decide:

- Which properties matter & how to represent
  - Initial State, Goal State, Possible Intermediate States
- Which actions are possible & how to represent
  - Operator Set: Actions and Transition Model
- Which action is next
  - Path Cost Function

CIS 521 - 2015



## Example: 8-puzzle




- States??
- Initial state??
- Actions??
- Transition Model??
- Goal test??
- Path cost??

CIS 521 - 2015



## Example: 8-puzzle



- States?? List of 9 locations- e.g., [7,2,4,5,-,6,8,3,1]
- Initial state?? [7,2,4,5,-,6,8,3,1]
- Actions?? {Left, Right, Up, Down}
- Transition Model?? ...
- Goal test?? Check if goal configuration is reached
- Path cost?? Number of actions to reach goal

CIS 521 - 2015



## Example: Missionaries & Cannibals

Three missionaries and three cannibals come to a river. A rowboat that seats two is available. If the cannibals ever outnumber the missionaries on either bank of the river, the missionaries will be eaten. (problem 3.9)

How shall they cross the river?



CIS 521 - 2015



## Formulation: Missionaries & Cannibals

### • How to formalize:

- Initial state: all M, all C, and boat on one bank
- Actions: ??
- Transition Model??
- Goal test: True if all M, all C, and boat on other bank
- Cost: ??

Remember:

- Representation:
  - States: Which properties matter & how to represent
  - Actions & Transition Model: Which actions are possible & how to represent
  - Path Cost: Deciding which action is next

CIS 521 - 2015



## Missionaries and Cannibals

States: (CL, ML, BL)

Initial 331

Goal 000

Actions:

Travel Across	Travel Back
-101	101
-201	201
-011	011
-021	021
-111	111

CIS 521 - 2015

