1/21/24, 5:19 PM about:blank

SQL Cheat Sheet: JOIN statements

Joins

Topic	Syntax	Description	Example
Cross Join	<pre>SELECT column_name(s) FROM table1 CROSS JOIN table2;</pre>	The CROSS JOIN is used to generate a paired combination of each row of the first table with each row of the second table.	SELECT DEPT_ID_DEP, LOCT_ID FROM DEPARTMENTS CROSS JOIN LOCATIONS;
Inner Join	<pre>SELECT column_name(s) FROM table1 INNER JOIN table2 ON table1.column_name = table2.column_name; WHERE condition;</pre>	You can use an inner join in a SELECT statement to retrieve only the rows that satisfy the join conditions on every specified table.	<pre>select E.F_NAME,E.L_NAME, JH.START_DATE from EMPLOYEES as E INNER JOIN JOB_HISTORY as JH on E.EMP_ID=JH.EMPL_ID where E.DEP_ID ='5';</pre>
Left Outer Join	<pre>SELECT column_name(s) FROM table1 LEFT OUTER JOIN table2 ON table1.column_name = table2.column_name WHERE condition;</pre>	The LEFT OUTER JOIN will return all records from the left side table and the matching records from the right table.	<pre>select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME from EMPLOYEES AS E LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP;</pre>
Right Outer Join	<pre>SELECT column_name(s) FROM table1 RIGHT OUTER JOIN table2 ON table1.column_name = table2.column_name WHERE condition;</pre>	The RIGHT OUTER JOIN returns all records from the right table, and the matching records from the left table.	select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME from EMPLOYEES AS E RIGHT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP;
Full Outer Join	<pre>SELECT column_name(s) FROM table1 FULL OUTER JOIN table2 ON table1.column_name = table2.column_name WHERE condition;</pre>	The FULL OUTER JOIN clause results in the inclusion of rows from two tables. If a value is missing when rows are joined, that value is null in the result table.	select E.F_NAME,E.L_NAME,D.DEP_NAME from EMPLOYEES AS E FULL OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP;
Self Join	SELECT column_name(s) FROM table1 T1, table1 T2 WHERE condition	A self join is regular join but it can be used to joined with itself.	SELECT B.* FROM EMPLOYEES A JOIN EMPLOYEES B ON A.MANAGER_ID = B.MANAGER_ID WHERE A.EMP_ID = 'E1001';
Joins in MySQL using phpMyAdmin			
	SELECT column_name(s) FROM table1 LEFT OUTER JOIN table2 ON		

SELECT statements.

table1.column_name = table2.column_name WHERE condition UNION

Full Outer Join

SELECT column_name(s) FROM table1 RIGHT OUTER JOIN table2

ON table1.column_name = table2.column_name

WHERE condition

select E.F NAME, E.L NAME, D.DEP NAME from EMPLOYEES AS E LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP ID=D.DEPT ID DEP

The UNION operator is used to combine the result-set of two or more

select E.F_NAME,E.L_NAME,D.DEP_NAME from EMPLOYEES AS E

RIGHT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP

Author(s)

D.M Naidu



Changelog

Date Version Changed by Change Description

2023-05-04 1.1 Benny Li Formatting changes 2022-10-04 1.0 D.M.Naidu Initial Version

1/1 about:blank