

PEL InverterOn Sublime T3 (Heat & Cool)— Features & Specifications

Key Specifications & Features — 12K Variant (Sublime T3)

Parameter	Value
Rated Cooling Capacity	2,989 W PEL
Rated Running Current (Cooling)	5.31 A PEL
Rated Heating Capacity	12,000 Btu/h PEL
Rated Running Current (Heating)	4.5 A PEL
Rated Power Input (Cooling)	1,196 W PEL
Rated Power Input (Heating)	1,049 W PEL
Energy Efficiency Ratio (EER)	2.50 PEL
Power Supply	220 – 240 V ~ / 50 Hz / 1 Phase PEL
Refrigerant	R-32, 0.49 kg charge PEL
Air Flow Volume	560 m³/h PEL
Outdoor Noise Level	50.00 dB(A) PEL
Indoor Unit Weight (Net)	8 kg PEL
Outdoor Unit Weight (Net)	22 kg PEL
Indoor Unit Dimensions (W × D × H)	790 × 275 × 192 mm PEL
Outdoor Unit Dimensions (W × D × H)	712 × 276 × 459 mm PEL

Additional Features & Highlights

- **Low-voltage start / operation:** It starts even at **155 Volts** [PEL](#)
- **High ambient cooling:** Designed to perform in environments up to **50 °C** [PEL](#)
- **4D Air Flow:** For more uniform cooling across the room [PEL](#)
- **Auto clean & moisture elimination:** Helps keep the AC interior dry & clean [PEL](#)
- **Flexible electricity consumption:** Adapts power use based on load / conditions [PEL](#)

- **Warranty:**
 - Compressor: 10 years [PEL](#)
 - PCB kit: 5 years [PEL](#)
 - Parts: 1 year [PEL](#)