

Assignment 2 Key

8.15 Show the result of each of the sample queries in Section 8.5 as it would apply to the database state in Figure 5.6

Q1. Find the name and address of all employees who work for the 'Research' department.

FNAME	LNAME	ADDRESS
John	Smith	731 Fondren, Houston, TX
Franklin	Wong	638 Voss, Houston, TX
Ramesh	Narayan	975 Fire Oak, Humble, TX
Joyce	English	5631 Rice, Houston, TX

Q2. For every project located in 'Stafford', list the project number, the controlling department number, and the department manager's last name, address, and birth date.

PNUMBER	DNUM	LNAME	ADDRESS	BDATE
10	4	Wallace	291 Berry, Bellaire, TX	20-JUN-41
30	4	Wallace	291 Berry, Bellaire, TX	20-JUN-41

Q3. Find the names of all employees who work on all the projects controlled by department number 5.

no rows selected

Q4. Make a list of project numbers for projects that involve an employee whose last name is 'Smith' as a worker or as a manager of the department that controls the project.

PNUMBER
1
2

Q5. List the names of all employees with two or more dependents.

FNAME	LNAME
John	Smith
Franklin	Wong

Q6. List the names of employees who have no dependents.

FNAME	LNAME
Joyce	English
Ramesh	Narayan
James	Borg
Ahmad	Jabbar
Alicia	Zelaya

Q7. List the names of managers who have at least one dependent.

FNAME	LNAME
Jennifer	Wallace
Franklin	Wong

8.16

- a. Retrieve the names of all employees in department 5 who work more than 10 hours per week on the ProductX project.

$WORK_X \leftarrow (\sigma_{PNAME='ProductX'} (PROJECT)) \bowtie_{PNUMBER=PNO} (WORKS_ON)$

$WORK_10 \leftarrow (EMPLOYEE) \bowtie_{SSN=ESSN} (\sigma_{HOURS>10} (WORK_X))$

$RESULT \leftarrow \pi_{FNAME, LNAME} (\sigma_{DNO=5} (WORK_10))$

FNAME	LNAME
John	Smith
Joyce	English

- b. List the names of all employees who have a dependent with the same first name as themselves.

$\pi_{FNAME, LNAME} ((EMPLOYEE) \bowtie_{SSN=ESSN \text{ AND } FNAME=DEPENDENT_NAME} (DEPENDENT))$

no rows selected

- c. Find the names of all employees who are directly supervised by 'Franklin Wong'.

$\pi_{FNAME, LNAME} ((EMPLOYEE) \bowtie_{SUPERSSN=SSN} (\pi_{SSN} (\sigma_{FNAME='Franklin' \text{ AND } LNAME='Wong'} (EMPLOYEE))))$

FNAME	LNAME
John	Smith
Ramesh	Narayan
Joyce	English

- d. For each project, list the project name and the total hours per week (by all employees) spent on that project.

$PROJ_HOURS (PNO, TOTAL_HRS) \leftarrow \rho_{PNO} \bowtie_{SUM(HOURS)} (WORKS_ON)$

$RESULT \leftarrow \pi_{PNAME, TOTAL_HRS} ((PROJ_HOURS) \bowtie_{PNO=PNUMBER} (PROJECT))$

* You can use operations like count, sum, average, max, min etc. Usage: $G \bowtie_{Aggregate-function(A)}$, you can see an example in above solution.

PNAME	SUM(HOURS)
Computerization	55
ProductZ	50
ProductY	37.5
ProductX	52.5
Reorganization	25
Newbenefits	55

- e. Retrieve the names of all employees who work on every project.

$$PE (PNO, SSN) \leftarrow \pi_{PNO, ESSN} (WORKS_ON)$$

$$ALL_PROJECTS(PNO) \leftarrow \pi_{PNUMBER} (PROJECT)$$

$$EMPS_ALL_PROJS \leftarrow PE \div ALL_PROJECTS$$

$$RESULT \leftarrow \pi_{FNAME, LNAME} (EMPLOYEE * EMP_ALL_PROJS)$$

no rows selected

- f. Retrieve the names of all employees who do not work on any project.

$$NON_WORKING \leftarrow (\pi_{SSN} (EMPLOYEE)) - (\pi_{ESSN} (WORKS_ON))$$

$$RESULT \leftarrow \pi_{FNAME, LNAME} (EMPLOYEE * NON_WORKING)$$

no rows selected

- g. For each department, retrieve the department name and the average salary of all employees working in that department.

$$\pi_{DNAME, AVG} ((DNAME \bowtie_{AVG(SALARY)} (EMPLOYEE)) \bowtie_{DNO=DNUMBER} (DEPARTMENT))$$

DNAME	AVG(SALARY)
Research	33250
Administration	31000
Headquarters	55000

- h. Retrieve the average salary of all female employees.

$$\bowtie_{AVG(SALARY)} (\sigma_{SEX='F'} (EMPLOYEE))$$

AVG(SALARY)
31000

- i. Find the names and addresses of all employees who work on at least one project located in Houston but whose department has no location in Houston.

```
HOUSTON_PROJS(SSN) ← πESSN (WORKS_ON ⋈PNO=PNUMBER (σPLOCATION='Houston' (PROJECT)))
NO_HOUST_DEPS ← πDNUMBER (DEPARTMENT) - πDNUMBER (σDLOCATION='Houston' (DEPARTMENT))
NO_HOUST_EMP_DEPS ← πSSN (EMPLOYEE ⋈DNO=DNUMBER (NO_HOUST_DEPS))
RESULT ← πFNAME, LNAME, ADDRESS (EMPLOYEE * (HOUSTON_PROJS - NO_HOUST_EMP_DEPS))
```

FNAME	LNAME	ADDRESS
Jennifer	Wallace	291 Berry, Bellaire, TX

- j. List the last names of all department managers who have no dependents.

```
πFNAME, LNAME (EMPLOYEE * (πMGRSSN (DEPARTMENT) - πESSN (DEPENDENT)))
```

FNAME	LNAME
James	Borg

8.17

- a. For each flight, list the flight number, the departure airport for the first leg of the flight, and the arrival airport for the last leg of the flight.

```
DEP <- πFlight_number, Dep_airport_code (Flight_number ⋈MIN(Leg_number) (FLIGHT_LEG)) * FLIGHT_LEG
ARR <- πFlight_number, Arr_airport_code (Flight_number ⋈MAX(Leg_number) (FLIGHT_LEG)) * FLIGHT_LEG
RESULT <- DEP * ARR
```

- b. List the flight numbers and weekdays of all flights or flight legs that depart from Houston Intercontinental Airport (airport code 'iah') and arrive in Los Angeles International Airport (airport code 'lax').

```
πFlight_number, Weekdays ((σDep_airport_code='iah' (FLIGHT_LEG) * σArr_airport_code='lax' (FLIGHT_LEG)) * FLIGHT)
```

- c. List the flight number, departure airport code, scheduled departure time, arrival airport code, scheduled arrival time, and weekdays of all flights or flight legs that depart from some airport in the city of Houston and arrive at some airport in the city of Los Angeles.

```
HOUSTON_LA <- σDep_airport_code='iah' (FLIGHT_LEG) * σArr_airport_code='lax' (FLIGHT_LEG)
RESULT <- πFlight_number, Dep_airport_code, Sched_dep_time, Arr_airport_code, Sched_arrival_time, Weekday (HOUSTON_LA * FLIGHT)
```

- d. List all fare information for flight number 'co197'.

```
σFlight_number='co197' (FARE)
```

- e. Retrieve the number of available seats for flight number 'co197' on '2009-10-09'.

π Number_of_available_seats (σ Flight_number='CO197' AND Date='1999-10-09'(LEG_INSTANCE))

8.18

- a. How many copies of the book titled *The Lost Tribe* are owned by the library branch whose name is 'Sharpstown'?

π No_of_copies (Book_Copies * (π Branch_id(σ Branch_name='Sharpstown'(Library_Branch))) * π Book_id (σ Title='The Lost Tribe'(Book)))

- b. How many copies of the book titled *The Lost Tribe* are owned by each library branch?

π BranchID, No_of_copies ((σ Title='The Lost Tribe'(BOOK)) * BOOKCOPIES

- c. Retrieve the names of all borrowers who do not have any books checked out.

π Name (Borrower * (π Card_no (Borrower) – π Card_no (Book Loans)))

- d. For each book that is loaned out from the Sharpstown branch and whose Due_date is today, retrieve the book title, the borrower's name, and the borrower's address.

ST <- π BranchId (σ BranchName='Sharpstown'(LIBRARY_BRANCH))
BORROWED_ST <- π BookId, CardNo ((σ DueDate=today (BOOKLOANS)) * ST)
RESULT <- π Title, Name, Address (BOOK * BORROWER * BORROWED_ST))

- e. For each library branch, retrieve the branch name and the total number of books loaned out from that branch.

TEMP (BranchId, Total) <- BranchId \bowtie COUNT (BookId, CardNo) (BOOK_LOANS)
RESULT <- π BranchName, Total (TEMP * LIBRARY_BRANCH))

- f. Retrieve the names, addresses, and number of books checked out for all borrowers who have more than five books checked out.

TEMP (CardNo, NumofBooks) <- CardNo \bowtie COUNT(BookId) (BOOK_LOANS)
RESULT <- π Name, Address, NumofBooks ((σ NumofBooks > 5(TEMP)) * BORROWER)

- g. For each book authored (or coauthored) by Stephen King, retrieve the title and the number of copies owned by the library branch whose name is Central.

STEPHEN (BookId, Title) <- (σ AuthorName='Stephen King' (BOOK_AUTHORS)) * BOOK
CENTRAL(BranchId) <- σ BranchName='Central' (LIBRARY_BRANCH)
RESULT <- π Title, No_of_copies (STEPHEN * BOOKCOPIES * CENTRAL)