# Hazard Analysis Mechatronics Engineering

Team #1, Back End Developers
Jessica Bae
Oliver Foote
Jonathan Hai
Anish Rangarajan
Nish Shah
Labeeb Zaker

Table 1: Revision History

Date	Developer(s)	Change
	Name(s) Name(s)	Description of changes Description of changes
•••	•••	•••

# Contents

1	Introduction	1		
2	Scope and Purpose of Hazard Analysis			
3	System Boundaries and Components			
	3.1 Battery/Power Management system	1		
	3.2 Sensor Array system	1		
	3.3 Prompt generation system	1		
	3.4 Display System	1		
	3.5 Data Storage system	1		
	3.6 Device Manager	2		
	3.7 Error Handler - Hardware	2		
	3.8 Error Handler - Software	2		
	3.9 Host Software	2		
4	Critical Assumptions	2		
5	Failure Mode and Effect Analysis			
6	3 Safety and Security Requirements			
7	Roadmap	2		

#### 1 Introduction

[You can include your definition of what a hazard is here. —SS]

### 2 Scope and Purpose of Hazard Analysis

### 3 System Boundaries and Components

The system consists of several components that make up the entire system

### 3.1 Battery/Power Management system

This component facilitates stepping down/up the source voltage from the battery to the necessary values required by different parts of the device. Moreover, it consists of a charge protection circuit for battery protection (Over-voltage and Discharge). Finally present is a battery level indicator that will generate an alert should the battery life fall below a certain threshold.

#### 3.2 Sensor Array system

This component represents all the various sensors that will be used to collect the state information about the user. Also consists of various filters to facilitate smooth and accurate data collection.

#### 3.3 Prompt generation system

This component handles all prompt generation, from the detection of when a prompt occurs, to its specific creation and finally its display on the screen.

#### 3.4 Display System

This system manages all functionality of the device's display, such as prompt display, showing basic user feedback such as date, time, temperature, etc.

#### 3.5 Data Storage system

This system handles all logging and storage of data collected by both the sensor array and the prompt generator. Data is stored along with an indication of which system it came from and all prompts will be stored with the data and time of entry.

#### 3.6 Device Manager

This system handles all connection and communication between the device and the host software.

#### 3.7 Error Handler - Hardware

This component constantly checks the states of every system present and ensures that if any of them fail or return an error, an alert is generated. Moreover the system will also try to fix the problem wherever possible.

#### 3.8 Error Handler - Software

This component monitors the state of the host software and will attempt to solve any errors that arise and will alert the user should the attempts fail.

#### 3.9 Host Software

This system is the primary interface for the researchers to analyze the data collected by the device. It consists of several features that allows the researcher to set different thresholds for activity tracking, calibrate all the sensors, update and create new records for participants, and finally interact with the data stored on the device.

## 4 Critical Assumptions

[These assumptions that are made about the software or system. You should minimize the number of assumptions that remove potential hazards. For instance, you could assume a part will never fail, but it is generally better to include this potential failure mode. —SS

## 5 Failure Mode and Effect Analysis

[Include your FMEA table here —SS]

# 6 Safety and Security Requirements

[Newly discovered requirements. These should also be added to the SRS. (A rationale design process how and why to fake it.) —SS]

## 7 Roadmap

[Which safety requirements will be implemented as part of the capstone time-line? Which requirements will be implemented in the future? —SS]