

National University of Computer and Emerging Sciences



Laboratory Manuals
for
Computer Networks

(CL -3001)

Department of Computer Science
FAST-NU, Lahore, Pakistan

Lab Manual 02

Objectives:

- To learn basic commands of Linux related to Directory and File Manipulation, Process management and Network Management
- Python Introduction

In-lab Statement

1. Find out the purpose of the following commands and execute them on your system with different parameters. [1]

ls, cd, pwd, mkdir, rmdir, rm , cp, mv, touch

2. Some commands may be new for most of you. Practice these terms on your own: [9]

top	The top program provides a dynamic real-time view of a running system. It can display system summary information as well as a list of tasks currently being managed by the Linux kernel.	top
ps	ps displays status of a selection of the active/currently running processes.	ps
kill pid	Kill is used to send a signal to a process. Where pid stands for process id Default syntax for this is kill [-signal number or name)] pid On your terminal to see the list of available signals. Kill -L A PID of -1 is special; it indicates all processes except the kill process itself and in it. It will terminate all programs and log off. BEWARE!	kill -SIGKILL pid
chmod	This command is used to grant or revert reading, writing, and executing permissions from a user, group or others. Following are the symbolic representation of three different roles: You can check the details by typing man chmod chmod 400 lab1.txt Check what happened to your file.	

	<p>Now write</p> <pre>chmod 700 lab1.txt</pre> <p>What happened to your file?</p>	
ifconfig	<p>ifconfig is used to configure the kernel-resident network interfaces.</p> <p>If no arguments are given, ifconfig displays the status of the currently active interfaces. If a single interface argument is given, it displays the status of the given interface only; if a single -a argument is given, it displays the status of all interfaces, even those that are down. Otherwise, it configures an interface.</p>	<p>ifconfig</p> <pre>ifconfig -a</pre> <pre>ifconfig eth0</pre>
route	<p>Route manipulates the kernel's IP routing tables. Its primary use is to set up static routes to specific hosts or networks via an interface.</p>	<pre>route</pre>
ss	<p>The command is used to investigate socket statistics.</p> <p>Use ss-u for udp and ss-t for tcp sockets to analyze which sockets are being used for which protocol.</p>	
wget	<p>wget stands for "web get". It is a command-line utility which downloads files over a network. It supports HTTP, HTTPS, and FTP protocols, as well as retrieval through HTTP proxies. wget has been designed for robustness over slow or unstable network connections; if a download fails due to a network problem, it will keep retrying until the whole file has been retrieved. If the server supports rejects permission, it will instruct the server to continue the download from where it left off.</p> <p>The simplest way to use wget is to simply provide it with the location of a file to download over HTTP. For example, to download the file http://website.com/files/file.zip, this command:</p> <pre>wget http://website.com/files/file.zip</pre> <p>Where will this file be downloaded?</p>	
traceroute	<p>traceroute prints the route that packets take to a network host. traceroute gives an insight to the entire path that a packet travels through, names and identity of routers and devices in your path,</p>	

	<p>network latency (the time taken to send and receive data to each devices on the path). It's a tool that can be used to verify the path that your data will take to reach its destination, without actually sending your data.</p> <p>Write on your terminal</p> <pre>tracert nu.edu.pk</pre>	
nslookup	<p>nslookup is a network administration tool for querying the Domain Name System (DNS) to obtain domain name or IP address mapping or any other specific DNS record. It is also used to troubleshoot DNS related problems.</p> <p>Write on your terminal window</p> <pre>nslookup www.google.com</pre>	
host	<p>It is an alternative of nslookup but with more details. Write up on your terminal window: <code>host www.google.com</code></p>	

3. Ping command: [2]

Ping is a command that is used to check the connection and latency rate between two computers in a network. One network pings another in order to exchange data packets (Response) to calculate the latency and exchange rate.

Syntax for Pinging is:

ping [other network's ID (Domain/IP Address)]

Question - You are required to ping at least 5 other networks (including your own address i.e. 127.0.0.1) and compare the latency rate of all networks.

- Write a python program that imports a textfile;input.txt , reads all the characters in a list. It removed all Alphanumeric values and writes the new contents in a new file called output.txt[3]