

Extending sqlc: augmented generation of repositories in Go


[Nikolay Kuznetsov](#)

FOSDEM Brussels

1 Feb 2026



About me

- Senior Software Engineer
- Zalando Helsinki 
- C → Java → Kotlin → **Go**
- Author of [pgx-outbox](#) and [sqlc++](#) projects

Goals

- Create repositories on top of *sql/c*-generated queries
- Keep strengths of *sql/c*: type safety & compile-time checks
- Decouple business logic from *sql/c*-generated records
- Automate repository creation with augmented generation

Repository

- Accepts and returns domain models
- Hides details of SQL, schema, query libraries
- Maps between DB records and domain models
- Orchestrates transactions across multiple operations

Domain model

Cart repository interface

```
type CartRepository interface {  
    // context.Context type is omitted for brevity  
    GetCart(ctx, ownerID string) (domain.Cart, error)  
    AddItem(ctx, ownerID string, item domain.CartItem) error  
    DeleteItem(ctx, ownerID string, productID uuid.UUID) (bool, error)  
}
```

Domain cart

```
type Cart struct {
    OwnerID string
    Items   []CartItem
}

type CartItem struct {
    ProductID uuid.UUID // google/uuid
    Price     Money
    CreatedAt time.Time
}

type Money struct {
    Amount    decimal.Decimal // shopspring/decimal
    Currency  currency.Unit     // x/text/currency
}
```

Cart items table

```
CREATE TABLE IF NOT EXISTS cart_items (  
    owner_id          VARCHAR(255)          NOT NULL,  
    product_id        UUID                  NOT NULL,  
    price_amount       DECIMAL              NOT NULL,  
    price_currency     VARCHAR(3)           NOT NULL,  
  
    created_at         TIMESTAMP DEFAULT CURRENT_TIMESTAMP NOT NULL,  
  
    PRIMARY KEY (owner_id, product_id)  
);
```


Postgres in Go

Working with Postgres in Go

- Pure stdlib *database/sql*
- *squirrel* + *sqlx*
- *pgx* driver API
- ***sqlc***
- ~~ORMs~~ (*GORM*, *Ent*, *Bun*): out of scope

Pure stdlib database/sql

- API: *stdlib database/sql*
- Driver: *lib/pq*
- Query builder: none
- Struct mapping: manual scanning

Pure stdlib *database/sql* example

```
func (r *repo) GetCart(ctx context.Context, ownerID string) (domain.Cart, error) {  
    // db *sql.DB  
    rows, _ := r.db.QueryContext(ctx,  
        `SELECT product_id, created_at FROM cart_items WHERE owner_id=$1`, ownerID)  
    defer rows.Close()  
  
    // scanning directly into domain model  
    var items []domain.CartItem  
    for rows.Next() {  
        var item domain.CartItem  
        _ = rows.Scan(&item.ProductID, &item.CreatedAt)  
        items = append(items, item)  
    }  
  
    // handle rows.Err()  
  
    return domain.Cart{OwnerID: ownerID, Items: items}, nil  
}
```

Adopting *squirrel* and *sqlx*

- API: *stdlib database/sql*
- Driver: *lib/pq*
- Query builder: *Masterminds/squirrel*
- Struct mapping: *jmoiron/sqlx*

Adopting *squirrel* and *sqlx* example

```
func (r *repo) GetCart(ctx context.Context, ownerID string) (domain.Cart, error) {  
    query, args, _ := sq.Select("product_id", "created_at").  
        From("cart_items").  
        Where(sq.Eq{"owner_id": ownerID}).  
        PlaceholderFormat(sq.Dollar).ToSql()  
  
    var dbItems []dbCartItem // local struct with `db` tags, aka DB records or models  
  
    // dbx *sqlx.DB  
    if err := r.dbx.SelectContext(ctx, &dbItems, query, args...); err != nil {  
        return domain.Cart{}, err  
    }  
  
    var items []domain.CartItem  
    // mapping of dbItems []dbCartItem to domain cart items  
  
    return domain.Cart{OwnerID: ownerID, Items: items}, nil  
}
```

Adopting *pgx*

- API: *jackc/pgx* (or *database/sql*)
- Driver: *jackc/pgx*
- Query builder: *Masterminds/squirrel*
- Struct mapping: *pgx.CollectRows* method

Adopting pgx driver and API


```
func (r *repo) GetCart(ctx context.Context, ownerID string) (domain.Cart, error) {  
    query, args, _ := sq.Select("product_id", "created_at").  
        ... // same as before  
  
    // pool *pgxpool.Pool  
    rows, _ := r.pool.Query(ctx, query, args...)  
  
    // collect directly into domain model  
    // pgx.CollectRows takes cares of closing rows  
    items, _ := pgx.CollectRows(rows, func(row pgx.CollectableRow) (domain.CartItem, error) {  
        var item domain.CartItem  
        err := row.Scan(&item.ProductID, &item.CreatedAt)  
        return item, err  
    })  
  
    return domain.Cart{OwnerID: ownerID, Items: items}, nil  
}
```


Pros of *pgx* API

- Full Postgres feature support
 - batching, LISTEN/NOTIFY, COPY, prepared statements
- Better type handling (JSON, arrays, UUID, etc)
- Advanced connection pool: *pgxpool*

sqlc

sqlc in a nutshell



Adopting *sqlc*

- API: *jackc/pgx*
- Driver: *jackc/pgx*
- Queries: pure SQL (almost)
- Struct mapping: automatic to *sqlc*-generated records

Generated records and queries

```
// Code generated by sqlc. DO NOT EDIT.  
// sqlc v1.29.0
```

```
const GetCart = `-- name: GetCart :many  
SELECT product_id, created_at  
FROM cart_items  
WHERE owner_id = $1  
`
```

```
type GetCartRow struct {  
    ProductID string  
    CreatedAt time.Time  
}
```

```
func (q *Queries) GetCart(ctx context.Context, ownerID string)([]GetCartRow, error) {  
    // generated implementation here  
}
```

Pros of *sqlc*

- Compile time schema and type safety
 - uses *Postgres* parser (*wasilibs/go-pgquery*) to produce *AST*
- Less boilerplate to write
 - query building, execution, rows scanning
- Separation of SQL and Go code

Simplified Abstract Syntax Tree


```
-- name: DeleteItem :execrows
```

```
DELETE FROM cart_items WHERE owner_id = $1 AND product_id = $2;
```



```
DeleteStmt
```

```
[ Relation: cart_items  
  [ WhereClause (BoolExpr: AND)  
    [ left: ColumnRef { Name: "owner_id" } = ParamRef{1}  
      right: ColumnRef { Name: "product_id" } = ParamRef{2}
```

sqlc under the hood



Challenges with *sqlc*

- Generated records leaking to business logic
- Mapping between records and domain models
- Dynamic conditional queries 
- Batch INSERTs and UPDATES 

Delegating to generated queries

```
func (r *repo) GetCart(ctx context.Context, ownerID string) (domain.Cart, error) {  
    // rows []GetCartRow - generated by sqlc  
    // q *db.Queries - generated by sqlc  
    rows, _ := r.q.GetCart(ctx, ownerID)  
  
    // map sqlc rows -> domain items  
    items := mapGetCartRowsToDomain(rows)  
  
    return domain.Cart{OwnerID: ownerID, Items: items}, nil  
}
```

Repository methods vs generated queries

- Repository methods align with **domain**, not SQL
- Repository methods compose multiple queries into a **transaction**
- Repository methods may add tracing, metrics, caching, etc

sqlc++


Introducing sqlc++

Let AI generate repository code by:

- Implementing provided interface (port)
- Using domain models and *sqlc*-generated artifacts
- Leveraging augmented generation




sqlc++ in a nutshell



sqlc++ variations

- Before agents: *langchain-go* & *text/template*
- **Agent with a custom command**
- Agent with skills



Introducing Crush

- Glamorous coding agent
- Written in Go, open source (FSL)
- Multi-model, LSP-enhanced
- Agent skills, MCP, custom commands

Custom command for Crush

Generate a repository file for domain model: \$ARGUMENTS

Follow these steps:

- Run ``sqlc generate`` command to generate files in ``db`` directory.
- Add generated files in ``db`` directory, ``domain/$ARGUMENTS.go`` and ``port/$ARGUMENTS.go`` to the context.
- Use this file from GitHub as a reference implementation:
``github.com/nikolayk812/sqlcpp/blob/main/repository/order_repository.go``
- Create file ``repository/$ARGUMENTS_repository.go``, it has to satisfy the port interface above.
- Make sure the generated file compiles and tests pass.

Reference implementation project

- Domain model: order
- 2 tables: orders, order_items
- Various operations: CRUD, search by filter, soft-delete
- Various field types
- Transactions support

Demo time

Charm™ Crush //////////////////////////////////////

~/MyProjects/sqlcpp-demo

◇ Claude Sonnet 4

LSPs

● go

MCPs

● godoc 1 tool

> Ready?

:::

:::

/ or ctrl+p commands • ctrl+l models • ctrl+j newline • ctrl+c quit • ctrl+g more

////// Charm™ v0.35.0
////// CALISH
//////

~/MyProjects/sqlcpp-demo

◇ Claude Sonnet 4

LSPs

● go

Commands // ○ System ● User

> Type to filter

project:generate-repository

tab switch selection • ↑↓ choose • enter confirm • esc cancel

~/MyProjects/sqlcpp-demo

◇ Claude Sonnet 4

LSPs

● go

project:generate-repository

Custom command from generate-repository.md

Arguments*:

cart

enter confirm • tab/↓ next • shift+tab/↑ previous •

I'll help you generate the repository file and integration tests for the cart domain model. Let me start by setting up the todo list and running the necessary steps.

✓ **To-Do** created 8 todos, starting first

→ Running sqlc generate to create SQLC code

- Add generated SQLC files to context
- Add domain model and port interface to context
- Create cart repository integration tests
- Create cart repository implementation
- Ensure compilation and fix any errors
- Organize imports with goimports
- Run tests and fix any failures

✓ **Bash** sqlc generate

✓ **To-Do 1/8** · completed 1, starting next

→ Adding generated SQLC files to context

⋮ **To-Do 3/8** Creating cart repository integration te...

ctrl+space open

✓ To-Do 8/8 · completed all

- ✓ Run tests and fix any failures
- ✓ Organize imports with goimports
- ✓ Ensure compilation and fix any errors
- ✓ Create cart repository implementation
- ✓ Create cart repository integration tests
- ✓ Add domain model and port interface to context
- ✓ Add generated SQLC files to context
- ✓ Run sqlc generate to create SQLC code

Perfect! I have successfully generated the repository file and integration tests for the cart domain model. Here's what was accomplished:

Generated Files

1. Cart Repository Implementation (`internal/repository/cart_repository.go`)

- Implements all methods from the `CartRepository` interface
- Uses SQLC-generated queries (`AddItem` , `GetCart` , `DeleteItem`)
- Proper mapping between SQLC records and domain models
- Error handling with descriptive messages

2. Cart Repository Tests (`internal/repository/cart_repository_test.go`)

Charm™ Crush //////////////////////////////////

Generate cart repository and integration tests

~/MyProjects/sqlcpp-demo

◇ Claude Sonnet 4
26% (52.8K) \$0.00

Modified Files —————

~/r/cart_repository_te... +314
~/r/cart_repository.go +98
~/r/repository_test.go +25

LSPs —————


● go :: 4

MCPs —————


● godoc 1 tool

Testing repositories

- Testcontainers + Postgres module
- *Suite* from *stretchr/testify*
- Table tests for each repository method
- Helpful libs: *gofakeit*, *go-cmp*



sqlc++ architecture recap



Takeaways

- Adopt **sqlc** and **Crush**, contribute
- Avoid *sqlc*-generated structs in business logic
- Repository boilerplate can be automated
- Augmented generation provides more stable results

Thank you!

Q&A



Nikolay Kuznetsov

 nikolayk812

 nkuznetsov

 github.com/nikolayk812/sqlcpp

