LEDGERLINE

Runbook

VERSION	1.0.0
DATE	2026-10-18
AUTHOR	Ledgerline platform team

Contents

Service overview 3

Start, stop, restart 3

Health checks 3

Routine tasks 3

Logs 3

Common problems 4

- Every /orders request returns 500 4
- KeyError: 'DATABASE_URL' 4
- API can't reach the database 4
- Deploy job fails in GitLab CI 4

Scaling 4

Escalation 4

Related documents 4

Assumptions and open questions 5

Service overview

Hosting	Not recorded in the repo ASSUMPTION
Components	`api` (FastAPI on uvicorn, port 8000) and `db` (PostgreSQL 16), from `docker-compose.yml`
Health endpoint	`GET /health` (`app/main.py`)
On-call	Not provided ASSUMPTION
Error tracking	Sentry, if `SENTRY_DSN` is set (`app/main.py`)

Start, stop, restart

Local or single-host deployment with Docker Compose:

```
docker compose up -d            # start api + db
docker compose stop             # stop
docker compose restart api      # restart the API only
```

Without Docker, for development:

```
make dev                        # uvicorn app.main:app --reload
```

Health checks

```
curl -fsS http://localhost:8000/health
```

Expected: `{"status":"ok"}`. This only proves the process is up. It doesn't touch the database.

Routine tasks

Task	Frequency	Command
Apply database migrations	each release	`make migrate`
Run tests with coverage	each change	`make test`
Lint	each change	`make lint`
Back up PostgreSQL	not configured	see Backup and Disaster Recovery

Logs

uvicorn writes access and error logs to stdout:

```
docker compose logs -f api
docker compose logs -f db
```

Common problems

Every `/orders` request returns 500

1. Check: `docker compose exec api printenv API_KEY`
2. Fix: set `API_KEY` in `.env` and run `docker compose up -d api`. `app/auth.py` reads `os.environ["API_KEY"]` on each request and raises `KeyError` when it's missing.

`KeyError: 'DATABASE_URL'`

1. Check: `.env` contains `DATABASE_URL` (see `.env.example`).
2. Fix: add it and restart. `app/db.py` reads it with `os.environ[...]` when the module loads.

API can't reach the database

1. Check: `docker compose ps db` shows the database as running.
2. Fix: inside Compose, the host must be `db`, not `localhost`: `postgresql+psycopg://ledger:<password>@db:5432/ledger`.

Deploy job fails in GitLab CI

The `deploy` job in `.gitlab-ci.yml` runs `./scripts/deploy.sh`, but that file isn't in the repository.

> **WARNING**
> Deploys from `main` fail until `scripts/deploy.sh` is added, or the job is changed to the real deploy command.

Scaling

`docker-compose.yml` defines one `api` container. To handle more load, run several uvicorn workers (`--workers N`) or more replicas behind a load balancer UNTESTED. The database is one PostgreSQL instance.

Escalation

No on-call contact was provided. See Incident Response once it has been written.

Related documents

API Reference · Data Model · Incident Response

Assumptions and open questions

#	Item	Type	Why unverified	Who can confirm
A1	Hosting environment	assumption	`hosting: unknown`	DevOps
A2	On-call contact	assumption	`oncall_contact: unknown`	engineering manager
A3	Scaling commands	assumption	not exercised	DevOps
Q1	What should `scripts/deploy.sh` do?	open question	referenced in CI but missing	DevOps
Q2	Should `/health` check the database?	open question	currently static	backend lead