



TCLD_J2EE_R-43_Angular_Quiz-2

Total points **17/20** ?

Angular in Detail

Trainee ID *

1256084

Trainee Name *

Gazi Rizveykhar Zaman

✓ What is the decorator used for configuring your module class?

1/1

☐ @NgApp

☒ @NgModule



☐ @NgAngular

☐ @NgModule



✓ Interpolation in angular 6 is done using *

1/1

- ☒ `{{}}` ✓
- ☐ `{{|var}}`
- ☐ `{{{}}}`
- ☐ `!!!!`

✓ This folder contains the NPM packages that are required for the application and for the Angular development tools *

1/1

- ☐ e2e
- ☐ src
- ☒ node_modules ✓
- ☐ app

✗ The square brackets (the [and] characters) tell Angular that this is a 0/1

- ☐ One way data binding
- ☐ Two way data binding
- ☐ String interpolation binding

☒ Property Binding



Correct answer

☒ One way data binding

✓ Access modifiers not supported by TypeScript is?

1/1

- ☐ Public
- ☐ Private
- ☒ Default
- ☐ Protected



✓ Which angular decorator allows us to define the pipe name that is globally available for use in any template in the across application? 1/1

☐ pipeName

☐ pipeDeco

☒ Pipe



☐ none of the above

✓ Which of the following filter is used to convert input to all uppercase? 1/1

☐ upper

☒ uppercase



☐ toUpper

☐ none of the above

✓ Which character is used for chaining multiple pipes?

1/1

- ☒ | ✓
- ☐ :
- ☐ Both
- ☐ None of the above

✓ In Angular, you can pass data from parent component to child component using

1/1

- ☐ @Output()
- ☒ @Input() ✓
- ☐ Input
- ☐ Output

✓ Which of the followings is attribute property binding

1/1

☒ [\[attr.name\]](#)



☐ [\[style.name\]](#)

☐ [\[class.name\]](#)

☐ [property]

✗ In typescript weakly or dynamically typed structures are of type

0/1

☒ Complex



☐ Any

☐ Dynamic

☐ Var

Correct answer

☒ Any

✓ Which Angular directive is used to binds the value of HTML controls (input, select, textarea) to application data? * 1/1

☐ ng-cloak

☐ ng-bind

☒ ng-model ✓

☐ ng-blur

✓ Integers are represented by type * 1/1

☐ Int

☒ Number ✓

☐ Int32

☐ Int64

✓ Which of the following is not built-in pipe in Angular? *

1/1

☐ DatePipe

☐ CurrencyPipe

☒ DataPipe



☐ PercentPipe

✗ Which directive is used to repeat a block of content at a specified location?

0/1

☐ ngTemplateOutlet

☒ ngFor



☐ ngSwitchCase

☐ ngClass

Correct answer

☒ ngTemplateOutlet

✓ There are different types of event object for different categories of event but all events share the three properties * 1/1

☒ type ✓

☒ target ✓

☒ timestamp ✓

☐ event

✓ The _____ operator is used to expand an array so that its contents can be used as function arguments or combined with other arrays. 1/1

☐ Identity

☒ Spread ✓

☐ Rest

☐ Assign

✓ which of the followings is not a ngFor Local Template Value?

1/1

☒ next



☐ odd

☐ first

☐ last

✓ A directive which modifies DOM hierarchy is called *

1/1

☒ Structural directive



☐ Attribute directive

✓ The Angular application is ----- at runtime *

1/1

☐ plain java

☐ plain typescript

☐ plain html

☒ plain JavaScript



This content is neither created nor endorsed by Google. - [Terms of Service](#) - [Privacy Policy](#).

Google Forms