

Statistical learning: 4th assignment

Ali Zamani(96123035) & Aryan Nasehzadeh

January 20, 2019

1 Machin lerning algorithms

In this section, we will use different machine learning algorithms such as LDA, QDA, KNN, Decision tree, and kernel SVM. To access source code you can check the link:

<https://github.com/zamaliani1995/Machine-learning-and-Neural-Network>

The sklearn package is used. Dataset has numbers of unknown features, one way is dropping all data with the unknown feature but in this approach, we lose a lot of data thus we should use other approaches. We replace unknown features with mean or min or max of features on that class, for example, if the unknown feature is associated with data in class 1, we replace that feature with the mean of features on class 1. we also train our model with scaled and unscaled data and results are reported in tables 1, 2, 3, 4, 5. In the SVM algorithm non-scaled data are used. As you see maximum accuracy belongs to **polynomial kernel SVM** and it is **58%**.

2 Neural Network(NN)

In this section, we will create an NN model with 3 hidden layers. We use shuffled and unscaled data. Table 6 shows results for different neurons numbers in each layer. Figure 3 show another result. As you can see in table 6 maximum test accuracy is 28% and it is less than 58% thus kernel SVM with polynomial kernel has better test accuracy.

3 Ideas

We have shown that if the concatenated dataset is used then we do not have good accuracy but if we use the first dataset as training we can have good accuracy. It is shown that our test dataset is correlated with first train dataset. We know that first dataset measures with one device and another dataset measures with another device we can add another feature two show that which device is used. We know that 36 class belong to 36 places that data is sampled so the data can be time series. according to this, we can use LSTM.

If we plot our test dataset we see that the number of class 16 is more than other classes so we faced unbalanced test dataset. according to this, if we make a model that predicts class 16, we have good accuracy in test dataset so it is better to use balanced test dataset and calculate the accuracy of the model.

We replace zeros with mean. Another approach can be used. For example, we can fit a natural cubic spline to our model and after that find value of unknown feature from the natural cubic spline.

To visualize data set a number of plots are placed at the end of the report.

Table 1: QDA

QDA			
Train	Merged	Scaled	ACC
	Yes	Yes	75%
	Yes	No	92%
	No	Yes	54%
	No	No	96%
Test	Yes	Yes	5.2%
	Yes	No	27%
	No	Yes	0%
	No	No	23%

Table 2: LDA

LDA			
Train	Merged	Scaled	ACC
	Yes	Yes	75%
	Yes	No	92%
	No	Yes	54%
	No	No	96%
Test	Yes	Yes	1%
	Yes	No	27%
	No	Yes	2.2%
	No	No	47%

Table 3: Decision tree

Decision tree			
Train	Merged	Scaled	ACC
	Yes	Yes	75%
	Yes	No	92%
	No	Yes	54%
	No	No	96%
Test	Yes	Yes	11%
	Yes	No	25%
	No	Yes	2.6%
	No	No	25%

Table 4: KNN

KNN			
Train	Merged	Scaled	ACC
	Yes	Yes	75%
	Yes	No	92%
	No	Yes	54%
	No	No	96%
Test			
	Yes	Yes	7%
	Yes	No	39%
	No	Yes	1.4%
	No	No	40%

Table 5: Kernel SVM

Kernel SVM			
Train	Merged	Kernel	ACC
	No	linear	96%
	No	polynomial	96%
	No	rbf	96%
	No	sigmoid	96%
	Yes	linear	92%
	Yes	polynomial	92%
	Yes	rbf	92%
	Yes	sigmoid	92%
Test			
	No	linear	51%
	No	polynomial	58%
	No	rbf	4%
	No	sigmoid	0.2%
	Yes	linear	28%
	Yes	polynomial	25%
	Yes	rbf	4%
	Yes	sigmoid	0.2%

Table 6: Neural Network

Neural Network (3 layers)						
Hidden 1	Hidden 2	Hidden 3	Batch size	Learning rate	Train ACC	Test ACC
40	30	20	40	0.001	82%	28%
50	40	30	40	0.001	88%	26%
50	40	10	40	0.001	79%	26%
40	40	30	20	0.001	90%	24%
200	150	100	40	0.001	97%	26%
100	90	80	60	0.0001	97%	28%

test accuracy = 0.24671916010498687




Figure 1: Neural Network




Figure 2: Number of data in each class

SVM test accuracy = 0.583989501312336




Figure 3: Predicted test in each algorithm




Figure 4: Value of each feature