Supply Bridge Asia

Product Catalogue 2026 — Power Generation & Distribution

Diesel generator sets 16 kW – 3,000 kW · 50 Hz & 60 Hz
Oil & dry-type transformers up to 33 kV · Package / box substations · RMU & LV switchgear

- Section 1 — Weichai sets, 50 Hz
- Section 2 — Weichai sets, 60 Hz
- Section 3 — Cummins (CCEC) sets, 50 Hz
- Section 4 — MTU sets, 50 Hz
- Section 5 — Transformers, substations & switchgear
- Section 6 — Standard scope, options & documents

Prices: see the separate FOB price list (updated monthly). Other engine brands (Yuchai, SDEC, Perkins, Volvo) on request.

zane@supplybridgeasia.com · supplybridgeasia.com

Section 1 — Weichai diesel generator sets, 50 Hz

1,500 rpm · prime / standby to ISO 8528

SBA model	Prime kW / kVA	Standby kW / kVA	Engine	Fuel L/h (100% prime)	Open set L×W×H mm	Weight kg
SBA-WC-375	300 / 375	320 / 400	WP13D385E310	78.7	3130×1380×1800	2750
SBA-WC-438	350 / 438	400 / 500	WP13D440E310	129.6	3650×1500×1850	4200
SBA-WC-500	400 / 500	440 / 550	WP13D490E310	129.6	3650×1500×1850	4200
SBA-WC-562	450 / 562	500 / 625	6M33D572E200	129.6	3650×1500×1850	4200
SBA-WC-625	500 / 625	550 / 688	6M33D633E200	143.9	3650×1500×1850	4200
SBA-WC-675	540 / 675	600 / 750	6M33D670E200	152.1	4300×1800×2400	7100
SBA-WC-800	640 / 800	700 / 875	12M26D792E200	190.3	4300×1800×2400	7100
SBA-WC-900	720 / 900	800 / 1000	12M26D902E200	190.3	4300×1800×2400	7100
SBA-WC-1000	800 / 1000	880 / 1100	12M26D968E200	195	4500×1700×2450	8500
SBA-WC-1125	900 / 1125	1000 / 1250	12M33D1108E200	210	4500×1700×2450	8500
SBA-WC-1250	1000 / 1250	1100 / 1375	12M33D1210E200	210	4800×1800×2450	9500
SBA-WC-1375	1100 / 1375	1200 / 1500	12M33D1320E200	225	5400×2050×2500	13125
SBA-WC-1500	1200 / 1500	1320 / 1650	12M33D1500E310	301.7	5400×2210×2800	10559
SBA-WC-1562	1250 / 1562	1400 / 1750	16M33D1530E310	301.7	5400×2210×2800	10559
SBA-WC-1625	1300 / 1625	1450 / 1812	16M33D1580E310	339.2	5400×2210×2800	10951
SBA-WC-1750	1400 / 1750	1520 / 1900	16M33D1680E310	339.2	5400×2210×2800	10951
SBA-WC-1875	1500 / 1875	1650 / 2062	16M33D1800E310	377.0	5600×2210×2930	12180
SBA-WC-2000	1600 / 2000	1800 / 2250	16M33D1980E310	377.0	6100×2620×2980	13303
SBA-WC-2250	1800 / 2250	2000 / 2500	20M33D2210E310	453.2	6300×2620×2980	14227
SBA-WC-2500	2000 / 2500	2200 / 2750	12M55D2450E310	503.0	7000×2620×3390	17402
SBA-WC-2750	2200 / 2750	2400 / 3000	12M55D2700E310	554.9	8300×3470×3850	21318
SBA-WC-3000	2400 / 3000	2650 / 3312	16M55D2900E310	554.9	8300×3470×3850	21318
SBA-WC-3250	2600 / 3250	3000 / 3750	16M55D3300E310	605.2	8300×3470×3850	21318
SBA-WC-3750	3000 / 3750	3300 / 4125	16M55D3600E310	605.2	8300×3470×3850	21318

400/230 V (50 Hz) or 480/277 V, 440 V, 380 V (60 Hz), 0.8 pf. Open-frame data shown; silent / containerised versions add length and weight — confirmed per quotation. TBC = to be confirmed on the set datasheet.

Section 2 — Weichai diesel generator sets, 60 Hz

1,800 rpm · for 60 Hz markets

SBA model	Prime kW / kVA	Standby kW / kVA	Engine	Fuel L/h (100% prime)	Open set L×W×H mm	Weight kg
SBA-WC-20-60	16 / 20	17.6 / 22	WP2.3D30E201	7.1	1465×650×1240	668
SBA-WC-30-60	24 / 30	26.4 / 33	WP2.3D41E201	6.0	1600×590×1250	720
SBA-WC-38-60	30 / 38	33 / 41	WP2.3D47E201	10.6	1860×700×1300	800
SBA-WC-50-60	40 / 50	44 / 55	WP2.3D58E201	10.6	1860×700×1300	800
SBA-WC-62-60	50 / 62	55 / 69	WP4.1D80E201	11.6	1860×700×1300	800
SBA-WC-80-60	64 / 80	70.4 / 88	WP4.1D95E201	11.6	1860×700×1300	800
SBA-WC-100-60	80 / 100	88 / 110	WP4.1D115E201	19.8	2350×730×1300	1050
SBA-WC-125-60	100 / 125	120 / 150	WP6D132E201	24.5	2350×750×1300	1150
SBA-WC-150-60	120 / 150	130 / 162	WP6D158E201	26.3	2400×750×1300	1250
SBA-WC-170-60	136 / 170	150 / 188	WP6D180E201	26.3	2400×750×1300	1250
SBA-WC-200-60	160 / 200	176 / 220	WP10D200E201	TBC	2400×750×1300	1250
SBA-WC-225-60	180 / 225	200 / 250	WP10D238E201	TBC	2400×750×1300	1250
SBA-WC-250-60	200 / 250	220 / 275	WP10D264E201	39.6	2450×780×1300	1380
SBA-WC-312-60	250 / 312	280 / 350	WP10D360E201	52.4	3000×960×1565	2090
SBA-WC-375-60	300 / 375	320 / 400	WP13D385E201	TBC	3000×960×1565	2090
SBA-WC-400-60	320 / 400	350 / 438	WP13D448E201	66.7	3100×1380×1780	2450
SBA-WC-438-60	350 / 438	400 / 500	WP13D460E311	TBC	3100×1380×1780	2450
SBA-WC-500-60	400 / 500	440 / 550	WP13D510E311	78.7	3130×1380×1800	2750
SBA-WC-625-60	500 / 625	550 / 688	6M33D670E201	143.9	3650×1500×1850	4200
SBA-WC-675-60	540 / 675	600 / 750	6M33D710E201	143.9	3650×1500×1850	4200
SBA-WC-800-60	640 / 800	700 / 875	12M26D902E201	TBC	4300×1800×2400	7100
SBA-WC-900-60	720 / 900	800 / 1000	12M26D1012E201	TBC	4300×1800×2400	7100
SBA-WC-1125-60	900 / 1125	1000 / 1250	12M33D1265E201	210	4500×1700×2450	8500
SBA-WC-1250-60	1000 / 1250	1100 / 1375	12M33D1320E201	210	4800×1800×2450	9500

SBA-WC-1375-60	1100 / 1375	1200 / 1500	12M33D1420E201	225	5400×2050×2500	13125
SBA-WC-1625-60	1300 / 1625	1450 / 1812	16M33D1680E311	301.7	5400×2210×2800	10559
SBA-WC-1750-60	1400 / 1750	1520 / 1900	16M33D1785E311	339.2	5400×2210×2800	10951
SBA-WC-1875-60	1500 / 1875	1650 / 2062	16M33D1920E311	377.0	5600×2210×2930	12180
SBA-WC-2000-60	1600 / 2000	1800 / 2250	20M33D2230E311	377.0	6100×2620×2980	13303
SBA-WC-2250-60	1800 / 2250	2000 / 2500	20M33D2460E311	453.2	6300×2620×2980	14227
SBA-WC-2500-60	2000 / 2500	2200 / 2750	12M55D2700E311	503.0	7000×2620×3390	17402
SBA-WC-2812-60	2250 / 2812	2500 / 3125	16M55D3150E311	554.9	8300×3470×3850	21318
SBA-WC-3000-60	2400 / 3000	2650 / 3312	16M55D3600E311	554.9	8300×3470×3850	21318

400/230 V (50 Hz) or 480/277 V, 440 V, 380 V (60 Hz), 0.8 pf. Open-frame data shown; silent / containerised versions add length and weight — confirmed per quotation. TBC = to be confirmed on the set datasheet.

Section 3 — Cummins (CCEC) diesel generator sets, 50 Hz

1,500 rpm

SBA model	Prime kW / kVA	Standby kW / kVA	Engine	Fuel L/h (100% prime)	Open set L×W×H mm	Weight kg
SBA-CU-625	500 / 625	550 / 688	KTAA19-G7	128	3684×1454×2000	4700
SBA-CU-712	570 / 712	630 / 788	KTA38-G1B	204	4385×1730×2450	7100
SBA-CU-750	600 / 750	660 / 825	KTA38-G2	204	4385×1730×2450	7100
SBA-CU-800	640 / 800	710 / 888	KTA38-G2B	204	4385×1730×2450	7100
SBA-CU-910	728 / 910	800 / 1000	KTA38-G2A	215	4385×1730×2450	7185
SBA-CU-1000	800 / 1000	880 / 1100	KTA38-G5	228	4374×1785×2229	7667
SBA-CU-1125	900 / 1125	1000 / 1250	KTA38-G9	233	4374×1785×2229	7800
SBA-CU-1250	1000 / 1250	1100 / 1375	KTA50-G3	261	5105×2120×2260	9099
SBA-CU-1375	1100 / 1375	1320 / 1650	KTA50-G8	289	5811×2033×2330	9664
SBA-CU-1675	1340 / 1675	1500 / 1875	KTA50-G15X	336	5811×2033×2330	9664
SBA-CU-1875	1500 / 1875	1650 / 2062	QSK60-G3	363	6175×2286×2537	15152
SBA-CU-2000	1600 / 2000	1800 / 2250	QSK60-G4	412	6175×2286×2537	16210
SBA-CU-2250	1800 / 2250	2000 / 2500	QSK60-G21	412	6175×2286×2537	16210
SBA-CU-2500	2000 / 2500	2200 / 2750	QSK60-G22	412	6175×2286×2537	16210

400/230 V (50 Hz) or 480/277 V, 440 V, 380 V (60 Hz), 0.8 pf. Open-frame data shown; silent / containerised versions add length and weight — confirmed per quotation. TBC = to be confirmed on the set datasheet.

Section 4 — MTU diesel generator sets, 50 Hz

1,500 rpm

SBA model	Prime kW / kVA	Standby kW / kVA	Engine	Fuel L/h (100% prime)	Open set L×W×H mm	Weight kg
SBA-MT-625	500 / 625	550 / 688	12V2000G25	130.1	3550×1414×2200	4500
SBA-MT-750	600 / 750	660 / 825	12V2000G65	165.2	3900×1414×2200	6180
SBA-MT-875	700 / 875	770 / 962	16V2000G25	188.5	4450×1580×2400	7000
SBA-MT-1000	800 / 1000	880 / 1100	16V2000G65	207.3	TBC	7300
SBA-MT-1125	900 / 1125	1000 / 1250	18V2000G65	236.4	4500×1805×2400	7700
SBA-MT-1250	1000 / 1250	1100 / 1375	12V4000G23F	253.7	4562×2200×2515	8775
SBA-MT-1750	1400 / 1750	1550 / 1938	12V4000G63F	357.6	4562×2200×2515	10575
SBA-MT-2000	1600 / 2000	1800 / 2250	16V4000G23F	401.7	5030×2200×2515	13000
SBA-MT-2250	1800 / 2250	2000 / 2500	16V4000G63F	424.3	5030×2200×2515	13400
SBA-MT-2500	2000 / 2500	2200 / 2750	20V4000G23F	468.9	5519×2570×2975	17900
SBA-MT-2750	2200 / 2750	2400 / 3000	20V4000G63F	537.6	6405×2570×2975	18400
SBA-MT-3000	2400 / 3000	2600 / 3250	20V4000G63LF	584.7	6405×2570×2975	18900

400/230 V (50 Hz) or 480/277 V, 440 V, 380 V (60 Hz), 0.8 pf. Open-frame data shown; silent / containerised versions add length and weight — confirmed per quotation. TBC = to be confirmed on the set datasheet.

Section 5 — Transformers, substations & switchgear

- **Oil-immersed distribution transformers**: 50 – 3,150 kVA, 6.6 / 11 / 13.2 / 13.8 / 20 / 22 / 23 / 33 / 34.5 kV primary; Cu or Al windings; ONAN; Dyn11 standard; IEC 60076 (ANSI / local standards on request).
- **Dry-type cast-resin transformers**: up to 2,500 kVA, 11 – 33 kV, class F/H, IP00 or IP21/IP23 enclosure.
- **Package / box substations**: European-type and American-type (pad-mounted), solar step-up units; MV RMU + transformer + LV panel in one enclosure.
- **MV / LV switchgear**: SF6 / air-insulated RMUs, LV distribution panels, ATS 63 – 3,200 A, generator synchronising panels.
- Losses, impedance and dimensions are stated on each quotation and confirmed by the factory routine test report.

Sample routine test report (1,250 kVA, 33 kV): supplybridgeasia.com/downloads/sample-routine-test-report-1250kVA-33kV.pdf

Section 6 — Standard scope, options & documents

- **Generator standard scope**: engine, brushless alternator (Stamford-type / domestic premium brands), digital controller (SmartGen / ComAp / Deep Sea), radiator, battery & charger, base fuel tank, circuit breaker, manuals.
- **Options**: silent canopy, 20/40 ft container, ATS, synchronising panel, remote monitoring, altitude & high-ambient derating packages, tropical / mining spec.
- **Documents with every order**: datasheet, factory load-test report and video, commercial invoice, packing list, certificate of origin, B/L. CE / ISO 8528 compliance; third-party inspection (SGS / BV) on request.
- **Terms**: FOB / CIF; 30% deposit, 70% before shipment; typical lead time 15 – 30 days for standard sets.

Specifications are for selection reference and may change; the quotation and datasheet issued for your order are binding.