

| | |
|--|---|
| Name: John Glen L. Paz | Date Performed: 9/18/2023 |
| Course/Section: CPE 232 - CPE31S6 | Date Submitted: 9/18/2023 |
| Instructor: Dr. Jonathan V. Taylar | Semester and SY: 1st Sem. - 2023 |
| Activity 5: Consolidating Playbook plays | |
| 1. Objectives: 1.1 Use when command in playbook for different OS distributions 1.2 Apply refactoring techniques in cleaning up the playbook codes | |
| 2. Discussion: <p>We are going to look at a way that we can differentiate a playbook by a host in terms of which distribution the host is running. It's very common in most Linux shops to run multiple distributions, for example, Ubuntu shop or Debian shop and you need a different distribution for a one off-case or perhaps you want to run plays only on certain distributions.</p> <p>It is a best practice in ansible when you are working in a collaborative environment to use the command git pull. git pull is a Git command used to update the local version of a repository from a remote. By default, git pull does two things. Updates the current local working branch (currently checked out branch) and updates the remote-tracking branches for all other branches. git pull essentially pulls down any changes that may have happened since the last time you worked on the repository.</p> <p>Requirement: In this activity, you will need to create a CentOS VM. Likewise, you need to activate the second adapter to a host-only adapter after the installations. Take note of the IP address of the CentOS VM. Make sure to use the command ssh-copy-id to copy the public key to CentOS. Verify if you can successfully SSH to CentOS VM.</p> | |
| Task 1: Use when command for different distributions 1. In the local machine, make sure you are in the local repository directory (CPE232_yourname). Issue the command git pull. When prompted, enter the correct passphrase or password. Describe what happened when you issue this command. Did something happen? Why? <pre>jgpaz@workstation:~/Pazsysads6\$ git pull Already up to date.</pre> | |
| 2. Edit the inventory file and add the IP address of the Centos VM. Issue the command we used to execute the playbook (the one we used in the last | |

activity): *ansible-playbook --ask-become-pass install_apache.yml*. After executing this command, you may notice that it did not become successful in the Centos VM. You can see that the Centos VM has failed=1. Only the two remote servers have been changed. The reason is that Centos VM does not support "apt" as the package manager. The default package manager for Centos is "yum."

3. Edit the *install_apache.yml* file and insert the lines shown below.

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        when: ansible_distribution == "Ubuntu"

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
        when: ansible_distribution == "Ubuntu"
```

Make sure to save the file and exit.

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

If you have a mix of Debian and Ubuntu servers, you can change the configuration of your playbook like this.

```
- name: update repository index
  apt:
    update_cache: yes
    when: ansible_distribution in ["Debian", "Ubuntu"]
```

Note: This will work also if you try. Notice the changes are highlighted.

```
jgpaz@workstation:~/Pazsysads6$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with yaml
plugin: YAML inventory has invalid structure, it should be a dictionary, got:
<class 'ansible.parsing.yaml.objects.AnsibleUnicode'>
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with ini plugin:
/home/jgpaz/Pazsysads6/inventory:2: Expected key=value host variable
assignment, got: -mod$
[WARNING]: Unable to parse /home/jgpaz/Pazsysads6/inventory as an inventory
source
[WARNING]: No inventory was parsed, only implicit localhost is available

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [192.168.56.102]

TASK [update repository index] *****
changed: [192.168.56.102]

TASK [install apache2 package] *****
ok: [192.168.56.102]

TASK [add PHP support for apache] *****
ok: [192.168.56.102]

PLAY RECAP *****
192.168.56.102      : ok=4    changed=1    unreachable=0    failed=0    skipped=0    rescue=0
```

4. Edit the *install_apache.yml* file and insert the lines shown below.

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        state: latest
      when: ansible_distribution == "Ubuntu"

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
        state: latest
      when: ansible_distribution == "Ubuntu"

    - name: update repository index
      dnf:
        update_cache: yes
      when: ansible_distribution == "CentOS"

    - name: install apache2 package
      dnf:
        name: httpd
        state: latest
      when: ansible_distribution == "CentOS"

    - name: add PHP support for apache
      dnf:
        name: php
        state: latest
      when: ansible_distribution == "CentOS"
```

Make sure to save and exit.

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

```

jgpaz@workstation:~/Pazsysads6$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with yaml plugin: YAML inventory h
a dictionary, got: <class 'ansible.parsing.yaml.objects.AnsibleUnicode'>
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with ini plugin: /home/jgpaz/Pazsy
key=value host variable assignment, got: -mod$
[WARNING]: Unable to parse /home/jgpaz/Pazsysads6/inventory as an inventory source
[WARNING]: No inventory was parsed, only implicit localhost is available

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [192.168.56.102]

TASK [update repository index] *****
changed: [192.168.56.102]

TASK [install apache2 package] *****
ok: [192.168.56.102]

TASK [add PHP support for apache] *****
ok: [192.168.56.102]

TASK [update repository index] *****
skipping: [192.168.56.102]

TASK [install apache2 package] *****
skipping: [192.168.56.102]


TASK [add PHP support for apache] *****
skipping: [192.168.56.102]

PLAY RECAP *****
192.168.56.102      : ok=4    changed=1    unreachable=0    failed=0    skipped=3    rescu

```

5. To verify the installations, go to CentOS VM and type its IP address on the browser. Was it successful? The answer is no. It's because the httpd service or the Apache HTTP server in the CentOS is not yet active. Thus, you need to

activate it first.



5.1 To activate, go to the CentOS VM terminal and enter the following:

systemctl status httpd

The result of this command tells you that the service is inactive.

```
[jpaz@localhost ~]$ systemctl status httpd
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.
          bled)
   Active: inactive (dead)
     Docs: man:httpd(8)
           man:apachectl(8)
```

5.2 Issue the following command to start the service:

sudo systemctl start httpd

```
led)
Active: active (running) since Mon 2023-09-18 06:
Docs: man:httpd(8)
      man:apachectl(8)
Main PID: 24217 (httpd)
Status: "Total requests: 0; Current requests/sec:
Tasks: 6
CGroup: /system.slice/httpd.service
└─24217 /usr/sbin/httpd -DFOREGROUND
└─24219 /usr/sbin/httpd -DFOREGROUND
└─24220 /usr/sbin/httpd -DFOREGROUND
└─24221 /usr/sbin/httpd -DFOREGROUND
└─24222 /usr/sbin/httpd -DFOREGROUND
└─24223 /usr/sbin/httpd -DFOREGROUND

sp 18 06:20:47 localhost.localdomain systemd[1]: St
sp 18 06:20:47 localhost.localdomain httpd[24217]:
sp 18 06:20:47 localhost.localdomain systemd[1]: St
int: Some lines were ellipsized, use -l to show in
jpaz@localhost ~]$
```


(When prompted, enter the sudo password)

sudo firewall-cmd --add-port=80/tcp

(The result should be a success)

```
[jpaz@localhost ~]$ sudo firewall-cmd --add-port=80/tcp
success
```

5.3 To verify the service is already running, go to CentOS VM and type its IP address on the browser. Was it successful? (Screenshot the browser)



Task 2: Refactoring playbook

This time, we want to make sure that our playbook is efficient and that the codes are easier to read. This will also makes run ansible more quickly if it has to execute fewer tasks to do the same thing.

1. Edit the playbook *install_apache.yml*. Currently, we have three tasks targeting our Ubuntu machines and 3 tasks targeting our CentOS machine. Right now, we try to consolidate some tasks that are typically the same. For example, we can consolidate two plays that install packages. We can do that by creating a list of installation packages as shown below:

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index Ubuntu
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        when: ansible_distribution == "Ubuntu"

    - name: update repository index for CentOS
      dnf:
        update_cache: yes
        when: ansible_distribution == "CentOS"

    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        when: ansible_distribution == "CentOS"
```

Make sure to save the file and exit.

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

```
jgpaz@workstation:~/Pazsysads6$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with yaml plugin: YAML inventory h
a dictionary, got: <class 'ansible.parsing.yaml.objects.AnsibleUnicode'>
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with ini plugin: /home/jgpaz/Pazsy
key=value host variable assignment, got: -mod$
[WARNING]: Unable to parse /home/jgpaz/Pazsysads6/inventory as an inventory source
[WARNING]: No inventory was parsed, only implicit localhost is available

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [192.168.56.102]

TASK [update repository index Ubuntu] *****
changed: [192.168.56.102]

TASK [install apache2 package and php packages for Ubuntu] *****
ok: [192.168.56.102]

TASK [update repository index for CentOS] *****
skipping: [192.168.56.102]

TASK [install apache and php packages for CentOS] *****
skipping: [192.168.56.102]

PLAY RECAP *****
192.168.56.102      : ok=3    changed=1    unreachable=0    failed=0    skipped=2    rescu
```

2. Edit the playbook *install_apache.yml* again. In task 2.1, we consolidated the plays into one play. This time we can actually consolidated everything in just 2 plays. This can be done by removing the update repository play and putting the command *update_cache: yes* below the command *state: latest*. See below for reference:

```
---
- hosts: all
  become: true
  tasks:

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        update_cache: yes
      when: ansible_distribution == "CentOS"
```

Make sure to save the file and exit.

Run `ansible-playbook --ask-become-pass install_apache.yml` and describe the result.

```
jgpaz@workstation:~/Pazsysads6$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with yaml plugin: YAML inventory
a dictionary, got: <class 'ansible.parsing.yaml.objects.AnsibleUnicode'>
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with ini plugin: /home/jgpaz/Pazs
key=value host variable assignment, got: -mod$
[WARNING]: Unable to parse /home/jgpaz/Pazsysads6/inventory as an inventory source
[WARNING]: No inventory was parsed, only implicit localhost is available

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [192.168.56.102]

TASK [install apache2 and php packages for Ubuntu] *****
ok: [192.168.56.102]

TASK [install apache and php packages for CentOS] *****
skipping: [192.168.56.102]

PLAY RECAP *****
192.168.56.102      : ok=2    changed=0    unreachable=0    failed=0    skipped=1    resc
```

3. Finally, we can consolidate these 2 plays in just 1 play. This can be done by declaring variables that will represent the packages that we want to install. Basically, the `apache_package` and `php_package` are variables. The names are arbitrary, which means we can choose different names. We also take out the line `when: ansible_distribution`. Edit the playbook `install_apache.yml` again and make sure to follow the below image. Make sure to save the file and exit.

```
--
- hosts: all
  become: true
  tasks:

  - name: install apache and php
    apt:
      name:
        - "{{ apache_package }}"
        - "{{ php_package }}"
      state: latest
      update_cache: yes
```

Run `ansible-playbook --ask-become-pass install_apache.yml` and describe the result.

```
jgpaz@workstation:~/Pazsysads6$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with yml plugin: YAML inventory h
a dictionary, got: <class 'ansible.parsing.yaml.objects.AnsibleUnicode'>
[WARNING]: * Failed to parse /home/jgpaz/Pazsysads6/inventory with ini plugin: /home/jgpaz/Pazsy
key=value host variable assignment, got: -mod$
[WARNING]: Unable to parse /home/jgpaz/Pazsysads6/inventory as an inventory source
[WARNING]: No inventory was parsed, only implicit localhost is available

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [192.168.56.102]

TASK [install apache and php] *****
Fatal: [192.168.56.102]: FAILED! => {"msg": "The task includes an option with an undefined variab
is undefined\n\nThe error appears to be in '/home/jgpaz/Pazsysads6/install_apache.yml': line 6, c
e file depending on the exact syntax problem.\n\nThe offending line appears to be:\n\n - name:
n")

PLAY RECAP *****
192.168.56.102 : ok=1 changed=0 unreachable=0 failed=1 skipped=0 rescu
```

4. Unfortunately, task 2.3 was not successful. It's because we need to change something in the inventory file so that the variables we declared will be in place. Edit the *inventory* file and follow the below configuration:

```
192.168.56.120 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.121 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.122 apache_package=httpd php_package=php
```

Make sure to save the *inventory* file and exit.

Finally, we still have one more thing to change in our *install_apache.yml* file. In task 2.3, you may notice that the package is assign as *apt*, which will not run in CentOS. Replace the *apt* with *package*. Package is a module in ansible that is generic, which is going to use whatever package manager the underlying host or the target server uses. For Ubuntu it will automatically use *apt*, and for CentOS it will automatically use *dnf*. Make sure to save the file and exit. For more details about the ansible package, you may refer to this documentation: [ansible.builtin.package – Generic OS package manager — Ansible Documentation](#)

Run *ansible-playbook --ask-become-pass install_apache.yml* and describe the result.

```
jgpaz@workstation:~/Pazsysads6$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [jgpaz@192.168.56.104]
ok: [192.168.56.102]
ok: [192.168.56.103]

TASK [install apache and php] *****
ok: [192.168.56.102]
ok: [192.168.56.103]
ok: [jgpaz@192.168.56.104]

PLAY RECAP *****
192.168.56.102      : ok=2    changed=0    unreachable=0    failed=0    skipped=0    res
192.168.56.103      : ok=2    changed=0    unreachable=0    failed=0    skipped=0    res
jgpaz@192.168.56.104 : ok=2    changed=0    unreachable=0    failed=0    skipped=0    res
```

Supplementary Activity:

1. Create a playbook that could do the previous tasks in Red Hat OS.

Reflections:

Answer the following:

1. Why do you think refactoring of playbook codes is important?
 - Refactoring of playbook codes is important because it helps improve the quality of the codebase, making it easier to maintain, understand, and scale.
2. When do we use the "when" command in playbook?
 - Is applied to task to add conditional statements. It only permits you to carry out an activity when a specific requirement is satisfied. The "when" command accepts a Boolean expression that is dependent on a value or variable from earlier jobs or information obtained from the remote hosts.

Conclusion:

In this activity, it gave us an understanding on the use of the "when" command in the playbook for adding conditional statements to tasks. Recognizing the advantages of refactoring in raising the codebase's quality. To improve playbook codes' maintainability, readability, performance, and scalability, learn how to utilize refactoring techniques. Overall, while doing this activity, I struggle a lot since I didn't recognize the error at first and it really pissed me off because my error is only to install the python3 in CentOS but I managed to finish it and pass it within the day.

