

Exam — QA automation framework

Closed book. Circle one letter. Part A is 15 points. Part B is 5 points. Total 20. Time: 40 minutes.

Name

Date

Score / 20

Part A — Selection

- Guest tests in `tests/ui/home.spec.js` import test from:
 - `fixtures/auth.fixtures.js`
 - `fixtures/test.fixtures.js`
 - `@playwright/test` only
 - `utils/session.js`
- Code after `await use(...)` in a fixture runs:
 - Before the test body
 - After the test, including when the test fails
 - Only when the test passes
 - Once per file, before any test
- `homePage` in `fixtures/auth.fixtures.js` is built from:
 - The default guest page
 - `authenticatedPage`
 - A context with an empty cookie jar
 - `freshSession.page`
- Two pages opened from the same browser context:
 - Are two different logged-in users
 - Share cookies, so they are one session
 - Each get a new `storageState`
 - Require two browser processes
- `openTwoSessions` starts both signups with `Promise.allSettled` because:
 - `Promise.all` cannot start two async functions
 - If one signup fails, the one that succeeded can still be cleaned up
 - `allSettled` cancels the slower signup
 - `allSettled` hides the error
- Both home pages are opened with `Promise.all`. That fits when:
 - Every cleanup must finish even if one throws
 - The first success is enough and failures can be ignored
 - Both actions should succeed
 - You want whichever call finishes first
- Which helper fulfills on the first success and ignores earlier rejections, unless every task rejects?
 - `Promise.all`
 - `Promise.allSettled`
 - `Promise.race`
 - `Promise.any`
- `Promise.race` is a poor way to wait for mail because it:
 - Waits for every search to finish
 - Settles on the first result, so an empty search can win before the message arrives
 - Marks the whole inbox as seen
 - Accepts only two promises

9. A test that clicks Logout uses `freshSession` because it:
- A Reuses `auth/user.json`
 - B Creates a throwaway user and deletes that account afterwards
 - C Types into the login form
 - D Shares cookies with `authenticatedPage`
10. `chromium-auth` depends on the `setup` project so that:
- A Guest home tests receive the shared cookies
 - B `auth/user.json` exists before logged-in specs run
 - C Two-context tests load the shared session
 - D The mailbox connects before the browser starts
11. The `two-contexts` project does not depend on `setup` because:
- A It must not load the shared account from `auth/user.json`
 - B A second context cannot be opened after `setup`
 - C `Setup` deletes every user on the site
 - D Those tests log in through the login form
12. `generateUniqueEmail` adds random bytes as well as the time because:
- A The site rejects emails that contain only digits
 - B Two signups in the same millisecond must not share an address
 - C IMAP allows only 16-character local parts
 - D Playwright requires a unique domain
13. With no `IMAP_HOST`, `IMAP_USER`, or `IMAP_PASSWORD`, the mail project:
- A Fails the Monday job
 - B Is dropped from `npm run test:ci`
 - C Skips the live mailbox check, and the rest of the suite can still pass
 - D Logs the mailbox password and continues
14. Which `playwright.config.js` pair matches this project?
- A `trace: 'on', screenshot: 'on'`
 - B `trace: 'on-first-retry', screenshot: 'only-on-failure'`
 - C `trace: 'off', screenshot: 'on'`
 - D `trace: 'retain-on-failure', screenshot: 'on-first-retry'`
15. The workflow `cron 0 8 * * 1` means:
- A Every day at 08:00 local time
 - B Monday at 08:00 UTC, and `npm run test:ci` runs every project
 - C The first day of the month at 08:00
 - D Eight minutes past every hour on Monday

Part B — Short task (5 points)

`allSettledOrThrow` in `utils/promises.js` runs every task, waits until all of them settle, then throws the first rejection in task order. Session cleanup already uses it.

Write `closeBoth`. If `contextA.close()` throws, `contextB.close()` still runs, and the error is still thrown. Do not use `Promise.all`. Do not await one close and then the other.

```
import { allSettledOrThrow } from './promises.js';
```

```
export async function closeBoth(contextA, contextB) {
```

```
_____  
_____  
_____  
_____  
_____
```

```
}
```