

AQUAPANEL® Tape (10 cm)

Glass fabric joint tape with alkali-resistant coating

AQUAPANEL®

Description

AQUAPANEL® Tape (10 cm) is a glass fibre tape with an alkali-resistant coating. It is used to reinforce joints on walls, ceilings and floors (only AQUAPANEL® Floor Tile Underlay) in interior areas and on walls and ceilings in exterior areas.

Technical data

Weight/unit area	approx. 160 g/m²	approx. 160 g/m²
Mesh size	4 x 4 mm	4 x 4 mm
Initial tear strength	approx. 2200 N/5 cm	approx. 2200 N/5 cm
Thickness	approx. 0.5 mm	approx. 0.5 mm
Width	10 cm	10 cm
Length	20 m	50 m
Colour	blue	blue

Processing/application

Fill joints with AQUAPANEL® Joint Filler & Skim Coating – white (interior walls and ceilings on AQUAPANEL® Cement Board Indoor), AQUAPANEL® Joint Filler – grey (exterior ceilings and walls on AQUAPANEL® Cement Board Outdoor), AQUAPANEL® SkyLite Joint Filler & Skim Coating (exterior and interior ceilings on AQUAPANEL® Cement Board SkyLite), or tile adhesive (interiors on AQUAPANEL® Cement Board Floor Tile Underlay) and embed AQUAPANEL® Tape (10 cm).

Material coverage

Approx. 2.1 m/m²

Method of delivery/storage

100 mm wide rolls x 20 m long. 18 rolls/carton.
Item code: 465546

100 mm wide rolls x 50 m long. 12 rolls/carton.
Item code: 429471

Store in a dry place and protect from moisture.

AQUAPANEL®

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

www.AQUAPANEL.com
aquapanel.info@knauf.com

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany

© 2017 EN-08/17

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. The constructional and structural properties and characteristic building physics of Knauf systems can solely be ensured with the exclusive use of Knauf system components, or other products expressly recommended by Knauf. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany.