SKYROCK®

REGULAR GYPSUM BOARD

9.5mm, 12.5mm and 15mm



INTRODUCTION

DESCRIPTION

Skyrock® Regular Gypsum Board is asbestos free products. Produced in standard dimension 1200mm x 2400mm composed of a noncombustible gypsum core and encased in a heavy natural-finish paper on the face side and a strong liner paper on the back side. The face paper is folded around the long edges to reinforced and protect the core. Board ends are square cut and finished smooth. Long edges of panels are recessed (tapered) allowing joints to be reinforced and concealed with a joint treatment.

FEATURES & BENEFITS

- Ideal for standards interior wall and ceiling panels
- Economical grade gypsum board
- Quick installation and decoration

INTENDED FOR

- Commercial or residential applications where regular panels are desired
- New or repair and remodel construction
- Non-fire-rated steel-framed wall and ceiling applications

PRODUCT DATA

Property			
Thickness*	9.5 mm	12.5 mm	15 mm
Weight[1], nominal	6.2 kg/m^2	8.1 kg/m^2	9.8 kg/m^2
Lengths[2]	2400 mm	2400 mm	2400 mm
Width	1200 mm	1200 mm	1200 mm
Edges	Tapered	Tapered	Tapered
Packaging	Two panels per bundle	Two panels per bundle	Two panels per bundle
Surface-burning characteristics per ASTM E84	Class A	Class A	Class A

Notes:
* 16mm thickness is available upon request please contact the nearest sales office.
1. Represents approximate weight for design and shipping purposes.
2. Other sizes available by special order.

COMPLIANCE

Comply with:

- ASTM C1396, DIN EN 520 for Dimensions and Flexural Strength

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma