
SKYROCK®


SOUNDBLOCK - Q12


Perforated Gypsum Tile

VISIT USGME.COM TO ORDER SAMPLES

PATTERN








FEATURES & BENEFITS


- 12mm Square perforation Gypsum Ceiling tiles with acoustic back fleece for high acoustic performance.
- Available in laminated and painted surface finish options.
- Various edges for modern and aesthetic look.
- Ultra-high humidity resistant; sag resistance ensures durability in standard or extreme environmental conditions.
- Scrub resistant. Dirt marks are easy to remove.
- Durable, scuff, and scratch resistant for longer life.
- Suitable for areas with high humidity.
- Economical and easy to trim and install.
- Demountable and designed to be installed on the DONN® Brand acoustical ceiling suspensions.

APPLICATION

- Schools
- Commercial retails
- Department stores
- Hotels
- Malls & residential

TILE AND EDGE DETAILS





Open Area 18% - 19.2%

SKYROCK®

SOUNDBLOCK - Q12





PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

CEILING ATTENUATION CLASS

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			NRC	CAC					>	$
SQ	GT-PS662-Q12 GT-PS622-Q12	600*600*12.5 600*1200*12.5	0.75		88%			7%	Low	$$$$
	LG-S662-Q12 LG-S622-Q12	600*600*12.5 600*1200*12.5	0.75		84%			7%	Low	$$$$
SL	GT-PSR662-Q12 GT-PSR622-Q12	600*600*12.5 600*1200*12.5	0.75		88%			7%	Low	$$$$
	LG-SR662-Q12 LG-SR622-Q12	600*600*12.5 600*1200*12.5	0.75		84%			7%	Low	$$$$
FL	GT-PSRF662-Q12 GT-PSRF622-Q12	600*600*12.5 600*1200*12.5	0.75		88%			7%	Low	$$$$
	LG-SRF662-Q12 LG-SRF622-Q12	600*600*12.5 600*1200*12.5	0.75		84%			7%	Low	$$$$

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DX/DXL SL Edge	DXT FL Edge	DXF FL Edge
			

SPECIFICATION DETAILS

Soundblock Q12 Ceiling Tile meets specifications in accordance with ASTM E1264.

Materials Classification
Type: XX,
Pattern: A

Substrate and Surface Finish
Laminated: Gypsum ceiling panel laminated with vinyl-faced
Painted: Gypsum ceiling panel finished with factory-applied water-based paint

Thickness
12.5mm

Size
600 x 600mm, 600 x 1200mm

Edge Detail Trim
Square, Reveal [SL, FL]

Weight
6.4 kg/m²

Open Area
600 x 600mm: 18%
600 x 1200mm: 19.2%

Noise Reduction Coefficient [NRC]
up to 0.75*

Mold Prevention
Inherent to Mold/Mildew growth panels are available upon request

Humidity Resistance
Maximum 95% RH / 40°C

Light Reflectance Coefficient [LR]
Laminated: 0.84
Painted: 0.88

Color
Laminated: White similar to RAL 9003
Painted: Matt White similar to RAL 9016

Surface Burning Characteristics as per ASTM E84
Laminated: Class A
Painted: Class A

Thermal Resistance
R 0.45

Washability / Scrubbability as per ASTM D4828 & D2486
Laminated: Exceeds 1000 Wash/Scrub Cycles without surface break or the extent of abrasion

Formaldehyde Classification
Class E1 as per EN717-1

** Using factory applied acoustical backer. Higher acoustic value can be achieved with additional Fiber glass/Stone wool backer panel*

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma

Notice: As we are involved in constant products development; this document information is subject to change without prior notice.
Please always refer to **usgme.com** for the updated products information document.
©2023 **Factory of USG Middle East LTD. Co.** All rights reserved.