OLYMPIA™



VISIT USGME.COM TO ORDER SAMPLES

FEATURES & BENEFITS

- Finely granulated surface texture.
- High light reflectance finish (up to LR-0.88) reduces wear and tear on light fixtures and energy use.
- Economical, non-directional pattern reduces installation time and waste.
- Fire resistant system options for life safety and protection of property.
- Available also in ClimaPlus™ formulation for 99% humidity resistance and various plank sizes.
- Available in Pedestal edge for 19mm thickness.

APPLICATIONS

- Reception
- Commercial stores
- Libraries
- Banks
- Fitness rooms
- Corridors/stairwell
- Waiting area
- Nursery
- Retail stores

Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
15mm	0.35	**0.25**	**0.15**	**0.15**	**0.20**	0.30	**0.15**

**Calculated to ASTM C 423-01*

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

OLYMPIA PEDESTAL EDGE



OLYMPIA™

EN 13964 : 2014 + A1 : 2007

CEILING ATTENUATION CLASS

FIRECODE

HIGH RECYCLED CONTENT

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			NRC	CAC						
SQ	OLS665 OLS225	600*600*15 610*610*15	0.15	33	86%			25%	Low	$
	OLC665 OLC225	600*600*15 610*610*15	0.15	33	88%	●		39%	Low	$
	OLC625 OLC245	600*1200*15 610*1220*15	0.15	33	88%	●		39%	Low	$
	OLX665 OLX225	600*600*15 610*610*15	0.15	35	86%		●	56%	Low	$$
PLANKS	OLC325 OLC145	300*1200*15 310*1220*15	0.15	33	88%	●		39%	Low	$$$
	OLS669 OLS229	600*600*19 610*610*19	0.15	37	86%			25%	Low	$$$
	OLC669 OLC229	600*600*19 610*610*19	0.15	37	88%	●		39%	Low	$$$
PLANKS	OLC359 OLC159	300*1500*19 310*1520*19	0.15	37	88%	●		39%	Low	$$$$
SLT	OLSR665 OLSR225	600*600*15 610*610*15	0.15	33	86%			25%	Low	$
	OLCR665 OLCR225	600*600*15 610*610*15	0.15	33	88%	●		39%	Low	$
PLANKS	OLCR325 OLCR145	300*1200*15 310*1220*15	0.15	33	88%	●		39%	Low	$$$
	OLSR669 OLSR229	600*600*19 610*610*19	0.15	37	86%			25%	Low	$$$
	OLC629 OLC249	600*1200*19 610*1220*19	0.15	37	88%	●		39%	Low	$$$
	OLCR629 OLCR245	600*1200*19 610*1220*19	0.15	37	88%	●		39%	Low	$$$
FLB	OLSRF665 OLSRF225	600*600*15 610*610*15	0.15	33	86%			25%	Low	$
	OLCRF665 OLCRF225	600*600*15 610*610*15	0.15	33	88%	●		39%	Low	$
PLANKS	OLCRF325 OLCRF145	300*1200*15 310*1220*15	0.15	33	88%	●		39%	Low	$$$
	OLSRF669 OLSRF229	600*600*19 610*610*19	0.15	37	86%			25%	Low	$$$
	OLXR629 OLXR249	600*1200*19 610*1220*19	0.15	37	86%		●	56%	Low	$$$
	OLCRF629 OLCRF249	600*1200*19 610*1220*19	0.15	37	88%	●		39%	Low	$$$
PEDESTAL	DP1OLCRI669 DP1OLCRI229	600*600*19 610*610*19	0.15	37	88%	●		39%	Low	$$$
	DP4OLCRI669 DP4OLCRI229	600*600*19 610*610*19	0.15	37	88%	●		39%	Low	$$$

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.
For firechief products.

OLYMPIA™







EN 13964 : 2014 + A1 : 2007

CEILING ATTENUATION CLASS

FIRECODE

HIGH RECYCLED CONTENT

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge	DX/DXL SLT Edge	DXT FLB Edge	DXF FLB Edge	DXT PEDESTAL
					

SPECIFICATION DETAILS

Olympia™ Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

Materials Classification
Type: III,
Form: 2,
Pattern: E

Substrate and Surface Finish
Mineral fiber substrate finished with factory-applied water-based paint

Thickness
15mm, 19mm

Size
300 x 1200mm, 310 x 1220mm, 300 x 1500mm, 310 x 1520mm, 600 x 600mm, 610 x 610mm, 600 x 1200mm, 610 x 1220mm

Edge Detail Trim
Square,
Reveal [SLT, FLB, Pedestal]

Weight
15mm [3.6 kg/m², Regular/ ClimaPlus™],
15mm [5.1 kg/m², Firecode®],
19mm [4.5 kg/m², Regular/ ClimaPlus™],
19mm [6.45 kg/m², Firecode®]

Noise Reduction Coefficient [NRC]
[0.15]

Ceiling Attenuation Class [CAC]
[35 - 37 dB]

Humidity Resistance
Maximum 99% RH / 40°C for ClimaPlus™

Light Reflectance Coefficient [LR]
0.86-0.88

Color
White similar to RAL 9016

Surface Burning Characteristics as per ASTM E84
Class A

Reaction to Fire as per EN 13501-1
Euroclass A2-s1, d0

Fire Rating as per ASTM E119
2hrs Time-Rated Assembly [J201]

Thermal Conductivity
λ = 0.057 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

Formaldehyde Classification
Class E1 as per EN717-1

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma