CEILINGS

OLYMPIA MICRO™



VISIT USGME.COM TO ORDER SAMPLES

FEATURES & BENEFITS

- Balanced Acoustics. High-NRC and High-CAC.
- Excellent combination of noise reduction (up to NRC-0.70) and sound attenuation (up to CAC-37).
- Excellent for critical lighting applications that require High Light Reflectance (0.88).
- High Humidity Resistance up to RH-99%.
- Light granulated surface texture with virtually invisible micro-perforation for a smoother look than standard perforations. Improves sound absorption. Reduces light fixture & energy usage.
- Fire resistant system options for life safety and protection of property.
- Available in HRC (High Recycled Content) for optimized recycled content formulations to help maximize LEED® recycled content contribution and sound absorption.
- Ideal solutions for classroom and educational facilities.
- Upon request, panel faces and back surfaces are treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits mold growth.

APPLICATIONS

- Classrooms
- Libraries
- Corridors and stairwell
- Reception and lobby areas
- Restaurant and cafe
- Sports hall
- General offices
- Shopping centers

Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
15mm	0.35	**0.35**	**0.50**	**0.65**	**0.60**	0.50	**0.55**
19mm	0.30	**0.45**	**0.70**	**0.70**	**0.70**	0.60	**0.65**
19mm HNRC	0.45	**0.50**	**0.75**	**0.85**	**0.80**	0.65	**0.70**

**Calculated to ASTM C 423-01*

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.



OLYMPIA MICRO™

EN 13964 : 2014 + A1 : 2007

TABLE OF PERFORMANCE

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS

HIGH SOUND ABSORPTION

CEILING ATTENUATION CLASS

FIRECODE

AVAILABLE IN CONCEALED EDGE

HIGH RECYCLED CONTENT

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			NRC	CAC						
SQ	OLPS665 OLPS225	600*600*15 610*610*15	0.55	35	88%			25%	Low	$
	OLPC665 OLPC225	600*600*15 610*610*15	0.55	35	88%	✓		39%	Low	$
	OLPC625 OLPC245	600*1200*15 610*1220*15	0.55	35	88%	✓		39%	Low	$
	OLPX665 OLPX225	600*600*15 610*610*15	0.55	36	88%		✓	56%	Low	$$
	OLPX625 OLPX245	600*1200*15 610*1220*15	0.55	36	88%		✓	56%	Low	$$
	OLPC325 OLPC145	300*1200*15 310*1220*15	0.55	35	88%	✓		39%	Low	$$
	OLPC669-HNRC OLPC229-HNRC	600*600*19 610*610*19	0.70	37	88%	✓		82%	Low	$$$
	OLPS669 OLPS229	600*600*19 610*610*19	0.65	37	88%			25%	Low	$$
	OLPC329 OLPC349	300*1200*19 310*1220*19	0.65	37	88%	✓		39%	Low	$$
	OLPC629-HNRC OLPC249-HNRC	600*1200*19 610*1220*19	0.70	37	88%	✓		82%	Low	$$$
SLT	OLPSR665 OLPSR225	600*600*15 610*610*15	0.55	35	88%			25%	Low	$
	OLPCR665 OLPCR225	600*600*15 610*610*15	0.55	35	88%	✓		39%	Low	$
	OLPSR669 OLPSR229	600*600*19 610*610*19	0.65	37	88%			25%	Low	$$
	OLPCR669-HNRC OLPCR229-HNRC	600*600*19 610*610*19	0.70	37	88%	✓		82%	Low	$$$
	OLPXR629 OLPXR249	600*1200*19 610*1220*19	0.65	37	88%		✓	56%	Low	$$$
	OLPCR629-HNRC OLPCR249-HNRC	600*1200*19 610*1220*19	0.70	37	88%	✓		82%	Low	$$$
FLB	OLPSRF665 OLPSRF225	600*600*15 610*610*15	0.55	35	88%			25%	Low	$
	OLPCRF665 OLPCRF225	600*600*15 610*610*15	0.55	35	88%	✓		39%	Low	$$
	OLPCRF325 OLPCRF145	300*1200*15 310*1220*15	0.55	35	88%	✓		39%	Low	$$
	OLPSRF669 OLPSRF229	600*600*19 610*610*19	0.65	37	88%			25%	Low	$$
	OLPCRF669-HNRC OLPCRF229-HNRC	600*600*19 610*610*19	0.70	37	88%	✓		82%	Low	$$$
	OLPCRF629-HNRC OLPCRF249-HNRC	600*1200*19 610*1220*19	0.70	37	88%	✓		82%	Low	$$$
	OLPCRF329 OLPCRF349	300*1200*19 310*1220*19	0.65	37	88%	✓		39%	Low	$$$
BESK	OLPXC665	600*600*15	0.55	36	88%		✓	56%	Low	$$$$
	OLPXC669	600*600*19	0.65	37	88%		✓	56%	Low	$$$$
D-BESK	OLPXRFDC325	300*1200*15	0.55	35	88%		✓	56%	Low	$$$$
	OLPXRFDC355	300*1500*15	0.55	35	88%		✓	56%	Low	$$$$
	OLPXRFDC385	300*1800*15	0.55	35	88%		✓	56%	Low	$$$$
	OLPXRFDC625	600*1200*15	0.55	35	88%		✓	56%	Low	$$$$

OLYMPIA MICRO™

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS

HIGH SOUND ABSORPTION

CEILING ATTENUATION CLASS

FIRECODE

AVAILABLE IN CONCEALED EDGE

HIGH RECYCLED CONTENT







TABLE OF PERFORMANCE



Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			NRC	CAC						$
D-BESK	OLPXRFDC655	600*1500*15	0.55	35	88%			56%	Low	$$$$
	OLPXRFDC685	600*1800*15	0.55	35	88%			56%	Low	$$$$
	OLPXRFDC329	300*1200*19	0.65	37	88%			56%	Low	$$$$
	OLPXRFDC359	300*1500*19	0.65	37	88%			56%	Low	$$$$
	OLPXRFDC389	300*1800*19	0.65	37	88%			56%	Low	$$$$
	OLPXRFDC629	600*1200*19	0.65	37	88%			56%	Low	$$$$
	OLPXRFDC659	600*1500*19	0.65	37	88%			56%	Low	$$$$
	OLPXRFDC689	600*1800*19	0.65	37	88%			56%	Low	$$$$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health (CDPH) Standard Method V1.2-2017 using a Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. UL. Tests are available on usgme.com and at spot.ul.com

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.
For firechief products.

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge	DX/DXL SLT Edge	DXT FLB Edge	DXF FLB Edge	DXI FLB Edge
					

DX/DXL BESK Edge	DX/DXL D-BESK Edge
	

SPECIFICATION DETAILS

Olympia Micro™ Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

Materials Classification
Type: III,
Form: 2,
Pattern: C, E

Substrate and Surface Finish
Mineral fiber substrate finished with factory-applied water-based paint

Thickness
15mm, 19mm

Size
300 x 1200mm, 310 x 1220mm,
300 x 1500mm, 310 x 1520mm,
300 x 1800mm, 310 x 1830mm,
600 x 600mm, 610 x 610mm,
600 x 1200mm, 610 x 1220mm,
600 x 1500mm, 610 x 1520mm,
600 x 1800mm, 610 x 1830mm

Edge Detail Trim
Square, Reveal [SLT, FLB],
Concealed [BESK, D-BESK]

Weight
15mm [3.6 kg/m², Regular/ ClimaPlus™]
15mm [5.1 kg/m², Firecode®]
19mm [4.5 kg/m², Regular/ ClimaPlus™]
19mm [6.45 kg/m², Firecode®]

Noise Reduction Coefficient [NRC]
[0.55] [0.65] [0.70]

Ceiling Attenuation Class [CAC]
[35 - 37 dB]

Humidity Resistance
Maximum 99% RH / 40°C for ClimaPlus™

Light Reflectance Coefficient [LR]
0.88

Color
White similar to RAL 9016

Surface Burning Characteristics as per ASTM E84
Class A

Reaction to Fire as per EN 13501-1
Euroclass A2-s1, d0

Fire Rating as per ASTM E119
2hrs Time-Rated Assembly [J201]

Thermal Conductivity
λ = 0.057 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

VOC Class
Greenguard Gold

Formaldehyde Classification
Class E1 as per EN717-1

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 |
MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 |
IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma