CEILINGS

LOUNA™ NATURAL



VISIT USGME.COM TO ORDER SAMPLES

FINISH OPTIONS

White

FEATURES & BENEFITS

- Specially engineered for cost-effective commercial projects that require improved sound absorption and a quality aesthetic look.
- Stone Wool substrate with monolithic white surface and mineral fleece membrane on the backside.
- High sound absorption with NRC values up to 0.95.
- High light reflectance (LR-0.88) reduces wear and tear on light fixtures and energy use.
- Moisture resistant to withstand severe conditions when used with DONN® brand suspension system.
- Eco-friendly mineral wool product made from natural stone.
- Washable & scrubbable finish.

APPLICATIONS

- Commercial offices
- Warehouses and parking lots
- Offices with indirect lighting
- Restaurants and cafes
- Schools
- Reception areas
- Libraries

Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
15mm	0.60	**0.85**	**0.80**	**0.95**	**1.0**	1.0	**0.90**
19mm	0.60	**0.90**	**0.85**	**1.0**	**1.0**	1.0	**0.95**

**Calculated to ASTM C 423-01*

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

LOUNA™ NATURAL

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

HIGH SOUND ABSORPTION

FIRECODE



TABLE OF PERFORMANCE

Edge Detail*	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold /Mildew & Sag Resistance	Fire Rating**	Recycled Content	VOC Emission	Cost
			NRC	CAC					>	$
SQ	LNC665 LNC225	600*600*15 610*610*15	0.90	-	88%		Class A	47%	N/A	$$
	LNC625 LNC245	600*1200*15 610*1220*15	0.90	-	88%		Class A	47%	N/A	$$
	LNC669 LNC229	600*600*19 610*610*19	0.95	25	88%		Class A	47%	N/A	$$
	LNC629 LNC249	600*1200*19 610*1220*19	0.95	25	88%		Class A	47%	N/A	$$

* Other edge details are available upon request and subject to minimum order quantity

** To ASTM E84

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge
	

SPECIFICATION DETAILS

Louna™ Natural Acoustical Ceiling meets specifications in accordance with ASTM E1264.

Materials Classification
Type: XX,
Pattern: G

Substrate and Surface Finish
Stone Wool substrate laminated with prepainted fiberglass scrim and back fiberglass tissue

Thickness
15mm, 19mm

Size
600 x 600mm, 610 x 610mm,
600 x 1200mm, 610 x 1220mm

Edge Detail Trim
Standard, Square.
Other edges are available upon request

Weight
15mm: 1.8 kg/m²
19mm: 2.28 kg/m²

Noise Reduction Coefficient [NRC]
[0.90] [0.95]

Ceiling Attenuation Class [CAC]
[25 dB]

Mold Prevention Application as per ASTM D3273
Rate 10

Humidity Resistance
Maximum 99% RH / 40°C for ClimaPlus™

Light Reflectance Coefficient [LR]
0.88

Color
Standard White similar to RAL 9016.
Other colors are available upon request

Surface Burning Characteristics as per ASTM E84
Class A

Thermal Conductivity
λ = 0.036 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma