HALCYON™



VISIT USGME.COM TO ORDER SAMPLES

FINISH OPTIONS

White, Light Grey, Dark Grey, Yellow, Green, Blue, Brown, Black

FEATURES & BENEFITS

- Fiberglass substrate with monolithic visual reduces installation time.
- Exceptional sound absorption with NRC values up to 1.
- Certificated for Environmental Product Declaration (EPD) as per ISO 14025.
- Elegant and refined acoustical facing and high performance mineral fleece membrane on the backside.
- High light reflectance (LR-0.88) reduces light fixture & energy use.
- Washable & scrubbable finish.
- Available in concealed edges D-Besk & S-Besk.
- Impact & scratch resistant.
- Available in plank sizes compatible with Logix™ integrated ceiling System.
- Available in black for ideal application in cinemas and theaters.

APPLICATIONS

- Open-plan areas
- Offices with indirect lighting
- Media rooms
- Receptions & lobby areas
- Libraries
- Convention halls and concourses
- Cinemas and theaters

Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
19mm	0.50	**0.90**	**1.0**	**0.90**	**0.95**	0.90	**0.95**
19mm Concealed	0.65	**0.85**	**0.80**	**0.95**	**1.0**	1.0	**0.95**
25mm	0.40	**0.90**	**1.0**	**0.95**	**1.0**	1.0	**1.0**
25mm Concealed	0.75	**0.85**	**0.85**	**1.0**	**1.0**	1.0	**1.0**
38mm	0.60	**0.90**	**1.0**	**1.0**	**1.0**	1.0	**1.0**

* *Calculated to ASTM C 423-01*

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.



HALCYON™

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

HIGH SOUND ABSORPTION

AVAILABLE IN CONCEALED EDGE







TABLE OF PERFORMANCE




Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating*	Recycled Content	VOC Emission	Cost
			NRC	CAC						$
SQ	HC669 HC229	600*600*19 610*610*19	0.95	24	88%		Class A	40%	N/A	$$$
	HC629 HC249	600*1200*19 610*1220*19	0.95	24	88%		Class A	40%	N/A	$$$
	HC6625 HC2225	600*600*25 610*610*25	1.0	25	88%		Class A	40%	N/A	$$$
	HC6638 HC2238	600*600*38 610*610*38	1.0	31	88%		Class A	40%	N/A	$$$
SL	HCR669 HCR229	600*600*19 610*610*19	0.95	25	88%		Class A	40%	N/A	$$$
	HCR629 HCR249	600*1200*19 610*1220*19	0.95	25	88%		Class A	40%	N/A	$$$
	HCR6625 HCR2225	600*600*25 610*610*25	1.0	28	88%		Class A	40%	N/A	$$$
	HCR6225 HCR2425	600*1200*25 610*1220*25	1.0	28	88%		Class A	40%	N/A	$$$
	HCR6638 HCR2238	600*600*38 610*610*38	1.0	32	88%		Class A	40%	N/A	$$$$
FL	HCRF669 HCRF229	600*600*19 610*610*19	0.95	25	88%		Class A	40%	N/A	$$$
	HCRF629 HCRF249	600*1200*19 610*1220*19	0.95	25	88%		Class A	40%	N/A	$$$
	HCRF6625 HCRF2225	600*600*25 610*610*25	1.0	28	88%		Class A	40%	N/A	$$$
	HCRF6225 HCRF2425	600*1200*25 610*1220*25	1.0	28	88%		Class A	40%	N/A	$$$$
	HCRF6638 HCRF2238	600*600*38 610*610*38	1.0	32	88%		Class A	40%	N/A	$$$$
D-BESK**	HCRFDC669	600*600*19	0.95	28	88%		Class A	40%	N/A	$$$$$
	HCRFDC6625	600*600*25	1.0	30	88%		Class A	40%	N/A	$$$$$
S-BESK**	HCDSC6625	600*600*25	1.0	30	88%		Class A	40%	N/A	$$$$$
BESK**	HCFC669	600*600*19	0.95	28	88%		Class A	40%	N/A	$$$$$
	HCFC6625	600*600*25	1.0	30	88%		Class A	40%	N/A	$$$$$

*To ASTM E84

**Additional concealed panels configurations are available on special order: 600 x 1200, 600 x 1500, 600 x 1800 and 600 x 2400

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge	DX/DXL SL Edge	DXT FL Edge	DXF FL Edge	DXI FL Edge
					

DX/DXL D-BESK Edge	DX/DXL S-BESK Edge	DX/DXL BESK Edge
		

HALCYON™

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

HIGH SOUND ABSORPTION

AVAILABLE IN CONCEALED EDGE

SPECIFICATION DETAILS

Halcyon™ Acoustical Ceiling meets specifications in accordance with ASTM E1264.

Materials Classification
Type: XII,
Form: 2,
Pattern: E, G

Substrate and Surface Finish
Glasswool substrate laminated with factory applied painted fiberglass scrim and back fiberglass tissue

Thickness
19mm, 25mm, 38mm

Size
600 x 600mm, 610 x 610mm,
600 x 1200mm, 610 x 1220mm

Edge Detail Trim
Square, Reveal [SL, FL]
Concealed [D-BESK, S-BESK, BESK]

Weight
Square
19mm [2.1 kg/m^2],
25mm [2.3 kg/m^2],
38mm [4.2 kg/m^2]
Reveal [SL, FL]
19mm [2.1 kg/m^2],
25mm [2.75 kg/m^2],
38mm [4.2 kg/m^2]
Concealed [D-BESK, S-BESK, BESK]
19mm [2.65 kg/m^2],
25mm [3.5 kg/m^2]

Noise Reduction Coefficient [NRC]
[0.90] [0.95] [1.0]

Ceiling Attenuation Class [CAC]
[24 - 32 dB]

Mold Prevention Application as per ASTM D3273
Rate 10

Humidity Resistance
Maximum 99% RH / 40°C

Light Reflectance Coefficient [LR]
0.88

Color
Standard: White similar to RAL 9016.
Other colors are available upon request

Surface Burning Characteristics as per ASTM E84
Class A

Thermal Conductivity
λ = 0.034 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma