HALCYON™ HEALTHCARE



VISIT USGME.COM TO ORDER SAMPLES

FINISH OPTIONS

White

FEATURES & BENEFITS

- Halcyon™ Healthcare is ISO 3 according to the norm ISO 14644-1 : 2015.
- Fiberglass substrate with water repellent facing membrane designed to be durable and safe with common disinfectants.
- Elegant and refined acoustical facing and high performance mineral fleece membrane on the backside.
- Exceptional sound absorption with NRC values up to 1.
- Certificated for Environmental Product Declaration (EPD) as per ISO 14025.
- High light reflectance (LR-0.88) reduces light fixture & energy use.
- Recommended to be used with CE grid for hospitals in high-humidity or wet-cleaned areas.
- Washable & scrubbable finish.
- Impact & scratch resistant.
- Available in plank sizes compatible with Logix™ integrated ceiling system.

APPLICATIONS AS PER 2018 FGI GUIDELINES

- Class 1 MRI & imaging rooms
- Laboratories
- Laundry areas
- ICU / NICU
- Pharmacies
- Lobbies
- Waiting areas
- Ware washing

Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
19mm	0.50	**0.90**	**1.0**	**0.90**	**0.95**	0.90	**0.95**
19mm Concealed	0.65	**0.85**	**0.80**	**0.95**	**1.0**	1.0	**0.95**
25mm	0.40	**0.90**	**1.0**	**0.95**	**1.0**	1.0	**1.0**
25mm Concealed	0.75	**0.85**	**0.85**	**1.0**	**1.0**	1.0	**1.0**
38mm	0.60	**0.90**	**1.0**	**1.0**	**1.0**	1.0	**1.0**

* *Calculated to ASTM C 423-01*

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.



HALCYON™ HEALTHCARE

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

HIGH SOUND ABSORPTION







AVAILABLE IN CONCEALED EDGE





HEALTHCARE APPLICATION

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating*	Recycled Content	VOC Emission	Cost
			NRC	CAC						$
SQ	HC669-HC HC229-HC	600*600*19 610*610*19	0.95	24	88%		Class A	40%	N/A	$$$$
	HC629-HC HC249-HC	600*1200*19 610*1220*19	0.95	24	88%		Class A	40%	N/A	$$$$
	HC6625-HC HC2225-HC	600*600*25 610*610*25	1.0	25	88%		Class A	40%	N/A	$$$$
	HC6225-HC HC2425-HC	600*1200*25 610*1220*25	1.0	25	88%		Class A	40%	N/A	$$$$
	HC6638-HC HC2238-HC	600*600*38 610*610*38	1.0	31	88%		Class A	40%	N/A	$$$$
	HC6238-HC HC2238-HC	600*1220*38 610*1220*38	1.0	31	88%		Class A	40%	N/A	$$$$
FL	HCRF6625-HC HCRF2225-HC	600*600*25 610*610*25	1.0	28	88%		Class A	40%	N/A	$$$$
	HCRF6225-HC HCRF2425-HC	600*1200*25 610*1220*25	1.0	28	88%		Class A	40%	N/A	$$$$
SL	HCR6625-HC HCR2225-HC	600*600*25 610*610*25	1.0	28	88%		Class A	40%	N/A	$$$$
	HCR6225-HC HCR2425-HC	600*1200*25 610*1220*25	1.0	28	88%		Class A	40%	N/A	$$$$
D-BESK**	HCRFDC669-HC	600*600*19	0.95	28	88%		Class A	40%	N/A	$$$$$
	HCRFDC6625-HC	600*600*25	1.0	30	88%		Class A	40%	N/A	$$$$$
S-BESK**	HCDSC6625-HC	600*600*25	1.0	30	88%		Class A	40%	N/A	$$$$$
BESK**	HCFC669-HC	600*600*19	0.95	28	88%		Class A	40%	N/A	$$$$$
	HCFC6625-HC	600*600*25	1.0	30	88%		Class A	40%	N/A	$$$$$

GRID PROFILE OPTIONS

DX/DXL SQ Edge	CE SQ Edge	DXLT SQ Edge	DXT FL Edge	DXF FL Edge	DXI FL Edge
					

DX/DXL-SL	DX/DXL D-BESK Edge	DX/DXL S-BESK Edge	DX/DXL BESK Edge
			

*To ASTM E84

**Additional concealed panels configurations are available on special order: 600 x 1200, 600 x 1500, 600 x 1800 and 600 x 2400

HALCYON™ HEALTHCARE



SPECIFICATION DETAILS

Halcyon™ Healthcare Acoustical Ceiling meets specifications in accordance with ASTM E1264.

Materials Classification
Type: XII, Form: 2, Pattern: E, G

Substrate and Surface Finish
Glasswool substrate laminated with factory applied painted fiberglass scrim and water repellent membrane, and back fiberglass tissue

Water Absorbance
Repellency membrane that resists mild water drippage for up to 2 hrs

Thickness
19mm, 25mm, 38mm

Size
600 x 600mm, 610 x 610mm,
600 x 1200mm, 610 x 1220mm

Edge Detail Trim
Square, Reveal [SL, FL]
Concealed [D-BESK, S-BESK, BESK]

Weight
Square
19mm [2.1 kg/m^2],
25mm [2.3 kg/m^2],
38mm [4.2 kg/m^2]
Reveal [SL, FL]
19mm [2.1 kg/m^2],
25mm [2.75 kg/m^2]
Concealed [D-BESK, S-BESK, BESK]
19mm [2.65 kg/m^2],
25mm [3.5 kg/m^2]

Noise Reduction Coefficient [NRC]
[0.95] [1.0]

Ceiling Attenuation Class [CAC]
[24 - 31 dB]

Clean Room Classification as per ISO 14644-1
ISO 3

Mold Prevention Application as per ASTM D3273
Rate 10

Humidity Resistance
Maximum 99% RH / 40°C

Light Reflectance Coefficient [LR]
0.88

Color
White similar to RAL 9016.

Surface Burning Characteristics as per ASTM E84
Class A

Thermal Conductivity
λ = 0.034 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co. All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma