LOUNA™ ELITE



VISIT USGME.COM TO ORDER SAMPLES

FINISH OPTIONS

White

FEATURES & BENEFITS

- Stone Wool substrate with stylish monolithic white surface and high performance mineral fleece membrane on the backside.
- Exceptional sound absorption with NRC values up to 1.0.
- Sanded surface finish with high light reflectance (LR-0.88) reduces wear and tear on light fixtures and energy use.
- Moisture resistance to withstand severe conditions when used with DONN® brand suspension system.
- Eco-friendly mineral wool product made from natural stone.
- Washable & scrubbable finish.

APPLICATIONS

- Open-plan offices
- Offices with indirect lighting
- Restaurants and cafes
- Media room
- Conference facilities
- Reception areas
- Libraries

Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
19mm	0.60	**0.95**	**0.85**	**0.95**	**1.0**	1.0	**0.95**
25mm	0.60	**1.0**	**0.90**	**1.0**	**1.0**	1.0	**1.0**

*Calculated to ASTM C 423-01

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

LOUNA™ ELITE

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

HIGH SOUND ABSORPTION

CEILING ATTENUATION CLASS







FIRECODE

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold /Mildew & Sag Resistance	Fire Rating*	Recycled Content	VOC Emission	Cost
			NRC	CAC						$
SQ	LEC669 LEC229	600*600*19 610*610*19	0.95	25	88%		Class A	47%	N/A	$$$
	LEC629 LEC249	600*1200*19 610*1220*19	0.95	25	88%		Class A	47%	N/A	$$$
	LEC6625 LEC2225	600*600*25 610*610*25	1.0	26	88%		Class A	47%	N/A	$$$$
	LEC6225 LEC2425	600*1200*25 610*1220*25	1.0	26	88%		Class A	47%	N/A	$$$$
SL	LECR669 LECR229	600*600*19 610*610*19	0.90	27	88%		Class A	47%	N/A	$$$$
	LECR629 LECR249	600*1200*19 610*1220*19	0.90	27	88%		Class A	47%	N/A	$$$$
	LECR6625 LECR2225	600*600*25 610*610*25	0.95	28	88%		Class A	47%	N/A	$$$$
	LECR6225 LECR2425	600*1200*25 610*1220*25	0.95	28	88%		Class A	47%	N/A	$$$$
FL	LECRF669 LECRF229	600*600*19 610*610*19	0.90	27	88%		Class A	47%	N/A	$$$$
	LECRF629 LECRF249	600*1200*19 610*1220*19	0.90	27	88%		Class A	47%	N/A	$$$$
	LECRF6625 LECRF2225	600*600*25 610*610*25	0.95	28	88%		Class A	47%	N/A	$$$$
	LECRF6225 LECRF2425	600*1200*25 610*1220*25	0.95	28	88%		Class A	47%	N/A	$$$$

* To ASTM E84

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXLT SQ Edge	DX/DXL SL Edge	DXT FL Edge	DXF FL Edge	DXI FL Edge
					

SPECIFICATION DETAILS

Louna™ Elite Acoustical Ceiling meets specifications in accordance with ASTM E1264.

Materials Classification
Type: XX,
Pattern: E, G

Substrate and Surface Finish
Stone Wool substrate finished with factory applied painted fiberglass scrim and back fiberglass tissue

Thickness
19mm, 25mm

Size
600 x 600mm, 610 x 610mm,
600 x 1200mm, 610 x 1220mm

Edge Detail Trim
Square, Reveal [SL, FL]

Weight
Square:
19mm: 2.28 kg/m²
25mm: 3 kg/m²
Reveal [SL, FL]:
19mm: 2.85 kg/m²
25mm: 3.75 kg/m²

Noise Reduction Coefficient [NRC]
[0.90] [0.95] [1.0]

Ceiling Attenuation Class [CAC]
[25 - 28 dB]

Mold Prevention Application as per ASTM D3273
Rate 10

Humidity Resistance
Maximum 99% RH / 40°C for ClimaPlus™

Light Reflectance Coefficient [LR]
0.88

Color
Standard White similar to RAL 9016.
Other colors are available upon request

Surface Burning Characteristics as per ASTM E84
Class A

Thermal Conductivity
λ = 0.036 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma