CEILINGS

LOUNA™ HI CAC



VISIT USGME.COM TO ORDER SAMPLES

FINISH OPTIONS

White, Light Grey, Dark Grey, Yellow, Green, Blue, Brown

FEATURES & BENEFITS

- Balanced Acoustics. High-NRC and High-CAC.
- Specifically engineered when high acoustic performance is needed to satisfy high-frequency performance criteria.
- Hybrid ceiling panel is made of soft fiber substrate with wet-felted mineral fiber substrate on the rear side. Finished with painted fiberglass scrim and sealed edge.
- Excellent combination of noise reduction (up to NRC-0.90 for 53mm) and sound attenuation (up to CAC-42).
- Impact & scratch resistant finish scrim.
- Available in different colors.

APPLICATIONS

- Recording studios and radio stations
- Music and sports hall
- Industrial premises
- Convention halls and concourses
- Restaurants
- Sports facilities

Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
43mm	0.45	**0.50**	**0.85**	**1.0**	**1.0**	1.0	**0.85**
53mm	0.40	**0.50**	**0.90**	**1.0**	**1.0**	1.0	**0.90**

**Calculated to ASTM C 423-01*

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

LOUNA™ HI CAC

EN 13964 : 2014 + A1 : 2007

HIGH SOUND ABSORPTION





CEILING ATTENUATION CLASS

FIRECODE

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			NRC	CAC						
SQ	LCX6643-MF LCX2243-MF	600*600*43 610*610*43	0.85	42	88%			40%	N/A	$$$$$
	LCX6243-MF LCX2443-MF	600*1200*43 610*1220*43	0.85	42	88%			40%	N/A	$$$$$
	LCXX6253-MF LCXX2453-MF	600*600*53 610*610*53	0.90	41	88%			40%	N/A	$$$$$
	LCXX6253-MF LCXX2453-MF	600*1200*53 610*1220*53	0.90	41	88%			40%	N/A	$$$$$
FL	LCXRF6643-MF LCXRF2243-MF	600*600*43 610*1220*43	0.85	42	88%			40%	N/A	$$$$$
	LCXRF6243-MF LCXRF2443-MF	600*1200*43 610*1220*43	0.85	42	88%			40%	N/A	$$$$$
	LCXXRF6253-MF LCXXRF2453-MF	600*600*53 610*1220*53	0.90	41	88%			40%	N/A	$$$$$
	LCXXRF6653-MF LCXXRF2253-MF	600*1200*53 610*1220*53	0.90	41	88%			40%	N/A	$$$$$

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge	DXT FL Edge	DXF FL Edge
			

SPECIFICATION DETAILS

Louna™ Hi CAC Acoustical Ceiling meets the specifications in accordance with ASTM E1264.

Materials Classification
Type: XX,
Pattern: G

Substrate and Surface Finish
Soft fiber substrate attach with wetfelted mineral fiber substrate on the rear side, and laminated with factory-applied painted fiberglass scrim on the surface

Thickness
43mm, 53mm

Size
600 x 600mm, 610 x 610mm,
600 x 1200mm, 610 x 1220mm

Edge Detail Trim
Square, Reveal [FL]

Weight
43mm [8.85 kg/m^2],
53mm [12 kg/m^2]

Noise Reduction Coefficient [NRC]
[0.85] [0.90]

Ceiling Attenuation Class [CAC]
[41 - 42 dB]

Mold Prevention Application as per ASTM D3273
Rate 10

Humidity Resistance
Maximum 99% RH / 40°C

Light Reflectance Coefficient [LR]
0.88

Color
Standard White similar to RAL 9016.
Other colors are available upon request

Surface Burning Characteristics as per ASTM E84
Class A

Thermal Conductivity:
Fiber glass: λ = 0.036 W/m°K
Mineral fiber: λ = 0.057 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 |
MR Credit 6 IEQ Credit 3 | IEQ Credit 3.2 |
IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma